

# **Linux Standard Base C++ Specification for S390X 4.0**

## **Linux Standard Base C++ Specification for S390X 4.0**

Copyright © 2008 Linux Foundation

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.1; with no Invariant Sections, with no Front-Cover Texts, and with no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".

Portions of the text may be copyrighted by the following parties:

- The Regents of the University of California
- Free Software Foundation
- Ian F. Darwin
- Paul Vixie
- BSDI (now Wind River)
- Andrew G Morgan
- Jean-loup Gailly and Mark Adler
- Massachusetts Institute of Technology
- Apple Inc.
- Easy Software Products
- artofcode LLC
- Till Kamppeter
- Manfred Wassman
- Python Software Foundation

These excerpts are being used in accordance with their respective licenses.

Linux is the registered trademark of Linus Torvalds in the U.S. and other countries.

UNIX is a registered trademark of The Open Group.

LSB is a trademark of the Linux Foundation in the United States and other countries.

AMD is a trademark of Advanced Micro Devices, Inc.

Intel and Itanium are registered trademarks and Intel386 is a trademark of Intel Corporation.

PowerPC is a registered trademark and PowerPC Architecture is a trademark of the IBM Corporation.

S/390 is a registered trademark of the IBM Corporation.

OpenGL is a registered trademark of Silicon Graphics, Inc.

# Contents

<u>I Introductory Elements</u> .....
1 Scope.....
1.1 General.....
1.2 Module Specific Scope.....
2 Normative References.....
3 Requirements.....
3.1 Relevant Libraries.....
3.2 LSB Implementation Conformance.....
3.3 LSB Application Conformance.....
4 Definitions.....
5 Terminology.....
6 Documentation Conventions.....
<u>II Base Libraries</u> .....
7 Libraries.....
7.1 Interfaces for libstdc++.....
7.2 Interface Definitions for libstdc++.....
<u>A GNU Free Documentation License (Informative)</u> .....
A.1 PREAMBLE.....
A.2 APPLICABILITY AND DEFINITIONS.....
A.3 VERBATIM COPYING.....
A.4 COPYING IN QUANTITY.....
A.5 MODIFICATIONS.....
A.6 COMBINING DOCUMENTS.....
A.7 COLLECTIONS OF DOCUMENTS.....
A.8 AGGREGATION WITH INDEPENDENT WORKS.....
A.9 TRANSLATION.....
A.10 TERMINATION.....
A.11 FUTURE REVISIONS OF THIS LICENSE.....
A.12 How to use this License for your documents.....

## List of Tables

<a href="#">2-1 Normative References</a>	.....
<a href="#">3-1 Standard Library Names</a>	.....
<a href="#">7-1 libstdc++ Definition</a>	.....
<a href="#">7-2 libstdc++ - C++ Runtime Support Function Interfaces</a>	.....
<a href="#">7-3 typeinfo for type_info</a>	.....
<a href="#">7-4 typeinfo for cxxabiv1:: enum_type_info</a>	.....
<a href="#">7-5 typeinfo for cxxabiv1:: array_type_info</a>	.....
<a href="#">7-6 Primary vtable for cxxabiv1:: class_type_info</a>	.....
<a href="#">7-7 typeinfo for cxxabiv1:: class_type_info</a>	.....
<a href="#">7-8 libstdc++ - Class cxxabiv1:: class_type_info Function Interfaces</a>	.....
<a href="#">7-9 typeinfo for cxxabiv1:: pbase_type_info</a>	.....
<a href="#">7-10 typeinfo for cxxabiv1:: pointer_type_info</a>	.....
<a href="#">7-11 typeinfo for cxxabiv1:: function_type_info</a>	.....
<a href="#">7-12 Primary vtable for cxxabiv1:: si_class_type_info</a>	.....
<a href="#">7-13 typeinfo for cxxabiv1:: si_class_type_info</a>	.....
<a href="#">7-14 libstdc++ - Class cxxabiv1:: si_class_type_info Function Interfaces</a>	.....
<a href="#">7-15 Primary vtable for cxxabiv1:: vmi_class_type_info</a>	.....
<a href="#">7-16 typeinfo for cxxabiv1:: vmi_class_type_info</a>	.....
<a href="#">7-17 libstdc++ - Class cxxabiv1:: vmi_class_type_info Function Interfaces</a>	.....
<a href="#">7-18 typeinfo for cxxabiv1:: fundamental_type_info</a>	.....
<a href="#">7-19 typeinfo for cxxabiv1:: pointer_to_member_type_info</a>	.....
<a href="#">7-20 libstdc++ - Class gnu_cxx:: pool_alloc_base Function Interfaces</a>	.....
<a href="#">7-21 Primary vtable for gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt;&gt;</a>	.....
<a href="#">7-22 Primary vtable for gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</a>	.....
<a href="#">7-23 typeinfo for exception</a>	.....
<a href="#">7-24 typeinfo for bad_typeid</a>	.....
<a href="#">7-25 typeinfo for logic_error</a>	.....
<a href="#">7-26 typeinfo for range_error</a>	.....
<a href="#">7-27 typeinfo for domain_error</a>	.....
<a href="#">7-28 typeinfo for length_error</a>	.....
<a href="#">7-29 typeinfo for out_of_range</a>	.....
<a href="#">7-30 typeinfo for bad_exception</a>	.....
<a href="#">7-31 typeinfo for runtime_error</a>	.....
<a href="#">7-32 typeinfo for overflow_error</a>	.....
<a href="#">7-33 typeinfo for underflow_error</a>	.....
<a href="#">7-34 typeinfo for invalid_argument</a>	.....
<a href="#">7-35 typeinfo for bad_cast</a>	.....
<a href="#">7-36 typeinfo for bad_alloc</a>	.....
<a href="#">7-37 typeinfo for ctype_base</a>	.....
<a href="#">7-38 libstdc++ - Class ctype&lt;char&gt; Function Interfaces</a>	.....
<a href="#">7-39 typeinfo for ctype&lt;wchar_t&gt;</a>	.....
<a href="#">7-40 libstdc++ - Class ctype&lt;wchar_t&gt; Function Interfaces</a>	.....
<a href="#">7-41 typeinfo for ctype_byname&lt;char&gt;</a>	.....
<a href="#">7-42 libstdc++ - Class ctype_byname&lt;char&gt; Function Interfaces</a>	.....
<a href="#">7-43 typeinfo for ctype_byname&lt;wchar_t&gt;</a>	.....
<a href="#">7-44 libstdc++ - Class ctype_byname&lt;wchar_t&gt; Function Interfaces</a>	.....
<a href="#">7-45 libstdc++ - Class basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt; Function Interfaces</a>	.....
<a href="#">7-46 libstdc++ - Class basic_string&lt;wchar_t, char_traits&lt;wchar_t&gt;,</a>	.....

<a href="#">allocator&lt;wchar_t&gt; &gt; Function Interfaces</a>	.....
<a href="#">7-47 Primary vtable for basic stringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</a>	.....
<a href="#">7-48 Secondary vtable for basic stringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</a>	.....
<a href="#">7-49 Secondary vtable for basic stringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</a>	.....
<a href="#">7-50 VTT for basic stringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</a>	.....
<a href="#">7-51 libstdc++ - Class basic stringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt; Function Interfaces</a>	.....
<a href="#">7-52 Primary vtable for basic stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;</a>	.....
<a href="#">7-53 Secondary vtable for basic stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;</a>	.....
<a href="#">7-54 Secondary vtable for basic stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;</a>	.....
<a href="#">7-55 VTT for basic stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;</a>	.....
<a href="#">7-56 libstdc++ - Class basic stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt; Function Interfaces</a>	.....
<a href="#">7-57 Primary vtable for basic istringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</a>	.....
<a href="#">7-58 Secondary vtable for basic istringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</a>	.....
<a href="#">7-59 VTT for basic istringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</a>	.....
<a href="#">7-60 libstdc++ - Class basic istringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt; Function Interfaces</a>	.....
<a href="#">7-61 Primary vtable for basic istringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;</a>	.....
<a href="#">7-62 Secondary vtable for basic istringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;</a>	.....
<a href="#">7-63 VTT for basic istringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;</a>	.....
<a href="#">7-64 libstdc++ - Class basic istringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt; Function Interfaces</a>	.....
<a href="#">7-65 Primary vtable for basic ostringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</a>	.....
<a href="#">7-66 Secondary vtable for basic ostringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</a>	.....
<a href="#">7-67 VTT for basic ostringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</a>	.....
<a href="#">7-68 libstdc++ - Class basic ostringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt; Function Interfaces</a>	.....
<a href="#">7-69 Primary vtable for basic ostringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;</a>	.....
<a href="#">7-70 Secondary vtable for basic ostringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;</a>	.....
<a href="#">7-71 VTT for basic ostringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;</a>	.....
<a href="#">7-72 libstdc++ - Class basic ostringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt; Function Interfaces</a>	.....
<a href="#">7-73 Primary vtable for basic stringbuf&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</a>	.....
<a href="#">7-74 typeinfo for basic stringbuf&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</a>	.....

<a href="#">7-75 libstdc++ - Class basic_stringbuf&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt; Function Interfaces</a>	.....
<a href="#">7-76 Primary vtable for basic_stringbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt;</a>	.....
<a href="#">7-77 typeinfo for basic_stringbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt;</a>	.....
<a href="#">7-78 libstdc++ - Class basic_stringbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt; Function Interfaces</a>	.....
<a href="#">7-79 Primary vtable for basic_iostream&lt;char, char_traits&lt;char&gt; &gt;</a>	.....
<a href="#">7-80 Secondary vtable for basic_iostream&lt;char, char_traits&lt;char&gt; &gt;</a>	.....
<a href="#">7-81 Secondary vtable for basic_iostream&lt;char, char_traits&lt;char&gt; &gt;</a>	.....
<a href="#">7-82 VTT for basic_iostream&lt;char, char_traits&lt;char&gt; &gt;</a>	.....
<a href="#">7-83 libstdc++ - Class basic_iostream&lt;char, char_traits&lt;char&gt; &gt; Function Interfaces</a>	.....
<a href="#">7-84 Primary vtable for basic_iostream&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;</a>	.....
<a href="#">7-85 Secondary vtable for basic_iostream&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;</a>	.....
<a href="#">7-86 Secondary vtable for basic_iostream&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;</a>	.....
<a href="#">7-87 VTT for basic_iostream&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;</a>	.....
<a href="#">7-88 libstdc++ - Class basic_iostream&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; Function Interfaces</a>	.....
<a href="#">7-89 Primary vtable for basic_istream&lt;char, char_traits&lt;char&gt; &gt;</a>	.....
<a href="#">7-90 Secondary vtable for basic_istream&lt;char, char_traits&lt;char&gt; &gt;</a>	.....
<a href="#">7-91 VTT for basic_istream&lt;char, char_traits&lt;char&gt; &gt;</a>	.....
<a href="#">7-92 libstdc++ - Class basic_istream&lt;char, char_traits&lt;char&gt; &gt; Function Interfaces</a>	.....
<a href="#">7-93 Primary vtable for basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;</a>	.....
<a href="#">7-94 Secondary vtable for basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;</a>	.....
<a href="#">7-95 VTT for basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;</a>	.....
<a href="#">7-96 libstdc++ - Class basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; Function Interfaces</a>	.....
<a href="#">7-97 Primary vtable for basic_ostream&lt;char, char_traits&lt;char&gt; &gt;</a>	.....
<a href="#">7-98 Secondary vtable for basic_ostream&lt;char, char_traits&lt;char&gt; &gt;</a>	.....
<a href="#">7-99 VTT for basic_ostream&lt;char, char_traits&lt;char&gt; &gt;</a>	.....
<a href="#">7-100 libstdc++ - Class basic_ostream&lt;char, char_traits&lt;char&gt; &gt; Function Interfaces</a>	.....
<a href="#">7-101 Primary vtable for basic_ostream&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;</a>	.....
<a href="#">7-102 Secondary vtable for basic_ostream&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;</a>	.....
<a href="#">7-103 VTT for basic_ostream&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;</a>	.....
<a href="#">7-104 libstdc++ - Class basic_ostream&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; Function Interfaces</a>	.....
<a href="#">7-105 Primary vtable for basic_fstream&lt;char, char_traits&lt;char&gt; &gt;</a>	.....
<a href="#">7-106 Secondary vtable for basic_fstream&lt;char, char_traits&lt;char&gt; &gt;</a>	.....
<a href="#">7-107 Secondary vtable for basic_fstream&lt;char, char_traits&lt;char&gt; &gt;</a>	.....
<a href="#">7-108 VTT for basic_fstream&lt;char, char_traits&lt;char&gt; &gt;</a>	.....
<a href="#">7-109 libstdc++ - Class basic_fstream&lt;char, char_traits&lt;char&gt; &gt; Function Interfaces</a>	.....
<a href="#">7-110 Primary vtable for basic_fstream&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;</a>	.....
<a href="#">7-111 Secondary vtable for basic_fstream&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;</a>	.....
<a href="#">7-112 Secondary vtable for basic_fstream&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;</a>	.....
<a href="#">7-113 VTT for basic_fstream&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;</a>	.....
<a href="#">7-114 libstdc++ - Class basic_fstream&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; Function Interfaces</a>	.....
<a href="#">7-115 Primary vtable for basic_ifstream&lt;char, char_traits&lt;char&gt; &gt;</a>	.....

<a href="#">7-116 Secondary vtable for basic_ifstream&lt;char, char_traits&lt;char&gt;&gt;.....</a>
<a href="#">7-117 VTT for basic_ifstream&lt;char, char_traits&lt;char&gt;&gt;.....</a>
<a href="#">7-118 libstdc++ - Class basic_ifstream&lt;char, char_traits&lt;char&gt;&gt; Function Interfaces.....</a>
<a href="#">7-119 Primary vtable for basic_ifstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;.....</a>
<a href="#">7-120 Secondary vtable for basic_ifstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;.....</a>
<a href="#">7-121 VTT for basic_ifstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;.....</a>
<a href="#">7-122 libstdc++ - Class basic_ifstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; Function Interfaces.....</a>
<a href="#">7-123 Primary vtable for basic_ofstream&lt;char, char_traits&lt;char&gt;&gt;.....</a>
<a href="#">7-124 Secondary vtable for basic_ofstream&lt;char, char_traits&lt;char&gt;&gt;.....</a>
<a href="#">7-125 VTT for basic_ofstream&lt;char, char_traits&lt;char&gt;&gt;.....</a>
<a href="#">7-126 libstdc++ - Class basic_ofstream&lt;char, char_traits&lt;char&gt;&gt; Function Interfaces.....</a>
<a href="#">7-127 Primary vtable for basic_ofstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;.....</a>
<a href="#">7-128 Secondary vtable for basic_ofstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;.....</a>
<a href="#">7-129 VTT for basic_ofstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;.....</a>
<a href="#">7-130 libstdc++ - Class basic_ofstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; Function Interfaces.....</a>
<a href="#">7-131 Primary vtable for basic_streambuf&lt;char, char_traits&lt;char&gt;&gt;.....</a>
<a href="#">7-132 typeinfo for basic_streambuf&lt;char, char_traits&lt;char&gt;&gt;.....</a>
<a href="#">7-133 libstdc++ - Class basic_streambuf&lt;char, char_traits&lt;char&gt;&gt; Function Interfaces.....</a>
<a href="#">7-134 Primary vtable for basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;.....</a>
<a href="#">7-135 typeinfo for basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;.....</a>
<a href="#">7-136 libstdc++ - Class basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; Function Interfaces.....</a>
<a href="#">7-137 Primary vtable for basic_filebuf&lt;char, char_traits&lt;char&gt;&gt;.....</a>
<a href="#">7-138 typeinfo for basic_filebuf&lt;char, char_traits&lt;char&gt;&gt;.....</a>
<a href="#">7-139 libstdc++ - Class basic_filebuf&lt;char, char_traits&lt;char&gt;&gt; Function Interfaces.....</a>
<a href="#">7-140 Primary vtable for basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;.....</a>
<a href="#">7-141 typeinfo for basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;.....</a>
<a href="#">7-142 libstdc++ - Class basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; Function Interfaces.....</a>
<a href="#">7-143 typeinfo for ios_base.....</a>
<a href="#">7-144 typeinfo for basic_ios&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;.....</a>
<a href="#">7-145 typeinfo for ios_base::failure.....</a>
<a href="#">7-146 typeinfo for timepunct&lt;char&gt;.....</a>
<a href="#">7-147 libstdc++ - Class timepunct&lt;char&gt; Function Interfaces.....</a>
<a href="#">7-148 typeinfo for timepunct&lt;wchar_t&gt;.....</a>
<a href="#">7-149 libstdc++ - Class timepunct&lt;wchar_t&gt; Function Interfaces.....</a>
<a href="#">7-150 typeinfo for messages_base.....</a>
<a href="#">7-151 libstdc++ - Class messages&lt;char&gt; Function Interfaces.....</a>
<a href="#">7-152 libstdc++ - Class messages&lt;wchar_t&gt; Function Interfaces.....</a>
<a href="#">7-153 typeinfo for messages_byname&lt;char&gt;.....</a>
<a href="#">7-154 libstdc++ - Class messages_byname&lt;char&gt; Function Interfaces.....</a>
<a href="#">7-155 typeinfo for messages_byname&lt;wchar_t&gt;.....</a>
<a href="#">7-156 libstdc++ - Class messages_byname&lt;wchar_t&gt; Function Interfaces.....</a>
<a href="#">7-157 typeinfo for numpunct&lt;char&gt;.....</a>
<a href="#">7-158 libstdc++ - Class numpunct&lt;char&gt; Function Interfaces.....</a>
<a href="#">7-159 typeinfo for numpunct&lt;wchar_t&gt;.....</a>
<a href="#">7-160 libstdc++ - Class numpunct&lt;wchar_t&gt; Function Interfaces.....</a>

[7-161 typeinfo for `numpunct` byname<char>.....](#)  
[7-162 libstdcxx - Class `numpunct` byname<char> Function Interfaces.....](#)  
[7-163 typeinfo for `numpunct` byname<wchar\\_t>.....](#)  
[7-164 libstdcxx - Class `numpunct` byname<wchar\\_t> Function Interfaces.....](#)  
[7-165 typeinfo for `codecvt` base.....](#)  
[7-166 Primary vtable for `codecvt<char, char, mbstate t>`.....](#)  
[7-167 typeinfo for `codecvt<char, char, mbstate t>`.....](#)  
[7-168 libstdcxx - Class `codecvt<char, char, mbstate t>` Function Interfaces.....](#)  
[7-169 Primary vtable for `codecvt<wchar\_t, char, mbstate t>`.....](#)  
[7-170 typeinfo for `codecvt<wchar\_t, char, mbstate t>`.....](#)  
[7-171 libstdcxx - Class `codecvt<wchar\_t, char, mbstate t>` Function Interfaces.....](#)  
[7-172 Primary vtable for `codecvt` byname<char, char, mbstate t>.....](#)  
[7-173 typeinfo for `codecvt` byname<char, char, mbstate t>.....](#)  
[7-174 libstdcxx - Class `codecvt` byname<char, char, mbstate t> Function Interfaces.....](#)  
[7-175 Primary vtable for `codecvt` byname<wchar\\_t, char, mbstate t>.....](#)  
[7-176 typeinfo for `codecvt` byname<wchar\\_t, char, mbstate t>.....](#)  
[7-177 typeinfo for `collate` byname<wchar\\_t>.....](#)  
[7-178 libstdcxx - Class `collate` byname<wchar\\_t, char, mbstate t> Function Interfaces.....](#)  
[7-179 typeinfo for `collate`<char>.....](#)  
[7-180 libstdcxx - Class `collate`<char> Function Interfaces.....](#)  
[7-181 typeinfo for `collate`<wchar\\_t>.....](#)  
[7-182 libstdcxx - Class `collate`<wchar\\_t> Function Interfaces.....](#)  
[7-183 typeinfo for `collate` byname<char>.....](#)  
[7-184 libstdcxx - Class `collate` byname<char> Function Interfaces.....](#)  
[7-185 typeinfo for `time` base.....](#)  
[7-186 typeinfo for `time` get byname<char, istreambuf iterator<char, char traits<char>>>.....](#)  
[7-187 libstdcxx - Class `time` get byname<char, istreambuf iterator<char, char traits<char>>> Function Interfaces.....](#)  
[7-188 typeinfo for `time` get byname<wchar\\_t, istreambuf iterator<wchar\\_t, char traits<wchar\\_t>>>.....](#)  
[7-189 libstdcxx - Class `time` get byname<wchar\\_t, istreambuf iterator<wchar\\_t, char traits<wchar\\_t>>> Function Interfaces.....](#)  
[7-190 typeinfo for `time` put byname<char, ostreambuf iterator<char, char traits<char>>>.....](#)  
[7-191 libstdcxx - Class `time` put byname<char, ostreambuf iterator<char, char traits<char>>> Function Interfaces.....](#)  
[7-192 typeinfo for `time` put byname<wchar\\_t, ostreambuf iterator<wchar\\_t, char traits<wchar\\_t>>>.....](#)  
[7-193 libstdcxx - Class `time` put byname<wchar\\_t, ostreambuf iterator<wchar\\_t, char traits<wchar\\_t>>> Function Interfaces.....](#)  
[7-194 libstdcxx - Class `time` get<char, istreambuf iterator<char, char traits<char>>> Function Interfaces.....](#)  
[7-195 libstdcxx - Class `time` get<wchar\\_t, istreambuf iterator<wchar\\_t, char traits<wchar\\_t>>> Function Interfaces.....](#)  
[7-196 typeinfo for `time` put<char, ostreambuf iterator<char, char traits<char>>>.....](#)  
[7-197 libstdcxx - Class `time` put<char, ostreambuf iterator<char, char traits<char>>> Function Interfaces.....](#)

<a href="#">7-198 typeinfo for time put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</a>	.....
<a href="#">7-199 libstdcxx - Class time put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; Function Interfaces</a>	.....
<a href="#">7-200 libstdcxx - Class moneypunct&lt;char, false&gt; Function Interfaces</a>	.....
<a href="#">7-201 libstdcxx - Class moneypunct&lt;char, true&gt; Function Interfaces</a>	.....
<a href="#">7-202 libstdcxx - Class moneypunct&lt;wchar_t, false&gt; Function Interfaces</a>	.....
<a href="#">7-203 libstdcxx - Class moneypunct&lt;wchar_t, true&gt; Function Interfaces</a>	.....
<a href="#">7-204 typeinfo for moneypunct_byname&lt;char, false&gt;</a>	.....
<a href="#">7-205 libstdcxx - Class moneypunct_byname&lt;char, false&gt; Function Interfaces</a>	.....
<a href="#">7-206 typeinfo for moneypunct_byname&lt;char, true&gt;</a>	.....
<a href="#">7-207 libstdcxx - Class moneypunct_byname&lt;char, true&gt; Function Interfaces</a>	.....
<a href="#">7-208 typeinfo for moneypunct_byname&lt;wchar_t, false&gt;</a>	.....
<a href="#">7-209 libstdcxx - Class moneypunct_byname&lt;wchar_t, false&gt; Function Interfaces</a>	.....
<a href="#">7-210 typeinfo for moneypunct_byname&lt;wchar_t, true&gt;</a>	.....
<a href="#">7-211 libstdcxx - Class moneypunct_byname&lt;wchar_t, true&gt; Function Interfaces</a>	.....
<a href="#">7-212 typeinfo for money_base</a>	.....
<a href="#">7-213 typeinfo for money_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;</a>	.....
<a href="#">7-214 libstdcxx - Class money_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; Function Interfaces</a>	.....
<a href="#">7-215 typeinfo for money_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</a>	.....
<a href="#">7-216 libstdcxx - Class money_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; Function Interfaces</a>	.....
<a href="#">7-217 typeinfo for money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;</a>	.....
<a href="#">7-218 libstdcxx - Class money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; Function Interfaces</a>	.....
<a href="#">7-219 typeinfo for money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</a>	.....
<a href="#">7-220 libstdcxx - Class money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; Function Interfaces</a>	.....
<a href="#">7-221 libstdcxx - Class locale Function Interfaces</a>	.....
<a href="#">7-222 typeinfo for locale::facet</a>	.....
<a href="#">7-223 typeinfo for num_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;</a>	.....
<a href="#">7-224 libstdcxx - Class num_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; Function Interfaces</a>	.....
<a href="#">7-225 typeinfo for num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</a>	.....
<a href="#">7-226 libstdcxx - Class num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; Function Interfaces</a>	.....
<a href="#">7-227 typeinfo for num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;</a>	.....
<a href="#">7-228 libstdcxx - Class num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; Function Interfaces</a>	.....
<a href="#">7-229 typeinfo for num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</a>	.....
<a href="#">7-230 libstdcxx - Class num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; Function Interfaces</a>	.....
<a href="#">7-231 libstdcxx - Class gslice Function Interfaces</a>	.....

[7-232 libstdc++ - Class `basic\_file<char>` Function Interfaces](#).....  
[7-233 libstdc++ - Class `valarray<unsigned int>` Function Interfaces](#).....  
[7-234 libstdc++ - Class `gnu\_cxx:: pool<true>` Function Interfaces](#).....  
[7-235 libstdc++ - Class `gnu\_cxx:: pool<false>` Function Interfaces](#).....  
[7-236 libstdc++ - Class `gnu\_cxx::free\_list` Function Interfaces](#).....  
[7-237 libstdc++ - Class `locale:: Impl` Function Interfaces](#).....  
[7-238 libstdc++ - Namespace std Functions Function Interfaces](#).....

## **Foreword**

This is version 4.0 of the Linux Standard Base C++ Specification for S390X. This specification is part of a family of specifications under the general title "Linux Standard Base". Developers of applications or implementations interested in using the LSB trademark should see the Linux Foundation Certification Policy for details.

## Introduction

The LSB defines a binary interface for application programs that are compiled and packaged for LSB-conforming implementations on many different hardware architectures. Since a binary specification shall include information specific to the computer processor architecture for which it is intended, it is not possible for a single document to specify the interface for all possible LSB-conforming implementations. Therefore, the LSB is a family of specifications, rather than a single one.

This document should be used in conjunction with the documents it references. This document enumerates the system components it includes, but descriptions of those components may be included entirely or partly in this document, partly in other documents, or entirely in other reference documents. For example, the section that describes system service routines includes a list of the system routines supported in this interface, formal declarations of the data structures they use that are visible to applications, and a pointer to the underlying referenced specification for information about the syntax and semantics of each call. Only those routines not described in standards referenced by this document, or extensions to those standards, are described in the detail. Information referenced in this way is as much a part of this document as is the information explicitly included here.

The specification carries a version number of either the form  $x.y$  or  $x.y.z$ . This version number carries the following meaning:

- The first number ( $x$ ) is the major version number. All versions with the same major version number should share binary compatibility. Any addition or deletion of a new library results in a new version number. Interfaces marked as deprecated may be removed from the specification at a major version change.
- The second number ( $y$ ) is the minor version number. Individual interfaces may be added if all certified implementations already had that (previously undocumented) interface. Interfaces may be marked as deprecated at a minor version change. Other minor changes may be permitted at the discretion of the LSB workgroup.
- The third number ( $z$ ), if present, is the editorial level. Only editorial changes should be included in such versions.

Since this specification is a descriptive Application Binary Interface, and not a source level API specification, it is not possible to make a guarantee of 100% backward compatibility between major releases. However, it is the intent that those parts of the binary interface that are visible in the source level API will remain backward compatible from version to version, except where a feature marked as "Deprecated" in one release may be removed from a future release.

Implementors are strongly encouraged to make use of symbol versioning to permit simultaneous support of applications conforming to different releases of this specification.

## I Introductory Elements

# 1 Scope

## 1.1 General

The Linux Standard Base (LSB) defines a system interface for compiled applications and a minimal environment for support of installation scripts. Its purpose is to enable a uniform industry standard environment for high-volume applications conforming to the LSB.

These specifications are composed of two basic parts: A common specification ("LSB-generic" or "generic LSB"), ISO/IEC 23360 Part 1, describing those parts of the interface that remain constant across all implementations of the LSB, and an architecture-specific part ("LSB-arch" or "archLSB") describing the parts of the interface that vary by processor architecture. Together, the LSB-generic and the relevant architecture-specific part of ISO/IEC 23360 for a single hardware architecture provide a complete interface specification for compiled application programs on systems that share a common hardware architecture.

ISO/IEC 23360 Part 1, the LSB-generic document, should be used in conjunction with an architecture-specific part. Whenever a section of the LSB-generic specification is supplemented by architecture-specific information, the LSB-generic document includes a reference to the architecture part. Architecture-specific parts of ISO/IEC 23360 may also contain additional information that is not referenced in the LSB-generic document.

The LSB contains both a set of Application Program Interfaces (APIs) and Application Binary Interfaces (ABIs). APIs may appear in the source code of portable applications, while the compiled binary of that application may use the larger set of ABIs. A conforming implementation provides all of the ABIs listed here. The compilation system may replace (e.g. by macro definition) certain APIs with calls to one or more of the underlying binary interfaces, and may insert calls to binary interfaces as needed.

The LSB is primarily a binary interface definition. Not all of the source level APIs available to applications may be contained in this specification.

## 1.2 Module Specific Scope

This is the C++ module of the Linux Standards Base (LSB). This module supplements the core interfaces by providing system interfaces, libraries, and a run-time environment for applications built using the C++ programming language. These interfaces provide low-level support for the core constructs of the language, and implement the standard base C++ libraries.

Interfaces described in this module are presented in terms of C++; the binary interfaces will use encoded or mangled versions of the names.

## 2 Normative References

The specifications listed below are referenced in whole or in part by this module of the Linux Standard Base. In this specification, where only a particular section of one of these references is identified, then the normative reference is to that section alone, and the rest of the referenced document is informative.

**Table 2-1 Normative References**

Name	Title	URL
ISO/IEC 23360 Part 1	ISO/IEC 23360:2005 Linux Standard Base - Part 1 Generic Specification	<a href="http://www.linuxbase.org/spec/">http://www.linuxbase.org/spec/</a>
ISO C (1999)	ISO/IEC 9899: 1999, Programming Languages --C	
ISO POSIX (2003)	ISO/IEC 9945-1:2003 Information technology -- Portable Operating System Interface (POSIX) -- Part 1: Base Definitions  ISO/IEC 9945-2:2003 Information technology -- Portable Operating System Interface (POSIX) -- Part 2: Sys- tem Interfaces  ISO/IEC 9945-3:2003 Information technology -- Portable Operating System Interface (POSIX) -- Part 3: Shell and Utilities  ISO/IEC 9945-4:2003 Information technology -- Portable Operating System Interface (POSIX) -- Part 4: Ratio- nale  Including Technical Cor. 1: 2004	<a href="http://www.unix.org/version3/">http://www.unix.org/ version3/</a>
ISO/IEC 14882: 2003 C++ Language	ISO/IEC 14882: 2003 Programming languages --C++	
Itanium™ C++ ABI	Itanium™ C++ ABI (Revision 1.83)	<a href="http://refspecs.linux-foundation.org/cxxabi-1.83.html">http://refspecs.linux- foundation.org/cxxabi- 1.83.html</a>

## 3 Requirements

### 3.1 Relevant Libraries

The libraries listed in [Table 3-1](#) shall be available on a Linux Standard Base system, with the specified runtime names.

**Table 3-1 Standard Library Names**

Library	Runtime Name
libstdcxx	libstdc++.so.6

These libraries will be in an implementation-defined directory which the dynamic linker shall search by default.

### 3.2 LSB Implementation Conformance

An implementation shall satisfy the following requirements:

- The implementation shall implement fully the architecture described in the hardware manual for the target processor architecture.
- The implementation shall be capable of executing compiled applications having the format and using the system interfaces described in this document.
- The implementation shall provide libraries containing the interfaces specified by this document, and shall provide a dynamic linking mechanism that allows these interfaces to be attached to applications at runtime. All the interfaces shall behave as specified in this document.
- The map of virtual memory provided by the implementation shall conform to the requirements of this document.
- The implementation's low-level behavior with respect to function call linkage, system traps, signals, and other such activities shall conform to the formats described in this document.
- The implementation shall provide all of the mandatory interfaces in their entirety.
- The implementation may provide one or more of the optional interfaces. Each optional interface that is provided shall be provided in its entirety. The product documentation shall state which optional interfaces are provided.
- The implementation shall provide all files and utilities specified as part of this document in the format defined here and in other referenced documents. All commands and utilities shall behave as required by this document. The implementation shall also provide all mandatory components of an application's runtime environment that are included or referenced in this document.
- The implementation, when provided with standard data formats and values at a named interface, shall provide the behavior defined for those values and data formats at that interface. However, a conforming implementation may consist of components which are separately packaged and/or sold. For example, a vendor of a conforming implementation might sell the hardware, operating system, and windowing system as separately packaged items.
- The implementation may provide additional interfaces with different names. It may also provide additional behavior corresponding to data values outside

the standard ranges, for standard named interfaces.

### 3.3 LSB Application Conformance

An application shall satisfy the following requirements:

- Its executable files are either shell scripts or object files in the format defined for the Object File Format system interface.
- Its object files participate in dynamic linking as defined in the Program Loading and Linking System interface.
- It employs only the instructions, traps, and other low-level facilities defined in the Low-Level System interface as being for use by applications.
- If it requires any optional interface defined in this document in order to be installed or to execute successfully, the requirement for that optional interface is stated in the application's documentation.
- It does not use any interface or data format that is not required to be provided by a conforming implementation, unless:
  - If such an interface or data format is supplied by another application through direct invocation of that application during execution, that application is in turn an LSB conforming application.
  - The use of that interface or data format, as well as its source, is identified in the documentation of the application.
- It shall not use any values for a named interface that are reserved for vendor extensions.

A strictly conforming application does not require or use any interface, facility, or implementation-defined extension that is not defined in this document in order to be installed or to execute successfully.

## 4 Definitions

For the purposes of this document, the following definitions, as specified in the *ISO/IEC Directives, Part 2, 2001, 4th Edition*, apply:

can

be able to; there is a possibility of; it is possible to

cannot

be unable to; there is no possibility of; it is not possible to

may

is permitted; is allowed; is permissible

need not

it is not required that; no...is required

shall

is to; is required to; it is required that; has to; only...is permitted; it is necessary

shall not

is not allowed [permitted] [acceptable] [permissible]; is required to be not; is required that...be not; is not to be

should

it is recommended that; ought to

should not

it is not recommended that; ought not to

## 5 Terminology

For the purposes of this document, the following terms apply:

### archLSB

The architectural part of the LSB Specification which describes the specific parts of the interface that are platform specific. The archLSB is complementary to the gLSB.

### Binary Standard

The total set of interfaces that are available to be used in the compiled binary code of a conforming application.

### gLSB

The common part of the LSB Specification that describes those parts of the interface that remain constant across all hardware implementations of the LSB.

### implementation-defined

Describes a value or behavior that is not defined by this document but is selected by an implementor. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence of the value or behavior. An application that relies on such a value or behavior cannot be assured to be portable across conforming implementations. The implementor shall document such a value or behavior so that it can be used correctly by an application.

### Shell Script

A file that is read by an interpreter (e.g., awk). The first line of the shell script includes a reference to its interpreter binary.

### Source Standard

The set of interfaces that are available to be used in the source code of a conforming application.

### undefined

Describes the nature of a value or behavior not defined by this document which results from use of an invalid program construct or invalid data input. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence or validity of the value or behavior. An application that relies on any particular value or behavior cannot be assured to be portable across conforming implementations.

### unspecified

Describes the nature of a value or behavior not specified by this document which results from use of a valid program construct or valid data input. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence or validity of the value or behavior. An application that relies on any particular value or behavior cannot be assured to be portable across conforming

## *5 Terminology*

implementations.

Other terms and definitions used in this document shall have the same meaning as defined in Chapter 3 of the Base Definitions volume of [ISO POSIX \(2003\)](#).

## 6 Documentation Conventions

Throughout this document, the following typographic conventions are used:

**function()**

the name of a function

**command**

the name of a command or utility

**CONSTANT**

a constant value

*parameter*

a parameter

**variable**

a variable

Throughout this specification, several tables of interfaces are presented. Each entry in these tables has the following format:

**name**

the name of the interface

**(symver)**

An optional symbol version identifier, if required.

**[refno]**

A reference number indexing the table of referenced specifications that follows this table.

For example,

**forkpty(GLIBC\_2.0) [SUSv3]**

refers to the interface named `forkpty()` with symbol version `GLIBC_2.0` that is defined in the SUSv3 reference.

**Note:** For symbols with versions which differ between architectures, the symbol versions are defined in the architecture specific parts of ISO/IEC 23360 only.

## **II Base Libraries**

## 7 Libraries

An LSB-conforming implementation shall support base libraries which provide interfaces for accessing the operating system, processor and other hardware in the system.

Only those interfaces that are unique to the z/Architecture platform are defined here. This section should be used in conjunction with the corresponding section in the Linux Standard Base Specification.

### 7.1 Interfaces for libstdc++

[Table 7-1](#) defines the library name and shared object name for the libstdc++ library

**Table 7-1 libstdc++ Definition**

Library:	libstdc++
SONAME:	libstdc++.so.6

The behavior of the interfaces in this library is specified by the following specifications:

- [CXXABI] [Itanium™ C++ ABI](#)
- [ISOCXX] [ISO/IEC 14882: 2003 C++ Language](#)
- [LSB] [ISO/IEC 23360 Part 1](#)

#### 7.1.1 C++ Runtime Support

##### 7.1.1.1 Interfaces for C++ Runtime Support

An LSB conforming implementation shall provide the architecture specific methods for C++ Runtime Support specified in [Table 7-2](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-2 libstdc++ - C++ Runtime Support Function Interfaces**

operator new[](unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
operator new[](unsigned long, nothrow_t const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
operator new(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
operator new(unsigned long, nothrow_t const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

#### 7.1.2 C++ type descriptors for built-in types

##### 7.1.2.1 Interfaces for C++ type descriptors for built-in types

No external methods are defined for libstdc++ - C++ type descriptors for built-in types in this part of the specification. See also the generic specification.

#### 7.1.3 C++ \_Rb\_tree

##### 7.1.3.1 Interfaces for C++ \_Rb\_tree

No external methods are defined for libstdc++ - C++ \_Rb\_tree in this part of the specification. See also the generic specification.

## 7.1.4 Class type\_info

### 7.1.4.1 Class data for type\_info

The virtual table for the std::type\_info class is described in the generic part of this specification.

The Run Time Type Information for the std::type\_info class is described by [Table 7-3](#)

**Table 7-3 typeinfo for type\_info**

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for type_info

### 7.1.4.2 Interfaces for Class type\_info

No external methods are defined for libstdcxx - Class std::type\_info in this part of the specification. See also the generic specification.

## 7.1.5 Class \_\_cxxabiv1::\_\_enum\_type\_info

### 7.1.5.1 Class data for \_\_cxxabiv1::\_\_enum\_type\_info

The virtual table for the \_\_cxxabiv1::\_\_enum\_type\_info class is described in the generic part of this specification.

The Run Time Type Information for the \_\_cxxabiv1::\_\_enum\_type\_info class is described by [Table 7-4](#)

**Table 7-4 typeinfo for \_\_cxxabiv1::\_\_enum\_type\_info**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for __cxxabiv1::__enum_type_info

### 7.1.5.2 Interfaces for Class \_\_cxxabiv1::\_\_enum\_type\_info

No external methods are defined for libstdcxx - Class \_\_cxxabiv1::\_\_enum\_type\_info in this part of the specification. See also the generic specification.

## 7.1.6 Class \_\_cxxabiv1::\_\_array\_type\_info

### 7.1.6.1 Class data for \_\_cxxabiv1::\_\_array\_type\_info

The virtual table for the \_\_cxxabiv1::\_\_array\_type\_info class is described in the generic part of this specification.

The Run Time Type Information for the \_\_cxxabiv1::\_\_array\_type\_info class is described by [Table 7-5](#)

**Table 7-5 typeinfo for \_\_cxxabiv1::\_\_array\_type\_info**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for

	<code>__cxxabiv1::__array_type_info</code>
--	--------------------------------------------

### 7.1.6.2 Interfaces for Class `__cxxabiv1::__array_type_info`

No external methods are defined for libstdc++ - Class `__cxxabiv1::__array_type_info` in this part of the specification. See also the generic specification.

## 7.1.7 Class `__cxxabiv1::__class_type_info`

### 7.1.7.1 Class data for `__cxxabiv1::__class_type_info`

The virtual table for the `__cxxabiv1::__class_type_info` class is described by [Table 7-6](#)

**Table 7-6 Primary vtable for `__cxxabiv1::__class_type_info`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>__cxxabiv1::__class_type_info</code>
vfunc[0]:	<code>__cxxabiv1::__class_type_info::~class_type_info()</code>
vfunc[1]:	<code>__cxxabiv1::__class_type_info::~class_type_info()</code>
vfunc[2]:	<code>type_info::is_pointer_p() const</code>
vfunc[3]:	<code>type_info::is_function_p() const</code>
vfunc[4]:	<code>__cxxabiv1::__class_type_info::do_catch(type_info const*, void**, unsigned int) const</code>
vfunc[5]:	<code>__cxxabiv1::__class_type_info::do_upcast(__cxxabiv1::__class_type_info const*, void**) const</code>
vfunc[6]:	<code>__cxxabiv1::__class_type_info::do_upcast(__cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info::upcast_result&amp;) const</code>
vfunc[7]:	<code>__cxxabiv1::__class_type_info::do_dyncast(long, __cxxabiv1::__class_type_info::sub_kind, __cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info::dyn_cast_result&amp;) const</code>
vfunc[8]:	<code>__cxxabiv1::__class_type_info::do_find_public_src(long, void const*, __cxxabiv1::__class_type_info const*, void const*) const</code>

The Run Time Type Information for the `__cxxabiv1::__class_type_info` class is described by [Table 7-7](#)

**Table 7-7 typeinfo for `__cxxabiv1::__class_type_info`**

Base Vtable	vtable for <code>__cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>__cxxabiv1::__class_type_info</code>

### 7.1.7.2 Interfaces for Class `__cxxabiv1::__class_type_info`

An LSB conforming implementation shall provide the architecture specific methods for Class `__cxxabiv1::__class_type_info` specified in [Table 7-8](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-8 libstdc++ - Class `__cxxabiv1::__class_type_info` Function Interfaces**

<code>__cxxabiv1::__class_type_info::__do_dyncast(long, __cxxabiv1::__class_type_info::__sub_kind, __cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info::__dyncast_result&amp;) const(CXXABI_1.3)</code> <a href="#">[CXXABI]</a>
<code>__cxxabiv1::__class_type_info::__do_find_public_src(long, void const*, __cxxabiv1::__class_type_info const*, void const*) const(CXXABI_1.3)</code> <a href="#">[CXXABI]</a>

## 7.1.8 Class `__cxxabiv1::__pbase_type_info`

### 7.1.8.1 Class data for `__cxxabiv1::__pbase_type_info`

The virtual table for the `__cxxabiv1::__pbase_type_info` class is described in the generic part of this specification.

The Run Time Type Information for the `__cxxabiv1::__pbase_type_info` class is described by [Table 7-9](#)

**Table 7-9 typeinfo for `__cxxabiv1::__pbase_type_info`**

Base Vtable	vtable for <code>__cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>__cxxabiv1::__pbase_type_info</code>

### 7.1.8.2 Interfaces for Class `__cxxabiv1::__pbase_type_info`

No external methods are defined for libstdc++ - Class `__cxxabiv1::__pbase_type_info` in this part of the specification. See also the generic specification.

## 7.1.9 Class `__cxxabiv1::__pointer_type_info`

### 7.1.9.1 Class data for `__cxxabiv1::__pointer_type_info`

The virtual table for the `__cxxabiv1::__pointer_type_info` class is described in the generic part of this specification.

The Run Time Type Information for the `__cxxabiv1::__pointer_type_info` class is described by [Table 7-10](#)

**Table 7-10 typeinfo for `__cxxabiv1::__pointer_type_info`**

Base Vtable	vtable for <code>__cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>__cxxabiv1::__pointer_type_info</code>

### 7.1.9.2 Interfaces for Class `__cxxabiv1::__pointer_type_info`

No external methods are defined for libstdcxx - Class `__cxxabiv1::__pointer_type_info` in this part of the specification. See also the generic specification.

## 7.1.10 Class `__cxxabiv1::__function_type_info`

### 7.1.10.1 Class data for `__cxxabiv1::__function_type_info`

The virtual table for the `__cxxabiv1::__function_type_info` class is described in the generic part of this specification.

The Run Time Type Information for the `__cxxabiv1::__function_type_info` class is described by [Table 7-11](#)

**Table 7-11 typeinfo for `__cxxabiv1::__function_type_info`**

Base Vtable	vtable for <code>__cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>__cxxabiv1::__function_type_info</code>

### 7.1.10.2 Interfaces for Class `__cxxabiv1::__function_type_info`

No external methods are defined for libstdcxx - Class `__cxxabiv1::__function_type_info` in this part of the specification. See also the generic specification.

## 7.1.11 Class `__cxxabiv1::__si_class_type_info`

### 7.1.11.1 Class data for `__cxxabiv1::__si_class_type_info`

The virtual table for the `__cxxabiv1::__si_class_type_info` class is described by [Table 7-12](#)

**Table 7-12 Primary vtable for `__cxxabiv1::__si_class_type_info`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>__cxxabiv1::__si_class_type_info</code>
vfunc[0]:	<code>__cxxabiv1::__si_class_type_info::~_si_class_type_info()</code>
vfunc[1]:	<code>__cxxabiv1::__si_class_type_info::~_si_class_type_info()</code>

vfunc[2]:	type_info::__is_pointer_p() const
vfunc[3]:	type_info::__is_function_p() const
vfunc[4]:	__cxxabiv1::__class_type_info::__do_catch(type_info const*, void**, unsigned int) const
vfunc[5]:	__cxxabiv1::__class_type_info::__do_upcast(__cxxabiv1::__class_type_info const*, void**) const
vfunc[6]:	__cxxabiv1::__si_class_type_info::__do_upcast(__cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info::upcast_result&) const
vfunc[7]:	__cxxabiv1::__si_class_type_info::__do_dyncast(long, __cxxabiv1::__class_type_info::__sub_kind, __cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info::dyncast_result&) const
vfunc[8]:	__cxxabiv1::__si_class_type_info::__do_find_public_src(long, void const*, __cxxabiv1::__class_type_info const*, void const*) const

The Run Time Type Information for the \_\_cxxabiv1::\_\_si\_class\_type\_info class is described by [Table 7-13](#)

**Table 7-13 typeinfo for \_\_cxxabiv1::\_\_si\_class\_type\_info**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for __cxxabiv1::__si_class_type_info

### 7.1.11.2 Interfaces for Class \_\_cxxabiv1::\_\_si\_class\_type\_info

An LSB conforming implementation shall provide the architecture specific methods for Class \_\_cxxabiv1::\_\_si\_class\_type\_info specified in [Table 7-14](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-14 libstdcxx - Class \_\_cxxabiv1::\_\_si\_class\_type\_info Function Interfaces**

```
__cxxabiv1::__si_class_type_info::__do_dyncast(long,
__cxxabiv1::__class_type_info::__sub_kind, __cxxabiv1::__class_type_info
const*, void const*, __cxxabiv1::__class_type_info const*, void const*,
__cxxabiv1::__class_type_info::dyncast_result&) const(CXXABI_1.3)
[CXXABI]
```

```

__cxxabiv1::__si_class_type_info::__do_find_public_src(long, void const*,
__cxxabiv1::__class_type_info const*, void const*) const(CXXABI_1.3)
\[CXXABI\]

```

## 7.1.12 Class \_\_cxxabiv1::\_\_vmi\_class\_type\_info

### 7.1.12.1 Class data for \_\_cxxabiv1::\_\_vmi\_class\_type\_info

The virtual table for the \_\_cxxabiv1::\_\_vmi\_class\_type\_info class is described by [Table 7-15](#)

**Table 7-15 Primary vtable for \_\_cxxabiv1::\_\_vmi\_class\_type\_info**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for __cxxabiv1::__vmi_class_type_info
vfunc[0]:	__cxxabiv1::__vmi_class_type_info:: ~vmi_class_type_info()
vfunc[1]:	__cxxabiv1::__vmi_class_type_info:: ~vmi_class_type_info()
vfunc[2]:	type_info:: is_pointer_p() const
vfunc[3]:	type_info:: is_function_p() const
vfunc[4]:	__cxxabiv1::__class_type_info::__do_ catch(type_info const*, void**, unsigned int) const
vfunc[5]:	__cxxabiv1::__class_type_info::__do_ upcast(__cxxabiv1::__class_type_info const*, void**) const
vfunc[6]:	__cxxabiv1::__vmi_class_type_info::__ do_upcast(__cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info::upc ast_result&) const
vfunc[7]:	__cxxabiv1::__vmi_class_type_info::__ do_dyncast(long, __cxxabiv1::__class_type_info::sub _kind, __cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info::dyn cast_result&) const
vfunc[8]:	__cxxabiv1::__vmi_class_type_info::__ do_find_public_src(long, void const*, __cxxabiv1::__class_type_info const*, void const*) const

The Run Time Type Information for the \_\_cxxabiv1::\_\_vmi\_class\_type\_info class is described by [Table 7-16](#)

**Table 7-16 typeinfo for \_\_cxxabiv1::\_\_vmi\_class\_type\_info**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for __cxxabiv1::__vmi_class_type_info

### 7.1.12.2 Interfaces for Class \_\_cxxabiv1::\_\_vmi\_class\_type\_info

An LSB conforming implementation shall provide the architecture specific methods for Class \_\_cxxabiv1::\_\_vmi\_class\_type\_info specified in [Table 7-17](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-17 libstdcxx - Class \_\_cxxabiv1::\_\_vmi\_class\_type\_info Function Interfaces**

<code>__cxxabiv1::__vmi_class_type_info::__do_dyncast(long, __cxxabiv1::__class_type_info::__sub_kind, __cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info::__dyncast_result&amp;) const(CXXABI_1.3)</code> <a href="#">[CXXABI]</a>
<code>__cxxabiv1::__vmi_class_type_info::__do_find_public_src(long, void const*, __cxxabiv1::__class_type_info const*, void const*) const(CXXABI_1.3)</code> <a href="#">[CXXABI]</a>

### 7.1.13 Class \_\_cxxabiv1::\_\_fundamental\_type\_info

#### 7.1.13.1 Class data for \_\_cxxabiv1::\_\_fundamental\_type\_info

The virtual table for the \_\_cxxabiv1::\_\_fundamental\_type\_info class is described in the generic part of this specification.

The Run Time Type Information for the \_\_cxxabiv1::\_\_fundamental\_type\_info class is described by [Table 7-18](#)

**Table 7-18 typeinfo for \_\_cxxabiv1::\_\_fundamental\_type\_info**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for __cxxabiv1::__fundamental_type_info

#### 7.1.13.2 Interfaces for Class \_\_cxxabiv1::\_\_fundamental\_type\_info

No external methods are defined for libstdcxx - Class \_\_cxxabiv1::\_\_fundamental\_type\_info in this part of the specification. See also the generic specification.

### 7.1.14 Class

#### \_\_cxxabiv1::\_\_pointer\_to\_member\_type\_info

##### 7.1.14.1 Class data for \_\_cxxabiv1::\_\_pointer\_to\_member\_type\_info

The virtual table for the \_\_cxxabiv1::\_\_pointer\_to\_member\_type\_info class is described in the generic part of this specification.

The Run Time Type Information for the `_cxxabiv1::__pointer_to_member_type_info` class is described by [Table 7-19](#)

**Table 7-19 typeinfo for `_cxxabiv1::__pointer_to_member_type_info`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>_cxxabiv1::__pointer_to_member_type_info</code>

#### 7.1.14.2 Interfaces for Class

##### **`_cxxabiv1::__pointer_to_member_type_info`**

No external methods are defined for libstdcxx - Class `_cxxabiv1::__pointer_to_member_type_info` in this part of the specification. See also the generic specification.

#### 7.1.15 Class `_gnu_cxx::stdio_filebuf<char, char_traits<char> >`

##### **7.1.15.1 Interfaces for Class `_gnu_cxx::stdio_filebuf<char, char_traits<char> >`**

No external methods are defined for libstdcxx - Class `_gnu_cxx::stdio_filebuf<char, std::char_traits<char> >` in this part of the specification. See also the generic specification.

#### 7.1.16 Class `_gnu_cxx::stdio_filebuf<wchar_t, char_traits<wchar_t> >`

##### **7.1.16.1 Interfaces for Class `_gnu_cxx::stdio_filebuf<wchar_t, char_traits<wchar_t> >`**

No external methods are defined for libstdcxx - Class `_gnu_cxx::stdio_filebuf<wchar_t, std::char_traits<wchar_t> >` in this part of the specification. See also the generic specification.

#### 7.1.17 Class `_gnu_cxx::__pool_alloc_base`

##### **7.1.17.1 Interfaces for Class `_gnu_cxx::__pool_alloc_base`**

An LSB conforming implementation shall provide the architecture specific methods for Class `_gnu_cxx::__pool_alloc_base` specified in [Table 7-20](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-20 libstdcxx - Class `_gnu_cxx::__pool_alloc_base` Function Interfaces**

<code>_gnu_cxx::__pool_alloc_base::__M_get_free_list(unsigned long)</code> (GLIBCXX_3.4.2) <a href="#">[LSB]</a>
<code>_gnu_cxx::__pool_alloc_base::__M_refill(unsigned long)</code> (GLIBCXX_3.4.2) <a href="#">[LSB]</a>

## 7.1.18 Class `__gnu_cxx::stdio_sync_filebuf<char, char_traits<char> >`

### 7.1.18.1 Class data for `__gnu_cxx::stdio_sync_filebuf<char, char_traits<char> >`

The virtual table for the `__gnu_cxx::stdio_sync_filebuf<char, std::char_traits<char> >` class is described by [Table 7-21](#)

**Table 7-21 Primary vtable for `__gnu_cxx::stdio_sync_filebuf<char, char_traits<char> >`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt; &gt;</code>
vfunc[0]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt; &gt;::~stdio_sync_filebuf()</code>
vfunc[1]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt; &gt;::~stdio_sync_filebuf()</code>
vfunc[2]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt; &gt;::imbue(locale const&amp;)</code>
vfunc[3]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt; &gt;::setbuf(char*, long)</code>
vfunc[4]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt; &gt;::seekoff(long, _Ios_Seekdir, _Ios_Openmode)</code>
vfunc[5]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt; &gt;::seekpos(fpos&lt;_mbstate_t&gt;, _Ios_Openmode)</code>
vfunc[6]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt; &gt;::sync()</code>
vfunc[7]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt; &gt;::showmanyc()</code>
vfunc[8]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt; &gt;::xsgetn(char*, long)</code>
vfunc[9]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt; &gt;::underflow()</code>
vfunc[10]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt; &gt;::uflow()</code>
vfunc[11]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt; &gt;::pbackfail(int)</code>

vfunc[12]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt; &gt;::xputn(char const*, long)</code>
vfunc[13]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt; &gt;::overflow(int)</code>

### 7.1.18.2 Interfaces for Class `__gnu_cxx::stdio_sync_filebuf<char, char_traits<char> >`

No external methods are defined for libstdcxx - Class `__gnu_cxx::stdio_sync_filebuf<char, std::char_traits<char> >` in this part of the specification. See also the generic specification.

### 7.1.19 Class `__gnu_cxx::stdio_sync_filebuf<wchar_t, char_traits<wchar_t> >`

#### 7.1.19.1 Class data for `__gnu_cxx::stdio_sync_filebuf<wchar_t, char_traits<wchar_t> >`

The virtual table for the `__gnu_cxx::stdio_sync_filebuf<wchar_t, std::char_traits<wchar_t> >` class is described by [Table 7-22](#)

**Table 7-22 Primary vtable for `__gnu_cxx::stdio_sync_filebuf<wchar_t, char_traits<wchar_t> >`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;</code>
vfunc[0]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::~stdio_sync_filebuf()</code>
vfunc[1]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::~stdio_sync_filebuf()</code>
vfunc[2]:	<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::imbue(locale const&amp;)</code>
vfunc[3]:	<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::setbuf(wchar_t*, long)</code>
vfunc[4]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::seekoff(long, _Ios_Seekdir, _Ios_Openmode)</code>
vfunc[5]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::seekpos(fpos&lt;__mbstate_t&gt;, _Ios_Openmode)</code>
vfunc[6]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::overflow(int)</code>

	<code>r_t, char_traits&lt;wchar_t&gt; &gt;::sync()</code>
vfunc[7]:	<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::showmany()</code>
vfunc[8]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::xsgetn(wchar_t*, long)</code>
vfunc[9]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::underflow()</code>
vfunc[10]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::uflow()</code>
vfunc[11]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::pbackfail(unsigned int)</code>
vfunc[12]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::xsputn(wchar_t const*, long)</code>
vfunc[13]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::overflow(unsigned int)</code>

### 7.1.19.2 Interfaces for Class

`__gnu_cxx::stdio_sync_filebuf<wchar_t, char_traits<wchar_t> >`

No external methods are defined for libstdcxx - Class `__gnu_cxx::stdio_sync_filebuf<wchar_t, std::char_traits<wchar_t> >` in this part of the specification. See also the generic specification.

## 7.1.20 Class exception

### 7.1.20.1 Class data for exception

The virtual table for the `std::exception` class is described in the generic part of this specification.

The Run Time Type Information for the `std::exception` class is described by [Table 7-23](#)

**Table 7-23 typeinfo for exception**

Base Vtable	vtable for <code>__cxxabiv1::__class_type_info</code>
Name	typeinfo name for exception

### 7.1.20.2 Interfaces for Class exception

No external methods are defined for libstdcxx - Class `std::exception` in this part of the specification. See also the generic specification.

## 7.1.21 Class bad\_typeid

### 7.1.21.1 Class data for bad\_typeid

The virtual table for the std::bad\_typeid class is described in the generic part of this specification.

The Run Time Type Information for the std::bad\_typeid class is described by [Table 7-24](#)

**Table 7-24 typeinfo for bad\_typeid**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for bad_typeid

### 7.1.21.2 Interfaces for Class bad\_typeid

No external methods are defined for libstdcxx - Class std::bad\_typeid in this part of the specification. See also the generic specification.

## 7.1.22 Class logic\_error

### 7.1.22.1 Class data for logic\_error

The virtual table for the std::logic\_error class is described in the generic part of this specification.

The Run Time Type Information for the std::logic\_error class is described by [Table 7-25](#)

**Table 7-25 typeinfo for logic\_error**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for logic_error

### 7.1.22.2 Interfaces for Class logic\_error

No external methods are defined for libstdcxx - Class std::logic\_error in this part of the specification. See also the generic specification.

## 7.1.23 Class range\_error

### 7.1.23.1 Class data for range\_error

The virtual table for the std::range\_error class is described in the generic part of this specification.

The Run Time Type Information for the std::range\_error class is described by [Table 7-26](#)

**Table 7-26 typeinfo for range\_error**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for range_error

### 7.1.23.2 Interfaces for Class range\_error

No external methods are defined for libstdcxx - Class std::range\_error in this part of the specification. See also the generic specification.

## 7.1.24 Class domain\_error

### 7.1.24.1 Class data for domain\_error

The virtual table for the std::domain\_error class is described in the generic part of this specification.

The Run Time Type Information for the std::domain\_error class is described by [Table 7-27](#)

**Table 7-27 typeinfo for domain\_error**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for domain_error

### 7.1.24.2 Interfaces for Class domain\_error

No external methods are defined for libstdcxx - Class std::domain\_error in this part of the specification. See also the generic specification.

## 7.1.25 Class length\_error

### 7.1.25.1 Class data for length\_error

The virtual table for the std::length\_error class is described in the generic part of this specification.

The Run Time Type Information for the std::length\_error class is described by [Table 7-28](#)

**Table 7-28 typeinfo for length\_error**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for length_error

### 7.1.25.2 Interfaces for Class length\_error

No external methods are defined for libstdcxx - Class std::length\_error in this part of the specification. See also the generic specification.

## 7.1.26 Class out\_of\_range

### 7.1.26.1 Class data for out\_of\_range

The virtual table for the std::out\_of\_range class is described in the generic part of this specification.

The Run Time Type Information for the std::out\_of\_range class is described by [Table 7-29](#)

**Table 7-29 typeinfo for out\_of\_range**

Base Vtable	vtable for
-------------	------------

	<code>__cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>out_of_range</code>

### 7.1.26.2 Interfaces for Class `out_of_range`

No external methods are defined for libstdc++ - Class `std::out_of_range` in this part of the specification. See also the generic specification.

## 7.1.27 Class `bad_exception`

### 7.1.27.1 Class data for `bad_exception`

The virtual table for the `std::bad_exception` class is described in the generic part of this specification.

The Run Time Type Information for the `std::bad_exception` class is described by [Table 7-30](#)

**Table 7-30 typeinfo for `bad_exception`**

Base Vtable	vtable for <code>__cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>bad_exception</code>

### 7.1.27.2 Interfaces for Class `bad_exception`

No external methods are defined for libstdc++ - Class `std::bad_exception` in this part of the specification. See also the generic specification.

## 7.1.28 Class `runtime_error`

### 7.1.28.1 Class data for `runtime_error`

The virtual table for the `std::runtime_error` class is described in the generic part of this specification.

The Run Time Type Information for the `std::runtime_error` class is described by [Table 7-31](#)

**Table 7-31 typeinfo for `runtime_error`**

Base Vtable	vtable for <code>__cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>runtime_error</code>

### 7.1.28.2 Interfaces for Class `runtime_error`

No external methods are defined for libstdc++ - Class `std::runtime_error` in this part of the specification. See also the generic specification.

## 7.1.29 Class `overflow_error`

### 7.1.29.1 Class data for `overflow_error`

The virtual table for the `std::overflow_error` class is described in the generic part of this specification.

The Run Time Type Information for the `std::overflow_error` class is described

by [Table 7-32](#)

**Table 7-32 typeinfo for overflow\_error**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for overflow_error

### 7.1.29.2 Interfaces for Class overflow\_error

No external methods are defined for libstdcxx - Class std::overflow\_error in this part of the specification. See also the generic specification.

## 7.1.30 Class underflow\_error

### 7.1.30.1 Class data for underflow\_error

The virtual table for the std::underflow\_error class is described in the generic part of this specification.

The Run Time Type Information for the std::underflow\_error class is described by [Table 7-33](#)

**Table 7-33 typeinfo for underflow\_error**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for underflow_error

### 7.1.30.2 Interfaces for Class underflow\_error

No external methods are defined for libstdcxx - Class std::underflow\_error in this part of the specification. See also the generic specification.

## 7.1.31 Class invalid\_argument

### 7.1.31.1 Class data for invalid\_argument

The virtual table for the std::invalid\_argument class is described in the generic part of this specification.

The Run Time Type Information for the std::invalid\_argument class is described by [Table 7-34](#)

**Table 7-34 typeinfo for invalid\_argument**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for invalid_argument

### 7.1.31.2 Interfaces for Class invalid\_argument

No external methods are defined for libstdcxx - Class std::invalid\_argument in this part of the specification. See also the generic specification.

## 7.1.32 Class `bad_cast`

### 7.1.32.1 Class data for `bad_cast`

The virtual table for the `std::bad_cast` class is described in the generic part of this specification.

The Run Time Type Information for the `std::bad_cast` class is described by [Table 7-35](#)

**Table 7-35 typeinfo for `bad_cast`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>bad_cast</code>

### 7.1.32.2 Interfaces for Class `bad_cast`

No external methods are defined for libstdc++ - Class `std::bad_cast` in this part of the specification. See also the generic specification.

## 7.1.33 Class `bad_alloc`

### 7.1.33.1 Class data for `bad_alloc`

The virtual table for the `std::bad_alloc` class is described in the generic part of this specification.

The Run Time Type Information for the `std::bad_alloc` class is described by [Table 7-36](#)

**Table 7-36 typeinfo for `bad_alloc`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>bad_alloc</code>

### 7.1.33.2 Interfaces for Class `bad_alloc`

No external methods are defined for libstdc++ - Class `std::bad_alloc` in this part of the specification. See also the generic specification.

## 7.1.34 struct `__numeric_limits_base`

### 7.1.34.1 Interfaces for struct `__numeric_limits_base`

No external methods are defined for libstdc++ - struct `__numeric_limits_base` in this part of the specification. See also the generic specification.

## 7.1.35 struct `numeric_limits<long double>`

### 7.1.35.1 Interfaces for struct `numeric_limits<long double>`

No external methods are defined for libstdc++ - struct `numeric_limits<long double>` in this part of the specification. See also the generic specification.

## 7.1.36 struct numeric\_limits<long long>

### 7.1.36.1 Interfaces for struct numeric\_limits<long long>

No external methods are defined for libstdcxx - struct numeric\_limits<long long> in this part of the specification. See also the generic specification.

## 7.1.37 struct numeric\_limits<unsigned long long>

### 7.1.37.1 Interfaces for struct numeric\_limits<unsigned long long>

No external methods are defined for libstdcxx - struct numeric\_limits<unsigned long long> in this part of the specification. See also the generic specification.

## 7.1.38 struct numeric\_limits<float>

### 7.1.38.1 Interfaces for struct numeric\_limits<float>

No external methods are defined for libstdcxx - struct numeric\_limits<float> in this part of the specification. See also the generic specification.

## 7.1.39 struct numeric\_limits<double>

### 7.1.39.1 Interfaces for struct numeric\_limits<double>

No external methods are defined for libstdcxx - struct numeric\_limits<double> in this part of the specification. See also the generic specification.

## 7.1.40 struct numeric\_limits<short>

### 7.1.40.1 Interfaces for struct numeric\_limits<short>

No external methods are defined for libstdcxx - struct numeric\_limits<short> in this part of the specification. See also the generic specification.

## 7.1.41 struct numeric\_limits<unsigned short>

### 7.1.41.1 Interfaces for struct numeric\_limits<unsigned short>

No external methods are defined for libstdcxx - struct numeric\_limits<unsigned short> in this part of the specification. See also the generic specification.

## 7.1.42 struct numeric\_limits<int>

### 7.1.42.1 Interfaces for struct numeric\_limits<int>

No external methods are defined for libstdcxx - struct numeric\_limits<int> in this part of the specification. See also the generic specification.

## 7.1.43 struct numeric\_limits<unsigned int>

### 7.1.43.1 Interfaces for struct numeric\_limits<unsigned int>

No external methods are defined for libstdcxx - struct numeric\_limits<unsigned int> in this part of the specification. See also the generic specification.

## **7.1.44 struct numeric\_limits<long>**

### **7.1.44.1 Interfaces for struct numeric\_limits<long>**

No external methods are defined for libstdcxx - struct numeric\_limits<long> in this part of the specification. See also the generic specification.

## **7.1.45 struct numeric\_limits<unsigned long>**

### **7.1.45.1 Interfaces for struct numeric\_limits<unsigned long>**

No external methods are defined for libstdcxx - struct numeric\_limits<unsigned long> in this part of the specification. See also the generic specification.

## **7.1.46 struct numeric\_limits<wchar\_t>**

### **7.1.46.1 Interfaces for struct numeric\_limits<wchar\_t>**

No external methods are defined for libstdcxx - struct numeric\_limits<wchar\_t> in this part of the specification. See also the generic specification.

## **7.1.47 struct numeric\_limits<unsigned char>**

### **7.1.47.1 Interfaces for struct numeric\_limits<unsigned char>**

No external methods are defined for libstdcxx - struct numeric\_limits<unsigned char> in this part of the specification. See also the generic specification.

## **7.1.48 struct numeric\_limits<signed char>**

### **7.1.48.1 Interfaces for struct numeric\_limits<signed char>**

No external methods are defined for libstdcxx - struct numeric\_limits<signed char> in this part of the specification. See also the generic specification.

## **7.1.49 struct numeric\_limits<char>**

### **7.1.49.1 Interfaces for struct numeric\_limits<char>**

No external methods are defined for libstdcxx - struct numeric\_limits<char> in this part of the specification. See also the generic specification.

## **7.1.50 struct numeric\_limits<bool>**

### **7.1.50.1 Interfaces for struct numeric\_limits<bool>**

No external methods are defined for libstdcxx - struct numeric\_limits<bool> in this part of the specification. See also the generic specification.

## **7.1.51 Class ctype\_base**

### **7.1.51.1 Class data for ctype\_base**

The Run Time Type Information for the std::ctype\_base class is described by [Table 7-37](#)

**Table 7-37 typeinfo for ctype\_base**

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for ctype_base

### 7.1.51.2 Interfaces for Class ctype\_base

No external methods are defined for libstdcxx - Class std::ctype\_base in this part of the specification. See also the generic specification.

## 7.1.52 Class \_\_ctype\_abstract\_base<char>

### 7.1.52.1 Class data for \_\_ctype\_abstract\_base<char>

The virtual table for the std::\_\_ctype\_abstract\_base<char> class is described in the generic part of this specification.

### 7.1.52.2 Interfaces for Class \_\_ctype\_abstract\_base<char>

No external methods are defined for libstdcxx - Class std::\_\_ctype\_abstract\_base<char> in this part of the specification. See also the generic specification.

## 7.1.53 Class \_\_ctype\_abstract\_base<wchar\_t>

### 7.1.53.1 Class data for \_\_ctype\_abstract\_base<wchar\_t>

The virtual table for the std::\_\_ctype\_abstract\_base<wchar\_t> class is described in the generic part of this specification.

### 7.1.53.2 Interfaces for Class \_\_ctype\_abstract\_base<wchar\_t>

No external methods are defined for libstdcxx - Class std::\_\_ctype\_abstract\_base<wchar\_t> in this part of the specification. See also the generic specification.

## 7.1.54 Class ctype<char>

### 7.1.54.1 Class data for ctype<char>

The virtual table for the std::ctype<char> class is described in the generic part of this specification.

### 7.1.54.2 Interfaces for Class ctype<char>

An LSB conforming implementation shall provide the architecture specific methods for Class std::ctype<char> specified in [Table 7-38](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-38 libstdcxx - Class ctype<char> Function Interfaces**

ctype<char>::ctype(__locale_struct*, unsigned short const*, bool, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype<char>::ctype(unsigned short const*, bool, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype<char>::ctype(__locale_struct*, unsigned short const*, bool, unsigned

long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype<char>::ctype(unsigned short const*, bool, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 7.1.55 Class ctype<wchar\_t>

### 7.1.55.1 Class data for ctype<wchar\_t>

The virtual table for the std::ctype<wchar\_t> class is described in the generic part of this specification.

The Run Time Type Information for the std::ctype<wchar\_t> class is described by [Table 7-39](#)

**Table 7-39 typeinfo for ctype<wchar\_t>**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for ctype<wchar_t>

### 7.1.55.2 Interfaces for Class ctype<wchar\_t>

An LSB conforming implementation shall provide the architecture specific methods for Class std::ctype<wchar\_t> specified in [Table 7-40](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-40 libstdc++ - Class ctype<wchar\_t> Function Interfaces**

ctype<wchar_t>::ctype(__locale_struct*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype<wchar_t>::ctype(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype<wchar_t>::ctype(__locale_struct*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype<wchar_t>::ctype(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 7.1.56 Class ctype\_byname<char>

### 7.1.56.1 Class data for ctype\_byname<char>

The virtual table for the std::ctype\_byname<char> class is described in the generic part of this specification.

The Run Time Type Information for the std::ctype\_byname<char> class is described by [Table 7-41](#)

**Table 7-41 typeinfo for ctype\_byname<char>**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for ctype_byname<char>

### 7.1.56.2 Interfaces for Class ctype\_byname<char>

An LSB conforming implementation shall provide the architecture specific methods for Class std::ctype\_byname<char> specified in [Table 7-42](#), with the

full mandatory functionality as described in the referenced underlying specification.

**Table 7-42 libstdcxx - Class ctype\_byname<char> Function Interfaces**

ctype_byname<char>::ctype_byname(char const*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype_byname<char>::ctype_byname(char const*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 7.1.57 Class ctype\_byname<wchar\_t>

### 7.1.57.1 Class data for ctype\_byname<wchar\_t>

The virtual table for the std::ctype\_byname<wchar\_t> class is described in the generic part of this specification.

The Run Time Type Information for the std::ctype\_byname<wchar\_t> class is described by [Table 7-43](#)

**Table 7-43 typeinfo for ctype\_byname<wchar\_t>**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for ctype_byname<wchar_t>

### 7.1.57.2 Interfaces for Class ctype\_byname<wchar\_t>

An LSB conforming implementation shall provide the architecture specific methods for Class std::ctype\_byname<wchar\_t> specified in [Table 7-44](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-44 libstdcxx - Class ctype\_byname<wchar\_t> Function Interfaces**

ctype_byname<wchar_t>::ctype_byname(char const*, unsigned long) (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
ctype_byname<wchar_t>::ctype_byname(char const*, unsigned long) (GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 7.1.58 Class basic\_string<char, char\_traits<char>, allocator<char> >

### 7.1.58.1 Interfaces for Class basic\_string<char, char\_traits<char>, allocator<char> >

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_string<char, std::char\_traits<char>, std::allocator<char> > specified in [Table 7-45](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-45 libstdcxx - Class basic\_string<char, char\_traits<char>, allocator<char> > Function Interfaces**

basic_string<char, char_traits<char>, allocator<char> >::find_last_of(char const*, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
-----------------------------------------------------------------------------------------------------------------------------------------------

basic_string<char, char_traits<char>, allocator<char> >::find_last_of(char const*, unsigned long, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::find_last_of(basic_string<char, char_traits<char>, allocator<char> > const&, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::find_last_of(char, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::find_first_of(char const*, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::find_first_of(char const*, unsigned long, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::find_first_of(basic_string<char, char_traits<char>, allocator<char> > const&, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::find_first_of(char, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::_M_check_length(unsigned long, unsigned long, char const*) const(GLIBCXX_3.4.5) <a href="#">[ISOCXXI]</a>
basic_string<char, char_traits<char>, allocator<char> >::find_last_not_of(char const*, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::find_last_not_of(char const*, unsigned long, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::find_last_not_of(basic_string<char, char_traits<char>, allocator<char> > const&, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::find_last_not_of(char, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::find_first_not_of(char const*, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::find_first_not_of(char const*, unsigned long, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::find_first_not_of(basic_string<char, char_traits<char>, allocator<char> > const&, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::find_first_not_of(char, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::at(unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::copy(char*, unsigned long, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::find(char const*, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

basic_string<char, char_traits<char>, allocator<char>>::find(char const*, unsigned long, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::find(basic_string<char, char_traits<char>, allocator<char>> const&, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::find(char, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::rfind(char const*, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::rfind(char const*, unsigned long, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::rfind(basic_string<char, char_traits<char>, allocator<char>> const&, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::rfind(char, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::substr(unsigned long, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::compare(unsigned long, unsigned long, char const*) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::compare(unsigned long, unsigned long, char const*, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::compare(unsigned long, unsigned long, basic_string<char, char_traits<char>, allocator<char>> const&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::compare(unsigned long, unsigned long, basic_string<char, char_traits<char>, allocator<char>> const&, unsigned long, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::_M_check(unsigned long, char const*) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::_M_limit(unsigned long, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::operator[](unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::_S_construct(unsigned long, char, allocator<char> const&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::_M_replace_aux(unsigned long, unsigned long, unsigned long, char) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::_M_replace_safe(unsigned long, unsigned long, char const*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::at(unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

basic_string<char, char_traits<char>, allocator<char>>::_Rep::_M_set_length_and_sharable(unsigned long)(GLIBCXX_3.4.5) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::_Rep::_M_clone(allocator<char> const&, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::_Rep::_S_create(unsigned long, unsigned long, allocator<char> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::erase(unsigned long, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::append(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::append(basic_string<char, char_traits<char>, allocator<char>> const&, unsigned long, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::append(unsigned long, char)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::assign(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::assign(basic_string<char, char_traits<char>, allocator<char>> const&, unsigned long, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::assign(unsigned long, char)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::insert(_gnu_cxx::__normal_iterator<char*>, basic_string<char, char_traits<char>, allocator<char>> const&, unsigned long, char)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::insert(unsigned long, char const*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::insert(unsigned long, char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::insert(unsigned long, basic_string<char, char_traits<char>, allocator<char>> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::insert(unsigned long, basic_string<char, char_traits<char>, allocator<char>> const&, unsigned long, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::insert(unsigned long, unsigned long, char)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::resize(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::resize(unsigned long, char)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::_M_copy(char*, char const*, unsigned long)(GLIBCXX_3.4.5) <a href="#">[ISOCXX]</a>

basic_string<char, char_traits<char>, allocator<char>>::_M_move(char*, char const*, unsigned long)(GLIBCXX_3.4.5) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::replace(_gnu_cxx::__normal_iterator<char*, basic_string<char, char_traits<char>, allocator<char>> >, _gnu_cxx::__normal_iterator<char*, basic_string<char, char_traits<char>, allocator<char>> >, char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::replace(_gnu_cxx::__normal_iterator<char*, basic_string<char, char_traits<char>, allocator<char>> >, _gnu_cxx::__normal_iterator<char*, basic_string<char, char_traits<char>, allocator<char>> >, unsigned long, char)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::replace(unsigned long, unsigned long, char const*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::replace(unsigned long, unsigned long, char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::replace(unsigned long, unsigned long, basic_string<char, char_traits<char>, allocator<char>> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::replace(unsigned long, unsigned long, basic_string<char, char_traits<char>, allocator<char>> const&, unsigned long, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::replace(unsigned long, unsigned long, unsigned long, char)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::reserve(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::_M_assign(char*, unsigned long, char)(GLIBCXX_3.4.5) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::_M_mutate(unsigned long, unsigned long, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::basic_string(char const*, unsigned long, allocator<char> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::basic_string(basic_string<char, char_traits<char>, allocator<char>> const&, unsigned long, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::basic_string(basic_string<char, char_traits<char>, allocator<char>> const&, unsigned long, unsigned long, allocator<char> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::basic_string(unsigned long, char, allocator<char> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::basic_string(char const*, unsigned long, allocator<char> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::basic_string(basic_string<char, char_traits<char>, allocator<char>> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

const&, unsigned long, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::basic_string(basic_string<char, char_traits<char>, allocator<char>>, const&, unsigned long, unsigned long, allocator<char> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::basic_string(unsigned long, char, allocator<char> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 7.1.59 Class `basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >`

### 7.1.59.1 Interfaces for Class `basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::basic_string<wchar_t, std::char_traits<wchar_t>, std::allocator<wchar_t> >` specified in [Table 7-46](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-46 libstdcxx - Class `basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >` Function Interfaces**

basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::find_last_of(wchar_t const*, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::find_last_of(wchar_t const*, unsigned long, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::find_last_of(basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>, const&, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::find_last_of(wchar_t, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::find_first_of(wchar_t const*, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::find_first_of(wchar_t const*, unsigned long, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::find_first_of(basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>, const&, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::find_first_of(wchar_t, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::_M_check_length(unsigned long, unsigned long, char const*) const(GLIBCXX_3.4.5) <a href="#">[ISOCXXI]</a>



basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::substr(unsigned long, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::compare(unsigned long, unsigned long, wchar_t const*) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::compare(unsigned long, unsigned long, wchar_t const*, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::compare(unsigned long, unsigned long, basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>> const&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::compare(unsigned long, unsigned long, basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>> const&, unsigned long, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::_M_check(unsigned long, char const*) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::_M_limit(unsigned long, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::operator[](unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::_S_construct(unsigned long, wchar_t, allocator<wchar_t> const&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::_M_replace_aux(unsigned long, unsigned long, unsigned long, wchar_t) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::_M_replace_safe(unsigned long, unsigned long, wchar_t const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::at(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::_Rep::_M_set_length_and_sharable(unsigned long)(GLIBCXX_3.4.5) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::_Rep::_M_clone(allocator<wchar_t> const&, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::_Rep::_S_create(unsigned long, unsigned long, allocator<wchar_t> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::erase(unsigned long, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::append(wchar_t const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>

>::append(basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>> const&, unsigned long, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::append(unsigned long, wchar_t)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::assign(wchar_t const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::assign(basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>> const&, unsigned long, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::assign(unsigned long, wchar_t)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::insert(__gnu_cxx::__normal_iterator<wchar_t*, basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>> >, unsigned long, wchar_t)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::insert(unsigned long, wchar_t const*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::insert(unsigned long, wchar_t const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::insert(unsigned long, basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::insert(unsigned long, basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>> const&, unsigned long, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::insert(unsigned long, unsigned long, wchar_t)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::resize(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::resize(unsigned long, wchar_t)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::_M_copy(wchar_t*, wchar_t const*, unsigned long)(GLIBCXX_3.4.5) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::_M_move(wchar_t*, wchar_t const*, unsigned long)(GLIBCXX_3.4.5) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::replace(__gnu_cxx::__normal_iterator<wchar_t*, basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>> >, __gnu_cxx::__normal_iterator<wchar_t*, basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>> >, wchar_t const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::replace(__gnu_cxx::__normal_iterator<wchar_t*, basic_string<wchar_t,

```

char_traits<wchar_t>, allocator<wchar_t> > >,
__gnu_cxx::__normal_iterator<wchar_t*, basic_string<wchar_t,
char_traits<wchar_t>, allocator<wchar_t> > >, unsigned long, wchar_t)
(GLIBCXX_3.4) [ISOCXX]
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>
>::replace(unsigned long, unsigned long, wchar_t const*)(GLIBCXX_3.4)
[ISOCXX]
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>
>::replace(unsigned long, unsigned long, wchar_t const*, unsigned long)
(GLIBCXX_3.4) [ISOCXX]
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>
>::replace(unsigned long, unsigned long, basic_string<wchar_t,
char_traits<wchar_t>, allocator<wchar_t> > const&)(GLIBCXX_3.4)
[ISOCXX]
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>
>::replace(unsigned long, unsigned long, basic_string<wchar_t,
char_traits<wchar_t>, allocator<wchar_t> > const&, unsigned long,
unsigned long)(GLIBCXX_3.4) [ISOCXX]
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>
>::replace(unsigned long, unsigned long, unsigned long, wchar_t)
(GLIBCXX_3.4) [ISOCXX]
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>
>::reserve(unsigned long)(GLIBCXX_3.4) [ISOCXX]
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>
>::_M_assign(wchar_t*, unsigned long, wchar_t)(GLIBCXX_3.4.5) [ISOCXX]
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>
>::_M_mutate(unsigned long, unsigned long, unsigned long)(GLIBCXX_3.4)
[ISOCXX]
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>
>::basic_string(wchar_t const*, unsigned long, allocator<wchar_t> const&)
(GLIBCXX_3.4) [ISOCXX]
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>
>::basic_string(basic_string<wchar_t, char_traits<wchar_t>,
allocator<wchar_t> > const&, unsigned long, unsigned long)
(GLIBCXX_3.4) [ISOCXX]
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>
>::basic_string(basic_string<wchar_t, char_traits<wchar_t>,
allocator<wchar_t> > const&, unsigned long, unsigned long,
allocator<wchar_t> const&)(GLIBCXX_3.4) [ISOCXX]
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>
>::basic_string(unsigned long, wchar_t, allocator<wchar_t> const&)
(GLIBCXX_3.4) [ISOCXX]
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>
>::basic_string(wchar_t const*, unsigned long, allocator<wchar_t> const&)
(GLIBCXX_3.4) [ISOCXX]
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>
>::basic_string(basic_string<wchar_t, char_traits<wchar_t>,
allocator<wchar_t> > const&, unsigned long, unsigned long)
(GLIBCXX_3.4) [ISOCXX]

```

[\[ISOCXX\]](#)

```
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::basic_string(basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> > const&, unsigned long, unsigned long, allocator<wchar_t> const&)(GLIBCXX_3.4) \[ISOCXX\]
```

```
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::basic_string(unsigned long, wchar_t, allocator<wchar_t> const&)(GLIBCXX_3.4) \[ISOCXX\]
```

```
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::operator[](unsigned long)(GLIBCXX_3.4) \[ISOCXX\]
```

## 7.1.60 Class `basic_stringstream<char, char_traits<char>, allocator<char> >`

### 7.1.60.1 Class data for `basic_stringstream<char, char_traits<char>, allocator<char> >`

The virtual table for the `std::basic_stringstream<char, std::char_traits<char>, std::allocator<char> >` class is described by [Table 7-47](#)

**Table 7-47 Primary vtable for `basic_stringstream<char, char_traits<char>, allocator<char> >`**

Base Offset	0
Virtual Base Offset	104
RTTI	typeinfo for <code>basic_stringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt;</code>
vfunc[0]:	<code>basic_stringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt;::~basic_stringstream()</code>
vfunc[1]:	<code>basic_stringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt;::~basic_stringstream()</code>

**Table 7-48 Secondary vtable for `basic_stringstream<char, char_traits<char>, allocator<char> >`**

Base Offset	-16
Virtual Base Offset	88
RTTI	typeinfo for <code>basic_stringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt;</code>
vfunc[0]:	non-virtual thunk to <code>basic_stringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt;::~basic_stringstream()</code>
vfunc[1]:	non-virtual thunk to <code>basic_stringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt;::~basic_stringstream()</code>

**Table 7-49 Secondary vtable for `basic_stringstream<char, char_traits<char>, allocator<char>` >**

Base Offset	-104
Virtual Base Offset	-104
RTTI	typeinfo for <code>basic_stringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >
vfunc[0]:	virtual thunk to <code>basic_stringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >::~ <code>basic_stringstream()</code>
vfunc[1]:	virtual thunk to <code>basic_stringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >::~ <code>basic_stringstream()</code>

The VTT for the `std::basic_stringstream<char, std::char_traits<char>, std::allocator<char>` class is described by [Table 7-50](#)

**Table 7-50 VTT for `basic_stringstream<char, char_traits<char>, allocator<char>` >**

VTT Name	_ZTTSt18basic_stringstreamIcSt11char_traitsIcESaIcEE
Number of Entries	10

### 7.1.60.2 Interfaces for Class `basic_stringstream<char, char_traits<char>, allocator<char>` >

An LSB conforming implementation shall provide the architecture specific methods for Class `std::basic_stringstream<char, std::char_traits<char>, std::allocator<char>` > specified in [Table 7-51](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-51 libstdc++ - Class `basic_stringstream<char, char_traits<char>, allocator<char>` > Function Interfaces**

non-virtual thunk to <code>basic_stringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >::~ <code>basic_stringstream()</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
non-virtual thunk to <code>basic_stringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >::~ <code>basic_stringstream()</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
virtual thunk to <code>basic_stringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >::~ <code>basic_stringstream()</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
virtual thunk to <code>basic_stringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >::~ <code>basic_stringstream()</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 7.1.61 Class `basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>`

### 7.1.61.1 Class data for `basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>`

The virtual table for the `std::basic_stringstream<wchar_t, std::char_traits<wchar_t>, std::allocator<wchar_t>` class is described by [Table 7-52](#)

**Table 7-52 Primary vtable for `basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>`**

Base Offset	0
Virtual Base Offset	104
RTTI	typeinfo for <code>basic_stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;</code>
vfunc[0]:	<code>basic_stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::~basic_stringstream()</code>
vfunc[1]:	<code>basic_stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::~basic_stringstream()</code>

**Table 7-53 Secondary vtable for `basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>`**

Base Offset	-16
Virtual Base Offset	88
RTTI	typeinfo for <code>basic_stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;</code>
vfunc[0]:	non-virtual thunk to <code>basic_stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::~basic_stringstream()</code>
vfunc[1]:	non-virtual thunk to <code>basic_stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::~basic_stringstream()</code>

**Table 7-54 Secondary vtable for `basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>`**

Base Offset	-104
-------------	------

Virtual Base Offset	-104
RTTI	typeinfo for basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >
vfunc[0]:	virtual thunk to basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::~basic_stringstream()
vfunc[1]:	virtual thunk to basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::~basic_stringstream()

The VTT for the `std::basic_stringstream<wchar_t, std::char_traits<wchar_t>, std::allocator<wchar_t> >` class is described by [Table 7-55](#)

**Table 7-55 VTT for `basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >`**

VTT Name	_ZTTSt18basic_stringstreamIwSt11char_traitsIwESaIwEE
Number of Entries	10

### 7.1.61.2 Interfaces for Class `basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::basic_stringstream<wchar_t, std::char_traits<wchar_t>, std::allocator<wchar_t> >` specified in [Table 7-56](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-56 libstdcxx - Class `basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >` Function Interfaces**

non-virtual thunk to <code>basic_stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt;::~basic_stringstream()</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
non-virtual thunk to <code>basic_stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt;::~basic_stringstream()</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
virtual thunk to <code>basic_stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt;::~basic_stringstream()</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
virtual thunk to <code>basic_stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt;::~basic_stringstream()</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>

### 7.1.62 Class `basic_istream<char, char_traits<char>, allocator<char> >`

#### 7.1.62.1 Class data for `basic_istream<char, char_traits<char>, allocator<char> >`

The virtual table for the `std::basic_istream<char, std::char_traits<char>, std::allocator<char> >`

`std::allocator<char>` > class is described by [Table 7-57](#)

**Table 7-57 Primary vtable for `basic_istream<char, char_traits<char>, allocator<char>` >**

Base Offset	0
Virtual Base Offset	96
RTTI	typeinfo for <code>basic_istream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >
vfunc[0]:	<code>basic_istream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >::~ <code>basic_istream()</code>
vfunc[1]:	<code>basic_istream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >::~ <code>basic_istream()</code>

**Table 7-58 Secondary vtable for `basic_istream<char, char_traits<char>, allocator<char>` >**

Base Offset	-96
Virtual Base Offset	-96
RTTI	typeinfo for <code>basic_istream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >
vfunc[0]:	virtual thunk to <code>basic_istream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >::~ <code>basic_istream()</code>
vfunc[1]:	virtual thunk to <code>basic_istream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >::~ <code>basic_istream()</code>

The VTT for the `std::basic_istream<char, std::char_traits<char>, std::allocator<char>` > class is described by [Table 7-59](#)

**Table 7-59 VTT for `basic_istream<char, char_traits<char>, allocator<char>` >**

VTT Name	_ZTTSt19basic_istreamIcSt11char_traitsIcESalcEE
Number of Entries	4

### 7.1.62.2 Interfaces for Class `basic_istream<char, char_traits<char>, allocator<char>` >

An LSB conforming implementation shall provide the architecture specific methods for Class `std::basic_istream<char, std::char_traits<char>, std::allocator<char>` > specified in [Table 7-60](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-60 libstdc++ - Class `basic_istringstream<char, char_traits<char>, allocator<char>` Function Interfaces**

virtual thunk to <code>basic_istringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;::~basic_istringstream()</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
virtual thunk to <code>basic_istringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;::~basic_istringstream()</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 7.1.63 Class `basic_istringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>`

### 7.1.63.1 Class data for `basic_istringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>`

The virtual table for the `std::basic_istringstream<wchar_t, std::char_traits<wchar_t>, std::allocator<wchar_t>` class is described by [Table 7-61](#)

**Table 7-61 Primary vtable for `basic_istringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>`**

Base Offset	0
Virtual Base Offset	96
RTTI	typeinfo for <code>basic_istringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;</code>
vfunc[0]:	<code>basic_istringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::~basic_istringstream()</code>
vfunc[1]:	<code>basic_istringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::~basic_istringstream()</code>

**Table 7-62 Secondary vtable for `basic_istringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>`**

Base Offset	-96
Virtual Base Offset	-96
RTTI	typeinfo for <code>basic_istringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;</code>
vfunc[0]:	virtual thunk to <code>basic_istringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::~basic_istringstream()</code>
vfunc[1]:	virtual thunk to <code>basic_istringstream&lt;wchar_t,</code>

	char_traits<wchar_t>, allocator<wchar_t> >::basic_istringstream()
--	-------------------------------------------------------------------------

The VTT for the std::basic\_istringstream<wchar\_t, std::char\_traits<wchar\_t>, std::allocator<wchar\_t> > class is described by [Table 7-63](#)

**Table 7-63 VTT for basic\_istringstream<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> >**

VTT Name	_ZTTSt19basic_istringstreamIwSt11char_traitsIwESaIwEE
Number of Entries	4

### 7.1.63.2 Interfaces for Class basic\_istringstream<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> >

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_istringstream<wchar\_t, std::char\_traits<wchar\_t>, std::allocator<wchar\_t> > specified in [Table 7-64](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-64 libstdcxx - Class basic\_istringstream<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> > Function Interfaces**

virtual thunk to basic_istringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::basic_istringstream()(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
virtual thunk to basic_istringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::basic_istringstream()(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

### 7.1.64 Class basic\_ostringstream<char, char\_traits<char>, allocator<char> >

#### 7.1.64.1 Class data for basic\_ostringstream<char, char\_traits<char>, allocator<char> >

The virtual table for the std::basic\_ostringstream<char, std::char\_traits<char>, std::allocator<char> > class is described by [Table 7-65](#)

**Table 7-65 Primary vtable for basic\_ostringstream<char, char\_traits<char>, allocator<char> >**

Base Offset	0
Virtual Base Offset	88
RTTI	typeinfo for basic_ostringstream<char, char_traits<char>, allocator<char> >
vfunc[0]:	basic_ostringstream<char, char_traits<char>, allocator<char> >::basic_ostringstream()
vfunc[1]:	basic_ostringstream<char, char_traits<char>, allocator<char> >::basic_ostringstream()

**Table 7-66 Secondary vtable for basic\_ostringstream<char, char\_traits<char>, allocator<char> >**

Base Offset	-88
Virtual Base Offset	-88
RTTI	typeinfo for basic_ostringstream<char, char_traits<char>, allocator<char> >
vfunc[0]:	virtual thunk to basic_ostringstream<char, char_traits<char>, allocator<char> >::~basic_ostringstream()
vfunc[1]:	virtual thunk to basic_ostringstream<char, char_traits<char>, allocator<char> >::~basic_ostringstream()

The VTT for the std::basic\_ostringstream<char, std::char\_traits<char>, std::allocator<char> > class is described by [Table 7-67](#)

**Table 7-67 VTT for basic\_ostringstream<char, char\_traits<char>, allocator<char> >**

VTT Name	_ZTTSt19basic_ostringstreamIcSt11char_traitsIcESaIcEE
Number of Entries	4

### 7.1.64.2 Interfaces for Class basic\_ostringstream<char, char\_traits<char>, allocator<char> >

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_ostringstream<char, std::char\_traits<char>, std::allocator<char> > specified in [Table 7-68](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-68 libstdcxx - Class basic\_ostringstream<char, char\_traits<char>, allocator<char> > Function Interfaces**

virtual thunk to basic_ostringstream<char, char_traits<char>, allocator<char> >::~basic_ostringstream()(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
virtual thunk to basic_ostringstream<char, char_traits<char>, allocator<char> >::~basic_ostringstream()(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

### 7.1.65 Class basic\_ostringstream<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> >

#### 7.1.65.1 Class data for basic\_ostringstream<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> >

The virtual table for the std::basic\_ostringstream<wchar\_t, std::char\_traits<wchar\_t>, std::allocator<wchar\_t> > class is described by [Table 7-69](#)

**Table 7-69 Primary vtable for basic\_ostringstream<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> >**

Base Offset	0
Virtual Base Offset	88
RTTI	typeinfo for basic_ostringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >
vfunc[0]:	basic_ostringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::~basic_ostringstream()
vfunc[1]:	basic_ostringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::~basic_ostringstream()

**Table 7-70 Secondary vtable for basic\_ostringstream<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> >**

Base Offset	-88
Virtual Base Offset	-88
RTTI	typeinfo for basic_ostringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >
vfunc[0]:	virtual thunk to basic_ostringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::~basic_ostringstream()
vfunc[1]:	virtual thunk to basic_ostringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::~basic_ostringstream()

The VTT for the `std::basic_ostringstream<wchar_t, std::char_traits<wchar_t>, std::allocator<wchar_t> >` class is described by [Table 7-71](#)

**Table 7-71 VTT for basic\_ostringstream<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> >**

VTT Name	_ZTTSt19basic_ostringstreamIwSt11char_traitsIwESaIwEE
Number of Entries	4

### 7.1.65.2 Interfaces for Class `basic_ostringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::basic_ostringstream<wchar_t, std::char_traits<wchar_t>, std::allocator<wchar_t> >`.

`std::allocator<wchar_t>` > specified in [Table 7-72](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-72 libstdcxx - Class `basic_ostringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>` Function Interfaces**

virtual thunk to <code>basic_ostringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;</code> >::~ <code>basic_ostringstream()</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

virtual thunk to <code>basic_ostringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;</code> >::~ <code>basic_ostringstream()</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

## 7.1.66 Class `basic_stringbuf<char, char_traits<char>, allocator<char>` >

### 7.1.66.1 Class data for `basic_stringbuf<char, char_traits<char>, allocator<char>` >

The virtual table for the `std::basic_stringbuf<char, std::char_traits<char>, std::allocator<char>` class is described by [Table 7-73](#)

**Table 7-73 Primary vtable for `basic_stringbuf<char, char_traits<char>, allocator<char>` >**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>basic_stringbuf&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >
vfunc[0]:	<code>basic_stringbuf&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >::~ <code>basic_stringbuf()</code>
vfunc[1]:	<code>basic_stringbuf&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >::~ <code>basic_stringbuf()</code>
vfunc[2]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt;</code> >::imbue(locale const&)
vfunc[3]:	<code>basic_stringbuf&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >::setbuf(char*, long)
vfunc[4]:	<code>basic_stringbuf&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >::seekoff(long, _Ios_Seekdir, _Ios_Openmode)
vfunc[5]:	<code>basic_stringbuf&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >::seekpos(fpos<__mbstate_t>, _Ios_Openmode)
vfunc[6]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt;</code> >::sync()
vfunc[7]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt;</code> >::showmanyc()

vfunc[8]:	basic_streambuf<char, char_traits<char> >::xsgetn(char*, long)
vfunc[9]:	basic_stringbuf<char, char_traits<char>, allocator<char> >::underflow()
vfunc[10]:	basic_streambuf<char, char_traits<char> >::uflow()
vfunc[11]:	basic_stringbuf<char, char_traits<char>, allocator<char> >::pbackfail(int)
vfunc[12]:	basic_streambuf<char, char_traits<char> >::xsputn(char const*, long)
vfunc[13]:	basic_stringbuf<char, char_traits<char>, allocator<char> >::overflow(int)

The Run Time Type Information for the std::basic\_stringbuf<char, std::char\_traits<char>, std::allocator<char> > class is described by [Table 7-74](#)

**Table 7-74 typeinfo for basic\_stringbuf<char, char\_traits<char>, allocator<char> >**

Base Vtable	vtable for <u>__cxxabiv1::__si_class_type_info</u>
Name	typeinfo name for basic_stringbuf<char, char_traits<char>, allocator<char> >

### 7.1.66.2 Interfaces for Class basic\_stringbuf<char, char\_traits<char>, allocator<char> >

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_stringbuf<char, std::char\_traits<char>, std::allocator<char> > specified in [Table 7-75](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-75 libstdcxx - Class basic\_stringbuf<char, char\_traits<char>, allocator<char> > Function Interfaces**

basic_stringbuf<char, char_traits<char>, allocator<char> >::setbuf(char*, long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringbuf<char, char_traits<char>, allocator<char> >::_M_sync(char*, unsigned long, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringbuf<char, char_traits<char>, allocator<char> >::seekoff(long, _Ios_Seekdir, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 7.1.67 Class `basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t>`

### 7.1.67.1 Class data for `basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t>`

The virtual table for the `std::basic_stringbuf<wchar_t, std::char_traits<wchar_t>, std::allocator<wchar_t>` class is described by [Table 7-76](#)

**Table 7-76 Primary vtable for `basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>basic_stringbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;</code>
vfunc[0]:	<code>basic_stringbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::~basic_stringbuf()</code>
vfunc[1]:	<code>basic_stringbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::~basic_stringbuf()</code>
vfunc[2]:	<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::imbue(locale const&amp;)</code>
vfunc[3]:	<code>basic_stringbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::setbuf(wchar_t*, long)</code>
vfunc[4]:	<code>basic_stringbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::seekoff(long, _Ios_Seekdir, _Ios_Openmode)</code>
vfunc[5]:	<code>basic_stringbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::seekpos(fpos&lt;_mbstate_t&gt;, _Ios_Openmode)</code>
vfunc[6]:	<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::sync()</code>
vfunc[7]:	<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::showmany()</code>
vfunc[8]:	<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code>

	>::xsgttn(wchar_t*, long)
vfunc[9]:	basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::underflow()
vfunc[10]:	basic_streambuf<wchar_t, char_traits<wchar_t>>::uflow()
vfunc[11]:	basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::pbackfail(unsigned int)
vfunc[12]:	basic_streambuf<wchar_t, char_traits<wchar_t> >::xsputn(wchar_t const*, long)
vfunc[13]:	basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::overflow(unsigned int)

The Run Time Type Information for the `std::basic_stringbuf<wchar_t, std::char_traits<wchar_t>, std::allocator<wchar_t>>` class is described by [Table 7-77](#)

**Table 7-77 typeinfo for basic\_stringbuf<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> >**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>basic_stringbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;</code>

### 7.1.67.2 Interfaces for Class `basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::basic_stringbuf<wchar_t, std::char_traits<wchar_t>, std::allocator<wchar_t>>` specified in [Table 7-78](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-78 libstdc++ - Class `basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >` Function Interfaces**

<code>basic_stringbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::setbuf(wchar_t*, long)(GLIBCXX_3.4) [ISOCXX]</code>
<code>basic_stringbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::_M_sync(wchar_t*, unsigned long, unsigned long)(GLIBCXX_3.4) [ISOCXX]</code>
<code>basic_stringbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::seekoff(long, _Ios_Seekdir, _Ios_Openmode)(GLIBCXX_3.4) [ISOCXX]</code>

## 7.1.68 Class `basic_iostream<char, char_traits<char>>`

### 7.1.68.1 Class data for `basic_iostream<char, char_traits<char>>`

The virtual table for the `std::basic_iostream<char, std::char_traits<char>>` class is described by [Table 7-79](#)

**Table 7-79 Primary vtable for `basic_iostream<char, char_traits<char>>`**

Base Offset	0
Virtual Base Offset	24
RTTI	typeinfo for <code>basic_iostream&lt;char, char_traits&lt;char&gt;&gt;</code>
vfunc[0]:	<code>basic_iostream&lt;char, char_traits&lt;char&gt;&gt;::~basic_iostream()</code>
vfunc[1]:	<code>basic_iostream&lt;char, char_traits&lt;char&gt;&gt;::~basic_iostream()</code>

**Table 7-80 Secondary vtable for `basic_iostream<char, char_traits<char>>`**

Base Offset	-16
Virtual Base Offset	8
RTTI	typeinfo for <code>basic_iostream&lt;char, char_traits&lt;char&gt;&gt;</code>
vfunc[0]:	non-virtual thunk to <code>basic_iostream&lt;char, char_traits&lt;char&gt;&gt;::~basic_iostream()</code>
vfunc[1]:	non-virtual thunk to <code>basic_iostream&lt;char, char_traits&lt;char&gt;&gt;::~basic_iostream()</code>

**Table 7-81 Secondary vtable for `basic_iostream<char, char_traits<char>>`**

Base Offset	-24
Virtual Base Offset	-24
RTTI	typeinfo for <code>basic_iostream&lt;char, char_traits&lt;char&gt;&gt;</code>
vfunc[0]:	virtual thunk to <code>basic_iostream&lt;char, char_traits&lt;char&gt;&gt;::~basic_iostream()</code>
vfunc[1]:	virtual thunk to <code>basic_iostream&lt;char, char_traits&lt;char&gt;&gt;::~basic_iostream()</code>

The VTT for the `std::basic_iostream<char, std::char_traits<char>>` class is de-

scribed by [Table 7-82](#)

**Table 7-82 VTT for basic\_iostream<char, char\_traits<char> >**

VTT Name	_ZTTSd
Number of Entries	7

### 7.1.68.2 Interfaces for Class basic\_iostream<char, char\_traits<char> >

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_iostream<char, std::char\_traits<char> > specified in [Table 7-83](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-83 libstdcxx - Class basic\_iostream<char, char\_traits<char> > Function Interfaces**

non-virtual thunk to basic_iostream<char, char_traits<char> >::~basic_iostream()(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
non-virtual thunk to basic_iostream<char, char_traits<char> >::~basic_iostream()(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
virtual thunk to basic_iostream<char, char_traits<char> >::~basic_iostream()(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
virtual thunk to basic_iostream<char, char_traits<char> >::~basic_iostream()(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

### 7.1.69 Class basic\_iostream<wchar\_t, char\_traits<wchar\_t> >

#### 7.1.69.1 Class data for basic\_iostream<wchar\_t, char\_traits<wchar\_t> >

The virtual table for the std::basic\_iostream<wchar\_t, std::char\_traits<wchar\_t> > class is described by [Table 7-84](#)

**Table 7-84 Primary vtable for basic\_iostream<wchar\_t, char\_traits<wchar\_t> >**

Base Offset	0
Virtual Base Offset	24
RTTI	typeinfo for basic_iostream<wchar_t, char_traits<wchar_t> >
vfunc[0]:	basic_iostream<wchar_t, char_traits<wchar_t> >::~basic_iostream()
vfunc[1]:	basic_iostream<wchar_t, char_traits<wchar_t> >::~basic_iostream()

**Table 7-85 Secondary vtable for basic\_iostream<wchar\_t, char\_traits<wchar\_t> >**

Base Offset	-16
-------------	-----

Virtual Base Offset	8
RTTI	typeinfo for basic_iostream<wchar_t, char_traits<wchar_t>>
vfunc[0]:	non-virtual thunk to basic_iostream<wchar_t, char_traits<wchar_t>>::~basic_iostream()
vfunc[1]:	non-virtual thunk to basic_iostream<wchar_t, char_traits<wchar_t>>::~basic_iostream()

**Table 7-86 Secondary vtable for basic\_iostream<wchar\_t, char\_traits<wchar\_t> >**

Base Offset	-24
Virtual Base Offset	-24
RTTI	typeinfo for basic_iostream<wchar_t, char_traits<wchar_t>>
vfunc[0]:	virtual thunk to basic_iostream<wchar_t, char_traits<wchar_t>>::~basic_iostream()
vfunc[1]:	virtual thunk to basic_iostream<wchar_t, char_traits<wchar_t>>::~basic_iostream()

The VTT for the std::basic\_iostream<wchar\_t, std::char\_traits<wchar\_t> > class is described by [Table 7-87](#)

**Table 7-87 VTT for basic\_iostream<wchar\_t, char\_traits<wchar\_t> >**

VTT Name	_ZTTSt14basic_iostreamIwSt11char_traitsIwEE
Number of Entries	7

### 7.1.69.2 Interfaces for Class basic\_iostream<wchar\_t, char\_traits<wchar\_t> >

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_iostream<wchar\_t, std::char\_traits<wchar\_t> > specified in [Table 7-88](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-88 libstdc++ - Class basic\_iostream<wchar\_t, char\_traits<wchar\_t> > Function Interfaces**

non-virtual thunk to basic_iostream<wchar_t, char_traits<wchar_t>>::~basic_iostream()(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
non-virtual thunk to basic_iostream<wchar_t, char_traits<wchar_t>>

>::~basic_istream()(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
virtual thunk to basic_istream<wchar_t, char_traits<wchar_t>>
>::~basic_istream()(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
virtual thunk to basic_istream<wchar_t, char_traits<wchar_t>>
>::~basic_istream()(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 7.1.70 Class `basic_istream<char, char_traits<char>>`

### 7.1.70.1 Class data for `basic_istream<char, char_traits<char>>`

The virtual table for the `std::basic_istream<char, std::char_traits<char>>` class is described by [Table 7-89](#)

**Table 7-89 Primary vtable for `basic_istream<char, char_traits<char>>`**

Base Offset	0
Virtual Base Offset	16
RTTI	typeinfo for <code>basic_istream&lt;char, char_traits&lt;char&gt;&gt;</code>
vfunc[0]:	<code>basic_istream&lt;char, char_traits&lt;char&gt;&gt;::~basic_istream()</code>
vfunc[1]:	<code>basic_istream&lt;char, char_traits&lt;char&gt;&gt;::~basic_istream()</code>

**Table 7-90 Secondary vtable for `basic_istream<char, char_traits<char>>`**

Base Offset	-16
Virtual Base Offset	-16
RTTI	typeinfo for <code>basic_istream&lt;char, char_traits&lt;char&gt;&gt;</code>
vfunc[0]:	virtual thunk to <code>basic_istream&lt;char, char_traits&lt;char&gt;&gt;::~basic_istream()</code>
vfunc[1]:	virtual thunk to <code>basic_istream&lt;char, char_traits&lt;char&gt;&gt;::~basic_istream()</code>

The VTT for the `std::basic_istream<char, std::char_traits<char>>` class is described by [Table 7-91](#)

**Table 7-91 VTT for `basic_istream<char, char_traits<char>>`**

VTT Name	ZTTSi
Number of Entries	2

### 7.1.70.2 Interfaces for Class `basic_istream<char, char_traits<char>>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::basic_istream<char, std::char_traits<char>>` specified in [Table 7-92](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-92 libstdc++ - Class `basic_istream<char, char_traits<char>` Function Interfaces**

<code>basic_istream&lt;char, char_traits&lt;char&gt;&gt;::get(char*, long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_istream&lt;char, char_traits&lt;char&gt;&gt;::get(char*, long, char)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_istream&lt;char, char_traits&lt;char&gt;&gt;::read(char*, long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_istream&lt;char, char_traits&lt;char&gt;&gt;::seekg(long, _Ios_Seekdir)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_istream&lt;char, char_traits&lt;char&gt;&gt;::ignore(long)(GLIBCXX_3.4.5)</code> <a href="#">[ISOCXX]</a>
<code>basic_istream&lt;char, char_traits&lt;char&gt;&gt;::ignore(long, int)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_istream&lt;char, char_traits&lt;char&gt;&gt;::getline(char*, long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_istream&lt;char, char_traits&lt;char&gt;&gt;::getline(char*, long, char)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_istream&lt;char, char_traits&lt;char&gt;&gt;::readsome(char*, long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
virtual thunk to <code>basic_istream&lt;char, char_traits&lt;char&gt;&gt;::~basic_istream()</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
virtual thunk to <code>basic_istream&lt;char, char_traits&lt;char&gt;&gt;::~basic_istream()</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 7.1.71 Class `basic_istream<wchar_t, char_traits<wchar_t>>`

### 7.1.71.1 Class data for `basic_istream<wchar_t, char_traits<wchar_t>>`

The virtual table for the `std::basic_istream<wchar_t, std::char_traits<wchar_t>>` class is described by [Table 7-93](#)

**Table 7-93 Primary vtable for `basic_istream<wchar_t, char_traits<wchar_t>>`**

Base Offset	0
Virtual Base Offset	16
RTTI	typeinfo for <code>basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code>
vfunc[0]:	<code>basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_istream()</code>
vfunc[1]:	<code>basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_istream()</code>

**Table 7-94 Secondary vtable for `basic_istream<wchar_t, char_traits<wchar_t>>`**

Base Offset	-16
Virtual Base Offset	-16
RTTI	typeinfo for <code>basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code>
vfunc[0]:	virtual thunk to <code>basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_istream()</code>
vfunc[1]:	virtual thunk to <code>basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_istream()</code>

The VTT for the `std::basic_istream<wchar_t, std::char_traits<wchar_t>>` class is described by [Table 7-95](#)

**Table 7-95 VTT for `basic_istream<wchar_t, char_traits<wchar_t>>`**

VTT Name	<code>_ZTTSt13basic_istreamIwSt11char_traitsIwEE</code>
Number of Entries	2

### 7.1.71.2 Interfaces for Class `basic_istream<wchar_t, char_traits<wchar_t>>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::basic_istream<wchar_t, std::char_traits<wchar_t>>` specified in [Table 7-96](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-96 libstdc++ - Class `basic_istream<wchar_t, char_traits<wchar_t>>` Function Interfaces**

<code>basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::get(wchar_t*, long)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::get(wchar_t*, long, wchar_t)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::read(wchar_t*, long)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::seekg(long, _Ios_Seekdir)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::ignore(long)</code> (GLIBCXX_3.4.5) <a href="#">[ISOCXX]</a>
<code>basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::ignore(long, unsigned int)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::getline(wchar_t*, long)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::getline(wchar_t*, long, wchar_t)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

`basic_istream<wchar_t, char_traits<wchar_t>>::readsome(wchar_t*, long)`  
(GLIBCXX\_3.4) [\[ISOCXX\]](#)

`virtual thunk to basic_istream<wchar_t, char_traits<wchar_t>>::~basic_istream()(GLIBCXX_3.4)` [\[CXXABI\]](#)

`virtual thunk to basic_istream<wchar_t, char_traits<wchar_t>>::~basic_istream()(GLIBCXX_3.4)` [\[CXXABI\]](#)

## 7.1.72 Class `istreambuf_iterator<wchar_t, char_traits<wchar_t> >`

### 7.1.72.1 Interfaces for Class `istreambuf_iterator<wchar_t, char_traits<wchar_t> >`

No external methods are defined for libstdcxx - Class `std::istreambuf_iterator<wchar_t, std::char_traits<wchar_t> >` in this part of the specification. See also the generic specification.

## 7.1.73 Class `istreambuf_iterator<char, char_traits<char> >`

### 7.1.73.1 Interfaces for Class `istreambuf_iterator<char, char_traits<char> >`

No external methods are defined for libstdcxx - Class `std::istreambuf_iterator<char, std::char_traits<char> >` in this part of the specification. See also the generic specification.

## 7.1.74 Class `basic_ostream<char, char_traits<char> >`

### 7.1.74.1 Class data for `basic_ostream<char, char_traits<char> >`

The virtual table for the `std::basic_ostream<char, std::char_traits<char> >` class is described by [Table 7-97](#)

**Table 7-97 Primary vtable for `basic_ostream<char, char_traits<char> >`**

Base Offset	0
Virtual Base Offset	8
RTTI	typeinfo for <code>basic_ostream&lt;char, char_traits&lt;char&gt; &gt;</code>
vfunc[0]:	<code>basic_ostream&lt;char, char_traits&lt;char&gt; &gt;::~basic_ostream()</code>
vfunc[1]:	<code>basic_ostream&lt;char, char_traits&lt;char&gt; &gt;::~basic_ostream()</code>

**Table 7-98 Secondary vtable for `basic_ostream<char, char_traits<char> >`**

Base Offset	-8
Virtual Base Offset	-8

RTTI	typeinfo for basic_ostream<char, char_traits<char> >
vfunc[0]:	virtual thunk to basic_ostream<char, char_traits<char> >::~basic_ostream()
vfunc[1]:	virtual thunk to basic_ostream<char, char_traits<char> >::~basic_ostream()

The VTT for the std::basic\_ostream<char, std::char\_traits<char> > class is described by [Table 7-99](#)

**Table 7-99 VTT for basic\_ostream<char, char\_traits<char> >**

VTT Name	ZTTSO
Number of Entries	2

#### 7.1.74.2 Interfaces for Class basic\_ostream<char, char\_traits<char> >

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_ostream<char, std::char\_traits<char> > specified in [Table 7-100](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-100 libstdc++ - Class basic\_ostream<char, char\_traits<char> > Function Interfaces**

basic_ostream<char, char_traits<char> >::seekp(long, _Ios_Seekdir) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<char, char_traits<char> >::write(char const*, long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<char, char_traits<char> >::_M_write(char const*, long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
virtual thunk to basic_ostream<char, char_traits<char> >::~basic_ostream() (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
virtual thunk to basic_ostream<char, char_traits<char> >::~basic_ostream() (GLIBCXX_3.4) <a href="#">[CXXABI]</a>

#### 7.1.75 Class basic\_ostream<wchar\_t, char\_traits<wchar\_t> >

##### 7.1.75.1 Class data for basic\_ostream<wchar\_t, char\_traits<wchar\_t> >

The virtual table for the std::basic\_ostream<wchar\_t, std::char\_traits<wchar\_t> > class is described by [Table 7-101](#)

**Table 7-101 Primary vtable for basic\_ostream<wchar\_t, char\_traits<wchar\_t> >**

Base Offset	0
Virtual Base Offset	8

RTTI	typeinfo for basic_ostream<wchar_t, char_traits<wchar_t>>
vfunc[0]:	basic_ostream<wchar_t, char_traits<wchar_t>>::~basic_ostream()
vfunc[1]:	basic_ostream<wchar_t, char_traits<wchar_t>>::~basic_ostream()

**Table 7-102 Secondary vtable for basic\_ostream<wchar\_t, char\_traits<wchar\_t>>**

Base Offset	-8
Virtual Base Offset	-8
RTTI	typeinfo for basic_ostream<wchar_t, char_traits<wchar_t>>
vfunc[0]:	virtual thunk to basic_ostream<wchar_t, char_traits<wchar_t>>::~basic_ostream()
vfunc[1]:	virtual thunk to basic_ostream<wchar_t, char_traits<wchar_t>>::~basic_ostream()

The VTT for the std::basic\_ostream<wchar\_t, std::char\_traits<wchar\_t>> class is described by [Table 7-103](#)

**Table 7-103 VTT for basic\_ostream<wchar\_t, char\_traits<wchar\_t>>**

VTT Name	_ZTTSt13basic_ostreamIwSt11char_traitsIwEE
Number of Entries	2

### 7.1.75.2 Interfaces for Class basic\_ostream<wchar\_t, char\_traits<wchar\_t>>

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_ostream<wchar\_t, std::char\_traits<wchar\_t>> specified in [Table 7-104](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-104 libstdcxx - Class basic\_ostream<wchar\_t, char\_traits<wchar\_t>> Function Interfaces**

basic_ostream<wchar_t, char_traits<wchar_t>>::seekp(long, _Ios_Seekdir) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::write(wchar_t const*, long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
virtual thunk to basic_ostream<wchar_t, char_traits<wchar_t>>::~basic_ostream() (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
virtual thunk to basic_ostream<wchar_t, char_traits<wchar_t>>

>::~basic_ostream()(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
-----------------------------------------------------------

## 7.1.76 Class `basic_fstream<char, char_traits<char>>`

### 7.1.76.1 Class data for `basic_fstream<char, char_traits<char>>`

The virtual table for the `std::basic_fstream<char, std::char_traits<char>>` class is described by [Table 7-105](#)

**Table 7-105 Primary vtable for `basic_fstream<char, char_traits<char>>`**

Base Offset	0
Virtual Base Offset	264
RTTI	typeinfo for <code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;</code>
vfunc[0]:	<code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;::~basic_fstream()</code>
vfunc[1]:	<code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;::~basic_fstream()</code>

**Table 7-106 Secondary vtable for `basic_fstream<char, char_traits<char>>`**

Base Offset	-16
Virtual Base Offset	248
RTTI	typeinfo for <code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;</code>
vfunc[0]:	non-virtual thunk to <code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;::~basic_fstream()</code>
vfunc[1]:	non-virtual thunk to <code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;::~basic_fstream()</code>

**Table 7-107 Secondary vtable for `basic_fstream<char, char_traits<char>>`**

Base Offset	-264
Virtual Base Offset	-264
RTTI	typeinfo for <code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;</code>
vfunc[0]:	virtual thunk to <code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;::~basic_fstream()</code>
vfunc[1]:	virtual thunk to <code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;::~basic_fstream()</code>

The VTT for the `std::basic_fstream<char, std::char_traits<char>>` class is described by [Table 7-108](#)

**Table 7-108 VTT for basic\_fstream<char, char\_traits<char> >**

VTT Name	_ZTTSt13basic_fstreamIcSt11char_tr_aitsIcEE
Number of Entries	10

### 7.1.76.2 Interfaces for Class basic\_fstream<char, char\_traits<char> >

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_fstream<char, std::char\_traits<char> > specified in [Table 7-109](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-109 libstdcxx - Class basic\_fstream<char, char\_traits<char> > Function Interfaces**

non-virtual thunk to basic_fstream<char, char_traits<char> >::~basic_fstream()(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
non-virtual thunk to basic_fstream<char, char_traits<char> >::~basic_fstream()(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
virtual thunk to basic_fstream<char, char_traits<char> >::~basic_fstream()(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
virtual thunk to basic_fstream<char, char_traits<char> >::~basic_fstream()(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

### 7.1.77 Class basic\_fstream<wchar\_t, char\_traits<wchar\_t> >

#### 7.1.77.1 Class data for basic\_fstream<wchar\_t, char\_traits<wchar\_t> >

The virtual table for the std::basic\_fstream<wchar\_t, std::char\_traits<wchar\_t> > class is described by [Table 7-110](#)

**Table 7-110 Primary vtable for basic\_fstream<wchar\_t, char\_traits<wchar\_t> >**

Base Offset	0
Virtual Base Offset	264
RTTI	typeinfo for basic_fstream<wchar_t, char_traits<wchar_t> >
vfunc[0]:	basic_fstream<wchar_t, char_traits<wchar_t> >::~basic_fstream()
vfunc[1]:	basic_fstream<wchar_t, char_traits<wchar_t> >::~basic_fstream()

**Table 7-111 Secondary vtable for basic\_fstream<wchar\_t, char\_traits<wchar\_t> >**

Base Offset	-16
Virtual Base Offset	248

RTTI	typeinfo for basic_fstream<wchar_t, char_traits<wchar_t>>
vfunc[0]:	non-virtual thunk to basic_fstream<wchar_t, char_traits<wchar_t> >::~basic_fstream()
vfunc[1]:	non-virtual thunk to basic_fstream<wchar_t, char_traits<wchar_t> >::~basic_fstream()

**Table 7-112 Secondary vtable for basic\_fstream<wchar\_t,  
char\_traits<wchar\_t>>**

Base Offset	-264
Virtual Base Offset	-264
RTTI	typeinfo for basic_fstream<wchar_t, char_traits<wchar_t>>
vfunc[0]:	virtual thunk to basic_fstream<wchar_t, char_traits<wchar_t> >::~basic_fstream()
vfunc[1]:	virtual thunk to basic_fstream<wchar_t, char_traits<wchar_t> >::~basic_fstream()

The VTT for the std::basic\_fstream<wchar\_t, std::char\_traits<wchar\_t> > class is described by [Table 7-113](#)

**Table 7-113 VTT for basic\_fstream<wchar\_t, char\_traits<wchar\_t>>**

VTT Name	_ZTTSt13basic_fstreamIwSt11char_tr aitsIwEE
Number of Entries	10

### 7.1.77.2 Interfaces for Class basic\_fstream<wchar\_t, char\_traits<wchar\_t>>

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_fstream<wchar\_t, std::char\_traits<wchar\_t> > specified in [Table 7-114](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-114 libstdcxx - Class basic\_fstream<wchar\_t, char\_traits<wchar\_t>>  
Function Interfaces**

non-virtual thunk to basic_fstream<wchar_t, char_traits<wchar_t> >::~basic_fstream()(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
non-virtual thunk to basic_fstream<wchar_t, char_traits<wchar_t> >::~basic_fstream()(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
virtual thunk to basic_fstream<wchar_t, char_traits<wchar_t> >::~basic_fstream()(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 7.1.78 Class basic\_ifstream<char, char\_traits<char>>

>

### 7.1.78.1 Class data for basic\_ifstream<char, char\_traits<char>>

The virtual table for the std::basic\_ifstream<char, std::char\_traits<char>> class is described by [Table 7-115](#)

**Table 7-115 Primary vtable for basic\_ifstream<char, char\_traits<char>>**

Base Offset	0
Virtual Base Offset	256
RTTI	typeinfo for basic_ifstream<char, char_traits<char>>
vfunc[0]:	basic_ifstream<char, char_traits<char>>::~basic_ifstream()
vfunc[1]:	basic_ifstream<char, char_traits<char>>::~basic_ifstream()

**Table 7-116 Secondary vtable for basic\_ifstream<char, char\_traits<char>>**

Base Offset	-256
Virtual Base Offset	-256
RTTI	typeinfo for basic_ifstream<char, char_traits<char>>
vfunc[0]:	virtual thunk to basic_ifstream<char, char_traits<char>>::~basic_ifstream()
vfunc[1]:	virtual thunk to basic_ifstream<char, char_traits<char>>::~basic_ifstream()

The VTT for the std::basic\_ifstream<char, std::char\_traits<char>> class is described by [Table 7-117](#)

**Table 7-117 VTT for basic\_ifstream<char, char\_traits<char>>**

VTT Name	_ZTTSt14basic_ifstreamIcSt11char_traitsIcEE
Number of Entries	4

### 7.1.78.2 Interfaces for Class basic\_ifstream<char, char\_traits<char>>

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_ifstream<char, std::char\_traits<char>> specified in [Table 7-118](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-118 libstdc++ - Class `basic_ifstream<char, char_traits<char>>` Function Interfaces**

virtual thunk to <code>basic_ifstream&lt;char, char_traits&lt;char&gt;&gt;::~basic_ifstream()</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
virtual thunk to <code>basic_ifstream&lt;char, char_traits&lt;char&gt;&gt;::~basic_ifstream()</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 7.1.79 Class `basic_ifstream<wchar_t, char_traits<wchar_t>>`

### 7.1.79.1 Class data for `basic_ifstream<wchar_t, char_traits<wchar_t>>`

The virtual table for the `std::basic_ifstream<wchar_t, std::char_traits<wchar_t>>` class is described by [Table 7-119](#)

**Table 7-119 Primary vtable for `basic_ifstream<wchar_t, char_traits<wchar_t>>`**

Base Offset	0
Virtual Base Offset	256
RTTI	typeinfo for <code>basic_ifstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code>
vfunc[0]:	<code>basic_ifstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_ifstream()</code>
vfunc[1]:	<code>basic_ifstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_ifstream()</code>

**Table 7-120 Secondary vtable for `basic_ifstream<wchar_t, char_traits<wchar_t>>`**

Base Offset	-256
Virtual Base Offset	-256
RTTI	typeinfo for <code>basic_ifstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code>
vfunc[0]:	virtual thunk to <code>basic_ifstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_ifstream()</code>
vfunc[1]:	virtual thunk to <code>basic_ifstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_ifstream()</code>

The VTT for the `std::basic_ifstream<wchar_t, std::char_traits<wchar_t>>` class is described by [Table 7-121](#)

**Table 7-121 VTT for `basic_ifstream<wchar_t, char_traits<wchar_t>>`**

VTT Name	<code>_ZTTSt14basic_ifstreamIwSt11char_t</code>
----------	-------------------------------------------------

	raitsIwEE
Number of Entries	4

### 7.1.79.2 Interfaces for Class `basic_ifstream<wchar_t, char_traits<wchar_t>>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::basic_ifstream<wchar_t, std::char_traits<wchar_t>>` specified in [Table 7-122](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-122 libstdc++ - Class `basic_ifstream<wchar_t, char_traits<wchar_t>>` Function Interfaces**

virtual thunk to <code>basic_ifstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_ifstream()(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>
virtual thunk to <code>basic_ifstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_ifstream()(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>

### 7.1.80 Class `basic_ofstream<char, char_traits<char>>`

#### 7.1.80.1 Class data for `basic_ofstream<char, char_traits<char>>`

The virtual table for the `std::basic_ofstream<char, std::char_traits<char>>` class is described by [Table 7-123](#)

**Table 7-123 Primary vtable for `basic_ofstream<char, char_traits<char>>`**

Base Offset	0
Virtual Base Offset	248
RTTI	typeinfo for <code>basic_ofstream&lt;char, char_traits&lt;char&gt;&gt;</code>
vfunc[0]:	<code>basic_ofstream&lt;char, char_traits&lt;char&gt;&gt;::~basic_ofstream()</code>
vfunc[1]:	<code>basic_ofstream&lt;char, char_traits&lt;char&gt;&gt;::~basic_ofstream()</code>

**Table 7-124 Secondary vtable for `basic_ofstream<char, char_traits<char>>`**

Base Offset	-248
Virtual Base Offset	-248
RTTI	typeinfo for <code>basic_ofstream&lt;char, char_traits&lt;char&gt;&gt;</code>
vfunc[0]:	virtual thunk to <code>basic_ofstream&lt;char, char_traits&lt;char&gt;&gt;::~basic_ofstream()</code>
vfunc[1]:	virtual thunk to <code>basic_ofstream&lt;char,</code>

	char_traits<char> >::~basic_ofstream()
--	-------------------------------------------

The VTT for the std::basic\_ofstream<char, std::char\_traits<char> > class is described by [Table 7-125](#)

**Table 7-125 VTT for basic\_ofstream<char, char\_traits<char> >**

VTT Name	_ZTTSt14basic_ofstreamIcSt11char_traitsIcEE
Number of Entries	4

### 7.1.80.2 Interfaces for Class basic\_ofstream<char, char\_traits<char> >

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_ofstream<char, std::char\_traits<char> > specified in [Table 7-126](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-126 libstdc++ - Class basic\_ofstream<char, char\_traits<char> > Function Interfaces**

virtual thunk to basic_ofstream<char, char_traits<char> >::~basic_ofstream() (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
virtual thunk to basic_ofstream<char, char_traits<char> >::~basic_ofstream() (GLIBCXX_3.4) <a href="#">[CXXABI]</a>

### 7.1.81 Class basic\_ofstream<wchar\_t, char\_traits<wchar\_t> >

#### 7.1.81.1 Class data for basic\_ofstream<wchar\_t, char\_traits<wchar\_t> >

The virtual table for the std::basic\_ofstream<wchar\_t, std::char\_traits<wchar\_t> > class is described by [Table 7-127](#)

**Table 7-127 Primary vtable for basic\_ofstream<wchar\_t, char\_traits<wchar\_t> >**

Base Offset	0
Virtual Base Offset	248
RTTI	typeinfo for basic_ofstream<wchar_t, char_traits<wchar_t> >
vfunc[0]:	basic_ofstream<wchar_t, char_traits<wchar_t> >::~basic_ofstream()
vfunc[1]:	basic_ofstream<wchar_t, char_traits<wchar_t> >::~basic_ofstream()

**Table 7-128 Secondary vtable for basic\_ofstream<wchar\_t, char\_traits<wchar\_t> >**

Base Offset	-248
Virtual Base Offset	-248
RTTI	typeinfo for basic_ofstream<wchar_t, char_traits<wchar_t> >
vfunc[0]:	virtual thunk to basic_ofstream<wchar_t, char_traits<wchar_t> >::~basic_ofstream()
vfunc[1]:	virtual thunk to basic_ofstream<wchar_t, char_traits<wchar_t> >::~basic_ofstream()

The VTT for the std::basic\_ofstream<wchar\_t, std::char\_traits<wchar\_t> > class is described by [Table 7-129](#)

**Table 7-129 VTT for basic\_ofstream<wchar\_t, char\_traits<wchar\_t> >**

VTT Name	_ZTTSt14basic_ofstreamIwSt11char_traitsIwEE
Number of Entries	4

### 7.1.81.2 Interfaces for Class basic\_ofstream<wchar\_t, char\_traits<wchar\_t> >

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_ofstream<wchar\_t, std::char\_traits<wchar\_t> > specified in [Table 7-130](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-130 libstdcxx - Class basic\_ofstream<wchar\_t, char\_traits<wchar\_t> > Function Interfaces**

virtual thunk to basic_ofstream<wchar_t, char_traits<wchar_t> >::~basic_ofstream()(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
virtual thunk to basic_ofstream<wchar_t, char_traits<wchar_t> >::~basic_ofstream()(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

### 7.1.82 Class basic\_streambuf<char, char\_traits<char> >

#### 7.1.82.1 Class data for basic\_streambuf<char, char\_traits<char> >

The virtual table for the std::basic\_streambuf<char, std::char\_traits<char> > class is described by [Table 7-131](#)

**Table 7-131 Primary vtable for basic\_streambuf<char, char\_traits<char> >**

Base Offset	0
Virtual Base Offset	0

RTTI	typeinfo for basic_streambuf<char, char_traits<char> >
vfunc[0]:	basic_streambuf<char, char_traits<char> >::~basic_streambuf()
vfunc[1]:	basic_streambuf<char, char_traits<char> >::~basic_streambuf()
vfunc[2]:	basic_streambuf<char, char_traits<char> >::imbue(locale const&)
vfunc[3]:	basic_streambuf<char, char_traits<char> >::setbuf(char*, long)
vfunc[4]:	basic_streambuf<char, char_traits<char> >::seekoff(long, _Ios_Seekdir, _Ios_Openmode)
vfunc[5]:	basic_streambuf<char, char_traits<char> >::seekpos(fpos<__mbstate_t>, _Ios_Openmode)
vfunc[6]:	basic_streambuf<char, char_traits<char> >::sync()
vfunc[7]:	basic_streambuf<char, char_traits<char> >::showmanyc()
vfunc[8]:	basic_streambuf<char, char_traits<char> >::xsgetn(char*, long)
vfunc[9]:	basic_streambuf<char, char_traits<char> >::underflow()
vfunc[10]:	basic_streambuf<char, char_traits<char> >::uflow()
vfunc[11]:	basic_streambuf<char, char_traits<char> >::pbackfail(int)
vfunc[12]:	basic_streambuf<char, char_traits<char> >::xsputn(char const*, long)
vfunc[13]:	basic_streambuf<char, char_traits<char> >::overflow(int)

The Run Time Type Information for the std::basic\_streambuf<char, std::char\_traits<char> > class is described by [Table 7-132](#)

**Table 7-132 typeinfo for basic\_streambuf<char, char\_traits<char> >**

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for basic_streambuf<char,

	char_traits<char> >
--	---------------------

### 7.1.82.2 Interfaces for Class **basic\_streambuf<char, char\_traits<char> >**

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_streambuf<char, std::char\_traits<char> > specified in [Table 7-133](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-133 libstdcxx - Class **basic\_streambuf<char, char\_traits<char> >** Function Interfaces**

basic_streambuf<char, char_traits<char> >::pubseekoff(long, _Ios_Seekdir, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::sgetn(char*, long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::sputn(char const*, long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::setbuf(char*, long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::xgetn(char*, long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::xsputn(char const*, long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::seekoff(long, _Ios_Seekdir, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::pubsetbuf(char*, long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

### 7.1.83 Class **basic\_streambuf<wchar\_t, char\_traits<wchar\_t> >**

#### 7.1.83.1 Class data for **basic\_streambuf<wchar\_t, char\_traits<wchar\_t> >**

The virtual table for the std::basic\_streambuf<wchar\_t, std::char\_traits<wchar\_t> > class is described by [Table 7-134](#)

**Table 7-134 Primary vtable for **basic\_streambuf<wchar\_t, char\_traits<wchar\_t> >****

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for basic_streambuf<wchar_t, char_traits<wchar_t> >
vfunc[0]:	basic_streambuf<wchar_t, char_traits<wchar_t> >::~basic_streambuf()
vfunc[1]:	basic_streambuf<wchar_t,

	<code>char_traits&lt;wchar_t&gt;</code> <code>&gt;::~basic_streambuf()</code>
vfunc[2]:	<code>basic_streambuf&lt;wchar_t,</code> <code>char_traits&lt;wchar_t&gt;</code> <code>&gt;::imbue(locale const&amp;)</code>
vfunc[3]:	<code>basic_streambuf&lt;wchar_t,</code> <code>char_traits&lt;wchar_t&gt;</code> <code>&gt;::setbuf(wchar_t*, long)</code>
vfunc[4]:	<code>basic_streambuf&lt;wchar_t,</code> <code>char_traits&lt;wchar_t&gt;</code> <code>&gt;::seekoff(long, _Ios_Seekdir,</code> <code>_Ios_Openmode)</code>
vfunc[5]:	<code>basic_streambuf&lt;wchar_t,</code> <code>char_traits&lt;wchar_t&gt;</code> <code>&gt;::seekpos(fpos&lt;__mbstate_t&gt;,</code> <code>_Ios_Openmode)</code>
vfunc[6]:	<code>basic_streambuf&lt;wchar_t,</code> <code>char_traits&lt;wchar_t&gt; &gt;::sync()</code>
vfunc[7]:	<code>basic_streambuf&lt;wchar_t,</code> <code>char_traits&lt;wchar_t&gt;</code> <code>&gt;::showmany()</code>
vfunc[8]:	<code>basic_streambuf&lt;wchar_t,</code> <code>char_traits&lt;wchar_t&gt;</code> <code>&gt;::xsgetn(wchar_t*, long)</code>
vfunc[9]:	<code>basic_streambuf&lt;wchar_t,</code> <code>char_traits&lt;wchar_t&gt; &gt;::underflow()</code>
vfunc[10]:	<code>basic_streambuf&lt;wchar_t,</code> <code>char_traits&lt;wchar_t&gt; &gt;::uflow()</code>
vfunc[11]:	<code>basic_streambuf&lt;wchar_t,</code> <code>char_traits&lt;wchar_t&gt;</code> <code>&gt;::pbackfail(unsigned int)</code>
vfunc[12]:	<code>basic_streambuf&lt;wchar_t,</code> <code>char_traits&lt;wchar_t&gt;</code> <code>&gt;::xsputn(wchar_t const*, long)</code>
vfunc[13]:	<code>basic_streambuf&lt;wchar_t,</code> <code>char_traits&lt;wchar_t&gt;</code> <code>&gt;::overflow(unsigned int)</code>

The Run Time Type Information for the `std::basic_streambuf<wchar_t, std::char_traits<wchar_t> >` class is described by [Table 7-135](#)

**Table 7-135 typeinfo for `basic_streambuf<wchar_t, char_traits<wchar_t> >`**

Base Vtable	vtable for <code>__cxxabiv1::__class_type_info</code>
Name	typeinfo name for <code>basic_streambuf&lt;wchar_t,</code> <code>char_traits&lt;wchar_t&gt; &gt;</code>

### 7.1.83.2 Interfaces for Class `basic_streambuf<wchar_t, char_traits<wchar_t>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::basic_streambuf<wchar_t, std::char_traits<wchar_t>` specified in [Table 7-136](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-136 libstdcxx - Class `basic_streambuf<wchar_t, char_traits<wchar_t>` Function Interfaces**

<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::pubseekoff(long, _Ios_Seekdir, _Ios_Openmode)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::sgetn(wchar_t*, long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::sputn(wchar_t const*, long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::setbuf(wchar_t*, long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::xsgetn(wchar_t*, long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::xsputn(wchar_t const*, long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::seekoff(long, _Ios_Seekdir, _Ios_Openmode)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::pubsetbuf(wchar_t*, long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

### 7.1.84 Class `basic_filebuf<char, char_traits<char>`

#### 7.1.84.1 Class data for `basic_filebuf<char, char_traits<char>`

The virtual table for the `std::basic_filebuf<char, std::char_traits<char>` class is described by [Table 7-137](#)

**Table 7-137 Primary vtable for `basic_filebuf<char, char_traits<char>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>basic_filebuf&lt;char, char_traits&lt;char&gt;</code>
vfunc[0]:	<code>basic_filebuf&lt;char, char_traits&lt;char&gt;&gt;::~basic_filebuf()</code>
vfunc[1]:	<code>basic_filebuf&lt;char, char_traits&lt;char&gt;&gt;::~basic_filebuf()</code>
vfunc[2]:	<code>basic_filebuf&lt;char, char_traits&lt;char&gt;&gt;::imbue(locale const&amp;)</code>
vfunc[3]:	<code>basic_filebuf&lt;char, char_traits&lt;char&gt;&gt;::setbuf(char*, long)</code>
vfunc[4]:	<code>basic_filebuf&lt;char, char_traits&lt;char&gt;&gt;::seekoff(long, _Ios_Seekdir,</code>

	_Ios_Openmode)
vfunc[5]:	basic_filebuf<char, char_traits<char>>::seekpos(fpos<__mbstate_t>, _Ios_Openmode)
vfunc[6]:	basic_filebuf<char, char_traits<char>>::sync()
vfunc[7]:	basic_filebuf<char, char_traits<char>>::showmany()
vfunc[8]:	basic_filebuf<char, char_traits<char>>::xsgetn(char*, long)
vfunc[9]:	basic_filebuf<char, char_traits<char>>::underflow()
vfunc[10]:	basic_streambuf<char, char_traits<char>>::uflow()
vfunc[11]:	basic_filebuf<char, char_traits<char>>::pbackfail(int)
vfunc[12]:	basic_filebuf<char, char_traits<char>>::xsputn(char const*, long)
vfunc[13]:	basic_filebuf<char, char_traits<char>>::overflow(int)

The Run Time Type Information for the std::basic\_filebuf<char, std::char\_traits<char> > class is described by [Table 7-138](#)

**Table 7-138 typeinfo for basic\_filebuf<char, char\_traits<char> >**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for basic_filebuf<char, char_traits<char> >

#### 7.1.84.2 Interfaces for Class basic\_filebuf<char, char\_traits<char> >

An LSB conforming implementation shall provide the architecture specific methods for Class std::basic\_filebuf<char, std::char\_traits<char> > specified in [Table 7-139](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-139 libstdc++ - Class basic\_filebuf<char, char\_traits<char> > Function Interfaces**

basic_filebuf<char, char_traits<char> >::_M_set_buffer(long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<char, char_traits<char> >::_M_convert_to_external(char*, long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<char, char_traits<char> >::setbuf(char*, long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<char, char_traits<char> >::xsgetn(char*, long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<char, char_traits<char> >::xsputn(char const*, long)

(GLIBCXX\_3.4) [\[ISOCXX\]](#)

basic\_filebuf<char, char\_traits<char>>::\_M\_seek(long, \_Ios\_Seekdir, \_mbstate\_t)(GLIBCXX\_3.4) [\[ISOCXX\]](#)

basic\_filebuf<char, char\_traits<char>>::seekoff(long, \_Ios\_Seekdir, \_Ios\_Openmode)(GLIBCXX\_3.4) [\[ISOCXX\]](#)

## 7.1.85 Class `basic_filebuf<wchar_t, char_traits<wchar_t>>`

### 7.1.85.1 Class data for `basic_filebuf<wchar_t, char_traits<wchar_t>>`

The virtual table for the `std::basic_filebuf<wchar_t, std::char_traits<wchar_t>>` class is described by [Table 7-140](#)

**Table 7-140 Primary vtable for `basic_filebuf<wchar_t, char_traits<wchar_t>>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code>
vfunc[0]:	<code>basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_filebuf()</code>
vfunc[1]:	<code>basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_filebuf()</code>
vfunc[2]:	<code>basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::imbue(locale const&amp;)</code>
vfunc[3]:	<code>basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::setbuf(wchar_t*, long)</code>
vfunc[4]:	<code>basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::seekoff(long, _Ios_Seekdir, _Ios_Openmode)</code>
vfunc[5]:	<code>basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::seekpos(fpos&lt;_mbstate_t&gt;, _Ios_Openmode)</code>
vfunc[6]:	<code>basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::sync()</code>
vfunc[7]:	<code>basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::showmany()</code>
vfunc[8]:	<code>basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::xsgetn(wchar_t*, long)</code>

vfunc[9]:	basic_filebuf<wchar_t, char_traits<wchar_t>>::underflow()
vfunc[10]:	basic_streambuf<wchar_t, char_traits<wchar_t>>::uflow()
vfunc[11]:	basic_filebuf<wchar_t, char_traits<wchar_t>>::pbackfail(unsigned int)
vfunc[12]:	basic_filebuf<wchar_t, char_traits<wchar_t>>::xsputn(wchar_t const*, long)
vfunc[13]:	basic_filebuf<wchar_t, char_traits<wchar_t>>::overflow(unsigned int)

The Run Time Type Information for the `std::basic_filebuf<wchar_t, std::char_traits<wchar_t>>` class is described by [Table 7-141](#)

**Table 7-141 typeinfo for basic\_filebuf<wchar\_t, char\_traits<wchar\_t>>**

Base Vtable	vtable for <code>_cxxabiv1::_si_class_type_info</code>
Name	typeinfo name for <code>basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code>

### 7.1.85.2 Interfaces for Class `basic_filebuf<wchar_t, char_traits<wchar_t>>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::basic_filebuf<wchar_t, std::char_traits<wchar_t>>` specified in [Table 7-142](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-142 libstdc++ - Class `basic_filebuf<wchar_t, char_traits<wchar_t>>` Function Interfaces**

<code>basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::_M_set_buffer(long)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::_M_convert_to_external(wchar_t*, long)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::setbuf(wchar_t*, long)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::xsgetn(wchar_t*, long)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::xsputn(wchar_t const*, long)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::_M_seek(long, _Ios_Seekdir, _mbstate_t)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::seekoff(long, _Ios_Seekdir, _Ios_Openmode)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_ostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::_M_write(wchar_t const*,</code>

long)(GLIBCXX\_3.4) [\[ISOCXX\]](#)

virtual thunk to basic\_fstream<wchar\_t, char\_traits<wchar\_t>>::~basic\_fstream()(GLIBCXX\_3.4) [\[CXXABI\]](#)

## 7.1.86 Class `ios_base`

### 7.1.86.1 Class data for `ios_base`

The virtual table for the `std::ios_base` class is described in the generic part of this specification.

The Run Time Type Information for the `std::ios_base` class is described by [Table 7-143](#)

**Table 7-143 typeinfo for `ios_base`**

Base Vtable	vtable for <code>__cxxabiv1::__class_type_info</code>
Name	typeinfo name for <code>ios_base</code>

### 7.1.86.2 Interfaces for Class `ios_base`

No external methods are defined for libstdc++ - Class `std::ios_base` in this part of the specification. See also the generic specification.

## 7.1.87 Class `basic_ios<char, char_traits<char>>`

### 7.1.87.1 Class data for `basic_ios<char, char_traits<char>>`

The virtual table for the `std::basic_ios<char, std::char_traits<char>>` class is described in the generic part of this specification.

### 7.1.87.2 Interfaces for Class `basic_ios<char, char_traits<char>>`

No external methods are defined for libstdc++ - Class `std::basic_ios<char, std::char_traits<char>>` in this part of the specification. See also the generic specification.

## 7.1.88 Class `basic_ios<wchar_t, char_traits<wchar_t>>`

### 7.1.88.1 Class data for `basic_ios<wchar_t, char_traits<wchar_t>>`

The virtual table for the `std::basic_ios<wchar_t, std::char_traits<wchar_t>>` class is described in the generic part of this specification.

The Run Time Type Information for the `std::basic_ios<wchar_t, std::char_traits<wchar_t>>` class is described by [Table 7-144](#)

**Table 7-144 typeinfo for `basic_ios<wchar_t, char_traits<wchar_t>>`**

Base Vtable	vtable for <code>__cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>basic_ios&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code>

flags:	8	
basetype:	typeinfo for ios_base	1026

### 7.1.88.2 Interfaces for Class `basic_ios<wchar_t, char_traits<wchar_t>`

No external methods are defined for libstdcxx - Class `std::basic_ios<wchar_t, std::char_traits<wchar_t>` in this part of the specification. See also the generic specification.

## 7.1.89 Class `ios_base::failure`

### 7.1.89.1 Class data for `ios_base::failure`

The virtual table for the `std::ios_base::failure` class is described in the generic part of this specification.

The Run Time Type Information for the `std::ios_base::failure` class is described by [Table 7-145](#)

**Table 7-145 typeinfo for `ios_base::failure`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>ios_base::failure</code>

### 7.1.89.2 Interfaces for Class `ios_base::failure`

No external methods are defined for libstdcxx - Class `std::ios_base::failure` in this part of the specification. See also the generic specification.

## 7.1.90 Class `__timepunct<char>`

### 7.1.90.1 Class data for `__timepunct<char>`

The virtual table for the `std::__timepunct<char>` class is described in the generic part of this specification.

The Run Time Type Information for the `std::__timepunct<char>` class is described by [Table 7-146](#)

**Table 7-146 typeinfo for `__timepunct<char>`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>__timepunct&lt;char&gt;</code>

### 7.1.90.2 Interfaces for Class `__timepunct<char>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::__timepunct<char>` specified in [Table 7-147](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-147 libstdcxx - Class `__timepunct<char>` Function Interfaces**

<code>__timepunct&lt;char&gt;::__M_put(char*, unsigned long, char const*, tm const*) const(GLIBCXX_3.4)</code> <a href="#">[ISO CXX]</a>
------------------------------------------------------------------------------------------------------------------------------------------

<code>__timepunct&lt;char&gt;::__timepunct(__locale_struct*, char const*, unsigned long)(GLIBCXX_3.4) [ISOCXX]</code>
<code>__timepunct&lt;char&gt;::__timepunct(__timepunct_cache&lt;char&gt;*, unsigned long)(GLIBCXX_3.4) [ISOCXX]</code>
<code>__timepunct&lt;char&gt;::__timepunct(unsigned long)(GLIBCXX_3.4) [ISOCXX]</code>
<code>__timepunct&lt;char&gt;::__timepunct(__locale_struct*, char const*, unsigned long)(GLIBCXX_3.4) [ISOCXX]</code>
<code>__timepunct&lt;char&gt;::__timepunct(__timepunct_cache&lt;char&gt;*, unsigned long)(GLIBCXX_3.4) [ISOCXX]</code>
<code>__timepunct&lt;char&gt;::__timepunct(unsigned long)(GLIBCXX_3.4) [ISOCXX]</code>

## 7.1.91 Class `__timepunct<wchar_t>`

### 7.1.91.1 Class data for `__timepunct<wchar_t>`

The virtual table for the `std::__timepunct<wchar_t>` class is described in the generic part of this specification.

The Run Time Type Information for the `std::__timepunct<wchar_t>` class is described by [Table 7-148](#)

**Table 7-148 typeinfo for `__timepunct<wchar_t>`**

Base Vtable	vtable for <code>__cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>__timepunct&lt;wchar_t&gt;</code>

### 7.1.91.2 Interfaces for Class `__timepunct<wchar_t>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::__timepunct<wchar_t>` specified in [Table 7-149](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-149 libstdc++ - Class `__timepunct<wchar_t>` Function Interfaces**

<code>__timepunct&lt;wchar_t&gt;::__M_put(wchar_t*, unsigned long, wchar_t const*, tm const*) const(GLIBCXX_3.4) [ISOCXX]</code>
<code>__timepunct&lt;wchar_t&gt;::__timepunct(__locale_struct*, char const*, unsigned long)(GLIBCXX_3.4) [ISOCXX]</code>
<code>__timepunct&lt;wchar_t&gt;::__timepunct(__timepunct_cache&lt;wchar_t&gt;*, unsigned long)(GLIBCXX_3.4) [ISOCXX]</code>
<code>__timepunct&lt;wchar_t&gt;::__timepunct(unsigned long)(GLIBCXX_3.4) [ISOCXX]</code>
<code>__timepunct&lt;wchar_t&gt;::__timepunct(__locale_struct*, char const*, unsigned long)(GLIBCXX_3.4) [ISOCXX]</code>
<code>__timepunct&lt;wchar_t&gt;::__timepunct(__timepunct_cache&lt;wchar_t&gt;*, unsigned long)(GLIBCXX_3.4) [ISOCXX]</code>
<code>__timepunct&lt;wchar_t&gt;::__timepunct(unsigned long)(GLIBCXX_3.4) [ISOCXX]</code>

## 7.1.92 Class messages\_base

### 7.1.92.1 Class data for messages\_base

The Run Time Type Information for the std::messages\_base class is described by [Table 7-150](#)

**Table 7-150 typeinfo for messages\_base**

Base Vtable	vtable for _cxxabiv1::__class_type_info
Name	typeinfo name for messages_base

### 7.1.92.2 Interfaces for Class messages\_base

No external methods are defined for libstdcxx - Class std::messages\_base in this part of the specification. See also the generic specification.

## 7.1.93 Class messages<char>

### 7.1.93.1 Class data for messages<char>

The virtual table for the std::messages<char> class is described in the generic part of this specification.

### 7.1.93.2 Interfaces for Class messages<char>

An LSB conforming implementation shall provide the architecture specific methods for Class std::messages<char> specified in [Table 7-151](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-151 libstdcxx - Class messages<char> Function Interfaces**

messages<char>::messages(__locale_struct*, char const*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages<char>::messages(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages<char>::messages(__locale_struct*, char const*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages<char>::messages(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 7.1.94 Class messages<wchar\_t>

### 7.1.94.1 Class data for messages<wchar\_t>

The virtual table for the std::messages<wchar\_t> class is described in the generic part of this specification.

### 7.1.94.2 Interfaces for Class messages<wchar\_t>

An LSB conforming implementation shall provide the architecture specific methods for Class std::messages<wchar\_t> specified in [Table 7-152](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-152 libstdcxx - Class messages<wchar\_t> Function Interfaces**

messages<wchar_t>::messages(__locale_struct*, char const*, unsigned long)
---------------------------------------------------------------------------

(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages<wchar_t>::messages(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages<wchar_t>::messages(__locale_struct*, char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages<wchar_t>::messages(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 7.1.95 Class messages\_byname<char>

### 7.1.95.1 Class data for messages\_byname<char>

The virtual table for the std::messages\_byname<char> class is described in the generic part of this specification.

The Run Time Type Information for the std::messages\_byname<char> class is described by [Table 7-153](#)

**Table 7-153 typeinfo for messages\_byname<char>**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for messages_byname<char>

### 7.1.95.2 Interfaces for Class messages\_byname<char>

An LSB conforming implementation shall provide the architecture specific methods for Class std::messages\_byname<char> specified in [Table 7-154](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-154 libstdc++ - Class messages\_byname<char> Function Interfaces**

messages_byname<char>::messages_byname(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages_byname<char>::messages_byname(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 7.1.96 Class messages\_byname<wchar\_t>

### 7.1.96.1 Class data for messages\_byname<wchar\_t>

The virtual table for the std::messages\_byname<wchar\_t> class is described in the generic part of this specification.

The Run Time Type Information for the std::messages\_byname<wchar\_t> class is described by [Table 7-155](#)

**Table 7-155 typeinfo for messages\_byname<wchar\_t>**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for messages_byname<wchar_t>

### 7.1.96.2 Interfaces for Class `messages_byname<wchar_t>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::messages_byname<wchar_t>` specified in [Table 7-156](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-156 libstdcxx - Class `messages_byname<wchar_t>` Function Interfaces**

messages_byname<wchar_t>::messages_byname(char const*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages_byname<wchar_t>::messages_byname(char const*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

### 7.1.97 Class `numpunct<char>`

#### 7.1.97.1 Class data for `numpunct<char>`

The virtual table for the `std::numpunct<char>` class is described in the generic part of this specification.

The Run Time Type Information for the `std::numpunct<char>` class is described by [Table 7-157](#)

**Table 7-157 typeinfo for `numpunct<char>`**

Base Vtable	vtable for <code>_cxxabiv1::_si_class_type_info</code>
Name	typeinfo name for <code>numpunct&lt;char&gt;</code>

#### 7.1.97.2 Interfaces for Class `numpunct<char>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::numpunct<char>` specified in [Table 7-158](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-158 libstdcxx - Class `numpunct<char>` Function Interfaces**

<code>numpunct&lt;char&gt;::numpunct(__locale_struct*, unsigned long)</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
<code>numpunct&lt;char&gt;::numpunct(__numpunct_cache&lt;char&gt;*, unsigned long)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>numpunct&lt;char&gt;::numpunct(unsigned long)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>numpunct&lt;char&gt;::numpunct(__locale_struct*, unsigned long)</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
<code>numpunct&lt;char&gt;::numpunct(__numpunct_cache&lt;char&gt;*, unsigned long)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>numpunct&lt;char&gt;::numpunct(unsigned long)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

### 7.1.98 Class `numpunct<wchar_t>`

#### 7.1.98.1 Class data for `numpunct<wchar_t>`

The virtual table for the `std::numpunct<wchar_t>` class is described in the generic part of this specification.

The Run Time Type Information for the std::numpunct<wchar\_t> class is described by [Table 7-159](#)

**Table 7-159 typeinfo for numpunct<wchar\_t>**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for numpunct<wchar_t>

### 7.1.98.2 Interfaces for Class numpunct<wchar\_t>

An LSB conforming implementation shall provide the architecture specific methods for Class std::numpunct<wchar\_t> specified in [Table 7-160](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-160 libstdc++ - Class numpunct<wchar\_t> Function Interfaces**

numpunct<wchar_t>::numpunct(__locale_struct*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<wchar_t>::numpunct(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<wchar_t>::numpunct(__locale_struct*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<wchar_t>::numpunct(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

### 7.1.99 Class numpunct\_byname<char>

#### 7.1.99.1 Class data for numpunct\_byname<char>

The virtual table for the std::numpunct\_byname<char> class is described in the generic part of this specification.

The Run Time Type Information for the std::numpunct\_byname<char> class is described by [Table 7-161](#)

**Table 7-161 typeinfo for numpunct\_byname<char>**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for numpunct_byname<char>

### 7.1.99.2 Interfaces for Class numpunct\_byname<char>

An LSB conforming implementation shall provide the architecture specific methods for Class std::numpunct\_byname<char> specified in [Table 7-162](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-162 libstdc++ - Class numpunct\_byname<char> Function Interfaces**

numpunct_byname<char>::numpunct_byname(char const*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct_byname<char>::numpunct_byname(char const*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 7.1.100 Class `numpunct_byname<wchar_t>`

### 7.1.100.1 Class data for `numpunct_byname<wchar_t>`

The virtual table for the `std::numpunct_byname<wchar_t>` class is described in the generic part of this specification.

The Run Time Type Information for the `std::numpunct_byname<wchar_t>` class is described by [Table 7-163](#)

**Table 7-163 typeinfo for `numpunct_byname<wchar_t>`**

Base Vtable	vtable for <code>_cxxabiv1::_si_class_type_info</code>
Name	typeinfo name for <code>numpunct_byname&lt;wchar_t&gt;</code>

### 7.1.100.2 Interfaces for Class `numpunct_byname<wchar_t>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::numpunct_byname<wchar_t>` specified in [Table 7-164](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-164 libstdcxx - Class `numpunct_byname<wchar_t>` Function Interfaces**

<code>numpunct_byname&lt;wchar_t&gt;::numpunct_byname(char const*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOcxx]</a>
<code>numpunct_byname&lt;wchar_t&gt;::numpunct_byname(char const*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOcxx]</a>

## 7.1.101 Class `__codecvt_abstract_base<char, char, __mbstate_t>`

### 7.1.101.1 Interfaces for Class `__codecvt_abstract_base<char, char, __mbstate_t>`

No external methods are defined for libstdcxx - Class `std::__codecvt_abstract_base<char, char, __mbstate_t>` in this part of the specification. See also the generic specification.

## 7.1.102 Class `__codecvt_abstract_base<wchar_t, char, __mbstate_t>`

### 7.1.102.1 Class data for `__codecvt_abstract_base<wchar_t, char, __mbstate_t>`

The virtual table for the `std::__codecvt_abstract_base<wchar_t, char, __mbstate_t>` class is described in the generic part of this specification.

### 7.1.102.2 Interfaces for Class `__codecvt_abstract_base<wchar_t, char, __mbstate_t>`

No external methods are defined for libstdcxx - Class `std::__codecvt_abstract_base<wchar_t, char, __mbstate_t>` in this part of the

specification. See also the generic specification.

## 7.1.103 Class `codecvt_base`

### 7.1.103.1 Class data for `codecvt_base`

The Run Time Type Information for the `std::codecvt_base` class is described by [Table 7-165](#)

**Table 7-165 typeinfo for `codecvt_base`**

Base Vtable	vtable for <code>__cxxabiv1::__class_type_info</code>
Name	typeinfo name for <code>codecvt_base</code>

### 7.1.103.2 Interfaces for Class `codecvt_base`

No external methods are defined for `libstdc++` - Class `std::codecvt_base` in this part of the specification. See also the generic specification.

## 7.1.104 Class `codecvt<char, char, __mbstate_t>`

### 7.1.104.1 Class data for `codecvt<char, char, __mbstate_t>`

The virtual table for the `std::codecvt<char, char, __mbstate_t>` class is described by [Table 7-166](#)

**Table 7-166 Primary vtable for `codecvt<char, char, __mbstate_t>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>codecvt&lt;char, char, __mbstate_t&gt;</code>
vfunc[0]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::~codecvt()</code>
vfunc[1]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::~codecvt()</code>
vfunc[2]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::do_out(__mbstate_t&amp;, char const*, char const*, char const*&amp;, char*, char*, char*&amp;) const</code>
vfunc[3]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::do_unshift(__mbstate_t&amp;, char*, char*, char*&amp;) const</code>
vfunc[4]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::do_in(__mbstate_t&amp;, char const*, char const*, char const*&amp;, char*, char*, char*&amp;) const</code>
vfunc[5]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::do_encoding() const</code>
vfunc[6]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::do_always_noconv() const</code>

vfunc[7]:	codecvt<char, char, __mbstate_t>::do_length(__mbstate_t&, char const*, char const*, unsigned long) const
vfunc[8]:	codecvt<char, char, __mbstate_t>::do_max_length() const

The Run Time Type Information for the std::codecvt<char, char, \_\_mbstate\_t> class is described by [Table 7-167](#)

**Table 7-167 typeinfo for codecvt<char, char, \_\_mbstate\_t>**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for codecvt<char, char, __mbstate_t>

### 7.1.104.2 Class data for \_\_codecvt\_abstract\_base<char, char, \_\_mbstate\_t>

The virtual table for the std::\_\_codecvt\_abstract\_base<char, char, \_\_mbstate\_t> class is described in the generic part of this specification.

### 7.1.104.3 Interfaces for Class codecvt<char, char, \_\_mbstate\_t>

An LSB conforming implementation shall provide the architecture specific methods for Class std::codecvt<char, char, \_\_mbstate\_t> specified in [Table 7-168](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-168 libstdc++ - Class codecvt<char, char, \_\_mbstate\_t> Function Interfaces**

codecvt<char, char, __mbstate_t>::do_length(__mbstate_t&, char const*, char const*, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
codecvt<char, char, __mbstate_t>::codecvt(__locale_struct*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
codecvt<char, char, __mbstate_t>::codecvt(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
codecvt<char, char, __mbstate_t>::codecvt(__locale_struct*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
codecvt<char, char, __mbstate_t>::codecvt(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

### 7.1.105 Class codecvt<wchar\_t, char, \_\_mbstate\_t>

#### 7.1.105.1 Class data for codecvt<wchar\_t, char, \_\_mbstate\_t>

The virtual table for the std::codecvt<wchar\_t, char, \_\_mbstate\_t> class is described by [Table 7-169](#)

**Table 7-169 Primary vtable for codecvt<wchar\_t, char, \_\_mbstate\_t>**

Base Offset	0
-------------	---

Virtual Base Offset	0
RTTI	typeinfo for codecvt<wchar_t, char, __mbstate_t>
vfunc[0]:	codecvt<wchar_t, char, __mbstate_t>::~codecvt()
vfunc[1]:	codecvt<wchar_t, char, __mbstate_t>::~codecvt()
vfunc[2]:	codecvt<wchar_t, char, __mbstate_t>::do_out(__mbstate_t&, wchar_t const*, wchar_t const*, wchar_t const*&, char*, char*, char*&) const
vfunc[3]:	codecvt<wchar_t, char, __mbstate_t>::do_unshift(__mbstate_t&, char*, char*, char*&) const
vfunc[4]:	codecvt<wchar_t, char, __mbstate_t>::do_in(__mbstate_t&, char const*, char const*, char const*&, wchar_t*, wchar_t*, wchar_t*&) const
vfunc[5]:	codecvt<wchar_t, char, __mbstate_t>::do_encoding() const
vfunc[6]:	codecvt<wchar_t, char, __mbstate_t>::do_always_noconv() const
vfunc[7]:	codecvt<wchar_t, char, __mbstate_t>::do_length(__mbstate_t&, char const*, char const*, unsigned long) const
vfunc[8]:	codecvt<wchar_t, char, __mbstate_t>::do_max_length() const

The Run Time Type Information for the std::codecvt<wchar\_t, char, \_\_mbstate\_t> class is described by [Table 7-170](#)

**Table 7-170 typeinfo for codecvt<wchar\_t, char, \_\_mbstate\_t>**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for codecvt<wchar_t, char, __mbstate_t>

### 7.1.105.2 Interfaces for Class codecvt<wchar\_t, char, \_\_mbstate\_t>

An LSB conforming implementation shall provide the architecture specific methods for Class std::codecvt<wchar\_t, char, \_\_mbstate\_t> specified in [Table 7-171](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-171 libstdc++ - Class `codecvt<wchar_t, char, __mbstate_t>` Function Interfaces**

<code>codecvt&lt;wchar_t, char, __mbstate_t&gt;::do_length(__mbstate_t&amp;, char const*, char const*, unsigned long) const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>codecvt&lt;wchar_t, char, __mbstate_t&gt;::codecvt(__locale_struct*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>codecvt&lt;wchar_t, char, __mbstate_t&gt;::codecvt(unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>codecvt&lt;wchar_t, char, __mbstate_t&gt;::codecvt(__locale_struct*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>codecvt&lt;wchar_t, char, __mbstate_t&gt;::codecvt(unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

## 7.1.106 Class `codecvt_byname<char, char, __mbstate_t>`

### 7.1.106.1 Class data for `codecvt_byname<char, char, __mbstate_t>`

The virtual table for the `std::codecvt_byname<char, char, __mbstate_t>` class is described by [Table 7-172](#)

**Table 7-172 Primary vtable for `codecvt_byname<char, char, __mbstate_t>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>codecvt_byname&lt;char, char, __mbstate_t&gt;</code>
vfunc[0]:	<code>codecvt_byname&lt;char, char, __mbstate_t&gt;::~codecvt_byname()</code>
vfunc[1]:	<code>codecvt_byname&lt;char, char, __mbstate_t&gt;::~codecvt_byname()</code>
vfunc[2]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::do_out(__mbstate_t&amp;, char const*, char const*, char const*&amp;, char*, char*, char*&amp;) const</code>
vfunc[3]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::do_unshift(__mbstate_t&amp;, char*, char*, char*&amp;) const</code>
vfunc[4]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::do_in(__mbstate_t&amp;, char const*, char const*, char const*&amp;, char*, char*, char*&amp;) const</code>
vfunc[5]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::do_encoding() const</code>
vfunc[6]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::do_always_noconv() const</code>
vfunc[7]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::do_length(__mbstate_</code>

	t&, char const*, char const*, unsigned long) const
vfunc[8]:	codecvt<char, char, __mbstate_t>::do_max_length() const

The Run Time Type Information for the std::codecvt\_byname<char, char, \_\_mbstate\_t> class is described by [Table 7-173](#)

**Table 7-173 typeinfo for codecvt\_byname<char, char, \_\_mbstate\_t>**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for codecvt_byname<char, char, __mbstate_t>

### 7.1.106.2 Interfaces for Class codecvt\_byname<char, char, \_\_mbstate\_t>

An LSB conforming implementation shall provide the architecture specific methods for Class std::codecvt\_byname<char, char, \_\_mbstate\_t> specified in [Table 7-174](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-174 libstdcxx - Class codecvt\_byname<char, char, \_\_mbstate\_t> Function Interfaces**

codecvt_byname<char, char, __mbstate_t>::codecvt_byname(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
codecvt_byname<char, char, __mbstate_t>::codecvt_byname(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>

### 7.1.107 Class codecvt\_byname<wchar\_t, char, \_\_mbstate\_t>

#### 7.1.107.1 Class data for codecvt\_byname<wchar\_t, char, \_\_mbstate\_t>

The virtual table for the std::codecvt\_byname<wchar\_t, char, \_\_mbstate\_t> class is described by [Table 7-175](#)

**Table 7-175 Primary vtable for codecvt\_byname<wchar\_t, char, \_\_mbstate\_t>**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for codecvt_byname<wchar_t, char, __mbstate_t>
vfunc[0]:	codecvt_byname<wchar_t, char, __mbstate_t>::~codecvt_byname()
vfunc[1]:	codecvt_byname<wchar_t, char, __mbstate_t>::~codecvt_byname()

vfunc[2]:	codecvt<wchar_t, char, __mbstate_t>::do_out(__mbstate_t&, wchar_t const*, wchar_t const*, wchar_t const*&, char*, char*, char*&) const
vfunc[3]:	codecvt<wchar_t, char, __mbstate_t>::do_unshift(__mbstate _t&, char*, char*, char*&) const
vfunc[4]:	codecvt<wchar_t, char, __mbstate_t>::do_in(__mbstate_t&, char const*, char const*, char const*&, wchar_t*, wchar_t*, wchar_t*&) const
vfunc[5]:	codecvt<wchar_t, char, __mbstate_t>::do_encoding() const
vfunc[6]:	codecvt<wchar_t, char, __mbstate_t>::do_always_noconv() const
vfunc[7]:	codecvt<wchar_t, char, __mbstate_t>::do_length(__mbstate _t&, char const*, char const*, unsigned long) const
vfunc[8]:	codecvt<wchar_t, char, __mbstate_t>::do_max_length() const

The Run Time Type Information for the std::codecvt\_byname<wchar\_t, char, \_\_mbstate\_t> class is described by [Table 7-176](#)

**Table 7-176 typeinfo for codecvt\_byname<wchar\_t, char, \_\_mbstate\_t>**

Base Vtable	vtable for <code>_cxxabiv1::_si_class_type_info</code>
Name	typeinfo name for codecvt_byname<wchar_t, char, __mbstate_t>

### 7.1.107.2 Class data for collate\_byname<wchar\_t>

The virtual table for the std::collate\_byname<wchar\_t> class is described in the generic part of this specification.

The Run Time Type Information for the std::collate\_byname<wchar\_t> class is described by [Table 7-177](#)

**Table 7-177 typeinfo for collate\_byname<wchar\_t>**

Base Vtable	vtable for <code>_cxxabiv1::_si_class_type_info</code>
Name	typeinfo name for collate_byname<wchar_t>

### **7.1.107.3 Interfaces for Class `codecvt_byname<wchar_t, char, __mbstate_t>`**

An LSB conforming implementation shall provide the architecture specific methods for Class std::codecvt\_byname<wchar\_t, char, \_\_mbstate\_t> specified in [Table 7-178](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-178 libstdc++ - Class `codecvt_byname<wchar_t, char, __mbstate_t>` Function Interfaces**

codecvt_byname<wchar_t, char, __mbstate_t>::codecvt_byname(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
codecvt_byname<wchar_t, char, __mbstate_t>::codecvt_byname(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
collate_byname<wchar_t>::collate_byname(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
collate_byname<wchar_t>::collate_byname(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>

### **7.1.108 Class `collate<char>`**

#### **7.1.108.1 Class data for `collate<char>`**

The virtual table for the std::collate<char> class is described in the generic part of this specification.

The Run Time Type Information for the std::collate<char> class is described by [Table 7-179](#)

**Table 7-179 typeinfo for `collate<char>`**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for collate<char>

#### **7.1.108.2 Interfaces for Class `collate<char>`**

An LSB conforming implementation shall provide the architecture specific methods for Class std::collate<char> specified in [Table 7-180](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-180 libstdc++ - Class `collate<char>` Function Interfaces**

collate<char>::_M_transform(char*, char const*, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
collate<char>::collate(__locale_struct*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
collate<char>::collate(unsigned long)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
collate<char>::collate(__locale_struct*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
collate<char>::collate(unsigned long)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>

## 7.1.109 Class `collate<wchar_t>`

### 7.1.109.1 Class data for `collate<wchar_t>`

The virtual table for the `std::collate<wchar_t>` class is described in the generic part of this specification.

The Run Time Type Information for the `std::collate<wchar_t>` class is described by [Table 7-181](#)

**Table 7-181 typeinfo for `collate<wchar_t>`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>collate&lt;wchar_t&gt;</code>

### 7.1.109.2 Interfaces for Class `collate<wchar_t>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::collate<wchar_t>` specified in [Table 7-182](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-182 libstdc++ - Class `collate<wchar_t>` Function Interfaces**

<code>collate&lt;wchar_t&gt;::__M_transform(wchar_t*, wchar_t const*, unsigned long)</code> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>collate&lt;wchar_t&gt;::collate(__locale_struct*, unsigned long)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>collate&lt;wchar_t&gt;::collate(unsigned long)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>collate&lt;wchar_t&gt;::collate(__locale_struct*, unsigned long)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>collate&lt;wchar_t&gt;::collate(unsigned long)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 7.1.110 Class `collate_byname<char>`

### 7.1.110.1 Class data for `collate_byname<char>`

The virtual table for the `std::collate_byname<char>` class is described in the generic part of this specification.

The Run Time Type Information for the `std::collate_byname<char>` class is described by [Table 7-183](#)

**Table 7-183 typeinfo for `collate_byname<char>`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>collate_byname&lt;char&gt;</code>

### 7.1.110.2 Interfaces for Class `collate_byname<char>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::collate_byname<char>` specified in [Table 7-184](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-184 libstdc++ - Class collate\_byname<char> Function Interfaces**

collate_byname<char>::collate_byname(char const*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
collate_byname<char>::collate_byname(char const*, unsigned long) (GLIBCXX_3.4) <a href="#">[ISO CXX]</a>

## 7.1.111 Class collate\_byname<wchar\_t>

### 7.1.111.1 Interfaces for Class collate\_byname<wchar\_t>

No external methods are defined for libstdc++ - Class std::collate\_byname<wchar\_t> in this part of the specification. See also the generic specification.

## 7.1.112 Class time\_base

### 7.1.112.1 Class data for time\_base

The Run Time Type Information for the std::time\_base class is described by [Table 7-185](#)

**Table 7-185 typeinfo for time\_base**

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for time_base

### 7.1.112.2 Interfaces for Class time\_base

No external methods are defined for libstdc++ - Class std::time\_base in this part of the specification. See also the generic specification.

## 7.1.113 Class time\_get\_byname<char, istreambuf\_iterator<char, char\_traits<char>>>

### 7.1.113.1 Class data for time\_get\_byname<char, istreambuf\_iterator<char, char\_traits<char>>>

The virtual table for the std::time\_get\_byname<char, std::istreambuf\_iterator<char, std::char\_traits<char>>> class is described in the generic part of this specification.

The Run Time Type Information for the std::time\_get\_byname<char, std::istreambuf\_iterator<char, std::char\_traits<char>>> class is described by [Table 7-186](#)

**Table 7-186 typeinfo for time\_get\_byname<char, istreambuf\_iterator<char, char\_traits<char>>>**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for time_get_byname<char, istreambuf_iterator<char, char_traits<char>>>

### 7.1.113.2 Interfaces for Class `time_get_byname<char, istreambuf_iterator<char, char_traits<char>>>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::time_get_byname<char, std::istreambuf_iterator<char, std::char_traits<char>>>` specified in [Table 7-187](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-187 libstdc++ - Class `time_get_byname<char, istreambuf_iterator<char, char_traits<char>>>` Function Interfaces**

<code>time_get_byname&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;::time_get_byname(char const*, unsigned long)(GLIBCXX_3.4) [ISOCXX]</code>
<code>time_get_byname&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;::time_get_byname(char const*, unsigned long)(GLIBCXX_3.4) [ISOCXX]</code>

### 7.1.114 Class `time_get_byname<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>`

#### 7.1.114.1 Class data for `time_get_byname<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>`

The virtual table for the `std::time_get_byname<wchar_t, std::istreambuf_iterator<wchar_t, std::char_traits<wchar_t>>>` class is described in the generic part of this specification.

The Run Time Type Information for the `std::time_get_byname<wchar_t, std::istreambuf_iterator<wchar_t, std::char_traits<wchar_t>>>` class is described by [Table 7-188](#)

**Table 7-188 typeinfo for `time_get_byname<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>`**

Base Vtable	vtable for <code>__cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>time_get_byname&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;</code>

#### 7.1.114.2 Interfaces for Class `time_get_byname<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::time_get_byname<wchar_t, std::istreambuf_iterator<wchar_t, std::char_traits<wchar_t>>>` specified in [Table 7-189](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-189 libstdc++ - Class `time_get_byname<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>` Function Interfaces**

<code>time_get_byname&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;::time_get_byname(char const*, unsigned long)(GLIBCXX_3.4) [ISOCXX]</code>
--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

<pre>time_get_byname&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;::time_get_byname(char const*, unsigned long) (GLIBCXX_3.4) [ISOCXX]</pre>
-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

## 7.1.115 Class `time_put_byname<char, ostreambuf_iterator<char, char_traits<char>>>`

### 7.1.115.1 Class data for `time_put_byname<char, ostreambuf_iterator<char, char_traits<char>>>`

The virtual table for the `std::time_put_byname<char, std::ostreambuf_iterator<char, std::char_traits<char>>>` class is described in the generic part of this specification.

The Run Time Type Information for the `std::time_put_byname<char, std::ostreambuf_iterator<char, std::char_traits<char>>>` class is described by [Table 7-190](#)

**Table 7-190 typeinfo for `time_put_byname<char, ostreambuf_iterator<char, char_traits<char>>>`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>time_put_byname&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;</code>

### 7.1.115.2 Interfaces for Class `time_put_byname<char, ostreambuf_iterator<char, char_traits<char>>>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::time_put_byname<char, std::ostreambuf_iterator<char, std::char_traits<char>>>` specified in [Table 7-191](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-191 libstdcxx - Class `time_put_byname<char, ostreambuf_iterator<char, char_traits<char>>>` Function Interfaces**

<pre>time_put_byname&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; &gt;::time_put_byname(char const*, unsigned long)(GLIBCXX_3.4) [ISOCXX]</pre>
----------------------------------------------------------------------------------------------------------------------------------------------------------------------

<pre>time_put_byname&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; &gt;::time_put_byname(char const*, unsigned long)(GLIBCXX_3.4) [ISOCXX]</pre>
----------------------------------------------------------------------------------------------------------------------------------------------------------------------

## 7.1.116 Class `time_put_byname<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>`

### 7.1.116.1 Class data for `time_put_byname<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>`

The virtual table for the `std::time_put_byname<wchar_t, std::ostreambuf_iterator<wchar_t, std::char_traits<wchar_t>>>` class is described in the generic part of this specification.

The Run Time Type Information for the `std::time_put_byname<wchar_t, std::ostreambuf_iterator<wchar_t, std::char_traits<wchar_t>>` class is described by [Table 7-192](#)

**Table 7-192 typeinfo for `time_put_byname<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>time_put_byname&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code>

### **7.1.116.2 Interfaces for Class `time_put_byname<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>`**

An LSB conforming implementation shall provide the architecture specific methods for Class `std::time_put_byname<wchar_t, std::ostreambuf_iterator<wchar_t, std::char_traits<wchar_t>>` specified in [Table 7-193](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-193 libstdcxx - Class `time_put_byname<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>` Function Interfaces**

<code>time_put_byname&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::time_put_byname(char const*, unsigned long)</code> (GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
<code>time_put_byname&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::time_put_byname(char const*, unsigned long)</code> (GLIBCXX_3.4) <a href="#">[ISO CXX]</a>

### **7.1.117 Class `time_get<char, istreambuf_iterator<char, char_traits<char>>`**

#### **7.1.117.1 Class data for `time_get<char, istreambuf_iterator<char, char_traits<char>>`**

The virtual table for the `std::time_get<char, std::istreambuf_iterator<char, std::char_traits<char>>` class is described in the generic part of this specification.

#### **7.1.117.2 Interfaces for Class `time_get<char, istreambuf_iterator<char, char_traits<char>>`**

An LSB conforming implementation shall provide the architecture specific methods for Class `std::time_get<char, std::istreambuf_iterator<char, std::char_traits<char>>` specified in [Table 7-194](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-194 libstdcxx - Class `time_get<char, istreambuf_iterator<char, char_traits<char>>` Function Interfaces**

<code>time_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;</code> ->::_M_extract_num(istreambuf_iterator<char, char_traits<char>>,
-------------------------------------------------------------------------------------------------------------------------------------------------------------

istreambuf_iterator<char, char_traits<char> >, int&, int, int, unsigned long, ios_base&, _Ios_Iostate&) const(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
time_get<char, istreambuf_iterator<char, char_traits<char> > >::_M_extract_name(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, int&, char const**, unsigned long, ios_base&, _Ios_Iostate&) const(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
time_get<char, istreambuf_iterator<char, char_traits<char> > >::time_get(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
time_get<char, istreambuf_iterator<char, char_traits<char> > >::time_get(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>

## 7.1.118 Class **time\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t> >**

>

### 7.1.118.1 Class data for **time\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t> > >**

The virtual table for the std::time\_get<wchar\_t, std::istreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t> > > class is described in the generic part of this specification.

### 7.1.118.2 Interfaces for Class **time\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t> > >**

An LSB conforming implementation shall provide the architecture specific methods for Class std::time\_get<wchar\_t, std::istreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t> > > specified in [Table 7-195](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-195 libstdc++ - Class **time\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t> > >** Function Interfaces**

time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >::_M_extract_num(istreambuf_iterator<wchar_t, char_traits<wchar_t> >, istreambuf_iterator<wchar_t, char_traits<wchar_t> >, int&, int, int, unsigned long, ios_base&, _Ios_Iostate&) const(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >::_M_extract_name(istreambuf_iterator<wchar_t, char_traits<wchar_t> >, istreambuf_iterator<wchar_t, char_traits<wchar_t> >, int&, wchar_t const**, unsigned long, ios_base&, _Ios_Iostate&) const(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >::time_get(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >::time_get(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>

### **7.1.119 Class `time_put<char, ostreambuf_iterator<char, char_traits<char> >`**

#### **7.1.119.1 Class data for `time_put<char, ostreambuf_iterator<char, char_traits<char> >`**

The virtual table for the `std::time_put<char, std::ostreambuf_iterator<char, std::char_traits<char> >` class is described in the generic part of this specification.

The Run Time Type Information for the `std::time_put<char, std::ostreambuf_iterator<char, std::char_traits<char> >` class is described by [Table 7-196](#)

**Table 7-196 typeinfo for `time_put<char, ostreambuf_iterator<char, char_traits<char> >`**

Base Vtable	vtable for <code>__cxxabiv1::__si_class_type_info</code>	
Name	typeinfo name for <code>time_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;</code>	
flags:	8	
basetype:	typeinfo for <code>locale::facet</code>	2
basetype:	typeinfo for <code>time_base</code>	2

#### **7.1.119.2 Interfaces for Class `time_put<char, ostreambuf_iterator<char, char_traits<char> >`**

An LSB conforming implementation shall provide the architecture specific methods for Class `std::time_put<char, std::ostreambuf_iterator<char, std::char_traits<char> >` specified in [Table 7-197](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-197 libstdc++ - Class `time_put<char, ostreambuf_iterator<char, char_traits<char> >` Function Interfaces**

<code>time_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;</code> <code>&gt;::time_put(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>time_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;</code> <code>&gt;::time_put(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>

### **7.1.120 Class `time_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> >`**

#### **7.1.120.1 Class data for `time_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> >`**

The virtual table for the `std::time_put<wchar_t,`

`std::ostreambuf_iterator<wchar_t, std::char_traits<wchar_t> > >` class is described in the generic part of this specification.

The Run Time Type Information for the `std::time_put<wchar_t, std::ostreambuf_iterator<wchar_t, std::char_traits<wchar_t> > >` class is described by [Table 7-198](#)

**Table 7-198 typeinfo for `time_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> > >`**

Base Vtable	vtable for <code>__cxxabiv1::__si_class_type_info</code>	
Name	typeinfo name for <code>time_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;</code>	
flags:	8	
basetype:	typeinfo for <code>locale::facet</code>	2
basetype:	typeinfo for <code>time_base</code>	2

### **7.1.120.2 Interfaces for Class `time_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> > >`**

An LSB conforming implementation shall provide the architecture specific methods for Class `std::time_put<wchar_t, std::ostreambuf_iterator<wchar_t, std::char_traits<wchar_t> > >` specified in [Table 7-199](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-199 libstdc++ - Class `time_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> > >` Function Interfaces**

<code>time_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;::time_put(unsigned long)(GLIBCXX_3.4) [ISOCXX]</code>
<code>time_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;::time_put(unsigned long)(GLIBCXX_3.4) [ISOCXX]</code>

## **7.1.121 Class `moneypunct<char, false>`**

### **7.1.121.1 Class data for `moneypunct<char, false>`**

The virtual table for the `std::moneypunct<char, false>` class is described in the generic part of this specification.

### **7.1.121.2 Interfaces for Class `moneypunct<char, false>`**

An LSB conforming implementation shall provide the architecture specific methods for Class `std::moneypunct<char, false>` specified in [Table 7-200](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-200 libstdc++ - Class moneypunct<char, false> Function Interfaces**

moneypunct<char, false>::moneypunct(__locale_struct*, char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
moneypunct<char, false>::moneypunct(__moneypunct_cache<char, false>*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
moneypunct<char, false>::moneypunct(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
moneypunct<char, false>::moneypunct(__locale_struct*, char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
moneypunct<char, false>::moneypunct(__moneypunct_cache<char, false>*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
moneypunct<char, false>::moneypunct(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>

## 7.1.122 Class moneypunct<char, true>

### 7.1.122.1 Class data for moneypunct<char, true>

The virtual table for the std::moneypunct<char, true> class is described in the generic part of this specification.

### 7.1.122.2 Interfaces for Class moneypunct<char, true>

An LSB conforming implementation shall provide the architecture specific methods for Class std::moneypunct<char, true> specified in [Table 7-201](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-201 libstdc++ - Class moneypunct<char, true> Function Interfaces**

moneypunct<char, true>::moneypunct(__locale_struct*, char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
moneypunct<char, true>::moneypunct(__moneypunct_cache<char, true>*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
moneypunct<char, true>::moneypunct(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
moneypunct<char, true>::moneypunct(__locale_struct*, char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
moneypunct<char, true>::moneypunct(__moneypunct_cache<char, true>*, unsigned long)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
moneypunct<char, true>::moneypunct(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>

## 7.1.123 Class moneypunct<wchar\_t, false>

### 7.1.123.1 Class data for moneypunct<wchar\_t, false>

The virtual table for the std::moneypunct<wchar\_t, false> class is described in the generic part of this specification.

### 7.1.123.2 Interfaces for Class `moneypunct<wchar_t, false>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::moneypunct<wchar_t, false>` specified in [Table 7-202](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-202 libstdc++ - Class `moneypunct<wchar_t, false>` Function Interfaces**

<code>moneypunct&lt;wchar_t, false&gt;::moneypunct(__locale_struct*, char const*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOcxx]</a>
<code>moneypunct&lt;wchar_t, false&gt;::moneypunct(__moneypunct_cache&lt;wchar_t, false&gt;*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOcxx]</a>
<code>moneypunct&lt;wchar_t, false&gt;::moneypunct(unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOcxx]</a>
<code>moneypunct&lt;wchar_t, false&gt;::moneypunct(__locale_struct*, char const*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOcxx]</a>
<code>moneypunct&lt;wchar_t, false&gt;::moneypunct(__moneypunct_cache&lt;wchar_t, false&gt;*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOcxx]</a>
<code>moneypunct&lt;wchar_t, false&gt;::moneypunct(unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOcxx]</a>

### 7.1.124 Class `moneypunct<wchar_t, true>`

#### 7.1.124.1 Class data for `moneypunct<wchar_t, true>`

The virtual table for the `std::moneypunct<wchar_t, true>` class is described in the generic part of this specification.

#### 7.1.124.2 Interfaces for Class `moneypunct<wchar_t, true>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::moneypunct<wchar_t, true>` specified in [Table 7-203](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-203 libstdc++ - Class `moneypunct<wchar_t, true>` Function Interfaces**

<code>moneypunct&lt;wchar_t, true&gt;::moneypunct(__locale_struct*, char const*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOcxx]</a>
<code>moneypunct&lt;wchar_t, true&gt;::moneypunct(__moneypunct_cache&lt;wchar_t, true&gt;*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOcxx]</a>
<code>moneypunct&lt;wchar_t, true&gt;::moneypunct(unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOcxx]</a>
<code>moneypunct&lt;wchar_t, true&gt;::moneypunct(__locale_struct*, char const*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOcxx]</a>
<code>moneypunct&lt;wchar_t, true&gt;::moneypunct(__moneypunct_cache&lt;wchar_t, true&gt;*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOcxx]</a>
<code>moneypunct&lt;wchar_t, true&gt;::moneypunct(unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOcxx]</a>

## 7.1.125 Class `moneypunct_byname<char, false>`

### 7.1.125.1 Class data for `moneypunct_byname<char, false>`

The virtual table for the `std::moneypunct_byname<char, false>` class is described in the generic part of this specification.

The Run Time Type Information for the `std::moneypunct_byname<char, false>` class is described by [Table 7-204](#)

**Table 7-204 typeinfo for `moneypunct_byname<char, false>`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>moneypunct_byname&lt;char, false&gt;</code>

### 7.1.125.2 Interfaces for Class `moneypunct_byname<char, false>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::moneypunct_byname<char, false>` specified in [Table 7-205](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-205 libstdc++ - Class `moneypunct_byname<char, false>` Function Interfaces**

<code>moneypunct_byname&lt;char, false&gt;::moneypunct_byname(char const*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISO CXX]</a>
<code>moneypunct_byname&lt;char, false&gt;::moneypunct_byname(char const*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISO CXX]</a>

## 7.1.126 Class `moneypunct_byname<char, true>`

### 7.1.126.1 Class data for `moneypunct_byname<char, true>`

The virtual table for the `std::moneypunct_byname<char, true>` class is described in the generic part of this specification.

The Run Time Type Information for the `std::moneypunct_byname<char, true>` class is described by [Table 7-206](#)

**Table 7-206 typeinfo for `moneypunct_byname<char, true>`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>moneypunct_byname&lt;char, true&gt;</code>

### 7.1.126.2 Interfaces for Class `moneypunct_byname<char, true>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::moneypunct_byname<char, true>` specified in [Table 7-207](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-207 libstdc++ - Class `moneypunct_byname<char, true>` Function Interfaces**

<code>moneypunct_byname&lt;char, true&gt;::moneypunct_byname(char const*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISO CXX]</a>
----------------------------------------------------------------------------------------------------------------------------------------

<code>moneypunct_byname&lt;char, true&gt;::moneypunct_byname(char const*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISO CXX]</a>
----------------------------------------------------------------------------------------------------------------------------------------

## 7.1.127 Class `moneypunct_byname<wchar_t, false>`

### 7.1.127.1 Class data for `moneypunct_byname<wchar_t, false>`

The virtual table for the `std::moneypunct_byname<wchar_t, false>` class is described in the generic part of this specification.

The Run Time Type Information for the `std::moneypunct_byname<wchar_t, false>` class is described by [Table 7-208](#)

**Table 7-208 typeinfo for `moneypunct_byname<wchar_t, false>`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>moneypunct_byname&lt;wchar_t, false&gt;</code>

### 7.1.127.2 Interfaces for Class `moneypunct_byname<wchar_t, false>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::moneypunct_byname<wchar_t, false>` specified in [Table 7-209](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-209 libstdc++ - Class `moneypunct_byname<wchar_t, false>` Function Interfaces**

<code>moneypunct_byname&lt;wchar_t, false&gt;::moneypunct_byname(char const*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISO CXX]</a>
--------------------------------------------------------------------------------------------------------------------------------------------

<code>moneypunct_byname&lt;wchar_t, false&gt;::moneypunct_byname(char const*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISO CXX]</a>
--------------------------------------------------------------------------------------------------------------------------------------------

## 7.1.128 Class `moneypunct_byname<wchar_t, true>`

### 7.1.128.1 Class data for `moneypunct_byname<wchar_t, true>`

The virtual table for the `std::moneypunct_byname<wchar_t, true>` class is described in the generic part of this specification.

The Run Time Type Information for the `std::moneypunct_byname<wchar_t, true>` class is described by [Table 7-210](#)

**Table 7-210 typeinfo for `moneypunct_byname<wchar_t, true>`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>moneypunct_byname&lt;wchar_t,</code>

	true>
--	-------

### 7.1.128.2 Interfaces for Class `moneypunct_byname<wchar_t, true>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::moneypunct_byname<wchar_t, true>` specified in [Table 7-211](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-211 libstdcxx - Class `moneypunct_byname<wchar_t, true>` Function Interfaces**

<code>moneypunct_byname&lt;wchar_t, true&gt;::moneypunct_byname(char const*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISO CXX]</a>
<code>moneypunct_byname&lt;wchar_t, true&gt;::moneypunct_byname(char const*, unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISO CXX]</a>

## 7.1.129 Class `money_base`

### 7.1.129.1 Class data for `money_base`

The Run Time Type Information for the `std::money_base` class is described by [Table 7-212](#)

**Table 7-212 typeinfo for `money_base`**

Base Vtable	vtable for <code>_cxxabiv1::__class_type_info</code>
Name	typeinfo name for <code>money_base</code>

### 7.1.129.2 Interfaces for Class `money_base`

No external methods are defined for libstdcxx - Class `std::money_base` in this part of the specification. See also the generic specification.

## 7.1.130 Class `money_get<char, istreambuf_iterator<char, char_traits<char>>>`

### 7.1.130.1 Class data for `money_get<char, istreambuf_iterator<char, char_traits<char>>>`

The virtual table for the `std::money_get<char, std::istreambuf_iterator<char, std::char_traits<char>>>` class is described in the generic part of this specification.

The Run Time Type Information for the `std::money_get<char, std::istreambuf_iterator<char, std::char_traits<char>>>` class is described by [Table 7-213](#)

**Table 7-213 typeinfo for `money_get<char, istreambuf_iterator<char, char_traits<char>>>`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>money_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;</code>

	char_traits<char> > >
--	-----------------------

### **7.1.130.2 Interfaces for Class `money_get<char, istreambuf_iterator<char, char_traits<char> > >`**

An LSB conforming implementation shall provide the architecture specific methods for Class `std::money_get<char, std::istreambuf_iterator<char, std::char_traits<char> > >` specified in [Table 7-214](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-214 libstdcxx - Class `money_get<char, istreambuf_iterator<char, char_traits<char> > >` Function Interfaces**

<code>money_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::money_get(unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISO CXX]</a>
<code>money_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::money_get(unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISO CXX]</a>

### **7.1.131 Class `money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >`**

>

#### **7.1.131.1 Class data for `money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >`**

The virtual table for the `std::money_get<wchar_t, std::istreambuf_iterator<wchar_t, std::char_traits<wchar_t> > >` class is described in the generic part of this specification.

The Run Time Type Information for the `std::money_get<wchar_t, std::istreambuf_iterator<wchar_t, std::char_traits<wchar_t> > >` class is described by [Table 7-215](#)

**Table 7-215 typeinfo for `money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>money_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;</code>

#### **7.1.131.2 Interfaces for Class `money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >`**

An LSB conforming implementation shall provide the architecture specific methods for Class `std::money_get<wchar_t, std::istreambuf_iterator<wchar_t, std::char_traits<wchar_t> > >` specified in [Table 7-216](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-216 libstdcxx - Class `money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >` Function Interfaces**

<code>money_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;</code>
---------------------------------------------------------------------------------------------------------

>::money_get(unsigned long)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >::money_get(unsigned long)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>

### 7.1.132 Class `money_put<char, ostreambuf_iterator<char, char_traits<char> > >`

#### 7.1.132.1 Class data for `money_put<char, ostreambuf_iterator<char, char_traits<char> > >`

The virtual table for the `std::money_put<char, std::ostreambuf_iterator<char, std::char_traits<char> > >` class is described in the generic part of this specification.

The Run Time Type Information for the `std::money_put<char, std::ostreambuf_iterator<char, std::char_traits<char> > >` class is described by [Table 7-217](#)

**Table 7-217 typeinfo for `money_put<char, ostreambuf_iterator<char, char_traits<char> > >`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;</code>

#### 7.1.132.2 Interfaces for Class `money_put<char, ostreambuf_iterator<char, char_traits<char> > >`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::money_put<char, std::ostreambuf_iterator<char, std::char_traits<char> > >` specified in [Table 7-218](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-218 libstdcxx - Class `money_put<char, ostreambuf_iterator<char, char_traits<char> > >` Function Interfaces**

<code>money_put<char, ostreambuf_iterator<char, char_traits<char> > >::money_put(unsigned long)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
<code>money_put<char, ostreambuf_iterator<char, char_traits<char> > >::money_put(unsigned long)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>

### 7.1.133 Class `money_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> > >`

#### 7.1.133.1 Class data for `money_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> > >`

The virtual table for the `std::money_put<wchar_t, std::ostreambuf_iterator<wchar_t, std::char_traits<wchar_t> > >` class is described in the generic part of this specification.

The Run Time Type Information for the std::money\_put<wchar\_t, std::ostreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t>> class is described by [Table 7-219](#)

**Table 7-219 typeinfo for money\_put<wchar\_t, ostreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for money_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>

### 7.1.133.2 Interfaces for Class money\_put<wchar\_t, ostreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>

An LSB conforming implementation shall provide the architecture specific methods for Class std::money\_put<wchar\_t, std::ostreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t>> specified in [Table 7-220](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-220 libstdc++ - Class money\_put<wchar\_t, ostreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>> Function Interfaces**

money_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>::money_put(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
money_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>::money_put(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 7.1.134 Class locale

### 7.1.134.1 Interfaces for Class locale

An LSB conforming implementation shall provide the architecture specific methods for Class std::locale specified in [Table 7-221](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-221 libstdc++ - Class locale Function Interfaces**

locale::Impl::Impl(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[LSB]</a>
locale::Impl::Impl(locale::Impl const&, unsigned long)(GLIBCXX_3.4) <a href="#">[LSB]</a>
locale::Impl::Impl(unsigned long)(GLIBCXX_3.4) <a href="#">[LSB]</a>
locale::Impl::Impl(char const*, unsigned long)(GLIBCXX_3.4) <a href="#">[LSB]</a>
locale::Impl::Impl(locale::Impl const&, unsigned long)(GLIBCXX_3.4) <a href="#">[LSB]</a>
locale::Impl::Impl(unsigned long)(GLIBCXX_3.4) <a href="#">[LSB]</a>

## 7.1.135 Class locale::facet

### 7.1.135.1 Class data for locale::facet

The virtual table for the std::locale::facet class is described in the generic part of this specification.

The Run Time Type Information for the std::locale::facet class is described by [Table 7-222](#)

**Table 7-222 typeinfo for locale::facet**

Base Vtable	vtable for _cxxabiv1::__class_type_info
Name	typeinfo name for locale::facet

### 7.1.135.2 Interfaces for Class locale::facet

No external methods are defined for libstdcxx - Class std::locale::facet in this part of the specification. See also the generic specification.

## 7.1.136 facet functions

### 7.1.136.1 Interfaces for facet functions

No external methods are defined for libstdcxx - facet functions in this part of the specification. See also the generic specification.

## 7.1.137 Class \_\_num\_base

### 7.1.137.1 Class data for \_\_num\_base

### 7.1.137.2 Interfaces for Class \_\_num\_base

No external methods are defined for libstdcxx - Class std::\_\_num\_base in this part of the specification. See also the generic specification.

## 7.1.138 Class num\_get<char, istreambuf\_iterator<char, char\_traits<char> > >

### 7.1.138.1 Class data for num\_get<char, istreambuf\_iterator<char, char\_traits<char> > >

The virtual table for the std::num\_get<char, std::istreambuf\_iterator<char, std::char\_traits<char> > > class is described in the generic part of this specification.

The Run Time Type Information for the std::num\_get<char, std::istreambuf\_iterator<char, std::char\_traits<char> > > class is described by [Table 7-223](#)

**Table 7-223 typeinfo for num\_get<char, istreambuf\_iterator<char,  
char\_traits<char> > >**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for num_get<char, istreambuf_iterator<char, char_traits<char> > >
basetype:	typeinfo for locale::facet

### **7.1.138.2 Interfaces for Class num\_get<char, istreambuf\_iterator<char, char\_traits<char> > >**

An LSB conforming implementation shall provide the architecture specific methods for Class std::num\_get<char, std::istreambuf\_iterator<char, std::char\_traits<char> > > specified in [Table 7-224](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-224 libstdcxx - Class num\_get<char, istreambuf\_iterator<char, char\_traits<char> > > Function Interfaces**

num_get<char, istreambuf_iterator<char, char_traits<char> > >::num_get(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
-----------------------------------------------------------------------------------------------------------------------------

num_get<char, istreambuf_iterator<char, char_traits<char> > >::num_get(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
-----------------------------------------------------------------------------------------------------------------------------

### **7.1.139 Class num\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t> > >**

#### **7.1.139.1 Class data for num\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t> > >**

The virtual table for the std::num\_get<wchar\_t, std::istreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t> > > class is described in the generic part of this specification.

The Run Time Type Information for the std::num\_get<wchar\_t, std::istreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t> > > class is described by [Table 7-225](#)

**Table 7-225 typeinfo for num\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t> > >**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for num_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >
basetype:	typeinfo for locale::facet

#### **7.1.139.2 Interfaces for Class num\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t> > >**

An LSB conforming implementation shall provide the architecture specific methods for Class std::num\_get<wchar\_t, std::istreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t> > > specified in [Table 7-226](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-226 libstdcxx - Class num\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t> > > Function Interfaces**

num_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >::num_get(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
--------------------------------------------------------------------------------------------------------------------------------------

num_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >::num_get(unsigned long)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
------------------------------------------------------------------------------------------------------------------------------------------

### 7.1.140 Class num\_put<char, ostreambuf\_iterator<char, char\_traits<char> > >

#### 7.1.140.1 Class data for num\_put<char, ostreambuf\_iterator<char, char\_traits<char> > >

The virtual table for the std::num\_put<char, std::ostreambuf\_iterator<char, std::char\_traits<char> > > class is described in the generic part of this specification.

The Run Time Type Information for the std::num\_put<char, std::ostreambuf\_iterator<char, std::char\_traits<char> > > class is described by [Table 7-227](#)

**Table 7-227 typeinfo for num\_put<char, ostreambuf\_iterator<char, char\_traits<char> > >**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for num_put<char, ostreambuf_iterator<char, char_traits<char> > >
basetype:	typeinfo for locale::facet

#### 7.1.140.2 Interfaces for Class num\_put<char, ostreambuf\_iterator<char, char\_traits<char> > >

An LSB conforming implementation shall provide the architecture specific methods for Class std::num\_put<char, std::ostreambuf\_iterator<char, std::char\_traits<char> > > specified in [Table 7-228](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-228 libstdc++ - Class num\_put<char, ostreambuf\_iterator<char, char\_traits<char> > > Function Interfaces**

num_put<char, ostreambuf_iterator<char, char_traits<char> > >::_M_group_int(char const*, unsigned long, char, ios_base&, char*, char*, int&) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
num_put<char, ostreambuf_iterator<char, char_traits<char> > >::_M_group_float(char const*, unsigned long, char, char const*, char*, char*, int&) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
num_put<char, ostreambuf_iterator<char, char_traits<char> > >::_M_pad(char, long, ios_base&, char*, char const*, int&) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
num_put<char, ostreambuf_iterator<char, char_traits<char> > >::num_put(unsigned long)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
num_put<char, ostreambuf_iterator<char, char_traits<char> > >::num_put(unsigned long)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>

## 7.1.141 Class num\_put<wchar\_t, ostreambuf\_iterator<wchar\_t, char\_traits<wchar\_t> > >

### 7.1.141.1 Class data for num\_put<wchar\_t, ostreambuf\_iterator<wchar\_t, char\_traits<wchar\_t> >>

The virtual table for the std::num\_put<wchar\_t, std::ostreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t> >> class is described in the generic part of this specification.

The Run Time Type Information for the std::num\_put<wchar\_t, std::ostreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t> >> class is described by [Table 7-229](#)

**Table 7-229 typeinfo for num\_put<wchar\_t, ostreambuf\_iterator<wchar\_t, char\_traits<wchar\_t> >>**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;&gt;</code>
basetype:	typeinfo for locale::facet

### 7.1.141.2 Interfaces for Class num\_put<wchar\_t, ostreambuf\_iterator<wchar\_t, char\_traits<wchar\_t> >>

An LSB conforming implementation shall provide the architecture specific methods for Class std::num\_put<wchar\_t, std::ostreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t> >> specified in [Table 7-230](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-230 libstdc++ - Class num\_put<wchar\_t, ostreambuf\_iterator<wchar\_t, char\_traits<wchar\_t> >> Function Interfaces**

<code>num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;&gt;::_M_group_int(char const*, unsigned long, wchar_t, ios_base&amp;, wchar_t*, wchar_t*, int&amp;) const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;&gt;::_M_group_float(char const*, unsigned long, wchar_t, wchar_t const*, wchar_t*, wchar_t*, int&amp;) const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;&gt;::_M_pad(wchar_t, long, ios_base&amp;, wchar_t*, wchar_t const*, int&amp;) const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;&gt;::num_put(unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;&gt;::num_put(unsigned long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

## 7.1.142 Class `gslice`

### 7.1.142.1 Class data for `gslice`

### 7.1.142.2 Interfaces for Class `gslice`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::gslice` specified in [Table 7-231](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-231 libstdc++ - Class `gslice` Function Interfaces**

<code>gslice::_Indexer::_Indexer(unsigned long, valarray&lt;unsigned long&gt; const&amp;, valarray&lt;unsigned long&gt; const&amp;)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>gslice::_Indexer::_Indexer(unsigned long, valarray&lt;unsigned long&gt; const&amp;, valarray&lt;unsigned long&gt; const&amp;)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

## 7.1.143 Class `__basic_file<char>`

### 7.1.143.1 Class data for `__basic_file<char>`

### 7.1.143.2 Interfaces for Class `__basic_file<char>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::__basic_file<char>` specified in [Table 7-232](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-232 libstdc++ - Class `__basic_file<char>` Function Interfaces**

<code>__basic_file&lt;char&gt;::xsgtn(char*, long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>__basic_file&lt;char&gt;::xspn(char const*, long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>__basic_file&lt;char&gt;::seekoff(long, _Ios_Seekdir)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>__basic_file&lt;char&gt;::xspn_2(char const*, long, char const*, long)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

## 7.1.144 Class `_List_node_base`

### 7.1.144.1 Interfaces for Class `_List_node_base`

No external methods are defined for libstdc++ - Class `std::_List_node_base` in this part of the specification. See also the generic specification.

## 7.1.145 Class `valarray<unsigned int>`

### 7.1.145.1 Class data for `valarray<unsigned int>`

### 7.1.145.2 Interfaces for Class `valarray<unsigned int>`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::valarray<unsigned int>` specified in [Table 7-233](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-233 libstdc++ - Class `valarray<unsigned int>` Function Interfaces**

<code>valarray&lt;unsigned long&gt;::size() const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
------------------------------------------------------------------------------------------------

valarray<unsigned long>::valarray(valarray<unsigned long> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
valarray<unsigned long>::valarray(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
valarray<unsigned long>::valarray(valarray<unsigned long> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
valarray<unsigned long>::valarray(unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
valarray<unsigned long>::~valarray()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
valarray<unsigned long>::~valarray()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
valarray<unsigned long>::operator[](unsigned long)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 7.1.146 Class allocator<char>

### 7.1.146.1 Class data for allocator<char>

### 7.1.146.2 Interfaces for Class allocator<char>

No external methods are defined for libstdcxx - Class std::allocator<char> in this part of the specification. See also the generic specification.

## 7.1.147 Class allocator<wchar\_t>

### 7.1.147.1 Class data for allocator<wchar\_t>

### 7.1.147.2 Interfaces for Class allocator<wchar\_t>

No external methods are defined for libstdcxx - Class std::allocator<wchar\_t> in this part of the specification. See also the generic specification.

## 7.1.148 Class \_\_gnu\_cxx::\_\_pool<true>

### 7.1.148.1 Interfaces for Class \_\_gnu\_cxx::\_\_pool<true>

An LSB conforming implementation shall provide the architecture specific methods for Class \_\_gnu\_cxx::\_\_pool<true> specified in [Table 7-234](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-234 libstdcxx - Class \_\_gnu\_cxx::\_\_pool<true> Function Interfaces**

__gnu_cxx::__pool<true>::__M_reclaim_block(char*, unsigned long)(GLIBCXX_3.4.4) <a href="#">[LSB]</a>
__gnu_cxx::__pool<true>::__M_reserve_block(unsigned long, unsigned long)(GLIBCXX_3.4.4) <a href="#">[LSB]</a>

## 7.1.149 Class \_\_gnu\_cxx::\_\_pool<false>

### 7.1.149.1 Interfaces for Class \_\_gnu\_cxx::\_\_pool<false>

An LSB conforming implementation shall provide the architecture specific methods for Class \_\_gnu\_cxx::\_\_pool<false> specified in [Table 7-235](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-235 libstdc++ - Class `__gnu_cxx::__pool<false>` Function Interfaces**

<code>__gnu_cxx::__pool&lt;false&gt;::__M_reclaim_block(char*, unsigned long)</code> (GLIBCXX_3.4.4) <a href="#">[LSB]</a>
<code>__gnu_cxx::__pool&lt;false&gt;::__M_reserve_block(unsigned long, unsigned long)</code> (GLIBCXX_3.4.4) <a href="#">[LSB]</a>

## 7.1.150 Class `__gnu_cxx::free_list`

### 7.1.150.1 Interfaces for Class `__gnu_cxx::free_list`

An LSB conforming implementation shall provide the architecture specific methods for Class `__gnu_cxx::free_list` specified in [Table 7-236](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-236 libstdc++ - Class `__gnu_cxx::free_list` Function Interfaces**

<code>__gnu_cxx::free_list::__M_get(unsigned long)</code> (GLIBCXX_3.4.4) <a href="#">[LSB]</a>
-------------------------------------------------------------------------------------------------

## 7.1.151 Class `locale::_Impl`

### 7.1.151.1 Interfaces for Class `locale::_Impl`

An LSB conforming implementation shall provide the architecture specific methods for Class `std::locale::_Impl` specified in [Table 7-237](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-237 libstdc++ - Class `locale::_Impl` Function Interfaces**

<code>locale::_Impl::__M_install_cache(locale::facet const*, unsigned long)</code> (GLIBCXX_3.4.7) <a href="#">[ISOCXX]</a>
--------------------------------------------------------------------------------------------------------------------------------

## 7.1.152 Namespace std Functions

### 7.1.152.1 Interfaces for Namespace std Functions

An LSB conforming implementation shall provide the architecture specific methods for Namespace std Functions specified in [Table 7-238](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-238 libstdc++ - Namespace std Functions Function Interfaces**

<code>long __copy_streambufs&lt;char, char_traits&lt;char&gt;&gt;(basic_streambuf&lt;char, char_traits&lt;char&gt;&gt;*, basic_streambuf&lt;char, char_traits&lt;char&gt;&gt;*)</code> (GLIBCXX_3.4.8) <a href="#">[ISOCXX]</a>
<code>long __copy_streambufs&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;(basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;*, basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;*)</code> (GLIBCXX_3.4.8) <a href="#">[ISOCXX]</a>

## 7.1.153 Class `char_traits<char>`

### 7.1.153.1 Interfaces for Class `char_traits<char>`

No external methods are defined for libstdc++ - Class `std::char_traits<char>` in this part of the specification. See also the generic specification.

## **7.1.154 Class `char_traits<wchar_t>`**

### **7.1.154.1 Interfaces for Class `char_traits<wchar_t>`**

No external methods are defined for libstdcxx - Class std::char\_traits<wchar\_t> in this part of the specification. See also the generic specification.

## **7.2 Interface Definitions for libstdcxx**

The interfaces defined on the following pages are included in libstdcxx and are defined by this specification. Unless otherwise noted, these interfaces shall be included in the source standard.

Other interfaces listed in [Section 7.1](#) shall behave as described in the referenced base document. For interfaces referencing LSB and not listed below, please see the generic part of the specification.

## **Annex A GNU Free Documentation License (Informative)**

This specification is published under the terms of the GNU Free Documentation License, Version 1.1, March 2000

Copyright (C) 2000 Free Software Foundation, Inc. 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

### **A.1 PREAMBLE**

The purpose of this License is to make a manual, textbook, or other written document "free" in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondarily, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of "copyleft", which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

### **A.2 APPLICABILITY AND DEFINITIONS**

This License applies to any manual or other work that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. The "Document", below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as "you".

A "Modified Version" of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A "Secondary Section" is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (For example, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The "Invariant Sections" are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License.

The "Cover Texts" are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License.

*(Informative)*

A "Transparent" copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, whose contents can be viewed and edited directly and straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup has been designed to thwart or discourage subsequent modification by readers is not Transparent. A copy that is not "Transparent" is called "Opaque".

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML designed for human modification. Opaque formats include PostScript, PDF, proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML produced by some word processors for output purposes only.

The "Title Page" means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, "Title Page" means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

### A.3 VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

### A.4 COPYING IN QUANTITY

If you publish printed copies of the Document numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a publicly-accessible computer-network location containing a complete Transparent copy of the Document, free of added material, which the general network-using public has access to download anonymously at no charge using public-standard network protocols. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

## A.5 MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

- A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.
- B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has less than five).
- C. State on the Title page the name of the publisher of the Modified Version, as the publisher.
- D. Preserve all the copyright notices of the Document.
- E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.
- F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.
- G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.
- H. Include an unaltered copy of this License.
  - I. Preserve the section entitled "History", and its title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.

(Informative)

- J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.
- K. In any section entitled "Acknowledgements" or "Dedications", preserve the section's title, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.
- L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.
- M. Delete any section entitled "Endorsements". Such a section may not be included in the Modified Version.
- N. Do not retitle any existing section as "Endorsements" or to conflict in title with any Invariant Section.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version's license notice. These titles must be distinct from any other section titles.

You may add a section entitled "Endorsements", provided it contains nothing but endorsements of your Modified Version by various parties--for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

## A.6 COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the ti-

tle of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections entitled "History" in the various original documents, forming one section entitled "History"; likewise combine any sections entitled "Acknowledgements", and any sections entitled "Dedications". You must delete all sections entitled "Endorsements."

## A.7 COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

## A.8 AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, does not as a whole count as a Modified Version of the Document, provided no compilation copyright is claimed for the compilation. Such a compilation is called an "aggregate", and this License does not apply to the other self-contained works thus compiled with the Document, on account of their being thus compiled, if they are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one quarter of the entire aggregate, the Document's Cover Texts may be placed on covers that surround only the Document within the aggregate. Otherwise they must appear on covers around the whole aggregate.

## A.9 TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License provided that you also include the original English version of this License. In case of a disagreement between the translation and the original English version of this License, the original English version will prevail.

## A.10 TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided for under this License. Any other attempt to copy, modify, sublicense or distribute the Document is void, and will automatically terminate your rights under this License. However, parties who have received copies, or

rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

## A.11 FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See <http://www.gnu.org/copyleft/>.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License "or any later version" applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation.

## A.12 How to use this License for your documents

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

Copyright (c) YEAR YOUR NAME. Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.1 or any later version published by the Free Software Foundation; with the Invariant Sections being LIST THEIR TITLES, with the Front-Cover Texts being LIST, and with the Back-Cover Texts being LIST. A copy of the license is included in the section entitled "GNU Free Documentation License".

If you have no Invariant Sections, write "with no Invariant Sections" instead of saying which ones are invariant. If you have no Front-Cover Texts, write "no Front-Cover Texts" instead of "Front-Cover Texts being LIST"; likewise for Back-Cover Texts.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.