

# **Linux Standard Base C++ Specification 4.0**

## **Linux Standard Base C++ Specification 4.0**

Copyright © 2008 Linux Foundation

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.1; with no Invariant Sections, with no Front-Cover Texts, and with no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".

Portions of the text may be copyrighted by the following parties:

- The Regents of the University of California
- Free Software Foundation
- Ian F. Darwin
- Paul Vixie
- BSDI (now Wind River)
- Andrew G Morgan
- Jean-loup Gailly and Mark Adler
- Massachusetts Institute of Technology
- Apple Inc.
- Easy Software Products
- artofcode LLC
- Till Kamppeter
- Manfred Wassman
- Python Software Foundation

These excerpts are being used in accordance with their respective licenses.

Linux is the registered trademark of Linus Torvalds in the U.S. and other countries.

UNIX is a registered trademark of The Open Group.

LSB is a trademark of the Linux Foundation in the United States and other countries.

AMD is a trademark of Advanced Micro Devices, Inc.

Intel and Itanium are registered trademarks and Intel386 is a trademark of Intel Corporation.

PowerPC is a registered trademark and PowerPC Architecture is a trademark of the IBM Corporation.

S/390 is a registered trademark of the IBM Corporation.

OpenGL is a registered trademark of Silicon Graphics, Inc.

# Contents

<u>I Introductory Elements</u> .....
1 Scope.....
1.1 General.....
1.2 Module Specific Scope.....
2 Normative References.....
3 Requirements.....
3.1 Relevant Libraries.....
3.2 LSB Implementation Conformance.....
3.3 LSB Application Conformance.....
4 Definitions.....
5 Terminology.....
6 Documentation Conventions.....
<u>II Low Level System Information</u> .....
7 C++ Class Representations.....
7.1 C++ Data Representation.....
8 Symbol Mapping.....
8.1 Symbol Mapping.....
<u>III Base Libraries</u> .....
9 Libraries.....
9.1 Interfaces for libstdcxx.....
9.2 Interface Definitions for libstdcxx.....
<u>A GNU Free Documentation License (Informative)</u> .....
A.1 PREAMBLE.....
A.2 APPLICABILITY AND DEFINITIONS.....
A.3 VERBATIM COPYING.....
A.4 COPYING IN QUANTITY.....
A.5 MODIFICATIONS.....
A.6 COMBINING DOCUMENTS.....
A.7 COLLECTIONS OF DOCUMENTS.....
A.8 AGGREGATION WITH INDEPENDENT WORKS.....
A.9 TRANSLATION.....
A.10 TERMINATION.....
A.11 FUTURE REVISIONS OF THIS LICENSE.....
A.12 How to use this License for your documents.....

## List of Figures

<a href="#"><u>7-1 Category 1 Virtual Table</u></a> .....
<a href="#"><u>7-2 Category 2 Virtual Table</u></a> .....
<a href="#"><u>7-3 Run-Time Type Information Prefix</u></a> .....
<a href="#"><u>7-4 Run-Time Type Information For Classes with no base class</u></a> .....
<a href="#"><u>7-5 Run-Time Type Information for Classes with a single base class</u></a> .....
<a href="#"><u>7-6 Run-Time Type Information for classes with multiple inheritance</u></a> .....
<a href="#"><u>7-7 Run-Time Type Information for pointer types</u></a> .....
<a href="#"><u>7-8 Run-Time Type Information for pointer to member types</u></a> .....

## **Foreword**

This is version 4.0 of the Linux Standard Base C++ Specification. This specification is part of a family of specifications under the general title "Linux Standard Base". Developers of applications or implementations interested in using the LSB trademark should see the Linux Foundation Certification Policy for details.

## Introduction

The LSB defines a binary interface for application programs that are compiled and packaged for LSB-conforming implementations on many different hardware architectures. Since a binary specification shall include information specific to the computer processor architecture for which it is intended, it is not possible for a single document to specify the interface for all possible LSB-conforming implementations. Therefore, the LSB is a family of specifications, rather than a single one.

This document should be used in conjunction with the documents it references. This document enumerates the system components it includes, but descriptions of those components may be included entirely or partly in this document, partly in other documents, or entirely in other reference documents. For example, the section that describes system service routines includes a list of the system routines supported in this interface, formal declarations of the data structures they use that are visible to applications, and a pointer to the underlying referenced specification for information about the syntax and semantics of each call. Only those routines not described in standards referenced by this document, or extensions to those standards, are described in the detail. Information referenced in this way is as much a part of this document as is the information explicitly included here.

The specification carries a version number of either the form  $x.y$  or  $x.y.z$ . This version number carries the following meaning:

- The first number ( $x$ ) is the major version number. All versions with the same major version number should share binary compatibility. Any addition or deletion of a new library results in a new version number. Interfaces marked as deprecated may be removed from the specification at a major version change.
- The second number ( $y$ ) is the minor version number. Individual interfaces may be added if all certified implementations already had that (previously undocumented) interface. Interfaces may be marked as deprecated at a minor version change. Other minor changes may be permitted at the discretion of the LSB workgroup.
- The third number ( $z$ ), if present, is the editorial level. Only editorial changes should be included in such versions.

Since this specification is a descriptive Application Binary Interface, and not a source level API specification, it is not possible to make a guarantee of 100% backward compatibility between major releases. However, it is the intent that those parts of the binary interface that are visible in the source level API will remain backward compatible from version to version, except where a feature marked as "Deprecated" in one release may be removed from a future release.

Implementors are strongly encouraged to make use of symbol versioning to permit simultaneous support of applications conforming to different releases of this specification.

## I Introductory Elements

# 1 Scope

## 1.1 General

The Linux Standard Base (LSB) defines a system interface for compiled applications and a minimal environment for support of installation scripts. Its purpose is to enable a uniform industry standard environment for high-volume applications conforming to the LSB.

These specifications are composed of two basic parts: A common specification ("LSB-generic" or "generic LSB"), ISO/IEC 23360 Part 1, describing those parts of the interface that remain constant across all implementations of the LSB, and an architecture-specific part ("LSB-arch" or "archLSB") describing the parts of the interface that vary by processor architecture. Together, the LSB-generic and the relevant architecture-specific part of ISO/IEC 23360 for a single hardware architecture provide a complete interface specification for compiled application programs on systems that share a common hardware architecture.

ISO/IEC 23360 Part 1, the LSB-generic document, should be used in conjunction with an architecture-specific part. Whenever a section of the LSB-generic specification is supplemented by architecture-specific information, the LSB-generic document includes a reference to the architecture part. Architecture-specific parts of ISO/IEC 23360 may also contain additional information that is not referenced in the LSB-generic document.

The LSB contains both a set of Application Program Interfaces (APIs) and Application Binary Interfaces (ABIs). APIs may appear in the source code of portable applications, while the compiled binary of that application may use the larger set of ABIs. A conforming implementation provides all of the ABIs listed here. The compilation system may replace (e.g. by macro definition) certain APIs with calls to one or more of the underlying binary interfaces, and may insert calls to binary interfaces as needed.

The LSB is primarily a binary interface definition. Not all of the source level APIs available to applications may be contained in this specification.

## 1.2 Module Specific Scope

This is the C++ module of the Linux Standards Base (LSB). This module supplements the core interfaces by providing system interfaces, libraries, and a run-time environment for applications built using the C++ programming language. These interfaces provide low-level support for the core constructs of the language, and implement the standard base C++ libraries.

Interfaces described in this module are presented in terms of C++; the binary interfaces will use encoded or mangled versions of the names.

## 2 Normative References

The specifications listed below are referenced in whole or in part by this module of the Linux Standard Base. In this specification, where only a particular section of one of these references is identified, then the normative reference is to that section alone, and the rest of the referenced document is informative.

**Table 2-1 Normative References**

Name	Title	URL
ISO/IEC 23360 Part 1	ISO/IEC 23360:2005 Linux Standard Base - Part 1 Generic Specification	<a href="http://www.linuxbase.org/spec/">http://www.linuxbase.org/spec/</a>
ISO C (1999)	ISO/IEC 9899: 1999, Programming Languages --C	
ISO POSIX (2003)	ISO/IEC 9945-1:2003 Information technology -- Portable Operating System Interface (POSIX) -- Part 1: Base Definitions  ISO/IEC 9945-2:2003 Information technology -- Portable Operating System Interface (POSIX) -- Part 2: Sys- tem Interfaces  ISO/IEC 9945-3:2003 Information technology -- Portable Operating System Interface (POSIX) -- Part 3: Shell and Utilities  ISO/IEC 9945-4:2003 Information technology -- Portable Operating System Interface (POSIX) -- Part 4: Ratio- nale  Including Technical Cor. 1: 2004	<a href="http://www.unix.org/version3/">http://www.unix.org/ version3/</a>
ISO/IEC 14882: 2003 C++ Language	ISO/IEC 14882: 2003 Programming languages --C++	
Itanium™ C++ ABI	Itanium™ C++ ABI (Revision 1.83)	<a href="http://refspecs.linux-foundation.org/cxxabi-1.83.html">http://refspecs.linux- foundation.org/cxxabi- 1.83.html</a>

## 3 Requirements

### 3.1 Relevant Libraries

The libraries listed in [Table 3-1](#) shall be available on a Linux Standard Base system, with the specified runtime names.

**Table 3-1 Standard Library Names**

Library	Runtime Name
libstdcxx	libstdc++.so.6

These libraries will be in an implementation-defined directory which the dynamic linker shall search by default.

### 3.2 LSB Implementation Conformance

An implementation shall satisfy the following requirements:

- The implementation shall implement fully the architecture described in the hardware manual for the target processor architecture.
- The implementation shall be capable of executing compiled applications having the format and using the system interfaces described in this document.
- The implementation shall provide libraries containing the interfaces specified by this document, and shall provide a dynamic linking mechanism that allows these interfaces to be attached to applications at runtime. All the interfaces shall behave as specified in this document.
- The map of virtual memory provided by the implementation shall conform to the requirements of this document.
- The implementation's low-level behavior with respect to function call linkage, system traps, signals, and other such activities shall conform to the formats described in this document.
- The implementation shall provide all of the mandatory interfaces in their entirety.
- The implementation may provide one or more of the optional interfaces. Each optional interface that is provided shall be provided in its entirety. The product documentation shall state which optional interfaces are provided.
- The implementation shall provide all files and utilities specified as part of this document in the format defined here and in other referenced documents. All commands and utilities shall behave as required by this document. The implementation shall also provide all mandatory components of an application's runtime environment that are included or referenced in this document.
- The implementation, when provided with standard data formats and values at a named interface, shall provide the behavior defined for those values and data formats at that interface. However, a conforming implementation may consist of components which are separately packaged and/or sold. For example, a vendor of a conforming implementation might sell the hardware, operating system, and windowing system as separately packaged items.
- The implementation may provide additional interfaces with different names. It may also provide additional behavior corresponding to data values outside

the standard ranges, for standard named interfaces.

### 3.3 LSB Application Conformance

An application shall satisfy the following requirements:

- Its executable files are either shell scripts or object files in the format defined for the Object File Format system interface.
- Its object files participate in dynamic linking as defined in the Program Loading and Linking System interface.
- It employs only the instructions, traps, and other low-level facilities defined in the Low-Level System interface as being for use by applications.
- If it requires any optional interface defined in this document in order to be installed or to execute successfully, the requirement for that optional interface is stated in the application's documentation.
- It does not use any interface or data format that is not required to be provided by a conforming implementation, unless:
  - If such an interface or data format is supplied by another application through direct invocation of that application during execution, that application is in turn an LSB conforming application.
  - The use of that interface or data format, as well as its source, is identified in the documentation of the application.
- It shall not use any values for a named interface that are reserved for vendor extensions.

A strictly conforming application does not require or use any interface, facility, or implementation-defined extension that is not defined in this document in order to be installed or to execute successfully.

## 4 Definitions

For the purposes of this document, the following definitions, as specified in the *ISO/IEC Directives, Part 2, 2001, 4th Edition*, apply:

can

be able to; there is a possibility of; it is possible to

cannot

be unable to; there is no possibility of; it is not possible to

may

is permitted; is allowed; is permissible

need not

it is not required that; no...is required

shall

is to; is required to; it is required that; has to; only...is permitted; it is necessary

shall not

is not allowed [permitted] [acceptable] [permissible]; is required to be not; is required that...be not; is not to be

should

it is recommended that; ought to

should not

it is not recommended that; ought not to

## 5 Terminology

For the purposes of this document, the following terms apply:

### archLSB

The architectural part of the LSB Specification which describes the specific parts of the interface that are platform specific. The archLSB is complementary to the gLSB.

### Binary Standard

The total set of interfaces that are available to be used in the compiled binary code of a conforming application.

### gLSB

The common part of the LSB Specification that describes those parts of the interface that remain constant across all hardware implementations of the LSB.

### implementation-defined

Describes a value or behavior that is not defined by this document but is selected by an implementor. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence of the value or behavior. An application that relies on such a value or behavior cannot be assured to be portable across conforming implementations. The implementor shall document such a value or behavior so that it can be used correctly by an application.

### Shell Script

A file that is read by an interpreter (e.g., awk). The first line of the shell script includes a reference to its interpreter binary.

### Source Standard

The set of interfaces that are available to be used in the source code of a conforming application.

### undefined

Describes the nature of a value or behavior not defined by this document which results from use of an invalid program construct or invalid data input. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence or validity of the value or behavior. An application that relies on any particular value or behavior cannot be assured to be portable across conforming implementations.

### unspecified

Describes the nature of a value or behavior not specified by this document which results from use of a valid program construct or valid data input. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence or validity of the value or behavior. An application that relies on any particular value or behavior cannot be assured to be portable across conforming

## *5 Terminology*

implementations.

Other terms and definitions used in this document shall have the same meaning as defined in Chapter 3 of the Base Definitions volume of [ISO POSIX \(2003\)](#).

## 6 Documentation Conventions

Throughout this document, the following typographic conventions are used:

**function()**

the name of a function

**command**

the name of a command or utility

**CONSTANT**

a constant value

*parameter*

a parameter

**variable**

a variable

Throughout this specification, several tables of interfaces are presented. Each entry in these tables has the following format:

**name**

the name of the interface

**(symver)**

An optional symbol version identifier, if required.

**[refno]**

A reference number indexing the table of referenced specifications that follows this table.

For example,

**forkpty(GLIBC\_2.0) [SUSv3]**

refers to the interface named `forkpty()` with symbol version `GLIBC_2.0` that is defined in the SUSv3 reference.

**Note:** For symbols with versions which differ between architectures, the symbol versions are defined in the architecture specific parts of ISO/IEC 23360 only.

## **II Low Level System Information**

# 7 C++ Class Representations

## 7.1 C++ Data Representation

Support for the C++ language shall be as specified in [Itanium™ C++ ABI](#).

**Note:** This document, although containing a few architecture specific matters, is written as a generic specification, to be usable by C++ implementations on a variety of architectures.

This section provides additional information to supplement [Itanium™ C++ ABI](#). Many of the definitions in that document are made in terms of C++. This section provides addition explanations using C terms to avoid self-referential problems.

### 7.1.1 Class Representation

An object file generated by the compilation process for a C++ program shall contain several closely related internal objects, or Class Components, to represent each C++ Class. Such objects are not a visible part of the source code. [Table 7-1](#) describes these Class Components at a high level.

**Table 7-1 Class Components**

Object	Contains
Class Data	All non-static Class members
Virtual Table	Information needed to dispatch virtual functions, access virtual base class subobjects and to access the RTTI information
RTTI	Run-Time Type Information used by the typeid and dynamic_cast operators, and exception handlers
Typeinfo Name	String representation of Class name
Construction Virtual Table	Information needed during construction and destruction of Classes with non-trivial inheritance relationships.
VTT	A table of virtual table pointers which holds the addresses of construction and non-construction virtual tables.

#### 7.1.1.1 Virtual Table

Virtual tables are specified in Section 2.5.3 of [Itanium™ C++ ABI](#).

Of the various categories of virtual table described in that specification, Category 1 (Leaf) is further described in [Figure 7-1](#) and Category 2 (Non-virtual bases only) is further described in [Figure 7-2](#). LSB conforming systems shall support these categories.

```
struct {
    ptrdiff_t      baseobject;
    const char     *typeinfo;
```

```

        fptr          virtfuncs[0];
    };

```

**Figure 7-1 Category 1 Virtual Table**

```

struct {
    unsigned long   vcalloffset;
    ptrdiff_t      baseobject;
    const char     *typeinfo;
    fptr           virtfuncs[0];
};

```

**Figure 7-2 Category 2 Virtual Table**

This specification describes requirements for virtual tables of C++ classes using tables of the following form:

**Table 7-2 Primary vtable for K (example)**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for K
vfunc[0]:	K::~K()
vfunc[1]:	K::~K()
vfunc[2]:	K::m1(int*)
vfunc[3]:	X::m2()
vfunc[4]:	<u>__cxa_pure_virtual()</u>
vfunc[5]:	NULL or X::m4(int)

Each row starting from 'vfunc[i]:' refers to a vtable entry 'vfunc[i]' of a class K, which is an entry for a virtual function A::m, where A is a base class of the class K as described in the [Itanium™ C++ ABI](#). This specification requires implementations to interpret the vtable entry information in the following way:

1. A conforming implementation shall contain a vtable of the class K in the specified shared library;
  2. The corresponding entry of this vtable 'vfunc[i]' shall be an entry for the virtual function A::m;
  3. If the second column of the row contains \_\_cxa\_pure\_virtual() the corresponding vtable entry of a LSB-conforming implementation shall contain \_\_cxa\_pure\_virtual() or 'Y::m', where Y is the class K, the class A or a base class of the class K derived from the class A.<sup>1</sup>
- 1 In this case virtual function A::m in class K is considered to be specified as pure virtual by this specification.
4. If the second column of the row contains 'X::m' the corresponding vtable entry of a LSB-conforming implementation shall contain 'Y::m', where Y is the class K, the class X or a base class of the class K derived from the class X.
  5. If the second column of the row contains 'NULL or X::m' the corresponding vtable entry of a LSB-conforming implementation shall contain NULL or 'Y::m', where Y is the class K, the class X or a base class of the class K derived from the class X.<sup>2</sup>
- 2 In this case virtual function A::m in class K is considered to be specified as inline by this

specification.

An application may use any non-pure virtual function specified in this specification, and can expect the specified behavior irrespective of which particular method implements this functionality. An application may not use inline virtual functions at the binary level since its vtable entry may be NULL.

### 7.1.1.2 Run-Time Type Information

Each type used in a C++ program has a data structure associated with it that provide information about the type which is used at runtime. This Run Time Type Information (RTTI) is defined in section 2.9.5 in [Itanium™ C++ ABI](#). Additional details about the layout of this data is provided here.

```
struct {
    void      *basevtable;
    char      *name;
};
```

**Figure 7-3 Run-Time Type Information Prefix**

```
struct {
    void      *basevtable;
    char      *name;
    void      *basetypeinfo[0];
};
```

**Figure 7-4 Run-Time Type Information For Classes with no base class**

```
struct {
    void      *basevtable;
    char      *name;
    void      *basetype;
    void      *basetypeinfo[0];
};
```

**Figure 7-5 Run-Time Type Information for Classes with a single base class**

```
struct base_type_info {
    char      *base_type;
    unsigned long offset_flags;
};

struct {
    void      *basevtable;
    char      *name;
    unsigned int   flags;
    unsigned int   base_count;
    struct base_type_info base_info[0];
};
```

**Figure 7-6 Run-Time Type Information for classes with multiple inheritance**

```
struct {
    void      *basevtable;
    char      *name;
    unsigned int   flags;
    void      *pointee;
    void      *basetypeinfo[0];
};
```

**Figure 7-7 Run-Time Type Information for pointer types**

```
struct {
    void      *basevtable;
    char      *name;
```

```
unsigned int    flags;
void      *pointee;
void      *context;
void      *basetypeinfo[0];
};
```

**Figure 7-8 Run-Time Type Information for pointer to member types**

## **8 Symbol Mapping**

This chapter defines how names are mapped from the source symbol to the object symbol.

### **8.1 Symbol Mapping**

Symbols in a source program are translated by the compilation system into symbols that exist in the object file. The rules for this translation are defined here.

#### **8.1.1 C++ Language**

External symbol names in a C++ object file shall be encoded according to the "name mangling" rules described in the [Itanium™ C++ ABI](#).

### **III Base Libraries**

## 9 Libraries

An LSB-conforming implementation shall support some base libraries which provide interfaces for accessing the operating system, processor and other hardware in the system.

### 9.1 Interfaces for libstdc++

[Table 9-1](#) defines the library name and shared object name for the libstdc++ library

**Table 9-1 libstdc++ Definition**

Library:	libstdc++
SONAME:	libstdc++.so.6

Unless stated otherwise, all symbols are in the `std::` namespace.

The behavior of the interfaces in this library is specified by the following specifications:

- [CXXABI] [Itanium™ C++ ABI](#)
- [ISOCXX] [ISO/IEC 14882: 2003 C++ Language](#)
- [LSB] [ISO/IEC 23360 Part 1](#)

#### 9.1.1 C++ Runtime Support

##### 9.1.1.1 Interfaces for C++ Runtime Support

An LSB conforming implementation shall provide the generic methods for C++ Runtime Support specified in [Table 9-2](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-2 libstdc++ - C++ Runtime Support Function Interfaces**

<code>_gnu_cxx::__atomic_add(int volatile*, int)(GLIBCXX_3.4)</code>	<a href="#">[CXXABI]</a>
<code>_gnu_cxx::__exchange_and_add(int volatile*, int)(GLIBCXX_3.4)</code>	<a href="#">[CXXABI]</a>
<code>_gnu_cxx::__verbose_terminate_handler()(CXXABI_1.3)</code>	<a href="#">[CXXABI]</a>
<code>unexpected()(GLIBCXX_3.4)</code>	<a href="#">[ISOCXX]</a>
<code>set_terminate(void (*)())(GLIBCXX_3.4)</code>	<a href="#">[ISOCXX]</a>
<code>set_unexpected(void (*)())(GLIBCXX_3.4)</code>	<a href="#">[ISOCXX]</a>
<code>set_new_handler(void (*)())(GLIBCXX_3.4)</code>	<a href="#">[ISOCXX]</a>
<code>_throw_bad_cast()(GLIBCXX_3.4)</code>	<a href="#">[ISOCXX]</a>
<code>_throw_bad_alloc()(GLIBCXX_3.4)</code>	<a href="#">[ISOCXX]</a>
<code>_throw_bad_typeid()(GLIBCXX_3.4)</code>	<a href="#">[ISOCXX]</a>
<code>uncaught_exception()(GLIBCXX_3.4)</code>	<a href="#">[ISOCXX]</a>
<code>_throw_ios_failure(char const*)(GLIBCXX_3.4)</code>	<a href="#">[ISOCXX]</a>
<code>_throw_logic_error(char const*)(GLIBCXX_3.4)</code>	<a href="#">[ISOCXX]</a>
<code>_throw_range_error(char const*)(GLIBCXX_3.4)</code>	<a href="#">[ISOCXX]</a>
<code>_throw_domain_error(char const*)(GLIBCXX_3.4)</code>	<a href="#">[ISOCXX]</a>
<code>_throw_length_error(char const*)(GLIBCXX_3.4)</code>	<a href="#">[ISOCXX]</a>

<a href="#">__throw_out_of_range(char const*)(GLIBCXX_3.4)</a>	<a href="#">[ISOcxx]</a>
<a href="#">__throw_bad_exception()(GLIBCXX_3.4)</a>	<a href="#">[ISOcxx]</a>
<a href="#">__throw_runtime_error(char const*)(GLIBCXX_3.4)</a>	<a href="#">[ISOcxx]</a>
<a href="#">__throw_overflow_error(char const*)(GLIBCXX_3.4)</a>	<a href="#">[ISOcxx]</a>
<a href="#">__throw_underflow_error(char const*)(GLIBCXX_3.4)</a>	<a href="#">[ISOcxx]</a>
<a href="#">__throw_invalid_argument(char const*)(GLIBCXX_3.4)</a>	<a href="#">[ISOcxx]</a>
<a href="#">terminate()(GLIBCXX_3.4)</a>	<a href="#">[ISOcxx]</a>
<a href="#">operator delete[](void*)(GLIBCXX_3.4)</a>	<a href="#">[ISOcxx]</a>
<a href="#">operator delete[](void*, nothrow_t const&amp;)(GLIBCXX_3.4)</a>	<a href="#">[ISOcxx]</a>
<a href="#">operator delete(void*)(GLIBCXX_3.4)</a>	<a href="#">[ISOcxx]</a>
<a href="#">operator delete(void*, nothrow_t const&amp;)(GLIBCXX_3.4)</a>	<a href="#">[ISOcxx]</a>
<a href="#">__cxa_allocate_exception(CXXABI_1.3)</a>	<a href="#">[Cxxabi]</a>
<a href="#">__cxa_bad_cast(CXXABI_1.3)</a>	<a href="#">[Cxxabi]</a>
<a href="#">__cxa_bad_typeid(CXXABI_1.3)</a>	<a href="#">[Cxxabi]</a>
<a href="#">__cxa_begin_catch(CXXABI_1.3)</a>	<a href="#">[Cxxabi]</a>
<a href="#">__cxa_call_unexpected(CXXABI_1.3)</a>	<a href="#">[Cxxabi]</a>
<a href="#">__cxa_current_exception_type(CXXABI_1.3)</a>	<a href="#">[Cxxabi]</a>
<a href="#">__cxa_demangle(CXXABI_1.3)</a>	<a href="#">[Cxxabi]</a>
<a href="#">__cxa_end_catch(CXXABI_1.3)</a>	<a href="#">[Cxxabi]</a>
<a href="#">__cxa_free_exception(CXXABI_1.3)</a>	<a href="#">[Cxxabi]</a>
<a href="#">__cxa_get_exception_ptr(CXXABI_1.3.1)</a>	<a href="#">[Cxxabi]</a>
<a href="#">__cxa_get_globals(CXXABI_1.3)</a>	<a href="#">[Cxxabi]</a>
<a href="#">__cxa_get_globals_fast(CXXABI_1.3)</a>	<a href="#">[Cxxabi]</a>
<a href="#">__cxa_guard_abort(CXXABI_1.3)</a>	<a href="#">[Cxxabi]</a>
<a href="#">__cxa_guard_acquire(CXXABI_1.3)</a>	<a href="#">[Cxxabi]</a>
<a href="#">__cxa_guard_release(CXXABI_1.3)</a>	<a href="#">[Cxxabi]</a>
<a href="#">__cxa_pure_virtual(CXXABI_1.3)</a>	<a href="#">[Cxxabi]</a>
<a href="#">__cxa_rethrow(CXXABI_1.3)</a>	<a href="#">[Cxxabi]</a>
<a href="#">__cxa_throw(CXXABI_1.3)</a>	<a href="#">[Cxxabi]</a>
<a href="#">__cxa_vec_cctor(CXXABI_1.3)</a>	<a href="#">[Cxxabi]</a>
<a href="#">__cxa_vec_cleanup(CXXABI_1.3)</a>	<a href="#">[Cxxabi]</a>
<a href="#">__cxa_vec_ctor(CXXABI_1.3)</a>	<a href="#">[Cxxabi]</a>
<a href="#">__cxa_vec_delete(CXXABI_1.3)</a>	<a href="#">[Cxxabi]</a>
<a href="#">__cxa_vec_delete2(CXXABI_1.3)</a>	<a href="#">[Cxxabi]</a>
<a href="#">__cxa_vec_delete3(CXXABI_1.3)</a>	<a href="#">[Cxxabi]</a>
<a href="#">__cxa_vec_dtor(CXXABI_1.3)</a>	<a href="#">[Cxxabi]</a>
<a href="#">__cxa_vec_new(CXXABI_1.3)</a>	<a href="#">[Cxxabi]</a>
<a href="#">__cxa_vec_new2(CXXABI_1.3)</a>	<a href="#">[Cxxabi]</a>
<a href="#">__cxa_vec_new3(CXXABI_1.3)</a>	<a href="#">[Cxxabi]</a>
<a href="#">__dynamic_cast(CXXABI_1.3)</a>	<a href="#">[Cxxabi]</a>

## \_\_gxx\_personality\_v0(CXXABI\_1.3) [CXXABI]

An LSB conforming implementation shall provide the generic data interfaces for C++ Runtime Support specified in [Table 9-3](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-3 libstdcxx - C++ Runtime Support Data Interfaces**

cin(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
cerr(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
clog(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
cout(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
wcin(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
wcerr(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
wclog(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
wcout(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
nothrow(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## **9.1.2 C++ type descriptors for built-in types**

### **9.1.2.1 Interfaces for C++ type descriptors for built-in types**

No external methods are defined for libstdcxx - C++ type descriptors for built-in types in this part of the specification. See also the relevant architecture specific part of this specification.

An LSB conforming implementation shall provide the generic data interfaces for C++ type descriptors for built-in types specified in [Table 9-4](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-4 libstdcxx - C++ type descriptors for built-in types Data Interfaces**

typeinfo for signed char const*(CXXABI_1.3) <a href="#">[CXXABI]</a>
typeinfo for bool const*(CXXABI_1.3) <a href="#">[CXXABI]</a>
typeinfo for char const*(CXXABI_1.3) <a href="#">[CXXABI]</a>
typeinfo for double const*(CXXABI_1.3) <a href="#">[CXXABI]</a>
typeinfo for long double const*(CXXABI_1.3) <a href="#">[CXXABI]</a>
typeinfo for float const*(CXXABI_1.3) <a href="#">[CXXABI]</a>
typeinfo for unsigned char const*(CXXABI_1.3) <a href="#">[CXXABI]</a>
typeinfo for int const*(CXXABI_1.3) <a href="#">[CXXABI]</a>
typeinfo for unsigned int const*(CXXABI_1.3) <a href="#">[CXXABI]</a>
typeinfo for long const*(CXXABI_1.3) <a href="#">[CXXABI]</a>
typeinfo for unsigned long const*(CXXABI_1.3) <a href="#">[CXXABI]</a>
typeinfo for short const*(CXXABI_1.3) <a href="#">[CXXABI]</a>
typeinfo for unsigned short const*(CXXABI_1.3) <a href="#">[CXXABI]</a>
typeinfo for void const*(CXXABI_1.3) <a href="#">[CXXABI]</a>
typeinfo for wchar_t const*(CXXABI_1.3) <a href="#">[CXXABI]</a>
typeinfo for long long const*(CXXABI_1.3) <a href="#">[CXXABI]</a>

typeinfo for unsigned long long const*(CXXABI_1.3) [CXXABI]
typeinfo for signed char*(CXXABI_1.3) [CXXABI]
typeinfo for bool*(CXXABI_1.3) [CXXABI]
typeinfo for char*(CXXABI_1.3) [CXXABI]
typeinfo for double*(CXXABI_1.3) [CXXABI]
typeinfo for long double*(CXXABI_1.3) [CXXABI]
typeinfo for float*(CXXABI_1.3) [CXXABI]
typeinfo for unsigned char*(CXXABI_1.3) [CXXABI]
typeinfo for int*(CXXABI_1.3) [CXXABI]
typeinfo for unsigned int*(CXXABI_1.3) [CXXABI]
typeinfo for long*(CXXABI_1.3) [CXXABI]
typeinfo for unsigned long*(CXXABI_1.3) [CXXABI]
typeinfo for short*(CXXABI_1.3) [CXXABI]
typeinfo for unsigned short*(CXXABI_1.3) [CXXABI]
typeinfo for void*(CXXABI_1.3) [CXXABI]
typeinfo for wchar_t*(CXXABI_1.3) [CXXABI]
typeinfo for long long*(CXXABI_1.3) [CXXABI]
typeinfo for unsigned long long*(CXXABI_1.3) [CXXABI]
typeinfo for signed char(CXXABI_1.3) [CXXABI]
typeinfo for bool(CXXABI_1.3) [CXXABI]
typeinfo for char(CXXABI_1.3) [CXXABI]
typeinfo for double(CXXABI_1.3) [CXXABI]
typeinfo for long double(CXXABI_1.3) [CXXABI]
typeinfo for float(CXXABI_1.3) [CXXABI]
typeinfo for unsigned char(CXXABI_1.3) [CXXABI]
typeinfo for int(CXXABI_1.3) [CXXABI]
typeinfo for unsigned int(CXXABI_1.3) [CXXABI]
typeinfo for long(CXXABI_1.3) [CXXABI]
typeinfo for unsigned long(CXXABI_1.3) [CXXABI]
typeinfo for short(CXXABI_1.3) [CXXABI]
typeinfo for unsigned short(CXXABI_1.3) [CXXABI]
typeinfo for void(CXXABI_1.3) [CXXABI]
typeinfo for wchar_t(CXXABI_1.3) [CXXABI]
typeinfo for long long(CXXABI_1.3) [CXXABI]
typeinfo for unsigned long long(CXXABI_1.3) [CXXABI]
typeinfo name for signed char const*(CXXABI_1.3) [CXXABI]
typeinfo name for bool const*(CXXABI_1.3) [CXXABI]
typeinfo name for char const*(CXXABI_1.3) [CXXABI]
typeinfo name for double const*(CXXABI_1.3) [CXXABI]
typeinfo name for long double const*(CXXABI_1.3) [CXXABI]

typeinfo name for float const*(CXXABI_1.3) [CXXABI]
typeinfo name for unsigned char const*(CXXABI_1.3) [CXXABI]
typeinfo name for int const*(CXXABI_1.3) [CXXABI]
typeinfo name for unsigned int const*(CXXABI_1.3) [CXXABI]
typeinfo name for long const*(CXXABI_1.3) [CXXABI]
typeinfo name for unsigned long const*(CXXABI_1.3) [CXXABI]
typeinfo name for short const*(CXXABI_1.3) [CXXABI]
typeinfo name for unsigned short const*(CXXABI_1.3) [CXXABI]
typeinfo name for void const*(CXXABI_1.3) [CXXABI]
typeinfo name for wchar_t const*(CXXABI_1.3) [CXXABI]
typeinfo name for long long const*(CXXABI_1.3) [CXXABI]
typeinfo name for unsigned long long const*(CXXABI_1.3) [CXXABI]
typeinfo name for signed char*(CXXABI_1.3) [CXXABI]
typeinfo name for bool*(CXXABI_1.3) [CXXABI]
typeinfo name for char*(CXXABI_1.3) [CXXABI]
typeinfo name for double*(CXXABI_1.3) [CXXABI]
typeinfo name for long double*(CXXABI_1.3) [CXXABI]
typeinfo name for float*(CXXABI_1.3) [CXXABI]
typeinfo name for unsigned char*(CXXABI_1.3) [CXXABI]
typeinfo name for int*(CXXABI_1.3) [CXXABI]
typeinfo name for unsigned int*(CXXABI_1.3) [CXXABI]
typeinfo name for long*(CXXABI_1.3) [CXXABI]
typeinfo name for unsigned long*(CXXABI_1.3) [CXXABI]
typeinfo name for short*(CXXABI_1.3) [CXXABI]
typeinfo name for unsigned short*(CXXABI_1.3) [CXXABI]
typeinfo name for void*(CXXABI_1.3) [CXXABI]
typeinfo name for wchar_t*(CXXABI_1.3) [CXXABI]
typeinfo name for long long*(CXXABI_1.3) [CXXABI]
typeinfo name for unsigned long long*(CXXABI_1.3) [CXXABI]
typeinfo name for signed char(CXXABI_1.3) [CXXABI]
typeinfo name for bool(CXXABI_1.3) [CXXABI]
typeinfo name for char(CXXABI_1.3) [CXXABI]
typeinfo name for double(CXXABI_1.3) [CXXABI]
typeinfo name for long double(CXXABI_1.3) [CXXABI]
typeinfo name for float(CXXABI_1.3) [CXXABI]
typeinfo name for unsigned char(CXXABI_1.3) [CXXABI]
typeinfo name for int(CXXABI_1.3) [CXXABI]
typeinfo name for unsigned int(CXXABI_1.3) [CXXABI]
typeinfo name for long(CXXABI_1.3) [CXXABI]
typeinfo name for unsigned long(CXXABI_1.3) [CXXABI]

typeinfo name for short(CXXABI_1.3) <a href="#">[CXXABI]</a>
typeinfo name for unsigned short(CXXABI_1.3) <a href="#">[CXXABI]</a>
typeinfo name for void(CXXABI_1.3) <a href="#">[CXXABI]</a>
typeinfo name for wchar_t(CXXABI_1.3) <a href="#">[CXXABI]</a>
typeinfo name for long long(CXXABI_1.3) <a href="#">[CXXABI]</a>
typeinfo name for unsigned long long(CXXABI_1.3) <a href="#">[CXXABI]</a>

### 9.1.3 C++ \_Rb\_tree

#### 9.1.3.1 Interfaces for C++ \_Rb\_tree

An LSB conforming implementation shall provide the generic methods for C++ \_Rb\_tree specified in [Table 9-5](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-5 libstdcxx - C++ \_Rb\_tree Function Interfaces**

_Rb_tree_decrement(_Rb_tree_node_base const*)(GLIBCXX_3.4) <a href="#">[LSB]</a>
_Rb_tree_decrement(_Rb_tree_node_base*)(GLIBCXX_3.4) <a href="#">[LSB]</a>
_Rb_tree_increment(_Rb_tree_node_base const*)(GLIBCXX_3.4) <a href="#">[LSB]</a>
_Rb_tree_increment(_Rb_tree_node_base*)(GLIBCXX_3.4) <a href="#">[LSB]</a>
_Rb_tree_black_count(_Rb_tree_node_base const*, _Rb_tree_node_base const*)(GLIBCXX_3.4) <a href="#">[LSB]</a>
_Rb_tree_rotate_left(_Rb_tree_node_base*, _Rb_tree_node_base*&)(GLIBCXX_3.4) <a href="#">[LSB]</a>
_Rb_tree_rotate_right(_Rb_tree_node_base*, _Rb_tree_node_base*&)(GLIBCXX_3.4) <a href="#">[LSB]</a>
_Rb_tree_rebalance_for_erase(_Rb_tree_node_base*, _Rb_tree_node_base&)(GLIBCXX_3.4) <a href="#">[LSB]</a>
_Rb_tree_insert_and_rebalance(bool, _Rb_tree_node_base*, _Rb_tree_node_base*, _Rb_tree_node_base&)(GLIBCXX_3.4) <a href="#">[LSB]</a>

### 9.1.4 Class type\_info

#### 9.1.4.1 Class data for type\_info

The virtual table for the std::type\_info class is described by [Table 9-6](#)

**Table 9-6 Primary vtable for type\_info**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for type_info
vfunc[0]:	type_info::~type_info()
vfunc[1]:	type_info::~type_info()
vfunc[2]:	type_info::__is_pointer_p() const
vfunc[3]:	type_info::__is_function_p() const
vfunc[4]:	type_info::__do_catch(type_info const*, void**, unsigned int) const

vfunc[5]:	type_info::__do_upcast(__cxxabiv1::__class_type_info const*, void**) const
-----------	--

The Run Time Type Information for the std::type\_info class is described by [Table 9-7](#)

**Table 9-7 typeinfo for type\_info**

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for type_info

### 9.1.4.2 Interfaces for Class type\_info

An LSB conforming implementation shall provide the generic methods for Class std::type\_info specified in [Table 9-8](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-8 libstdc++ - Class type\_info Function Interfaces**

type_info::__do_catch(type_info const*, void**, unsigned int) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
type_info::__do_upcast(__cxxabiv1::__class_type_info const*, void**) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
type_info::__is_pointer_p() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
type_info::__is_function_p() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
type_info::~type_info()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
type_info::~type_info()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
type_info::~type_info()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::type\_info specified in [Table 9-9](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-9 libstdc++ - Class type\_info Data Interfaces**

typeinfo for type_info(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for type_info(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for type_info(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

### 9.1.5 Class \_\_cxxabiv1::\_\_enum\_type\_info

#### 9.1.5.1 Class data for \_\_cxxabiv1::\_\_enum\_type\_info

The virtual table for the \_\_cxxabiv1::\_\_enum\_type\_info class is described by [Table 9-10](#)

**Table 9-10 Primary vtable for \_\_cxxabiv1::\_\_enum\_type\_info**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for __cxxabiv1::__enum_type_info

vfunc[0]:	<code>__cxxabiv1::__enum_type_info::~_enum_type_info()</code>
vfunc[1]:	<code>__cxxabiv1::__enum_type_info::~_enum_type_info()</code>
vfunc[2]:	<code>type_info::is_pointer_p() const</code>
vfunc[3]:	<code>type_info::is_function_p() const</code>
vfunc[4]:	<code>type_info::do_catch(type_info const*, void**, unsigned int) const</code>
vfunc[5]:	<code>type_info::do_upcast(__cxxabiv1::__class_type_info const*, void**) const</code>

The Run Time Type Information for the `__cxxabiv1::__enum_type_info` class is described by [Table 9-11](#)

**Table 9-11 typeinfo for `__cxxabiv1::__enum_type_info`**

Base Vtable	vtable for <code>__cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>__cxxabiv1::__enum_type_info</code>

### 9.1.5.2 Interfaces for Class `__cxxabiv1::__enum_type_info`

An LSB conforming implementation shall provide the generic methods for Class `__cxxabiv1::__enum_type_info` specified in [Table 9-12](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-12 libstdcxx - Class `__cxxabiv1::__enum_type_info` Function Interfaces**

<code>__cxxabiv1::__enum_type_info::~_enum_type_info()</code> (CXXABI_1.3) <a href="#">[CXXABI]</a>
<code>__cxxabiv1::__enum_type_info::~_enum_type_info()</code> (CXXABI_1.3) <a href="#">[CXXABI]</a>
<code>__cxxabiv1::__enum_type_info::~_enum_type_info()</code> (CXXABI_1.3) <a href="#">[CXXABI]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class `__cxxabiv1::__enum_type_info` specified in [Table 9-13](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-13 libstdcxx - Class `__cxxabiv1::__enum_type_info` Data Interfaces**

typeinfo for <code>__cxxabiv1::__enum_type_info</code> (CXXABI_1.3) <a href="#">[CXXABI]</a>
typeinfo name for <code>__cxxabiv1::__enum_type_info</code> (CXXABI_1.3) <a href="#">[CXXABI]</a>
vtable for <code>__cxxabiv1::__enum_type_info</code> (CXXABI_1.3) <a href="#">[CXXABI]</a>

### 9.1.6 Class `__cxxabiv1::__array_type_info`

#### 9.1.6.1 Class data for `__cxxabiv1::__array_type_info`

The virtual table for the `__cxxabiv1::__array_type_info` class is described by

[Table 9-14](#)

**Table 9-14 Primary vtable for \_\_cxxabiv1::\_\_array\_type\_info**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for __cxxabiv1::__array_type_info
vfunc[0]:	__cxxabiv1::__array_type_info::~__array_type_info()
vfunc[1]:	__cxxabiv1::__array_type_info::~__array_type_info()
vfunc[2]:	type_info::__is_pointer_p() const
vfunc[3]:	type_info::__is_function_p() const
vfunc[4]:	type_info::__do_catch(type_info const*, void**, unsigned int) const
vfunc[5]:	type_info::__do_upcast(__cxxabiv1::__class_type_info const*, void**) const

The Run Time Type Information for the \_\_cxxabiv1::\_\_array\_type\_info class is described by [Table 9-15](#)

**Table 9-15 typeinfo for \_\_cxxabiv1::\_\_array\_type\_info**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for __cxxabiv1::__array_type_info

### 9.1.6.2 Interfaces for Class \_\_cxxabiv1::\_\_array\_type\_info

An LSB conforming implementation shall provide the generic methods for Class \_\_cxxabiv1::\_\_array\_type\_info specified in [Table 9-16](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-16 libstdcxx - Class \_\_cxxabiv1::\_\_array\_type\_info Function Interfaces**

__cxxabiv1::__array_type_info::~__array_type_info()(CXXABI_1.3) <a href="#">[CXXABI]</a>
__cxxabiv1::__array_type_info::~__array_type_info()(CXXABI_1.3) <a href="#">[CXXABI]</a>
__cxxabiv1::__array_type_info::~__array_type_info()(CXXABI_1.3) <a href="#">[CXXABI]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class \_\_cxxabiv1::\_\_array\_type\_info specified in [Table 9-17](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-17 libstdcxx - Class \_\_cxxabiv1::\_\_array\_type\_info Data Interfaces**

typeinfo for __cxxabiv1::__array_type_info(CXXABI_1.3) <a href="#">[CXXABI]</a>
typeinfo name for __cxxabiv1::__array_type_info(CXXABI_1.3) <a href="#">[CXXABI]</a>
vtable for __cxxabiv1::__array_type_info(CXXABI_1.3) <a href="#">[CXXABI]</a>

## 9.1.7 Class \_\_cxxabiv1::\_\_class\_type\_info

### 9.1.7.1 Class data for \_\_cxxabiv1::\_\_class\_type\_info

The virtual table for the \_\_cxxabiv1::\_\_class\_type\_info class is described by [Table 9-18](#)

**Table 9-18 Primary vtable for \_\_cxxabiv1::\_\_class\_type\_info**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for __cxxabiv1::__class_type_info
vfunc[0]:	__cxxabiv1::__class_type_info::~class_type_info()
vfunc[1]:	__cxxabiv1::__class_type_info::~class_type_info()
vfunc[2]:	type_info::is_pointer_p() const
vfunc[3]:	type_info::is_function_p() const
vfunc[4]:	__cxxabiv1::__class_type_info::do_catch(type_info const*, void**, unsigned int) const
vfunc[5]:	__cxxabiv1::__class_type_info::do_upcast(__cxxabiv1::__class_type_info const*, void**) const
vfunc[6]:	__cxxabiv1::__class_type_info::do_upcast(__cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info::upcast_result&) const

The Run Time Type Information for the \_\_cxxabiv1::\_\_class\_type\_info class is described by [Table 9-19](#)

**Table 9-19 typeinfo for \_\_cxxabiv1::\_\_class\_type\_info**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for __cxxabiv1::__class_type_info

### 9.1.7.2 Interfaces for Class \_\_cxxabiv1::\_\_class\_type\_info

An LSB conforming implementation shall provide the generic methods for Class \_\_cxxabiv1::\_\_class\_type\_info specified in [Table 9-20](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-20 libstdcxx - Class \_\_cxxabiv1::\_\_class\_type\_info Function Interfaces**

__cxxabiv1::__class_type_info::~class_type_info()(CXXABI_1.3) <a href="#">[CXXABI]</a>
__cxxabiv1::__class_type_info::~class_type_info()(CXXABI_1.3) <a href="#">[CXXABI]</a>
__cxxabiv1::__class_type_info::~class_type_info()(CXXABI_1.3) <a href="#">[CXXABI]</a>

<code>__cxxabiv1::__class_type_info::__do_catch(type_info const*, void**, unsigned int) const(CXXABI_1.3)</code> <a href="#">[CXXABI]</a>
<code>__cxxabiv1::__class_type_info::__do_upcast(__cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info::__upcast_result&amp;) const(CXXABI_1.3)</code> <a href="#">[CXXABI]</a>
<code>__cxxabiv1::__class_type_info::__do_upcast(__cxxabiv1::__class_type_info const*, void**) const(CXXABI_1.3)</code> <a href="#">[CXXABI]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class `__cxxabiv1::__class_type_info` specified in [Table 9-21](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-21 libstdcxx - Class `__cxxabiv1::__class_type_info` Data Interfaces**

<code>typeinfo for __cxxabiv1::__class_type_info(CXXABI_1.3)</code> <a href="#">[CXXABI]</a>
<code>typeinfo name for __cxxabiv1::__class_type_info(CXXABI_1.3)</code> <a href="#">[CXXABI]</a>
<code>vtable for __cxxabiv1::__class_type_info(CXXABI_1.3)</code> <a href="#">[CXXABI]</a>

## 9.1.8 Class `__cxxabiv1::__pbase_type_info`

### 9.1.8.1 Class data for `__cxxabiv1::__pbase_type_info`

The virtual table for the `__cxxabiv1::__pbase_type_info` class is described by [Table 9-22](#)

**Table 9-22 Primary vtable for `__cxxabiv1::__pbase_type_info`**

Base Offset	0
Virtual Base Offset	0
RTTI	<code>typeinfo for __cxxabiv1::__pbase_type_info</code>
vfunc[0]:	<code>__cxxabiv1::__pbase_type_info::~__pbase_type_info()</code>
vfunc[1]:	<code>__cxxabiv1::__pbase_type_info::~__pbase_type_info()</code>
vfunc[2]:	<code>type_info::__is_pointer_p() const</code>
vfunc[3]:	<code>type_info::__is_function_p() const</code>
vfunc[4]:	<code>__cxxabiv1::__pbase_type_info::__do_catch(type_info const*, void**, unsigned int) const</code>
vfunc[5]:	<code>type_info::__do_upcast(__cxxabiv1::__class_type_info const*, void**) const</code>
vfunc[6]:	<code>__cxxabiv1::__pbase_type_info::__pointer_catch(__cxxabiv1::__pbase_type_info const*, void**, unsigned int) const</code>

The Run Time Type Information for the `__cxxabiv1::__pbase_type_info` class is described by [Table 9-23](#)

**Table 9-23 typeinfo for \_\_cxxabiv1::\_\_pbase\_type\_info**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for __cxxabiv1::__pbase_type_info

### 9.1.8.2 Interfaces for Class \_\_cxxabiv1::\_\_pbase\_type\_info

An LSB conforming implementation shall provide the generic methods for Class \_\_cxxabiv1::\_\_pbase\_type\_info specified in [Table 9-24](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-24 libstdcxx - Class \_\_cxxabiv1::\_\_pbase\_type\_info Function Interfaces**

__cxxabiv1::__pbase_type_info::~__pbase_type_info()(CXXABI_1.3) <a href="#">[CXXABI]</a>
__cxxabiv1::__pbase_type_info::~__pbase_type_info()(CXXABI_1.3) <a href="#">[CXXABI]</a>
__cxxabiv1::__pbase_type_info::~__pbase_type_info()(CXXABI_1.3) <a href="#">[CXXABI]</a>
__cxxabiv1::__pbase_type_info::__do_catch(type_info const*, void**, unsigned int) const(CXXABI_1.3) <a href="#">[CXXABI]</a>
__cxxabiv1::__pbase_type_info::__pointer_catch(__cxxabiv1::__pbase_type_info const*, void**, unsigned int) const(CXXABI_1.3) <a href="#">[CXXABI]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class \_\_cxxabiv1::\_\_pbase\_type\_info specified in [Table 9-25](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-25 libstdcxx - Class \_\_cxxabiv1::\_\_pbase\_type\_info Data Interfaces**

typeinfo for __cxxabiv1::__pbase_type_info(CXXABI_1.3) <a href="#">[CXXABI]</a>
typeinfo name for __cxxabiv1::__pbase_type_info(CXXABI_1.3) <a href="#">[CXXABI]</a>
vtable for __cxxabiv1::__pbase_type_info(CXXABI_1.3) <a href="#">[CXXABI]</a>

### 9.1.9 Class \_\_cxxabiv1::\_\_pointer\_type\_info

#### 9.1.9.1 Class data for \_\_cxxabiv1::\_\_pointer\_type\_info

The virtual table for the \_\_cxxabiv1::\_\_pointer\_type\_info class is described by [Table 9-26](#)

**Table 9-26 Primary vtable for \_\_cxxabiv1::\_\_pointer\_type\_info**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for __cxxabiv1::__pointer_type_info
vfunc[0]:	__cxxabiv1::__pointer_type_info::~__pointer_type_info()
vfunc[1]:	__cxxabiv1::__pointer_type_info::~__pointer_type_info()

vfunc[2]:	<code>__cxxabiv1::__pointer_type_info::__is_pointer_p() const</code>
vfunc[3]:	<code>type_info::__is_function_p() const</code>
vfunc[4]:	<code>__cxxabiv1::__pbase_type_info::__do_catch(type_info const*, void**, unsigned int) const</code>
vfunc[5]:	<code>type_info::__do_upcast(__cxxabiv1::__class_type_info const*, void**) const</code>
vfunc[6]:	<code>__cxxabiv1::__pointer_type_info::__pointer_catch(__cxxabiv1::__pbase_type_info const*, void**, unsigned int) const</code>

The Run Time Type Information for the `__cxxabiv1::__pointer_type_info` class is described by [Table 9-27](#)

**Table 9-27 typeinfo for `__cxxabiv1::__pointer_type_info`**

Base Vtable	vtable for <code>__cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>__cxxabiv1::__pointer_type_info</code>

### 9.1.9.2 Interfaces for Class `__cxxabiv1::__pointer_type_info`

An LSB conforming implementation shall provide the generic methods for Class `__cxxabiv1::__pointer_type_info` specified in [Table 9-28](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-28 libstdc++ - Class `__cxxabiv1::__pointer_type_info` Function Interfaces**

<code>__cxxabiv1::__pointer_type_info::~__pointer_type_info()</code> (CXXABI_1.3) [CXXABI]
<code>__cxxabiv1::__pointer_type_info::~__pointer_type_info()</code> (CXXABI_1.3) [CXXABI]
<code>__cxxabiv1::__pointer_type_info::~__pointer_type_info()</code> (CXXABI_1.3) [CXXABI]
<code>__cxxabiv1::__pointer_type_info::__is_pointer_p() const</code> (CXXABI_1.3) [CXXABI]
<code>__cxxabiv1::__pointer_type_info::__pointer_catch(__cxxabiv1::__pbase_type_info const*, void**, unsigned int) const</code> (CXXABI_1.3) [CXXABI]

An LSB conforming implementation shall provide the generic data interfaces for Class `__cxxabiv1::__pointer_type_info` specified in [Table 9-29](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-29 libstdc++ - Class `__cxxabiv1::__pointer_type_info` Data Interfaces**

typeinfo for <code>__cxxabiv1::__pointer_type_info</code> (CXXABI_1.3) [CXXABI]
typeinfo name for <code>__cxxabiv1::__pointer_type_info</code> (CXXABI_1.3) [CXXABI]

vtable for __cxxabiv1::__pointer_type_info(CXXABI_1.3) <a href="#">[CXXABI]</a>
---

## 9.1.10 Class \_\_cxxabiv1::\_\_function\_type\_info

### 9.1.10.1 Class data for \_\_cxxabiv1::\_\_function\_type\_info

The virtual table for the \_\_cxxabiv1::\_\_function\_type\_info class is described by [Table 9-30](#)

**Table 9-30 Primary vtable for \_\_cxxabiv1::\_\_function\_type\_info**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for __cxxabiv1::__function_type_info
vfunc[0]:	__cxxabiv1::__function_type_info::~__function_type_info()
vfunc[1]:	__cxxabiv1::__function_type_info::~__function_type_info()
vfunc[2]:	type_info::__is_pointer_p() const
vfunc[3]:	__cxxabiv1::__function_type_info::__is_function_p() const
vfunc[4]:	type_info::__do_catch(type_info const*, void**, unsigned int) const
vfunc[5]:	type_info::__do_upcast(__cxxabiv1::__class_type_info const*, void**) const

The Run Time Type Information for the \_\_cxxabiv1::\_\_function\_type\_info class is described by [Table 9-31](#)

**Table 9-31 typeinfo for \_\_cxxabiv1::\_\_function\_type\_info**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for __cxxabiv1::__function_type_info

### 9.1.10.2 Interfaces for Class \_\_cxxabiv1::\_\_function\_type\_info

An LSB conforming implementation shall provide the generic methods for Class \_\_cxxabiv1::\_\_function\_type\_info specified in [Table 9-32](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-32 libstdcxx - Class \_\_cxxabiv1::\_\_function\_type\_info Function Interfaces**

__cxxabiv1::__function_type_info::~__function_type_info()(CXXABI_1.3) <a href="#">[CXXABI]</a>
__cxxabiv1::__function_type_info::~__function_type_info()(CXXABI_1.3) <a href="#">[CXXABI]</a>
__cxxabiv1::__function_type_info::~__function_type_info()(CXXABI_1.3) <a href="#">[CXXABI]</a>

<code>__cxxabiv1::__function_type_info::__is_function_p() const(CXXABI_1.3)</code>
<a href="#">[CXXABI]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class `__cxxabiv1::__function_type_info` specified in [Table 9-33](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-33 libstdc++ - Class `__cxxabiv1::__function_type_info` Data Interfaces**

<code>typeinfo for __cxxabiv1::__function_type_info(CXXABI_1.3)</code>
<a href="#">[CXXABI]</a>
<code>typeinfo name for __cxxabiv1::__function_type_info(CXXABI_1.3)</code>
<a href="#">[CXXABI]</a>
<code>vtable for __cxxabiv1::__function_type_info(CXXABI_1.3)</code>
<a href="#">[CXXABI]</a>

## 9.1.11 Class `__cxxabiv1::__si_class_type_info`

### 9.1.11.1 Class data for `__cxxabiv1::__si_class_type_info`

The virtual table for the `__cxxabiv1::__si_class_type_info` class is described by [Table 9-34](#)

**Table 9-34 Primary vtable for `__cxxabiv1::__si_class_type_info`**

Base Offset	0
Virtual Base Offset	0
RTTI	<code>typeinfo for __cxxabiv1::__si_class_type_info</code>
vfunc[0]:	<code>__cxxabiv1::__si_class_type_info::~_si_class_type_info()</code>
vfunc[1]:	<code>__cxxabiv1::__si_class_type_info::~_si_class_type_info()</code>
vfunc[2]:	<code>type_info::__is_pointer_p() const</code>
vfunc[3]:	<code>type_info::__is_function_p() const</code>
vfunc[4]:	<code>__cxxabiv1::__class_type_info::__do_catch(type_info const*, void**, unsigned int) const</code>
vfunc[5]:	<code>__cxxabiv1::__class_type_info::__do_upcast(__cxxabiv1::__class_type_info const*, void**) const</code>
vfunc[6]:	<code>__cxxabiv1::__si_class_type_info::__do_upcast(__cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info::__upcast_result&amp;) const</code>

The Run Time Type Information for the `__cxxabiv1::__si_class_type_info` class is described by [Table 9-35](#)

**Table 9-35 typeinfo for `__cxxabiv1::__si_class_type_info`**

Base Vtable	<code>vtable for __cxxabiv1::__si_class_type_info</code>
Name	<code>typeinfo name for</code>

	<code>__cxxabiv1::__si_class_type_info</code>
--	---

### 9.1.11.2 Interfaces for Class `__cxxabiv1::__si_class_type_info`

An LSB conforming implementation shall provide the generic methods for Class `__cxxabiv1::__si_class_type_info` specified in [Table 9-36](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-36 libstdcxx - Class `__cxxabiv1::__si_class_type_info` Function Interfaces**

<code>__cxxabiv1::__si_class_type_info::~si_class_type_info()</code> (CXXABI_1.3) <a href="#">[CXXABI]</a>
<code>__cxxabiv1::__si_class_type_info::~si_class_type_info()</code> (CXXABI_1.3) <a href="#">[CXXABI]</a>
<code>__cxxabiv1::__si_class_type_info::~si_class_type_info()</code> (CXXABI_1.3) <a href="#">[CXXABI]</a>
<code>__cxxabiv1::__si_class_type_info::__do_upcast(__cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info::__upcast_result&amp;)</code> const(CXXABI_1.3) <a href="#">[CXXABI]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class `__cxxabiv1::__si_class_type_info` specified in [Table 9-37](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-37 libstdcxx - Class `__cxxabiv1::__si_class_type_info` Data Interfaces**

typeinfo for <code>__cxxabiv1::__si_class_type_info</code> (CXXABI_1.3) <a href="#">[CXXABI]</a>
typeinfo name for <code>__cxxabiv1::__si_class_type_info</code> (CXXABI_1.3) <a href="#">[CXXABI]</a>
vtable for <code>__cxxabiv1::__si_class_type_info</code> (CXXABI_1.3) <a href="#">[CXXABI]</a>

### 9.1.12 Class `__cxxabiv1::__vmi_class_type_info`

#### 9.1.12.1 Class data for `__cxxabiv1::__vmi_class_type_info`

The virtual table for the `__cxxabiv1::__vmi_class_type_info` class is described by [Table 9-38](#)

**Table 9-38 Primary vtable for `__cxxabiv1::__vmi_class_type_info`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>__cxxabiv1::__vmi_class_type_info</code>
vfunc[0]:	<code>__cxxabiv1::__vmi_class_type_info::~vmi_class_type_info()</code>
vfunc[1]:	<code>__cxxabiv1::__vmi_class_type_info::~vmi_class_type_info()</code>
vfunc[2]:	<code>type_info::__is_pointer_p() const</code>
vfunc[3]:	<code>type_info::__is_function_p() const</code>
vfunc[4]:	<code>__cxxabiv1::__class_type_info::__do_catch(type_info const*, void**,</code>

	unsigned int) const
vfunc[5]:	<code>__cxxabiv1::__class_type_info::__do_upcast(__cxxabiv1::__class_type_info const*, void**) const</code>
vfunc[6]:	<code>__cxxabiv1::__vmi_class_type_info::__do_upcast(__cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info::__upcast_result&amp;) const</code>

The Run Time Type Information for the `__cxxabiv1::__vmi_class_type_info` class is described by [Table 9-39](#)

**Table 9-39 typeinfo for `__cxxabiv1::__vmi_class_type_info`**

Base Vtable	vtable for <code>__cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>__cxxabiv1::__vmi_class_type_info</code>

### 9.1.12.2 Interfaces for Class `__cxxabiv1::__vmi_class_type_info`

An LSB conforming implementation shall provide the generic methods for Class `__cxxabiv1::__vmi_class_type_info` specified in [Table 9-40](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-40 libstdcxx - Class `__cxxabiv1::__vmi_class_type_info` Function Interfaces**

<code>__cxxabiv1::__vmi_class_type_info::~__vmi_class_type_info()</code> (CXXABI_1.3) <a href="#">[CXXABI]</a>
<code>__cxxabiv1::__vmi_class_type_info::~__vmi_class_type_info()</code> (CXXABI_1.3) <a href="#">[CXXABI]</a>
<code>__cxxabiv1::__vmi_class_type_info::~__vmi_class_type_info()</code> (CXXABI_1.3) <a href="#">[CXXABI]</a>
<code>__cxxabiv1::__vmi_class_type_info::__do_upcast(__cxxabiv1::__class_type_info const*, void const*, __cxxabiv1::__class_type_info::__upcast_result&amp;) const</code> (CXXABI_1.3) <a href="#">[CXXABI]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class `__cxxabiv1::__vmi_class_type_info` specified in [Table 9-41](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-41 libstdcxx - Class `__cxxabiv1::__vmi_class_type_info` Data Interfaces**

typeinfo for <code>__cxxabiv1::__vmi_class_type_info</code> (CXXABI_1.3) <a href="#">[CXXABI]</a>
typeinfo name for <code>__cxxabiv1::__vmi_class_type_info</code> (CXXABI_1.3) <a href="#">[CXXABI]</a>
vtable for <code>__cxxabiv1::__vmi_class_type_info</code> (CXXABI_1.3) <a href="#">[CXXABI]</a>

## 9.1.13 Class `__cxxabiv1::__fundamental_type_info`

### 9.1.13.1 Class data for `__cxxabiv1::__fundamental_type_info`

The virtual table for the `__cxxabiv1::__fundamental_type_info` class is described by [Table 9-42](#)

**Table 9-42 Primary vtable for `__cxxabiv1::__fundamental_type_info`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>__cxxabiv1::__fundamental_type_info</code>
vfunc[0]:	<code>__cxxabiv1::__fundamental_type_info::~__fundamental_type_info()</code>
vfunc[1]:	<code>__cxxabiv1::__fundamental_type_info::~__fundamental_type_info()</code>
vfunc[2]:	<code>type_info::is_pointer_p() const</code>
vfunc[3]:	<code>type_info::is_function_p() const</code>
vfunc[4]:	<code>type_info::do_catch(type_info const*, void**, unsigned int) const</code>
vfunc[5]:	<code>type_info::do_upcast(__cxxabiv1::__class_type_info const*, void**) const</code>

The Run Time Type Information for the `__cxxabiv1::__fundamental_type_info` class is described by [Table 9-43](#)

**Table 9-43 typeinfo for `__cxxabiv1::__fundamental_type_info`**

Base Vtable	vtable for <code>__cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>__cxxabiv1::__fundamental_type_info</code>

### 9.1.13.2 Interfaces for Class `__cxxabiv1::__fundamental_type_info`

An LSB conforming implementation shall provide the generic methods for Class `__cxxabiv1::__fundamental_type_info` specified in [Table 9-44](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-44 libstdc++ - Class `__cxxabiv1::__fundamental_type_info` Function Interfaces**

<code>__cxxabiv1::__fundamental_type_info::~__fundamental_type_info()</code> (CXXABI_1.3) <a href="#">[CXXABI]</a>
<code>__cxxabiv1::__fundamental_type_info::~__fundamental_type_info()</code> (CXXABI_1.3) <a href="#">[CXXABI]</a>
<code>__cxxabiv1::__fundamental_type_info::~__fundamental_type_info()</code> (CXXABI_1.3) <a href="#">[CXXABI]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class `_cxxabiv1::__fundamental_type_info` specified in [Table 9-45](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-45 libstdcxx - Class `_cxxabiv1::__fundamental_type_info` Data Interfaces**

typeinfo for <code>_cxxabiv1::__fundamental_type_info(CXXABI_1.3)</code> <a href="#">[CXXABI]</a>
typeinfo name for <code>_cxxabiv1::__fundamental_type_info(CXXABI_1.3)</code> <a href="#">[CXXABI]</a>
vtable for <code>_cxxabiv1::__fundamental_type_info(CXXABI_1.3)</code> <a href="#">[CXXABI]</a>

## 9.1.14 Class

### `_cxxabiv1::__pointer_to_member_type_info`

#### 9.1.14.1 Class data for `_cxxabiv1::__pointer_to_member_type_info`

The virtual table for the `_cxxabiv1::__pointer_to_member_type_info` class is described by [Table 9-46](#)

**Table 9-46 Primary vtable for `_cxxabiv1::__pointer_to_member_type_info`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>_cxxabiv1::__pointer_to_member_type_info</code>
vfunc[0]:	<code>_cxxabiv1::__pointer_to_member_type_info::~__pointer_to_member_type_info()</code>
vfunc[1]:	<code>_cxxabiv1::__pointer_to_member_type_info::~__pointer_to_member_type_info()</code>
vfunc[2]:	<code>type_info::__is_pointer_p() const</code>
vfunc[3]:	<code>type_info::__is_function_p() const</code>
vfunc[4]:	<code>_cxxabiv1::__pbase_type_info::__do_catch(type_info const*, void**, unsigned int) const</code>
vfunc[5]:	<code>type_info::__do_upcast(_cxxabiv1::__class_type_info const*, void**) const</code>
vfunc[6]:	<code>_cxxabiv1::__pointer_to_member_type_info::__pointer_catch(_cxxabiv1::__pbase_type_info const*, void**, unsigned int) const</code>

The Run Time Type Information for the `_cxxabiv1::__pointer_to_member_type_info` class is described by [Table 9-47](#)

**Table 9-47 typeinfo for `_cxxabiv1::__pointer_to_member_type_info`**

Base Vtable	vtable for
-------------	------------

	<code>__cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>__cxxabiv1::__pointer_to_member_type_info</code>

### 9.1.14.2 Interfaces for Class

#### `__cxxabiv1::__pointer_to_member_type_info`

An LSB conforming implementation shall provide the generic methods for Class `__cxxabiv1::__pointer_to_member_type_info` specified in [Table 9-48](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-48 libstdcxx - Class `__cxxabiv1::__pointer_to_member_type_info` Function Interfaces**

<code>__cxxabiv1::__pointer_to_member_type_info::~__pointer_to_member_type_info()</code> (CXXABI_1.3) <a href="#">[CXXABI]</a>
<code>__cxxabiv1::__pointer_to_member_type_info::~__pointer_to_member_type_info()</code> (CXXABI_1.3) <a href="#">[CXXABI]</a>
<code>__cxxabiv1::__pointer_to_member_type_info::~__pointer_to_member_type_info()</code> (CXXABI_1.3) <a href="#">[CXXABI]</a>
<code>__cxxabiv1::__pointer_to_member_type_info::__pointer_catch(__cxxabiv1::__pbase_type_info const*, void**, unsigned int) const</code> (CXXABI_1.3) <a href="#">[CXXABI]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class `__cxxabiv1::__pointer_to_member_type_info` specified in [Table 9-49](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-49 libstdcxx - Class `__cxxabiv1::__pointer_to_member_type_info` Data Interfaces**

typeinfo for <code>__cxxabiv1::__pointer_to_member_type_info</code> (CXXABI_1.3) <a href="#">[CXXABI]</a>
typeinfo name for <code>__cxxabiv1::__pointer_to_member_type_info</code> (CXXABI_1.3) <a href="#">[CXXABI]</a>
vtable for <code>__cxxabiv1::__pointer_to_member_type_info</code> (CXXABI_1.3) <a href="#">[CXXABI]</a>

### 9.1.15 Class `__gnu_cxx::stdio_filebuf<char, char_traits<char> >`

#### `9.1.15.1 Interfaces for Class __gnu_cxx::stdio_filebuf<char, char_traits<char> >`

No external methods are defined for libstdcxx - Class `__gnu_cxx::stdio_filebuf<char, std::char_traits<char> >` in this part of the specification. See also the relevant architecture specific part of this specification.

An LSB conforming implementation shall provide the generic data interfaces for Class `__gnu_cxx::stdio_filebuf<char, std::char_traits<char> >` specified in [Table 9-50](#), with the full mandatory functionality as described in the referenced under-

lying specification.

**Table 9-50 libstdcxx - Class `__gnu_cxx::stdio_filebuf<char, char_traits<char>>` Data Interfaces**

typeinfo for <code>__gnu_cxx::stdio_filebuf&lt;char, char_traits&lt;char&gt;&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for <code>__gnu_cxx::stdio_filebuf&lt;char, char_traits&lt;char&gt;&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.16 Class `__gnu_cxx::stdio_filebuf<wchar_t, char_traits<wchar_t>>`

### 9.1.16.1 Interfaces for Class `__gnu_cxx::stdio_filebuf<wchar_t, char_traits<wchar_t>>`

No external methods are defined for libstdcxx - Class `__gnu_cxx::stdio_filebuf<wchar_t, std::char_traits<wchar_t>>` in this part of the specification. See also the relevant architecture specific part of this specification.

An LSB conforming implementation shall provide the generic data interfaces for Class `__gnu_cxx::stdio_filebuf<wchar_t, std::char_traits<wchar_t>>` specified in [Table 9-51](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-51 libstdcxx - Class `__gnu_cxx::stdio_filebuf<wchar_t, char_traits<wchar_t>>` Data Interfaces**

typeinfo for <code>__gnu_cxx::stdio_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for <code>__gnu_cxx::stdio_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.17 Class `__gnu_cxx::__pool_alloc_base`

### 9.1.17.1 Interfaces for Class `__gnu_cxx::__pool_alloc_base`

An LSB conforming implementation shall provide the generic methods for Class `__gnu_cxx::__pool_alloc_base` specified in [Table 9-52](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-52 libstdcxx - Class `__gnu_cxx::__pool_alloc_base` Function Interfaces**

<code>__gnu_cxx::__pool_alloc_base::M_get_mutex()</code> (GLIBCXX_3.4.2) <a href="#">[LSB]</a>
--

## 9.1.18 Class `__gnu_cxx::stdio_sync_filebuf<char, char_traits<char>>`

### 9.1.18.1 Class data for `__gnu_cxx::stdio_sync_filebuf<char, char_traits<char>>`

The virtual table for the `__gnu_cxx::stdio_sync_filebuf<char, std::char_traits<char>>` class is described by [Table 9-53](#)

**Table 9-53 Primary vtable for `__gnu_cxx::stdio_sync_filebuf<char, char_traits<char>>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt;&gt;</code>
vfunc[0]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt;&gt;::~stdio_sync_filebuf()</code>
vfunc[1]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt;&gt;::~stdio_sync_filebuf()</code>
vfunc[2]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt;&gt;::imbue(locale const&amp;)</code>
vfunc[3]:	See The Architecture Specific Specification
vfunc[4]:	See The Architecture Specific Specification
vfunc[5]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt;&gt;::seekpos(fpos&lt;__mbstate_t&gt;, _Ios_Openmode)</code>
vfunc[6]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt;&gt;::sync()</code>
vfunc[7]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt;&gt;::showmany()</code>
vfunc[8]:	See The Architecture Specific Specification
vfunc[9]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt;&gt;::underflow()</code>
vfunc[10]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt;&gt;::uflow()</code>
vfunc[11]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt;&gt;::pbackfail(int)</code>
vfunc[12]:	See The Architecture Specific Specification
vfunc[13]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt;&gt;::overflow(int)</code>

### 9.1.18.2 Interfaces for Class `__gnu_cxx::stdio_sync_filebuf<char, char_traits<char>>`

An LSB conforming implementation shall provide the generic methods for Class `__gnu_cxx::stdio_sync_filebuf<char, std::char_traits<char>>` specified in [Table 9-54](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-54 libstdc++ - Class `__gnu_cxx::stdio_sync_filebuf<char, char_traits<char>>` Function Interfaces**

<code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt;&gt;::file()</code> (GLIBCXX_3.4.2) <a href="#">[LSB]</a>
--

An LSB conforming implementation shall provide the generic data interfaces for Class `__gnu_cxx::stdio_sync_filebuf<char, std::char_traits<char>>` specified in [Table 9-55](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-55 libstdc++ - Class `__gnu_cxx::stdio_sync_filebuf<char, char_traits<char>>` Data Interfaces**

typeinfo for <code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt;&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
---

typeinfo name for <code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt;&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
--

vtable for <code>__gnu_cxx::stdio_sync_filebuf&lt;char, char_traits&lt;char&gt;&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
---

## 9.1.19 Class `__gnu_cxx::stdio_sync_filebuf<wchar_t, char_traits<wchar_t>>`

### 9.1.19.1 Class data for `__gnu_cxx::stdio_sync_filebuf<wchar_t, char_traits<wchar_t>>`

The virtual table for the `__gnu_cxx::stdio_sync_filebuf<wchar_t, std::char_traits<wchar_t>>` class is described by [Table 9-56](#)

**Table 9-56 Primary vtable for `__gnu_cxx::stdio_sync_filebuf<wchar_t, char_traits<wchar_t>>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code>
vfunc[0]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~stdio_sync_filebuf()</code>
vfunc[1]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~stdio_sync_filebuf()</code>
vfunc[2]:	<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::imbue(locale const&amp;)</code>
vfunc[3]:	See The Architecture Specific Specification
vfunc[4]:	See The Architecture Specific Specification
vfunc[5]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::file()</code>

	<code>r_t, char_traits&lt;wchar_t&gt;&gt;::seekpos(fpos&lt;__mbstate_t&gt;, _Ios_Openmode)</code>
vfunc[6]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::sync()</code>
vfunc[7]:	<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::showmany()</code>
vfunc[8]:	See The Architecture Specific Specification
vfunc[9]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::underflow()</code>
vfunc[10]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::uflow()</code>
vfunc[11]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::pbackfail(unsigned int)</code>
vfunc[12]:	See The Architecture Specific Specification
vfunc[13]:	<code>__gnu_cxx::stdio_sync_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::overflow(unsigned int)</code>

### 9.1.19.2 Interfaces for Class

#### `__gnu_cxx::stdio_sync_filebuf<wchar_t, char_traits<wchar_t>>`

An LSB conforming implementation shall provide the generic methods for Class `__gnu_cxx::stdio_sync_filebuf<wchar_t, std::char_traits<wchar_t>>` specified in [Table 9-57](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-57 libstdcxx - Class `__gnu_cxx::stdio_sync_filebuf<wchar_t, char_traits<wchar_t>>` Function Interfaces**

`__gnu_cxx::stdio_sync_filebuf<wchar_t, char_traits<wchar_t>>::file()`  
(GLIBCXX\_3.4.2) [\[LSB\]](#)

An LSB conforming implementation shall provide the generic data interfaces for Class `__gnu_cxx::stdio_sync_filebuf<wchar_t, std::char_traits<wchar_t>>` specified in [Table 9-58](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-58 libstdcxx - Class `__gnu_cxx::stdio_sync_filebuf<wchar_t, char_traits<wchar_t>>` Data Interfaces**

typeinfo for `__gnu_cxx::stdio_sync_filebuf<wchar_t, char_traits<wchar_t>>`(GLIBCXX\_3.4) [\[CXXABI\]](#)

typeinfo name for `__gnu_cxx::stdio_sync_filebuf<wchar_t, char_traits<wchar_t>>`(GLIBCXX\_3.4) [\[CXXABI\]](#)

vtable for `__gnu_cxx::stdio_sync_filebuf<wchar_t, char_traits<wchar_t>>`(GLIBCXX\_3.4) [\[CXXABI\]](#)

## 9.1.20 Class exception

### 9.1.20.1 Class data for exception

The virtual table for the std::exception class is described by [Table 9-59](#)

**Table 9-59 Primary vtable for exception**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for exception
vfunc[0]:	exception::~exception()
vfunc[1]:	exception::~exception()
vfunc[2]:	exception::what() const

The Run Time Type Information for the std::exception class is described by [Table 9-60](#)

**Table 9-60 typeinfo for exception**

Base Vtable	vtable for <code>_cxxabiv1::__class_type_info</code>
Name	typeinfo name for exception

### 9.1.20.2 Interfaces for Class exception

An LSB conforming implementation shall provide the generic methods for Class std::exception specified in [Table 9-61](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-61 libstdcxx - Class exception Function Interfaces**

exception::what() const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
exception::~exception()(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
exception::~exception()(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
exception::~exception()(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::exception specified in [Table 9-62](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-62 libstdcxx - Class exception Data Interfaces**

typeinfo for exception(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for exception(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for exception(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.21 Class bad\_typeid

### 9.1.21.1 Class data for bad\_typeid

The virtual table for the std::bad\_typeid class is described by [Table 9-63](#)

**Table 9-63 Primary vtable for bad\_typeid**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for bad_typeid
vfunc[0]:	bad_typeid::~bad_typeid()
vfunc[1]:	bad_typeid::~bad_typeid()
vfunc[2]:	exception::what() const

The Run Time Type Information for the std::bad\_typeid class is described by [Table 9-64](#)

**Table 9-64 typeinfo for bad\_typeid**

Base Vtable	vtable for _cxxabiv1::_si_class_type_info
Name	typeinfo name for bad_typeid

### 9.1.21.2 Interfaces for Class bad\_typeid

An LSB conforming implementation shall provide the generic methods for Class std::bad\_typeid specified in [Table 9-65](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-65 libstdc++ - Class bad\_typeid Function Interfaces**

bad_typeid::~bad_typeid()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
bad_typeid::~bad_typeid()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
bad_typeid::~bad_typeid()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::bad\_typeid specified in [Table 9-66](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-66 libstdc++ - Class bad\_typeid Data Interfaces**

typeinfo for bad_typeid(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for bad_typeid(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for bad_typeid(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

### 9.1.22 Class logic\_error

#### 9.1.22.1 Class data for logic\_error

The virtual table for the std::logic\_error class is described by [Table 9-67](#)

**Table 9-67 Primary vtable for logic\_error**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for logic_error
vfunc[0]:	logic_error::~logic_error()
vfunc[1]:	logic_error::~logic_error()
vfunc[2]:	logic_error::what() const

The Run Time Type Information for the std::logic\_error class is described by [Table 9-68](#)

**Table 9-68 typeinfo for logic\_error**

Base Vtable	vtable for _cxxabiv1:: _si_class_type_info
Name	typeinfo name for logic_error

### 9.1.22.2 Interfaces for Class logic\_error

An LSB conforming implementation shall provide the generic methods for Class std::logic\_error specified in [Table 9-69](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-69 libstdc++ - Class logic\_error Function Interfaces**

logic_error::what() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
logic_error::logic_error(basic_string<char, char_traits<char>, allocator<char> > const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
logic_error::logic_error(basic_string<char, char_traits<char>, allocator<char> > const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
logic_error::~logic_error()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
logic_error::~logic_error()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
logic_error::~logic_error()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::logic\_error specified in [Table 9-70](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-70 libstdc++ - Class logic\_error Data Interfaces**

typeinfo for logic_error(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for logic_error(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for logic_error(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.23 Class range\_error

### 9.1.23.1 Class data for range\_error

The virtual table for the std::range\_error class is described by [Table 9-71](#)

**Table 9-71 Primary vtable for range\_error**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for range_error
vfunc[0]:	range_error::~range_error()
vfunc[1]:	range_error::~range_error()
vfunc[2]:	runtime_error::what() const

The Run Time Type Information for the std::range\_error class is described by [Table 9-72](#)

**Table 9-72 typeinfo for range\_error**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for range_error

### 9.1.23.2 Interfaces for Class range\_error

An LSB conforming implementation shall provide the generic methods for Class std::range\_error specified in [Table 9-73](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-73 libstdc++ - Class range\_error Function Interfaces**

range_error::range_error(basic_string<char, char_traits<char>, allocator<char> > const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
range_error::range_error(basic_string<char, char_traits<char>, allocator<char> > const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
range_error::~range_error()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
range_error::~range_error()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::range\_error specified in [Table 9-74](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-74 libstdc++ - Class range\_error Data Interfaces**

typeinfo for range_error(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for range_error(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for range_error(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.24 Class domain\_error

### 9.1.24.1 Class data for domain\_error

The virtual table for the std::domain\_error class is described by [Table 9-75](#)

**Table 9-75 Primary vtable for domain\_error**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for domain_error
vfunc[0]:	domain_error::~domain_error()
vfunc[1]:	domain_error::~domain_error()
vfunc[2]:	logic_error::what() const

The Run Time Type Information for the std::domain\_error class is described by [Table 9-76](#)

**Table 9-76 typeinfo for domain\_error**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for domain_error

### 9.1.24.2 Interfaces for Class domain\_error

An LSB conforming implementation shall provide the generic methods for Class std::domain\_error specified in [Table 9-77](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-77 libstdc++ - Class domain\_error Function Interfaces**

domain_error::domain_error(basic_string<char, char_traits<char>, allocator<char> > const&)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
domain_error::domain_error(basic_string<char, char_traits<char>, allocator<char> > const&)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
domain_error::~domain_error()(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
domain_error::~domain_error()(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::domain\_error specified in [Table 9-78](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-78 libstdc++ - Class domain\_error Data Interfaces**

typeinfo for domain_error(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for domain_error(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for domain_error(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.25 Class length\_error

### 9.1.25.1 Class data for length\_error

The virtual table for the std::length\_error class is described by [Table 9-79](#)

**Table 9-79 Primary vtable for length\_error**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for length_error
vfunc[0]:	length_error::~length_error()
vfunc[1]:	length_error::~length_error()
vfunc[2]:	logic_error::what() const

The Run Time Type Information for the std::length\_error class is described by [Table 9-80](#)

**Table 9-80 typeinfo for length\_error**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for length_error

### 9.1.25.2 Interfaces for Class length\_error

An LSB conforming implementation shall provide the generic methods for Class std::length\_error specified in [Table 9-81](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-81 libstdc++ - Class length\_error Function Interfaces**

length_error::length_error(basic_string<char, char_traits<char>, allocator<char> > const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
length_error::length_error(basic_string<char, char_traits<char>, allocator<char> > const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
length_error::~length_error()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
length_error::~length_error()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::length\_error specified in [Table 9-82](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-82 libstdc++ - Class length\_error Data Interfaces**

typeinfo for length_error(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for length_error(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for length_error(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.26 Class out\_of\_range

### 9.1.26.1 Class data for out\_of\_range

The virtual table for the std::out\_of\_range class is described by [Table 9-83](#)

**Table 9-83 Primary vtable for out\_of\_range**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for out_of_range
vfunc[0]:	out_of_range::~out_of_range()
vfunc[1]:	out_of_range::~out_of_range()
vfunc[2]:	logic_error::what() const

The Run Time Type Information for the std::out\_of\_range class is described by [Table 9-84](#)

**Table 9-84 typeinfo for out\_of\_range**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for out_of_range

### 9.1.26.2 Interfaces for Class out\_of\_range

An LSB conforming implementation shall provide the generic methods for Class std::out\_of\_range specified in [Table 9-85](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-85 libstdc++ - Class out\_of\_range Function Interfaces**

out_of_range::out_of_range(basic_string<char, char_traits<char>, allocator<char> > const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
out_of_range::out_of_range(basic_string<char, char_traits<char>,

allocator<char> > const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
out_of_range::~out_of_range()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
out_of_range::~out_of_range()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::out\_of\_range specified in [Table 9-86](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-86 libstdcxx - Class out\_of\_range Data Interfaces**

typeinfo for out_of_range(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for out_of_range(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for out_of_range(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.27 Class bad\_exception

### 9.1.27.1 Class data for bad\_exception

The virtual table for the std::bad\_exception class is described by [Table 9-87](#)

**Table 9-87 Primary vtable for bad\_exception**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for bad_exception
vfunc[0]:	bad_exception::~bad_exception()
vfunc[1]:	bad_exception::~bad_exception()
vfunc[2]:	exception::what() const

The Run Time Type Information for the std::bad\_exception class is described by [Table 9-88](#)

**Table 9-88 typeinfo for bad\_exception**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for bad_exception

### 9.1.27.2 Interfaces for Class bad\_exception

An LSB conforming implementation shall provide the generic methods for Class std::bad\_exception specified in [Table 9-89](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-89 libstdcxx - Class bad\_exception Function Interfaces**

bad_exception::~bad_exception()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
bad_exception::~bad_exception()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
bad_exception::~bad_exception()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::bad\_exception specified in [Table 9-90](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-90 libstdc++ - Class bad\_exception Data Interfaces**

typeinfo for bad_exception(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for bad_exception(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for bad_exception(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.28 Class runtime\_error

### 9.1.28.1 Class data for runtime\_error

The virtual table for the std::runtime\_error class is described by [Table 9-91](#)

**Table 9-91 Primary vtable for runtime\_error**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for runtime_error
vfunc[0]:	runtime_error::~runtime_error()
vfunc[1]:	runtime_error::~runtime_error()
vfunc[2]:	runtime_error::what() const

The Run Time Type Information for the std::runtime\_error class is described by [Table 9-92](#)

**Table 9-92 typeinfo for runtime\_error**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for runtime_error

### 9.1.28.2 Interfaces for Class runtime\_error

An LSB conforming implementation shall provide the generic methods for Class std::runtime\_error specified in [Table 9-93](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-93 libstdc++ - Class runtime\_error Function Interfaces**

runtime_error::what() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
runtime_error::runtime_error(basic_string<char, char_traits<char>, allocator<char> > const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
runtime_error::runtime_error(basic_string<char, char_traits<char>, allocator<char> > const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
runtime_error::~runtime_error()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
runtime_error::~runtime_error()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
runtime_error::~runtime_error()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::runtime\_error specified in [Table 9-94](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-94 libstdc++ - Class runtime\_error Data Interfaces**

typeinfo for runtime_error(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
--

typeinfo name for runtime_error(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for runtime_error(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.29 Class overflow\_error

### 9.1.29.1 Class data for overflow\_error

The virtual table for the std::overflow\_error class is described by [Table 9-95](#)

**Table 9-95 Primary vtable for overflow\_error**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for overflow_error
vfunc[0]:	overflow_error::~overflow_error()
vfunc[1]:	overflow_error::~overflow_error()
vfunc[2]:	runtime_error::what() const

The Run Time Type Information for the std::overflow\_error class is described by [Table 9-96](#)

**Table 9-96 typeinfo for overflow\_error**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for overflow_error

### 9.1.29.2 Interfaces for Class overflow\_error

An LSB conforming implementation shall provide the generic methods for Class std::overflow\_error specified in [Table 9-97](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-97 libstdc++ - Class overflow\_error Function Interfaces**

overflow_error::overflow_error(basic_string<char, char_traits<char>, allocator<char> > const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
overflow_error::overflow_error(basic_string<char, char_traits<char>, allocator<char> > const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
overflow_error::~overflow_error()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
overflow_error::~overflow_error()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::overflow\_error specified in [Table 9-98](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-98 libstdc++ - Class overflow\_error Data Interfaces**

typeinfo for overflow_error(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for overflow_error(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for overflow_error(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.30 Class underflow\_error

### 9.1.30.1 Class data for underflow\_error

The virtual table for the std::underflow\_error class is described by [Table 9-99](#)

**Table 9-99 Primary vtable for underflow\_error**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for underflow_error
vfunc[0]:	underflow_error::~underflow_error() )
vfunc[1]:	underflow_error::~underflow_error() )
vfunc[2]:	runtime_error::what() const

The Run Time Type Information for the std::underflow\_error class is described by [Table 9-100](#)

**Table 9-100 typeinfo for underflow\_error**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for underflow_error

### 9.1.30.2 Interfaces for Class underflow\_error

An LSB conforming implementation shall provide the generic methods for Class std::underflow\_error specified in [Table 9-101](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-101 libstdc++ - Class underflow\_error Function Interfaces**

underflow_error::underflow_error(basic_string<char, char_traits<char>, allocator<char> > const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
underflow_error::underflow_error(basic_string<char, char_traits<char>, allocator<char> > const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
underflow_error::~underflow_error()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
underflow_error::~underflow_error()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::underflow\_error specified in [Table 9-102](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-102 libstdc++ - Class underflow\_error Data Interfaces**

typeinfo for underflow_error(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for underflow_error(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for underflow_error(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.31 Class invalid\_argument

### 9.1.31.1 Class data for invalid\_argument

The virtual table for the std::invalid\_argument class is described by [Table 9-103](#)

**Table 9-103 Primary vtable for invalid\_argument**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for invalid_argument
vfunc[0]:	invalid_argument::~invalid_argument()
vfunc[1]:	invalid_argument::~invalid_argument()
vfunc[2]:	logic_error::what() const

The Run Time Type Information for the std::invalid\_argument class is described by [Table 9-104](#)

**Table 9-104 typeinfo for invalid\_argument**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for invalid_argument

### 9.1.31.2 Interfaces for Class invalid\_argument

An LSB conforming implementation shall provide the generic methods for Class std::invalid\_argument specified in [Table 9-105](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-105 libstdc++ - Class invalid\_argument Function Interfaces**

invalid_argument::invalid_argument(basic_string<char, char_traits<char>, allocator<char> > const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
invalid_argument::invalid_argument(basic_string<char, char_traits<char>, allocator<char> > const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
invalid_argument::~invalid_argument()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
invalid_argument::~invalid_argument()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::invalid\_argument specified in [Table 9-106](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-106 libstdc++ - Class invalid\_argument Data Interfaces**

typeinfo for invalid_argument(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for invalid_argument(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for invalid_argument(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.32 Class `bad_cast`

### 9.1.32.1 Class data for `bad_cast`

The virtual table for the `std::bad_cast` class is described by [Table 9-107](#)

**Table 9-107 Primary vtable for `bad_cast`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>bad_cast</code>
vfunc[0]:	<code>bad_cast::~bad_cast()</code>
vfunc[1]:	<code>bad_cast::~bad_cast()</code>
vfunc[2]:	<code>exception::what() const</code>

The Run Time Type Information for the `std::bad_cast` class is described by [Table 9-108](#)

**Table 9-108 typeinfo for `bad_cast`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>bad_cast</code>

### 9.1.32.2 Interfaces for Class `bad_cast`

An LSB conforming implementation shall provide the generic methods for Class `std::bad_cast` specified in [Table 9-109](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-109 libstdc++ - Class `bad_cast` Function Interfaces**

<code>bad_cast::~bad_cast()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>bad_cast::~bad_cast()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>bad_cast::~bad_cast()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class `std::bad_cast` specified in [Table 9-110](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-110 libstdc++ - Class `bad_cast` Data Interfaces**

<code>typeinfo for bad_cast(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>
<code>typeinfo name for bad_cast(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>
<code>vtable for bad_cast(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>

## 9.1.33 Class `bad_alloc`

### 9.1.33.1 Class data for `bad_alloc`

The virtual table for the `std::bad_alloc` class is described by [Table 9-111](#)

**Table 9-111 Primary vtable for `bad_alloc`**

Base Offset	0
-------------	---

Virtual Base Offset	0
RTTI	typeinfo for bad_alloc
vfunc[0]:	bad_alloc::~bad_alloc()
vfunc[1]:	bad_alloc::~bad_alloc()
vfunc[2]:	exception::what() const

The Run Time Type Information for the std::bad\_alloc class is described by [Table 9-112](#)

**Table 9-112 typeinfo for bad\_alloc**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for bad_alloc

### 9.1.33.2 Interfaces for Class bad\_alloc

An LSB conforming implementation shall provide the generic methods for Class std::bad\_alloc specified in [Table 9-113](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-113 libstdc++ - Class bad\_alloc Function Interfaces**

bad_alloc::~bad_alloc()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
bad_alloc::~bad_alloc()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
bad_alloc::~bad_alloc()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::bad\_alloc specified in [Table 9-114](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-114 libstdc++ - Class bad\_alloc Data Interfaces**

typeinfo for bad_alloc(GLIBCXX_3.4) <a href="#">[Cxxabi]</a>
typeinfo name for bad_alloc(GLIBCXX_3.4) <a href="#">[Cxxabi]</a>
vtable for bad_alloc(GLIBCXX_3.4) <a href="#">[Cxxabi]</a>

### 9.1.34 struct \_\_numeric\_limits\_base

#### 9.1.34.1 Interfaces for struct \_\_numeric\_limits\_base

No external methods are defined for libstdc++ - struct \_\_numeric\_limits\_base in this part of the specification. See also the relevant architecture specific part of this specification.

An LSB conforming implementation shall provide the generic data interfaces for struct \_\_numeric\_limits\_base specified in [Table 9-115](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-115 libstdc++ - struct \_\_numeric\_limits\_base Data Interfaces**

__numeric_limits_base::has_denorm(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
__numeric_limits_base::is_bounded(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
__numeric_limits_base::is_integer(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>

<code>_numeric_limits_base::round_style(GLIBCXX_3.4)</code>	<a href="#">[ISO CXX]</a>
<code>_numeric_limits_base::has_infinity(GLIBCXX_3.4)</code>	<a href="#">[ISO CXX]</a>
<code>_numeric_limits_base::max_exponent(GLIBCXX_3.4)</code>	<a href="#">[ISO CXX]</a>
<code>_numeric_limits_base::min_exponent(GLIBCXX_3.4)</code>	<a href="#">[ISO CXX]</a>
<code>_numeric_limits_base::has_quiet_NaN(GLIBCXX_3.4)</code>	<a href="#">[ISO CXX]</a>
<code>_numeric_limits_base::is_specialized(GLIBCXX_3.4)</code>	<a href="#">[ISO CXX]</a>
<code>_numeric_limits_base::max_exponent10(GLIBCXX_3.4)</code>	<a href="#">[ISO CXX]</a>
<code>_numeric_limits_base::min_exponent10(GLIBCXX_3.4)</code>	<a href="#">[ISO CXX]</a>
<code>_numeric_limits_base::has_denorm_loss(GLIBCXX_3.4)</code>	<a href="#">[ISO CXX]</a>
<code>_numeric_limits_base::tinyness_before(GLIBCXX_3.4)</code>	<a href="#">[ISO CXX]</a>
<code>_numeric_limits_base::has_signaling_NaN(GLIBCXX_3.4)</code>	<a href="#">[ISO CXX]</a>
<code>_numeric_limits_base::radix(GLIBCXX_3.4)</code>	<a href="#">[ISO CXX]</a>
<code>_numeric_limits_base::traps(GLIBCXX_3.4)</code>	<a href="#">[ISO CXX]</a>
<code>_numeric_limits_base::digits(GLIBCXX_3.4)</code>	<a href="#">[ISO CXX]</a>
<code>_numeric_limits_base::digits10(GLIBCXX_3.4)</code>	<a href="#">[ISO CXX]</a>
<code>_numeric_limits_base::is_exact(GLIBCXX_3.4)</code>	<a href="#">[ISO CXX]</a>
<code>_numeric_limits_base::is_iec559(GLIBCXX_3.4)</code>	<a href="#">[ISO CXX]</a>
<code>_numeric_limits_base::is_modulo(GLIBCXX_3.4)</code>	<a href="#">[ISO CXX]</a>
<code>_numeric_limits_base::is_signed(GLIBCXX_3.4)</code>	<a href="#">[ISO CXX]</a>

## 9.1.35 struct numeric\_limits<long double>

### 9.1.35.1 Interfaces for struct numeric\_limits<long double>

No external methods are defined for libstdc++ - struct numeric\_limits<long double> in this part of the specification. See also the relevant architecture specific part of this specification.

An LSB conforming implementation shall provide the generic data interfaces for struct numeric\_limits<long double> specified in [Table 9-116](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-116 libstdc++ - struct numeric\_limits<long double> Data Interfaces**

<code>numeric_limits&lt;long double&gt;::has_denorm(GLIBCXX_3.4)</code>	<a href="#">[ISO CXX]</a>
<code>numeric_limits&lt;long double&gt;::is_bounded(GLIBCXX_3.4)</code>	<a href="#">[ISO CXX]</a>
<code>numeric_limits&lt;long double&gt;::is_integer(GLIBCXX_3.4)</code>	<a href="#">[ISO CXX]</a>
<code>numeric_limits&lt;long double&gt;::round_style(GLIBCXX_3.4)</code>	<a href="#">[ISO CXX]</a>
<code>numeric_limits&lt;long double&gt;::has_infinity(GLIBCXX_3.4)</code>	<a href="#">[ISO CXX]</a>
<code>numeric_limits&lt;long double&gt;::max_exponent(GLIBCXX_3.4)</code>	<a href="#">[ISO CXX]</a>
<code>numeric_limits&lt;long double&gt;::min_exponent(GLIBCXX_3.4)</code>	<a href="#">[ISO CXX]</a>
<code>numeric_limits&lt;long double&gt;::has_quiet_NaN(GLIBCXX_3.4)</code>	<a href="#">[ISO CXX]</a>
<code>numeric_limits&lt;long double&gt;::is_specialized(GLIBCXX_3.4)</code>	<a href="#">[ISO CXX]</a>
<code>numeric_limits&lt;long double&gt;::max_exponent10(GLIBCXX_3.4)</code>	<a href="#">[ISO CXX]</a>
<code>numeric_limits&lt;long double&gt;::min_exponent10(GLIBCXX_3.4)</code>	<a href="#">[ISO CXX]</a>

numeric_limits<long double>::has_denorm_loss(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
numeric_limits<long double>::tinyness_before(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
numeric_limits<long double>::has_signaling_NaN(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
numeric_limits<long double>::radix(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
numeric_limits<long double>::traps(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
numeric_limits<long double>::digits(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
numeric_limits<long double>::digits10(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
numeric_limits<long double>::is_exact(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
numeric_limits<long double>::is_iec559(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
numeric_limits<long double>::is_modulo(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
numeric_limits<long double>::is_signed(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>

## 9.1.36 struct numeric\_limits<long long>

### 9.1.36.1 Interfaces for struct numeric\_limits<long long>

No external methods are defined for libstdcxx - struct numeric\_limits<long long> in this part of the specification. See also the relevant architecture specific part of this specification.

An LSB conforming implementation shall provide the generic data interfaces for struct numeric\_limits<long long> specified in [Table 9-117](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-117 libstdcxx - struct numeric\_limits<long long> Data Interfaces**

numeric_limits<long long>::has_denorm(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
numeric_limits<long long>::is_bounded(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
numeric_limits<long long>::is_integer(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
numeric_limits<long long>::round_style(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
numeric_limits<long long>::has_infinity(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
numeric_limits<long long>::max_exponent(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
numeric_limits<long long>::min_exponent(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
numeric_limits<long long>::has_quiet_NaN(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
numeric_limits<long long>::is_specialized(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
numeric_limits<long long>::max_exponent10(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
numeric_limits<long long>::min_exponent10(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
numeric_limits<long long>::has_denorm_loss(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
numeric_limits<long long>::tinyness_before(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
numeric_limits<long long>::has_signaling_NaN(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
numeric_limits<long long>::radix(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
numeric_limits<long long>::traps(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
numeric_limits<long long>::digits(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
numeric_limits<long long>::digits10(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
numeric_limits<long long>::is_exact(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>

numeric_limits<long long>::is_iec559(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
numeric_limits<long long>::is_modulo(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
numeric_limits<long long>::is_signed(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>

## 9.1.37 struct numeric\_limits<unsigned long long>

### 9.1.37.1 Interfaces for struct numeric\_limits<unsigned long long>

No external methods are defined for libstdcxx - struct numeric\_limits<unsigned long long> in this part of the specification. See also the relevant architecture specific part of this specification.

An LSB conforming implementation shall provide the generic data interfaces for struct numeric\_limits<unsigned long long> specified in [Table 9-118](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-118 libstdcxx - struct numeric\_limits<unsigned long long> Data Interfaces**

numeric_limits<unsigned long long>::has_denorm(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
numeric_limits<unsigned long long>::is_bounded(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
numeric_limits<unsigned long long>::is_integer(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
numeric_limits<unsigned long long>::round_style(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
numeric_limits<unsigned long long>::has_INFINITY(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
numeric_limits<unsigned long long>::max_exponent(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
numeric_limits<unsigned long long>::min_exponent(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
numeric_limits<unsigned long long>::has_quiet_NaN(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
numeric_limits<unsigned long long>::is_specialized(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
numeric_limits<unsigned long long>::max_exponent10(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
numeric_limits<unsigned long long>::min_exponent10(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
numeric_limits<unsigned long long>::has_denorm_loss(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
numeric_limits<unsigned long long>::tininess_before(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
numeric_limits<unsigned long long>::has_signaling_NaN(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
numeric_limits<unsigned long long>::radix(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
numeric_limits<unsigned long long>::traps(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
numeric_limits<unsigned long long>::digits(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
numeric_limits<unsigned long long>::digits10(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
numeric_limits<unsigned long long>::is_exact(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>

numeric_limits<unsigned long long>::is_iec559(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<unsigned long long>::is_modulo(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<unsigned long long>::is_signed(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 9.1.38 struct numeric\_limits<float>

### 9.1.38.1 Interfaces for struct numeric\_limits<float>

No external methods are defined for libstdcxx - struct numeric\_limits<float> in this part of the specification. See also the relevant architecture specific part of this specification.

An LSB conforming implementation shall provide the generic data interfaces for struct numeric\_limits<float> specified in [Table 9-119](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-119 libstdcxx - struct numeric\_limits<float> Data Interfaces**

numeric_limits<float>::has_denorm(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<float>::is_bounded(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<float>::is_integer(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<float>::round_style(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<float>::has_infinity(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<float>::max_exponent(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<float>::min_exponent(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<float>::has_quiet_NaN(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<float>::is_specialized(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<float>::max_exponent10(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<float>::min_exponent10(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<float>::has_denorm_loss(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<float>::tinyness_before(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<float>::has_signaling_NaN(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<float>::radix(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<float>::traps(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<float>::digits(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<float>::digits10(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<float>::is_exact(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<float>::is_iec559(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<float>::is_modulo(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<float>::is_signed(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 9.1.39 struct numeric\_limits<double>

### 9.1.39.1 Interfaces for struct numeric\_limits<double>

No external methods are defined for libstdcxx - struct numeric\_limits<double> in this part of the specification. See also the relevant architecture specific part of this specification.

An LSB conforming implementation shall provide the generic data interfaces for struct numeric\_limits<double> specified in [Table 9-120](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-120 libstdcxx - struct numeric\_limits<double> Data Interfaces**

numeric_limits<double>::has_denorm(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<double>::is_bounded(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<double>::is_integer(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<double>::round_style(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<double>::has_infinity(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<double>::max_exponent(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<double>::min_exponent(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<double>::has_quiet_NaN(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<double>::is_specialized(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<double>::max_exponent10(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<double>::min_exponent10(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<double>::has_denorm_loss(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<double>::tinytess_before(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<double>::has_signaling_NaN(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<double>::radix(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<double>::traps(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<double>::digits(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<double>::digits10(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<double>::is_exact(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<double>::is_iec559(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<double>::is_modulo(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<double>::is_signed(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 9.1.40 struct numeric\_limits<short>

### 9.1.40.1 Interfaces for struct numeric\_limits<short>

No external methods are defined for libstdcxx - struct numeric\_limits<short> in this part of the specification. See also the relevant architecture specific part of this specification.

An LSB conforming implementation shall provide the generic data interfaces for struct numeric\_limits<short> specified in [Table 9-121](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-121 libstdcxx - struct numeric\_limits<short> Data Interfaces**

numeric_limits<short>::has_denorm(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<short>::is_bounded(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<short>::is_integer(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<short>::round_style(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<short>::has_infinity(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

numeric_limits<short>::max_exponent(GLIBCXX_3.4) [ISOCXX]
numeric_limits<short>::min_exponent(GLIBCXX_3.4) [ISOCXX]
numeric_limits<short>::has_quiet_NaN(GLIBCXX_3.4) [ISOCXX]
numeric_limits<short>::is_specialized(GLIBCXX_3.4) [ISOCXX]
numeric_limits<short>::max_exponent10(GLIBCXX_3.4) [ISOCXX]
numeric_limits<short>::min_exponent10(GLIBCXX_3.4) [ISOCXX]
numeric_limits<short>::has_denorm_loss(GLIBCXX_3.4) [ISOCXX]
numeric_limits<short>::tinyness_before(GLIBCXX_3.4) [ISOCXX]
numeric_limits<short>::has_signaling_NaN(GLIBCXX_3.4) [ISOCXX]
numeric_limits<short>::radix(GLIBCXX_3.4) [ISOCXX]
numeric_limits<short>::traps(GLIBCXX_3.4) [ISOCXX]
numeric_limits<short>::digits(GLIBCXX_3.4) [ISOCXX]
numeric_limits<short>::digits10(GLIBCXX_3.4) [ISOCXX]
numeric_limits<short>::is_exact(GLIBCXX_3.4) [ISOCXX]
numeric_limits<short>::is_iec559(GLIBCXX_3.4) [ISOCXX]
numeric_limits<short>::is_modulo(GLIBCXX_3.4) [ISOCXX]
numeric_limits<short>::is_signed(GLIBCXX_3.4) [ISOCXX]

## 9.1.41 struct numeric\_limits<unsigned short>

### 9.1.41.1 Interfaces for struct numeric\_limits<unsigned short>

No external methods are defined for libstdcxx - struct numeric\_limits<unsigned short> in this part of the specification. See also the relevant architecture specific part of this specification.

An LSB conforming implementation shall provide the generic data interfaces for struct numeric\_limits<unsigned short> specified in [Table 9-122](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-122 libstdcxx - struct numeric\_limits<unsigned short> Data Interfaces**

numeric_limits<unsigned short>::has_denorm(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned short>::is_bounded(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned short>::is_integer(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned short>::round_style(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned short>::has_infinity(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned short>::max_exponent(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned short>::min_exponent(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned short>::has_quiet_NaN(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned short>::is_specialized(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned short>::max_exponent10(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned short>::min_exponent10(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned short>::has_denorm_loss(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned short>::tinyness_before(GLIBCXX_3.4) [ISOCXX]

numeric_limits<unsigned short>::has_signaling_NaN(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned short>::radix(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned short>::traps(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned short>::digits(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned short>::digits10(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned short>::is_exact(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned short>::is_iec559(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned short>::is_modulo(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned short>::is_signed(GLIBCXX_3.4) [ISOCXX]

## 9.1.42 struct numeric\_limits<int>

### 9.1.42.1 Interfaces for struct numeric\_limits<int>

No external methods are defined for libstdcxx - struct numeric\_limits<int> in this part of the specification. See also the relevant architecture specific part of this specification.

An LSB conforming implementation shall provide the generic data interfaces for struct numeric\_limits<int> specified in [Table 9-123](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-123 libstdcxx - struct numeric\_limits<int> Data Interfaces**

numeric_limits<int>::has_denorm(GLIBCXX_3.4) [ISOCXX]
numeric_limits<int>::is_bounded(GLIBCXX_3.4) [ISOCXX]
numeric_limits<int>::is_integer(GLIBCXX_3.4) [ISOCXX]
numeric_limits<int>::round_style(GLIBCXX_3.4) [ISOCXX]
numeric_limits<int>::has_infinity(GLIBCXX_3.4) [ISOCXX]
numeric_limits<int>::max_exponent(GLIBCXX_3.4) [ISOCXX]
numeric_limits<int>::min_exponent(GLIBCXX_3.4) [ISOCXX]
numeric_limits<int>::has_quiet_NaN(GLIBCXX_3.4) [ISOCXX]
numeric_limits<int>::is_specialized(GLIBCXX_3.4) [ISOCXX]
numeric_limits<int>::max_exponent10(GLIBCXX_3.4) [ISOCXX]
numeric_limits<int>::min_exponent10(GLIBCXX_3.4) [ISOCXX]
numeric_limits<int>::has_denorm_loss(GLIBCXX_3.4) [ISOCXX]
numeric_limits<int>::tinytess_before(GLIBCXX_3.4) [ISOCXX]
numeric_limits<int>::has_signaling_NaN(GLIBCXX_3.4) [ISOCXX]
numeric_limits<int>::radix(GLIBCXX_3.4) [ISOCXX]
numeric_limits<int>::traps(GLIBCXX_3.4) [ISOCXX]
numeric_limits<int>::digits(GLIBCXX_3.4) [ISOCXX]
numeric_limits<int>::digits10(GLIBCXX_3.4) [ISOCXX]
numeric_limits<int>::is_exact(GLIBCXX_3.4) [ISOCXX]
numeric_limits<int>::is_iec559(GLIBCXX_3.4) [ISOCXX]
numeric_limits<int>::is_modulo(GLIBCXX_3.4) [ISOCXX]

numeric_limits<int>::is_signed(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
--

## 9.1.43 struct numeric\_limits<unsigned int>

### 9.1.43.1 Interfaces for struct numeric\_limits<unsigned int>

No external methods are defined for libstdcxx - struct numeric\_limits<unsigned int> in this part of the specification. See also the relevant architecture specific part of this specification.

An LSB conforming implementation shall provide the generic data interfaces for struct numeric\_limits<unsigned int> specified in [Table 9-124](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-124 libstdcxx - struct numeric\_limits<unsigned int> Data Interfaces**

numeric_limits<unsigned int>::has_denorm(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<unsigned int>::is_bounded(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<unsigned int>::is_integer(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<unsigned int>::round_style(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<unsigned int>::has_infinity(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<unsigned int>::max_exponent(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<unsigned int>::min_exponent(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<unsigned int>::has_quiet_NaN(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<unsigned int>::is_specialized(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<unsigned int>::max_exponent10(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<unsigned int>::min_exponent10(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<unsigned int>::has_denorm_loss(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<unsigned int>::tinyness_before(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<unsigned int>::has_signaling_NaN(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<unsigned int>::radix(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<unsigned int>::traps(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<unsigned int>::digits(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<unsigned int>::digits10(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<unsigned int>::is_exact(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<unsigned int>::is_iec559(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<unsigned int>::is_modulo(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<unsigned int>::is_signed(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 9.1.44 struct numeric\_limits<long>

### 9.1.44.1 Interfaces for struct numeric\_limits<long>

No external methods are defined for libstdcxx - struct numeric\_limits<long> in this part of the specification. See also the relevant architecture specific part of this specification.

An LSB conforming implementation shall provide the generic data interfaces for struct numeric\_limits<long> specified in [Table 9-125](#), with the full mandatory

functionality as described in the referenced underlying specification.

**Table 9-125 libstdcxx - struct numeric\_limits<long> Data Interfaces**

numeric_limits<long>::has_denorm(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<long>::is_bounded(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<long>::is_integer(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<long>::round_style(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<long>::has_infinity(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<long>::max_exponent(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<long>::min_exponent(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<long>::has_quiet_NaN(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<long>::is_specialized(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<long>::max_exponent10(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<long>::min_exponent10(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<long>::has_denorm_loss(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<long>::tinytess_before(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<long>::has_signaling_NaN(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<long>::radix(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<long>::traps(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<long>::digits(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<long>::digits10(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<long>::is_exact(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<long>::is_iec559(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<long>::is_modulo(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<long>::is_signed(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 9.1.45 struct numeric\_limits<unsigned long>

### 9.1.45.1 Interfaces for struct numeric\_limits<unsigned long>

No external methods are defined for libstdcxx - struct numeric\_limits<unsigned long> in this part of the specification. See also the relevant architecture specific part of this specification.

An LSB conforming implementation shall provide the generic data interfaces for struct numeric\_limits<unsigned long> specified in [Table 9-126](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-126 libstdcxx - struct numeric\_limits<unsigned long> Data Interfaces**

numeric_limits<unsigned long>::has_denorm(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<unsigned long>::is_bounded(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<unsigned long>::is_integer(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<unsigned long>::round_style(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<unsigned long>::has_infinity(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<unsigned long>::max_exponent(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

numeric_limits<unsigned long>::min_exponent(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned long>::has_quiet_NaN(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned long>::is_specialized(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned long>::max_exponent10(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned long>::min_exponent10(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned long>::has_denorm_loss(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned long>::tinyness_before(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned long>::has_signaling_NaN(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned long>::radix(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned long>::traps(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned long>::digits(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned long>::digits10(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned long>::is_exact(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned long>::is_iec559(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned long>::is_modulo(GLIBCXX_3.4) [ISOCXX]
numeric_limits<unsigned long>::is_signed(GLIBCXX_3.4) [ISOCXX]

## 9.1.46 struct numeric\_limits<wchar\_t>

### 9.1.46.1 Interfaces for struct numeric\_limits<wchar\_t>

No external methods are defined for libstdcxx - struct numeric\_limits<wchar\_t> in this part of the specification. See also the relevant architecture specific part of this specification.

An LSB conforming implementation shall provide the generic data interfaces for struct numeric\_limits<wchar\_t> specified in [Table 9-127](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-127 libstdcxx - struct numeric\_limits<wchar\_t> Data Interfaces**

numeric_limits<wchar_t>::has_denorm(GLIBCXX_3.4) [ISOCXX]
numeric_limits<wchar_t>::is_bounded(GLIBCXX_3.4) [ISOCXX]
numeric_limits<wchar_t>::is_integer(GLIBCXX_3.4) [ISOCXX]
numeric_limits<wchar_t>::round_style(GLIBCXX_3.4) [ISOCXX]
numeric_limits<wchar_t>::has_infinity(GLIBCXX_3.4) [ISOCXX]
numeric_limits<wchar_t>::max_exponent(GLIBCXX_3.4) [ISOCXX]
numeric_limits<wchar_t>::min_exponent(GLIBCXX_3.4) [ISOCXX]
numeric_limits<wchar_t>::has_quiet_NaN(GLIBCXX_3.4) [ISOCXX]
numeric_limits<wchar_t>::is_specialized(GLIBCXX_3.4) [ISOCXX]
numeric_limits<wchar_t>::max_exponent10(GLIBCXX_3.4) [ISOCXX]
numeric_limits<wchar_t>::min_exponent10(GLIBCXX_3.4) [ISOCXX]
numeric_limits<wchar_t>::has_denorm_loss(GLIBCXX_3.4) [ISOCXX]
numeric_limits<wchar_t>::tinyness_before(GLIBCXX_3.4) [ISOCXX]
numeric_limits<wchar_t>::has_signaling_NaN(GLIBCXX_3.4) [ISOCXX]

numeric_limits<wchar_t>::radix(GLIBCXX_3.4) [ISOcxx]
numeric_limits<wchar_t>::traps(GLIBCXX_3.4) [ISOcxx]
numeric_limits<wchar_t>::digits(GLIBCXX_3.4) [ISOcxx]
numeric_limits<wchar_t>::digits10(GLIBCXX_3.4) [ISOcxx]
numeric_limits<wchar_t>::is_exact(GLIBCXX_3.4) [ISOcxx]
numeric_limits<wchar_t>::is_iec559(GLIBCXX_3.4) [ISOcxx]
numeric_limits<wchar_t>::is_modulo(GLIBCXX_3.4) [ISOcxx]
numeric_limits<wchar_t>::is_signed(GLIBCXX_3.4) [ISOcxx]

## 9.1.47 struct numeric\_limits<unsigned char>

### 9.1.47.1 Interfaces for struct numeric\_limits<unsigned char>

No external methods are defined for libstdcxx - struct numeric\_limits<unsigned char> in this part of the specification. See also the relevant architecture specific part of this specification.

An LSB conforming implementation shall provide the generic data interfaces for struct numeric\_limits<unsigned char> specified in [Table 9-128](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-128 libstdcxx - struct numeric\_limits<unsigned char> Data Interfaces**

numeric_limits<unsigned char>::has_denorm(GLIBCXX_3.4) [ISOcxx]
numeric_limits<unsigned char>::is_bounded(GLIBCXX_3.4) [ISOcxx]
numeric_limits<unsigned char>::is_integer(GLIBCXX_3.4) [ISOcxx]
numeric_limits<unsigned char>::round_style(GLIBCXX_3.4) [ISOcxx]
numeric_limits<unsigned char>::has_infinity(GLIBCXX_3.4) [ISOcxx]
numeric_limits<unsigned char>::max_exponent(GLIBCXX_3.4) [ISOcxx]
numeric_limits<unsigned char>::min_exponent(GLIBCXX_3.4) [ISOcxx]
numeric_limits<unsigned char>::has_quiet_NaN(GLIBCXX_3.4) [ISOcxx]
numeric_limits<unsigned char>::is_specialized(GLIBCXX_3.4) [ISOcxx]
numeric_limits<unsigned char>::max_exponent10(GLIBCXX_3.4) [ISOcxx]
numeric_limits<unsigned char>::min_exponent10(GLIBCXX_3.4) [ISOcxx]
numeric_limits<unsigned char>::has_denorm_loss(GLIBCXX_3.4) [ISOcxx]
numeric_limits<unsigned char>::tinyness_before(GLIBCXX_3.4) [ISOcxx]
numeric_limits<unsigned char>::has_signaling_NaN(GLIBCXX_3.4) [ISOcxx]
numeric_limits<unsigned char>::radix(GLIBCXX_3.4) [ISOcxx]
numeric_limits<unsigned char>::traps(GLIBCXX_3.4) [ISOcxx]
numeric_limits<unsigned char>::digits(GLIBCXX_3.4) [ISOcxx]
numeric_limits<unsigned char>::digits10(GLIBCXX_3.4) [ISOcxx]
numeric_limits<unsigned char>::is_exact(GLIBCXX_3.4) [ISOcxx]
numeric_limits<unsigned char>::is_iec559(GLIBCXX_3.4) [ISOcxx]
numeric_limits<unsigned char>::is_modulo(GLIBCXX_3.4) [ISOcxx]
numeric_limits<unsigned char>::is_signed(GLIBCXX_3.4) [ISOcxx]

## 9.1.48 struct numeric\_limits<signed char>

### 9.1.48.1 Interfaces for struct numeric\_limits<signed char>

No external methods are defined for libstdcxx - struct numeric\_limits<signed char> in this part of the specification. See also the relevant architecture specific part of this specification.

An LSB conforming implementation shall provide the generic data interfaces for struct numeric\_limits<signed char> specified in [Table 9-129](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-129 libstdcxx - struct numeric\_limits<signed char> Data Interfaces**

numeric_limits<signed char>::has_denorm(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<signed char>::is_bounded(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<signed char>::is_integer(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<signed char>::round_style(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<signed char>::has_infinity(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<signed char>::max_exponent(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<signed char>::min_exponent(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<signed char>::has_quiet_NaN(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<signed char>::is_specialized(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<signed char>::max_exponent10(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<signed char>::min_exponent10(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<signed char>::has_denorm_loss(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<signed char>::tinyness_before(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<signed char>::has_signaling_NaN(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<signed char>::radix(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<signed char>::traps(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<signed char>::digits(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<signed char>::digits10(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<signed char>::is_exact(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<signed char>::is_iec559(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<signed char>::is_modulo(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<signed char>::is_signed(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 9.1.49 struct numeric\_limits<char>

### 9.1.49.1 Interfaces for struct numeric\_limits<char>

No external methods are defined for libstdcxx - struct numeric\_limits<char> in this part of the specification. See also the relevant architecture specific part of this specification.

An LSB conforming implementation shall provide the generic data interfaces for struct numeric\_limits<char> specified in [Table 9-130](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-130 libstdc++ - struct numeric\_limits<char> Data Interfaces**

numeric_limits<char>::has_denorm(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<char>::is_bounded(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<char>::is_integer(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<char>::round_style(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<char>::has_infinity(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<char>::max_exponent(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<char>::min_exponent(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<char>::has_quiet_NaN(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<char>::is_specialized(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<char>::max_exponent10(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<char>::min_exponent10(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<char>::has_denorm_loss(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<char>::tinyness_before(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<char>::has_signaling_NaN(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<char>::radix(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<char>::traps(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<char>::digits(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<char>::digits10(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<char>::is_exact(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<char>::is_iec559(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<char>::is_modulo(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<char>::is_signed(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 9.1.50 struct numeric\_limits<bool>

### 9.1.50.1 Interfaces for struct numeric\_limits<bool>

No external methods are defined for libstdc++ - struct numeric\_limits<bool> in this part of the specification. See also the relevant architecture specific part of this specification.

An LSB conforming implementation shall provide the generic data interfaces for struct numeric\_limits<bool> specified in [Table 9-131](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-131 libstdc++ - struct numeric\_limits<bool> Data Interfaces**

numeric_limits<bool>::has_denorm(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<bool>::is_bounded(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<bool>::is_integer(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<bool>::round_style(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<bool>::has_infinity(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<bool>::max_exponent(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<bool>::min_exponent(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numeric_limits<bool>::has_quiet_NaN(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

numeric_limits<bool>::is_specialized(GLIBCXX_3.4) [ISOCXX]
numeric_limits<bool>::max_exponent10(GLIBCXX_3.4) [ISOCXX]
numeric_limits<bool>::min_exponent10(GLIBCXX_3.4) [ISOCXX]
numeric_limits<bool>::has_denorm_loss(GLIBCXX_3.4) [ISOCXX]
numeric_limits<bool>::tinyness_before(GLIBCXX_3.4) [ISOCXX]
numeric_limits<bool>::has_signaling_NaN(GLIBCXX_3.4) [ISOCXX]
numeric_limits<bool>::radix(GLIBCXX_3.4) [ISOCXX]
numeric_limits<bool>::traps(GLIBCXX_3.4) [ISOCXX]
numeric_limits<bool>::digits(GLIBCXX_3.4) [ISOCXX]
numeric_limits<bool>::digits10(GLIBCXX_3.4) [ISOCXX]
numeric_limits<bool>::is_exact(GLIBCXX_3.4) [ISOCXX]
numeric_limits<bool>::is_iec559(GLIBCXX_3.4) [ISOCXX]
numeric_limits<bool>::is_modulo(GLIBCXX_3.4) [ISOCXX]
numeric_limits<bool>::is_signed(GLIBCXX_3.4) [ISOCXX]

## 9.1.51 Class ctype\_base

### 9.1.51.1 Class data for ctype\_base

The Run Time Type Information for the std::ctype\_base class is described by [Table 9-132](#)

**Table 9-132 typeinfo for ctype\_base**

Base Vtable	vtable for _cxxabiv1::__class_type_info
Name	typeinfo name for ctype_base

### 9.1.51.2 Interfaces for Class ctype\_base

No external methods are defined for libstdc++ - Class std::ctype\_base in this part of the specification. See also the relevant architecture specific part of this specification.

An LSB conforming implementation shall provide the generic data interfaces for Class std::ctype\_base specified in [Table 9-133](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-133 libstdc++ - Class ctype\_base Data Interfaces**

ctype_base::alnum(GLIBCXX_3.4) [ISOCXX]
ctype_base::alpha(GLIBCXX_3.4) [ISOCXX]
ctype_base::cntrl(GLIBCXX_3.4) [ISOCXX]
ctype_base::digit(GLIBCXX_3.4) [ISOCXX]
ctype_base::graph(GLIBCXX_3.4) [ISOCXX]
ctype_base::lower(GLIBCXX_3.4) [ISOCXX]
ctype_base::print(GLIBCXX_3.4) [ISOCXX]
ctype_base::punct(GLIBCXX_3.4) [ISOCXX]
ctype_base::space(GLIBCXX_3.4) [ISOCXX]

ctype_base::upper(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype_base::xdigit(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
typeinfo for ctype_base(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for ctype_base(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.52 Class \_\_ctype\_abstract\_base<char>

### 9.1.52.1 Class data for \_\_ctype\_abstract\_base<char>

The virtual table for the std::\_\_ctype\_abstract\_base<char> class is described by [Table 9-134](#)

**Table 9-134 Primary vtable for \_\_ctype\_abstract\_base<char>**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for __ctype_abstract_base<char>
vfunc[0]:	NULL or __ctype_abstract_base<char>::~__ctype_abstract_base()
vfunc[1]:	NULL or __ctype_abstract_base<char>::~__ctype_abstract_base()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	__cxa_pure_virtual
vfunc[6]:	__cxa_pure_virtual
vfunc[7]:	__cxa_pure_virtual
vfunc[8]:	__cxa_pure_virtual
vfunc[9]:	__cxa_pure_virtual
vfunc[10]:	__cxa_pure_virtual
vfunc[11]:	__cxa_pure_virtual
vfunc[12]:	__cxa_pure_virtual
vfunc[13]:	__cxa_pure_virtual

### 9.1.52.2 Interfaces for Class \_\_ctype\_abstract\_base<char>

No external methods are defined for libstdcxx - Class std::\_\_ctype\_abstract\_base<char> in this part of the specification. See also the relevant architecture specific part of this specification.

An LSB conforming implementation shall provide the generic data interfaces for Class std::\_\_ctype\_abstract\_base<char> specified in [Table 9-135](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-135 libstdcxx - Class \_\_ctype\_abstract\_base<char> Data Interfaces**

typeinfo for __ctype_abstract_base<char>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
--

typeinfo name for <code>__ctype_abstract_base&lt;char&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for <code>__ctype_abstract_base&lt;char&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.53 Class `__ctype_abstract_base<wchar_t>`

### 9.1.53.1 Class data for `__ctype_abstract_base<wchar_t>`

The virtual table for the `std::__ctype_abstract_base<wchar_t>` class is described by [Table 9-136](#)

**Table 9-136 Primary vtable for `__ctype_abstract_base<wchar_t>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>__ctype_abstract_base&lt;wchar_t&gt;</code>
vfunc[0]:	NULL or <code>__ctype_abstract_base&lt;wchar_t&gt;::~__ctype_abstract_base()</code>
vfunc[1]:	NULL or <code>__ctype_abstract_base&lt;wchar_t&gt;::~__ctype_abstract_base()</code>
vfunc[2]:	<code>_cxa_pure_virtual</code>
vfunc[3]:	<code>_cxa_pure_virtual</code>
vfunc[4]:	<code>_cxa_pure_virtual</code>
vfunc[5]:	<code>_cxa_pure_virtual</code>
vfunc[6]:	<code>_cxa_pure_virtual</code>
vfunc[7]:	<code>_cxa_pure_virtual</code>
vfunc[8]:	<code>_cxa_pure_virtual</code>
vfunc[9]:	<code>_cxa_pure_virtual</code>
vfunc[10]:	<code>_cxa_pure_virtual</code>
vfunc[11]:	<code>_cxa_pure_virtual</code>
vfunc[12]:	<code>_cxa_pure_virtual</code>
vfunc[13]:	<code>_cxa_pure_virtual</code>

### 9.1.53.2 Interfaces for Class `__ctype_abstract_base<wchar_t>`

No external methods are defined for libstdcxx - Class `std::__ctype_abstract_base<wchar_t>` in this part of the specification. See also the relevant architecture specific part of this specification.

An LSB conforming implementation shall provide the generic data interfaces for Class `std::__ctype_abstract_base<wchar_t>` specified in [Table 9-137](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-137 libstdcxx - Class `__ctype_abstract_base<wchar_t>` Data Interfaces**

typeinfo for <code>__ctype_abstract_base&lt;wchar_t&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for <code>__ctype_abstract_base&lt;wchar_t&gt;</code> (GLIBCXX_3.4)

[\[CXXABI\]](#)vtable for `__ctype_abstract_base<wchar_t>(GLIBCXX_3.4)` [\[CXXABI\]](#)

## 9.1.54 Class `ctype<char>`

### 9.1.54.1 Class data for `ctype<char>`

The virtual table for the `std::ctype<char>` class is described by [Table 9-138](#)

**Table 9-138 Primary vtable for `ctype<char>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>ctype&lt;char&gt;</code>
vfunc[0]:	<code>ctype&lt;char&gt;::~ctype()</code>
vfunc[1]:	<code>ctype&lt;char&gt;::~ctype()</code>
vfunc[2]:	<code>ctype&lt;char&gt;::do_toupper(char) const</code>
vfunc[3]:	<code>ctype&lt;char&gt;::do_toupper(char*, char const*) const</code>
vfunc[4]:	<code>ctype&lt;char&gt;::do_tolower(char) const</code>
vfunc[5]:	<code>ctype&lt;char&gt;::do_tolower(char*, char const*) const</code>
vfunc[6]:	<code>ctype&lt;char&gt;::do_widen(char) const</code>
vfunc[7]:	<code>ctype&lt;char&gt;::do_widen(char const*, char const*, char*) const</code>
vfunc[8]:	<code>ctype&lt;char&gt;::do_narrow(char, char) const</code>
vfunc[9]:	<code>ctype&lt;char&gt;::do_narrow(char const*, char const*, char, char*) const</code>

### 9.1.54.2 Interfaces for Class `ctype<char>`

An LSB conforming implementation shall provide the generic methods for Class `std::ctype<char>` specified in [Table 9-139](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-139 libstdcxx - Class `ctype<char>` Function Interfaces**

<code>ctype&lt;char&gt;::do_tolower(char*, char const*) const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>ctype&lt;char&gt;::do_tolower(char) const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>ctype&lt;char&gt;::do_toupper(char*, char const*) const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>ctype&lt;char&gt;::do_toupper(char) const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>ctype&lt;char&gt;::do_widen(char const*, char const*, char*) const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>ctype&lt;char&gt;::do_widen(char) const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>ctype&lt;char&gt;::do_narrow(char const*, char const*, char, char*) const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>ctype&lt;char&gt;::do_narrow(char, char) const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>ctype&lt;char&gt;::classic_table()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

ctype<char>::~ctype()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype<char>::~ctype()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype<char>::~ctype()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
bool has_facet<ctype<char>>(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXXI]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::ctype<char> specified in [Table 9-140](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-140 libstdcxx - Class ctype<char> Data Interfaces**

ctype<char>::table_size(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype<char>::id(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
typeinfo for ctype<char>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for ctype<char>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for ctype<char>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.55 Class ctype<wchar\_t>

### 9.1.55.1 Class data for ctype<wchar\_t>

The virtual table for the std::ctype<wchar\_t> class is described by [Table 9-141](#)

**Table 9-141 Primary vtable for ctype<wchar\_t>**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for ctype<wchar_t>
vfunc[0]:	ctype<wchar_t>::~ctype()
vfunc[1]:	ctype<wchar_t>::~ctype()
vfunc[2]:	ctype<wchar_t>::do_is(unsigned short, wchar_t) const
vfunc[3]:	ctype<wchar_t>::do_is(wchar_t const*, wchar_t const*, unsigned short*) const
vfunc[4]:	ctype<wchar_t>::do_scan_is(unsigned short, wchar_t const*, wchar_t const*) const
vfunc[5]:	ctype<wchar_t>::do_scan_not(unsigned short, wchar_t const*, wchar_t const*) const
vfunc[6]:	ctype<wchar_t>::do_toupper(wchar_t) const
vfunc[7]:	ctype<wchar_t>::do_toupper(wchar_t*, wchar_t const*) const
vfunc[8]:	ctype<wchar_t>::do_tolower(wchar_t) const
vfunc[9]:	ctype<wchar_t>::do_tolower(wchar_t*, wchar_t const*) const

vfunc[10]:	ctype<wchar_t>::do_widen(char) const
vfunc[11]:	ctype<wchar_t>::do_widen(char const*, char const*, wchar_t*) const
vfunc[12]:	ctype<wchar_t>::do_narrow(wchar_t, char) const
vfunc[13]:	ctype<wchar_t>::do_narrow(wchar_t const*, wchar_t const*, char, char*) const

The Run Time Type Information for the std::ctype<wchar\_t> class is described by [Table 9-142](#)

**Table 9-142 typeinfo for ctype<wchar\_t>**

Base Vtable	vtable for <code>_cxxabiv1::_si_class_type_info</code>
Name	typeinfo name for ctype<wchar_t>

### 9.1.55.2 Interfaces for Class ctype<wchar\_t>

An LSB conforming implementation shall provide the generic methods for Class std::ctype<wchar\_t> specified in [Table 9-143](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-143 libstdc++ - Class ctype<wchar\_t> Function Interfaces**

ctype<wchar_t>::do_scan_is(unsigned short, wchar_t const*, wchar_t const*) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype<wchar_t>::do_tolower(wchar_t*, wchar_t const*) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype<wchar_t>::do_tolower(wchar_t) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype<wchar_t>::do_toupper(wchar_t*, wchar_t const*) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype<wchar_t>::do_toupper(wchar_t) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype<wchar_t>::do_scan_not(unsigned short, wchar_t const*, wchar_t const*) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype<wchar_t>::_M_convert_to_wmask(unsigned short) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype<wchar_t>::do_is(wchar_t const*, wchar_t const*, unsigned short*) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype<wchar_t>::do_is(unsigned short, wchar_t) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype<wchar_t>::do_widen(char const*, char const*, wchar_t*) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype<wchar_t>::do_widen(char) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype<wchar_t>::do_narrow(wchar_t const*, wchar_t const*, char, char*) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype<wchar_t>::do_narrow(wchar_t, char) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype<wchar_t>::_M_initialize_ctype()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

ctype<wchar_t>::~ctype()(GLIBCXX_3.4) [ISOCXX]
ctype<wchar_t>::~ctype()(GLIBCXX_3.4) [ISOCXX]
ctype<wchar_t>::~ctype()(GLIBCXX_3.4) [ISOCXX]

An LSB conforming implementation shall provide the generic data interfaces for Class std::ctype<wchar\_t> specified in [Table 9-144](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-144 libstdcxx - Class ctype<wchar\_t> Data Interfaces**

ctype<wchar_t>::id(GLIBCXX_3.4) [ISOCXX]
typeinfo for ctype<wchar_t>(GLIBCXX_3.4) [CXXABI]
typeinfo name for ctype<wchar_t>(GLIBCXX_3.4) [CXXABI]
vtable for ctype<wchar_t>(GLIBCXX_3.4) [CXXABI]

## 9.1.56 Class ctype\_byname<char>

### 9.1.56.1 Class data for ctype\_byname<char>

The virtual table for the std::ctype\_byname<char> class is described by [Table 9-145](#)

**Table 9-145 Primary vtable for ctype\_byname<char>**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for ctype_byname<char>
vfunc[0]:	ctype_byname<char>::~ctype_byname()
vfunc[1]:	ctype_byname<char>::~ctype_byname()
vfunc[2]:	ctype<char>::do_toupper(char) const
vfunc[3]:	ctype<char>::do_toupper(char*, char const*) const
vfunc[4]:	ctype<char>::do_tolower(char) const
vfunc[5]:	ctype<char>::do_tolower(char*, char const*) const
vfunc[6]:	ctype<char>::do_widen(char) const
vfunc[7]:	ctype<char>::do_widen(char const*, char const*, char*) const
vfunc[8]:	ctype<char>::do_narrow(char, char) const
vfunc[9]:	ctype<char>::do_narrow(char const*, char const*, char, char*) const

The Run Time Type Information for the std::ctype\_byname<char> class is described by [Table 9-146](#)

**Table 9-146 typeinfo for ctype\_byname<char>**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for ctype_byname<char>

### 9.1.56.2 Interfaces for Class ctype\_byname<char>

An LSB conforming implementation shall provide the generic methods for Class std::ctype\_byname<char> specified in [Table 9-147](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-147 libstdc++ - Class ctype\_byname<char> Function Interfaces**

ctype_byname<char>::~ctype_byname()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype_byname<char>::~ctype_byname()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype_byname<char>::~ctype_byname()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::ctype\_byname<char> specified in [Table 9-148](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-148 libstdc++ - Class ctype\_byname<char> Data Interfaces**

typeinfo for ctype_byname<char>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for ctype_byname<char>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for ctype_byname<char>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

### 9.1.57 Class ctype\_byname<wchar\_t>

#### 9.1.57.1 Class data for ctype\_byname<wchar\_t>

The virtual table for the std::ctype\_byname<wchar\_t> class is described by [Table 9-149](#)

**Table 9-149 Primary vtable for ctype\_byname<wchar\_t>**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for ctype_byname<wchar_t>
vfunc[0]:	ctype_byname<wchar_t>::~ctype_byname()
vfunc[1]:	ctype_byname<wchar_t>::~ctype_byname()
vfunc[2]:	ctype<wchar_t>::do_is(unsigned short, wchar_t) const
vfunc[3]:	ctype<wchar_t>::do_is(wchar_t const*, wchar_t const*, unsigned short*) const
vfunc[4]:	ctype<wchar_t>::do_scan_is(unsigned short, wchar_t const*, wchar_t)

	const*) const
vfunc[5]:	ctype<wchar_t>::do_scan_not(unsigned short, wchar_t const*, wchar_t const*) const
vfunc[6]:	ctype<wchar_t>::do_toupper(wchar_t) const
vfunc[7]:	ctype<wchar_t>::do_toupper(wchar_t*, wchar_t const*) const
vfunc[8]:	ctype<wchar_t>::do_tolower(wchar_t) const
vfunc[9]:	ctype<wchar_t>::do_tolower(wchar_t*, wchar_t const*) const
vfunc[10]:	ctype<wchar_t>::do_widen(char) const
vfunc[11]:	ctype<wchar_t>::do_widen(char const*, char const*, wchar_t*) const
vfunc[12]:	ctype<wchar_t>::do_narrow(wchar_t, char) const
vfunc[13]:	ctype<wchar_t>::do_narrow(wchar_t const*, wchar_t const*, char, char*) const

The Run Time Type Information for the std::ctype\_byname<wchar\_t> class is described by [Table 9-150](#)

**Table 9-150 typeinfo for ctype\_byname<wchar\_t>**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for ctype_byname<wchar_t>

### 9.1.57.2 Interfaces for Class ctype\_byname<wchar\_t>

An LSB conforming implementation shall provide the generic methods for Class std::ctype\_byname<wchar\_t> specified in [Table 9-151](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-151 libstdc++ - Class ctype\_byname<wchar\_t> Function Interfaces**

ctype_byname<wchar_t>::~ctype_byname()(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
ctype_byname<wchar_t>::~ctype_byname()(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
ctype_byname<wchar_t>::~ctype_byname()(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::ctype\_byname<wchar\_t> specified in [Table 9-152](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-152 libstdc++ - Class ctype\_byname<wchar\_t> Data Interfaces**

typeinfo for ctype_byname<wchar_t>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for ctype_byname<wchar_t>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

vtable for ctype_byname<wchar_t>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
--

## 9.1.58 Class `basic_string<char, char_traits<char>, allocator<char>` >

### 9.1.58.1 Interfaces for Class `basic_string<char, char_traits<char>, allocator<char>` >

An LSB conforming implementation shall provide the generic methods for Class `std::basic_string<char, std::char_traits<char>, std::allocator<char>>` specified in [Table 9-153](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-153 libstdcxx - Class `basic_string<char, char_traits<char>, allocator<char>` > Function Interfaces**

<code>basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;::_M_disjunct(char const*) const(GLIBCXX_3.4.5) <a href="#">[ISOCXX]</a></code>
<code>basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;::get_allocator() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;::end() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;::_Rep::_M_is_leaked() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;::_Rep::_M_is_shared() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;::data() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;::rend() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;::size() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;::begin() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;::c_str() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;::empty() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;::_M_rep() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;::length() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;::rbegin() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;::_M_data() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;::_M_iend() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>

basic_string<char, char_traits<char>, allocator<char> >::compare(char const*) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::compare(basic_string<char, char_traits<char>, allocator<char> > const&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::capacity() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::max_size() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::_M_ibegin() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::_Alloc_hider::_Alloc_hider(char*, allocator<char> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::_Alloc_hider::_Alloc_hider(char*, allocator<char> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::_M_leak_hard()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::_S_empty_rep()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::_S_copy_chars(char*, __gnu_cxx::__normal_iterator<char const*, basic_string<char, char_traits<char>, allocator<char> > >, __gnu_cxx::__normal_iterator<char const*, basic_string<char, char_traits<char>, allocator<char> > >)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::_S_copy_chars(char*, __gnu_cxx::__normal_iterator<char const*, basic_string<char, char_traits<char>, allocator<char> > >, __gnu_cxx::__normal_iterator<char const*, basic_string<char, char_traits<char>, allocator<char> > >)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::_S_copy_chars(char*, char const*, char const*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::_S_copy_chars(char*, char*, char*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::end()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::_Rep::_M_destroy(allocator<char> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::_Rep::_M_dispose(allocator<char> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::_Rep::_M_refcopy()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::_Rep::_M_refdata()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::_Rep::_S_empty_rep()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

basic_string<char, char_traits<char>, allocator<char>>::_Rep::_M_set_leaked()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::_Rep::_M_set_sharable()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::_Rep::_M_grab(allocator<char> const&, allocator<char> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::rend()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::swap(basic_string<char, char_traits<char>, allocator<char>>&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::begin()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::clear()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::erase(__gnu_cxx::__normal_iterator<char*, basic_string<char, char_traits<char>, allocator<char>>>)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::erase(__gnu_cxx::__normal_iterator<char*, basic_string<char, char_traits<char>, allocator<char>>>, __gnu_cxx::__normal_iterator<char*, basic_string<char, char_traits<char>, allocator<char>>>)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::append(char const*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::append(basic_string<char, char_traits<char>, allocator<char>> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::assign(char const*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::assign(basic_string<char, char_traits<char>, allocator<char>> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::insert(__gnu_cxx::__normal_iterator<char*, basic_string<char, char_traits<char>, allocator<char>>>, char)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::rbegin()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::_M_data(char*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::_M_leak()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char>>::replace(__gnu_cxx::__normal_iterator<char*, basic_string<char, char_traits<char>, allocator<char>>>, __gnu_cxx::__normal_iterator<char*, basic_string<char, char_traits<char>, allocator<char>>>,

`_gnu_cxx::__normal_iterator<char const*, basic_string<char, char_traits<char>, allocator<char> >, _gnu_cxx::__normal_iterator<char const*, basic_string<char, char_traits<char>, allocator<char> > >`  
(GLIBCXX 3.4) [ISO CXX]

```
basic_string<char, char_traits<char>, allocator<char>
>::replace(__gnu_cxx::__normal_iterator<char*, basic_string<char,
char_traits<char>, allocator<char> >>, __gnu_cxx::__normal_iterator<char*,  

basic_string<char, char_traits<char>, allocator<char> >>, char const*)
(GLIBCXX_3.4) [ISO CXX]
```

```
basic_string<char, char_traits<char>, allocator<char>
>::replace(__gnu_cxx::__normal_iterator<char*, basic_string<char,
char_traits<char>, allocator<char> >>, __gnu_cxx::__normal_iterator<char*, basic_string<char, char_traits<char>, allocator<char> >>, char const*, char const*)(GLIBCXX_3.4) [ISO_CXX]
```

```
basic_string<char, char_traits<char>, allocator<char>
>::replace(__gnu_cxx::__normal_iterator<char*, basic_string<char,
char_traits<char>, allocator<char> >, __gnu_cxx::__normal_iterator<char*, basic_string<char, char_traits<char>, allocator<char> >, basic_string<char, char_traits<char>, allocator<char> > const&)(GLIBCXX_3.4) [ISOcxx]
```

```
basic_string<char, char_traits<char>, allocator<char>
>::replace(__gnu_cxx::__normal_iterator<char*, basic_string<char,
char_traits<char>, allocator<char> >>, __gnu_cxx::__normal_iterator<char*, basic_string<char, char_traits<char>, allocator<char> >>, char*, char*)
(GLIBCXX_3.4) [ISO CXX]
```

```
basic_string<char, char_traits<char>, allocator<char>
>::replace(_gnu_cxx::__normal_iterator<char*, basic_string<char,
char_traits<char>, allocator<char> > , _gnu_cxx::__normal_iterator<char*, basic_string<char, char_traits<char>, allocator<char> > ,
_gnu_cxx::__normal_iterator<char*, basic_string<char, char_traits<char>, allocator<char> > , _gnu_cxx::__normal_iterator<char*, basic_string<char, char_traits<char>, allocator<char> > ))(GLIBCXX_3.4) [ISOCXX]
```

`basic_string<char, char_traits<char>, allocator<char> >::push_back(char)`  
(GLIBCXX\_3.4) [\[ISO CXX\]](#)

`basic_string<char, char_traits<char>, allocator<char> >::basic_string(char const*, allocator<char> const&)(GLIBCXX_3.4) [ISOCXX]`

`basic_string<char, char_traits<char>, allocator<char>>::basic_string(allocator<char> const&)(GLIBCXX_3.4) [ISOCXX]`

`basic_string<char, char_traits<char>, allocator<char>>::basic_string(basic_string<char, char_traits<char>, allocator<char> > const&)(GLIBCXX_3.4) [ISOCXX]`

`basic_string<char, char_traits<char>, allocator<char>>::basic_string()`  
(GLIBCXX\_3.4) [\[ISO CXX\]](#)

```
basic_string<char, char_traits<char>, allocator<char>
>::basic_string<__gnu_cxx::__normal_iterator<char*, basic_string<char,
char_traits<char>, allocator<char>> >
>(__gnu_cxx::__normal_iterator<char*, basic_string<char, char_traits<char>,
allocator<char>>>, __gnu_cxx::__normal_iterator<char*, basic_string<char,
char_traits<char>, allocator<char>>>, allocator<char> const&)
(GLIBCXX_3.4) [ISOcxx]
```

basic_string<char, char_traits<char>, allocator<char>>::basic_string<char const*>(char const*, char const*, allocator<char> const&)(GLIBCXX_3.4) [ISOCXX]
basic_string<char, char_traits<char>, allocator<char>>::basic_string<char*>(char*, char*, allocator<char> const&)(GLIBCXX_3.4) [ISOCXX]
basic_string<char, char_traits<char>, allocator<char>>::basic_string(char const*, allocator<char> const&)(GLIBCXX_3.4) [ISOCXX]
basic_string<char, char_traits<char>, allocator<char>>::basic_string(allocator<char> const&)(GLIBCXX_3.4) [ISOCXX]
basic_string<char, char_traits<char>, allocator<char>>::basic_string(basic_string<char, char_traits<char>, allocator<char>> const&)(GLIBCXX_3.4) [ISOCXX]
basic_string<char, char_traits<char>, allocator<char>>::basic_string() (GLIBCXX_3.4) [ISOCXX]
basic_string<char, char_traits<char>, allocator<char>>::basic_string<char const*>(_gnu_cxx::__normal_iterator<char*, basic_string<char, char_traits<char>, allocator<char>> > >(_gnu_cxx::__normal_iterator<char*, basic_string<char, char_traits<char>, allocator<char>> > >, _gnu_cxx::__normal_iterator<char*, basic_string<char, char_traits<char>, allocator<char>> > >, allocator<char> const&)(GLIBCXX_3.4) [ISOCXX]
basic_string<char, char_traits<char>, allocator<char>>::basic_string<char const*>(char const*, char const*, allocator<char> const&)(GLIBCXX_3.4) [ISOCXX]
basic_string<char, char_traits<char>, allocator<char>>::basic_string<char*>(char*, char*, allocator<char> const&)(GLIBCXX_3.4) [ISOCXX]
basic_string<char, char_traits<char>, allocator<char>>::~basic_string() (GLIBCXX_3.4) [ISOCXX]
basic_string<char, char_traits<char>, allocator<char>>::~basic_string() (GLIBCXX_3.4) [ISOCXX]
basic_string<char, char_traits<char>, allocator<char>>::operator=(char const*)(GLIBCXX_3.4) [ISOCXXI]
basic_string<char, char_traits<char>, allocator<char>>::operator=(basic_string<char, char_traits<char>, allocator<char>> const&)(GLIBCXX_3.4) [ISOCXX]
basic_string<char, char_traits<char>, allocator<char>>::operator=(char)(GLIBCXX_3.4) [ISOCXX]
basic_string<char, char_traits<char>, allocator<char>>::operator+=(char const*)(GLIBCXX_3.4) [ISOCXXI]
basic_string<char, char_traits<char>, allocator<char>>::operator+=(basic_string<char, char_traits<char>, allocator<char>> const&)(GLIBCXX_3.4) [ISOCXX]
basic_string<char, char_traits<char>, allocator<char>>::operator+=(char)(GLIBCXX_3.4) [ISOCXX]

An LSB conforming implementation shall provide the generic data interfaces for

Class std::basic\_string<char, std::char\_traits<char>, std::allocator<char> > specified in [Table 9-154](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-154 libstdcxx - Class basic\_string<char, char\_traits<char>, allocator<char> > Data Interfaces**

basic_string<char, char_traits<char>, allocator<char> >::_Rep::S_max_size(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::_Rep::S_terminal(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::_Rep::S_empty_rep_storage(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<char, char_traits<char>, allocator<char> >::npos(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 9.1.59 Class basic\_string<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> >

### 9.1.59.1 Interfaces for Class basic\_string<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> >

An LSB conforming implementation shall provide the generic methods for Class std::basic\_string<wchar\_t, std::char\_traits<wchar\_t>, std::allocator<wchar\_t> > specified in [Table 9-155](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-155 libstdcxx - Class basic\_string<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> > Function Interfaces**

basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::_M_disjunct(wchar_t const*) const(GLIBCXX_3.4.5) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::get_allocator() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::end() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::_Rep::_M_is_leaked() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::_Rep::_M_is_shared() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::data() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::rend() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::size() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::begin() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::c_str() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::empty() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::_M_rep() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::length() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::rbegin() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::_M_data() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::_M_iend() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::compare(wchar_t const*) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::compare(basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> > const&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::capacity() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::max_size() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::_M_ibegin() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::_Alloc_hider::_Alloc_hider(wchar_t*, allocator<wchar_t> const&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::_Alloc_hider::_Alloc_hider(wchar_t*, allocator<wchar_t> const&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::_M_leak_hard()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::_S_empty_rep()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::_S_copy_chars(wchar_t*, __gnu_cxx::__normal_iterator<wchar_t const*, basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >,  __gnu_cxx::__normal_iterator<wchar_t const*, basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::_S_copy_chars(wchar_t*, __gnu_cxx::__normal_iterator<wchar_t*, basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >,  __gnu_cxx::__normal_iterator<wchar_t*, basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::_S_copy_chars(wchar_t*, wchar_t const*, wchar_t const*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>

>::_S_copy_chars(wchar_t*, wchar_t*, wchar_t*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::end() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::_Rep::_M_destroy(allocator<wchar_t> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::_Rep::_M_dispose(allocator<wchar_t> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::_Rep::_M_refcopy()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::_Rep::_M_refdata()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::_Rep::_S_empty_rep()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::_Rep::_M_set_leaked()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::_Rep::_M_set_sharable()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::_Rep::_M_grab(allocator<wchar_t> const&, allocator<wchar_t> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::rend() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::swap(basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::begin() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::clear() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::erase(__gnu_cxx::__normal_iterator<wchar_t*, basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>>)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::erase(__gnu_cxx::__normal_iterator<wchar_t*, basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>>, __gnu_cxx::__normal_iterator<wchar_t*, basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>>)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::append(wchar_t const*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::append(basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::assign(wchar_t const*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::assign(basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>> >







(GLIBCXX\_3.4) [\[ISO CXX\]](#)

An LSB conforming implementation shall provide the generic data interfaces for Class `std::basic_string<wchar_t, std::char_traits<wchar_t>, std::allocator<wchar_t> >` specified in [Table 9-156](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-156 libstdc++ - Class `basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >` Data Interfaces**

<code>basic_string&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt;::Rep::S_max_size(GLIBCXX_3.4)</code> <a href="#">[ISO CXX]</a>
<code>basic_string&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt;::Rep::S_terminal(GLIBCXX_3.4)</code> <a href="#">[ISO CXX]</a>
<code>basic_string&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt;::Rep::S_empty_rep_storage(GLIBCXX_3.4)</code> <a href="#">[ISO CXX]</a>
<code>basic_string&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt;::npos(GLIBCXX_3.4)</code> <a href="#">[ISO CXX]</a>

## 9.1.60 Class `basic_stringstream<char, char_traits<char>, allocator<char> >`

### 9.1.60.1 Class data for `basic_stringstream<char, char_traits<char>, allocator<char> >`

The virtual table for the `std::basic_stringstream<char, std::char_traits<char>, std::allocator<char> >` class is described in the relevant architecture specific part of this specification.

The VTT for the `std::basic_stringstream<char, std::char_traits<char>, std::allocator<char> >` class is described by [Table 9-157](#)

**Table 9-157 VTT for `basic_stringstream<char, char_traits<char>, allocator<char> >`**

VTT Name	<code>_ZTTSt18basic_stringstreamIcSt11char_traitsIcESaIcEE</code>
Number of Entries	10

### 9.1.60.2 Interfaces for Class `basic_stringstream<char, char_traits<char>, allocator<char> >`

An LSB conforming implementation shall provide the generic methods for Class `std::basic_stringstream<char, std::char_traits<char>, std::allocator<char> >` specified in [Table 9-158](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-158 libstdc++ - Class `basic_stringstream<char, char_traits<char>, allocator<char> >` Function Interfaces**

<code>basic_stringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt;::str() const(GLIBCXX_3.4)</code> <a href="#">[ISO CXX]</a>
<code>basic_stringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt;::rdbuf() const(GLIBCXX_3.4)</code> <a href="#">[ISO CXX]</a>

basic_stringstream<char, char_traits<char>, allocator<char>>::str(basic_string<char, char_traits<char>, allocator<char>> const&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringstream<char, char_traits<char>, allocator<char>>::basic_stringstream(basic_string<char, char_traits<char>, allocator<char>> const&, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringstream<char, char_traits<char>, allocator<char>>::basic_stringstream(_Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringstream<char, char_traits<char>, allocator<char>>::basic_stringstream(basic_string<char, char_traits<char>, allocator<char>> const&, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringstream<char, char_traits<char>, allocator<char>>::basic_stringstream(_Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringstream<char, char_traits<char>, allocator<char>>::~basic_stringstream()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringstream<char, char_traits<char>, allocator<char>>::~basic_stringstream()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringstream<char, char_traits<char>, allocator<char>>::~basic_stringstream()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class `std::basic_stringstream<char, std::char_traits<char>, std::allocator<char>>` specified in [Table 9-159](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-159 libstdcxx - Class `basic_stringstream<char, char_traits<char>, allocator<char>>` Data Interfaces**

typeinfo for basic_stringstream<char, char_traits<char>, allocator<char>>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for basic_stringstream<char, char_traits<char>, allocator<char>>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
VTT for basic_stringstream<char, char_traits<char>, allocator<char>>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for basic_stringstream<char, char_traits<char>, allocator<char>>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.61 Class `basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>`

### 9.1.61.1 Class data for `basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>`

The virtual table for the `std::basic_stringstream<wchar_t, std::char_traits<wchar_t>, std::allocator<wchar_t>>` class is described in the relevant architecture specific part of this specification.

The VTT for the `std::basic_stringstream<wchar_t, std::char_traits<wchar_t>, std::allocator<wchar_t>>` class is described by [Table 9-160](#)

**Table 9-160 VTT for `basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>`**

VTT Name	<code>_ZTTSt18basic_stringstreamIwSt11char_traitsIwESaIwEE</code>
Number of Entries	10

### **9.1.61.2 Interfaces for Class `basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>`**

An LSB conforming implementation shall provide the generic methods for Class `std::basic_stringstream<wchar_t, std::char_traits<wchar_t>, std::allocator<wchar_t> >` specified in [Table 9-161](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-161 libstdcxx - Class `basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>` Function Interfaces**

<code>basic_stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt;::str() const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt;::rdbuf() const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt;::str(basic_string&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt; const&amp;)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt;::basic_stringstream(basic_string&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt; const&amp;, _Ios_Openmode)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt;::basic_stringstream(_Ios_Openmode)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt;::basic_stringstream(basic_string&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt; const&amp;, _Ios_Openmode)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt;::basic_stringstream(_Ios_Openmode)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt;::~basic_stringstream()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt;::~basic_stringstream()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt;::~basic_stringstream()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class `std::basic_stringstream<wchar_t, std::char_traits<wchar_t>, std::allocator<wchar_t> >` specified in [Table 9-162](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-162 libstdcxx - Class `basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>` Data Interfaces**

<code>typeinfo for basic_stringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt;(GLIBCXX_3.4)</code> <a href="#">[CXABI]</a>
---

typeinfo name for basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
---

VTT for basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
---

vtable for basic_stringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
--

## 9.1.62 Class basic\_istringstream<char, char\_traits<char>, allocator<char> >

### 9.1.62.1 Class data for basic\_istringstream<char, char\_traits<char>, allocator<char> >

The virtual table for the std::basic\_istringstream<char, std::char\_traits<char>, std::allocator<char> > class is described in the relevant architecture specific part of this specification.

The VTT for the std::basic\_istringstream<char, std::char\_traits<char>, std::allocator<char> > class is described by [Table 9-163](#)

**Table 9-163 VTT for basic\_istringstream<char, char\_traits<char>, allocator<char> >**

VTT Name	_ZTTSt19basic_istringstreamIcSt11char_traitsIcESaIcEE
Number of Entries	4

### 9.1.62.2 Interfaces for Class basic\_istringstream<char, char\_traits<char>, allocator<char> >

An LSB conforming implementation shall provide the generic methods for Class std::basic\_istringstream<char, std::char\_traits<char>, std::allocator<char> > specified in [Table 9-164](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-164 libstdcxx - Class basic\_istringstream<char, char\_traits<char>, allocator<char> > Function Interfaces**

basic_istringstream<char, char_traits<char>, allocator<char> >::str() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
--

basic_istringstream<char, char_traits<char>, allocator<char> >::rdbuf() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
--

basic_istringstream<char, char_traits<char>, allocator<char> >::str(basic_string<char, char_traits<char>, allocator<char> > const&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
---

basic_istringstream<char, char_traits<char>, allocator<char> >::basic_istringstream(basic_string<char, char_traits<char>, allocator<char> > const&, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
--

basic_istringstream<char, char_traits<char>, allocator<char> >::basic_istringstream(_Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
--

basic_istringstream<char, char_traits<char>, allocator<char> >::basic_istringstream(basic_string<char, char_traits<char>, allocator<char> > const&, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
--

basic_istringstream<char, char_traits<char>, allocator<char>>::basic_istringstream(_Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_istringstream<char, char_traits<char>, allocator<char>>::~basic_istringstream()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_istringstream<char, char_traits<char>, allocator<char>>::~basic_istringstream()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_istringstream<char, char_traits<char>, allocator<char>>::~basic_istringstream()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::basic\_istringstream<char, std::char\_traits<char>, std::allocator<char>> specified in [Table 9-165](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-165 libstdc++ - Class basic\_istringstream<char, char\_traits<char>, allocator<char> > Data Interfaces**

typeinfo for basic_istringstream<char, char_traits<char>, allocator<char>>(GLIBCXX_3.4) <a href="#">[Cxxabi]</a>
typeinfo name for basic_istringstream<char, char_traits<char>, allocator<char>>(GLIBCXX_3.4) <a href="#">[Cxxabi]</a>
VTT for basic_istringstream<char, char_traits<char>, allocator<char>>(GLIBCXX_3.4) <a href="#">[Cxxabi]</a>
vtable for basic_istringstream<char, char_traits<char>, allocator<char>>(GLIBCXX_3.4) <a href="#">[Cxxabi]</a>

## 9.1.63 Class basic\_istringstream<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> >

### 9.1.63.1 Class data for basic\_istringstream<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> >

The virtual table for the std::basic\_istringstream<wchar\_t, std::char\_traits<wchar\_t>, std::allocator<wchar\_t>> class is described in the relevant architecture specific part of this specification.

The VTT for the std::basic\_istringstream<wchar\_t, std::char\_traits<wchar\_t>, std::allocator<wchar\_t>> class is described by [Table 9-166](#)

**Table 9-166 VTT for basic\_istringstream<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> >**

VTT Name	_ZTTSt19basic_istringstreamIwSt11char_traitsIwESaIwEE
Number of Entries	4

### 9.1.63.2 Interfaces for Class basic\_istringstream<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> >

An LSB conforming implementation shall provide the generic methods for Class std::basic\_istringstream<wchar\_t, std::char\_traits<wchar\_t>, std::allocator<wchar\_t>> specified in [Table 9-167](#) with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-167 libstdc++ - Class `basic_istringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>` Function Interfaces**

<code>basic_istringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::str() const(GLIBCXX_3.4) [ISOCXX]</code>
<code>basic_istringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::rdbuf() const(GLIBCXX_3.4) [ISOCXX]</code>
<code>basic_istringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::str(basic_string&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt; const&amp;)(GLIBCXX_3.4) [ISOCXX]</code>
<code>basic_istringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::basic_istringstream(basic_string&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt; const&amp;, _Ios_Openmode)(GLIBCXX_3.4) [ISOCXX]</code>
<code>basic_istringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::basic_istringstream(_Ios_Openmode)(GLIBCXX_3.4) [ISOCXX]</code>
<code>basic_istringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::basic_istringstream(basic_string&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt; const&amp;, _Ios_Openmode)(GLIBCXX_3.4) [ISOCXX]</code>
<code>basic_istringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::basic_istringstream(_Ios_Openmode)(GLIBCXX_3.4) [ISOCXX]</code>
<code>basic_istringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::~basic_istringstream()(GLIBCXX_3.4) [ISOCXX]</code>
<code>basic_istringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::~basic_istringstream()(GLIBCXX_3.4) [ISOCXX]</code>
<code>basic_istringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;::~basic_istringstream()(GLIBCXX_3.4) [ISOCXX]</code>

An LSB conforming implementation shall provide the generic data interfaces for Class `std::basic_istringstream<wchar_t, std::char_traits<wchar_t>, std::allocator<wchar_t>>` specified in [Table 9-168](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-168 libstdc++ - Class `basic_istringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>` Data Interfaces**

<code>typeinfo for basic_istringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;(GLIBCXX_3.4) [CXABI]</code>
<code>typeinfo name for basic_istringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;(GLIBCXX_3.4) [CXABI]</code>
<code>VTT for basic_istringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;(GLIBCXX_3.4) [CXABI]</code>
<code>vtable for basic_istringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;(GLIBCXX_3.4) [CXABI]</code>

## 9.1.64 Class `basic_ostringstream<char, char_traits<char>, allocator<char>`

### 9.1.64.1 Class data for `basic_ostringstream<char, char_traits<char>, allocator<char>`

The virtual table for the `std::basic_ostringstream<char, std::char_traits<char>, std::allocator<char>>`,

`std::allocator<char>` > class is described in the relevant architecture specific part of this specification.

The VTT for the `std::basic_ostringstream<char, std::char_traits<char>, std::allocator<char>` class is described by [Table 9-169](#)

**Table 9-169 VTT for `basic_ostringstream<char, char_traits<char>, allocator<char>` >**

VTT Name	<code>_ZTTSt19basic_ostringstreamIcSt11char_traitsIcESaIcEE</code>
Number of Entries	4

### **9.1.64.2 Interfaces for Class `basic_ostringstream<char, char_traits<char>, allocator<char>` >**

An LSB conforming implementation shall provide the generic methods for Class `std::basic_ostringstream<char, std::char_traits<char>, std::allocator<char>` > specified in [Table 9-170](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-170 libstdc++ - Class `basic_ostringstream<char, char_traits<char>, allocator<char>` > Function Interfaces**

<code>basic_ostringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >:: <code>str()</code> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_ostringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >:: <code>rdbuf()</code> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_ostringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >:: <code>str(basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> > const&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_ostringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >:: <code>basic_ostringstream(basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> > const&, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_ostringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >:: <code>basic_ostringstream(_Ios_Openmode)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_ostringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >:: <code>basic_ostringstream(basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> > const&, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_ostringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >:: <code>basic_ostringstream(_Ios_Openmode)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_ostringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >:: <code>~basic_ostringstream()</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_ostringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >:: <code>~basic_ostringstream()</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_ostringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >:: <code>~basic_ostringstream()</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class `std::basic_ostringstream<char, std::char_traits<char>, std::allocator<char>` > specified in [Table 9-171](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-171 libstdc++ - Class `basic_ostringstream<char, char_traits<char>, allocator<char>` > Data Interfaces**

typeinfo for <code>basic_ostringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for <code>basic_ostringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
VTT for <code>basic_ostringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for <code>basic_ostringstream&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;</code> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.65 Class `basic_ostringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>` >

### 9.1.65.1 Class data for `basic_ostringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>` >

The virtual table for the `std::basic_ostringstream<wchar_t, std::char_traits<wchar_t>, std::allocator<wchar_t>` class is described in the relevant architecture specific part of this specification.

The VTT for the `std::basic_ostringstream<wchar_t, std::char_traits<wchar_t>, std::allocator<wchar_t>` class is described by [Table 9-172](#)

**Table 9-172 VTT for `basic_ostringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>` >**

VTT Name	_ZTTSt19basic_ostringstreamIwSt11char_traitsIwESaIwEE
Number of Entries	4

### 9.1.65.2 Interfaces for Class `basic_ostringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>` >

An LSB conforming implementation shall provide the generic methods for Class `std::basic_ostringstream<wchar_t, std::char_traits<wchar_t>, std::allocator<wchar_t>` specified in [Table 9-173](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-173 libstdc++ - Class `basic_ostringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>` Function Interfaces**

<code>basic_ostringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;</code> >::str() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_ostringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;</code> >::rdbuf() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_ostringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;</code> >::str(basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>) const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_ostringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;</code> >::basic_ostringstream(basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>) const&, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_ostringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;</code>

>::basic_ostringstream(_Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_ostringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::basic_ostringstream(basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>> const&, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_ostringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::basic_ostringstream(_Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_ostringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::~basic_ostringstream()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_ostringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::~basic_ostringstream()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_ostringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::~basic_ostringstream()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class `std::basic_ostringstream<wchar_t, std::char_traits<wchar_t>, std::allocator<wchar_t>>` specified in [Table 9-174](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-174 libstdcxx - Class `basic_ostringstream<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>` Data Interfaces**

typeinfo for <code>basic_ostringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;</code> (GLIBCXX_3.4) <a href="#">[Cxxabi]</a>
typeinfo name for <code>basic_ostringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;</code> (GLIBCXX_3.4) <a href="#">[Cxxabi]</a>
VTT for <code>basic_ostringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;</code> (GLIBCXX_3.4) <a href="#">[Cxxabi]</a>
vtable for <code>basic_ostringstream&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;</code> (GLIBCXX_3.4) <a href="#">[Cxxabi]</a>

## 9.1.66 Class `basic_stringbuf<char, char_traits<char>, allocator<char>>`

### 9.1.66.1 Class data for `basic_stringbuf<char, char_traits<char>, allocator<char>>`

The virtual table for the `std::basic_stringbuf<char, std::char_traits<char>, std::allocator<char>>` class is described by [Table 9-175](#)

**Table 9-175 Primary vtable for `basic_stringbuf<char, char_traits<char>, allocator<char>>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>basic_stringbuf&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;</code>
vfunc[0]:	<code>basic_stringbuf&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;::~basic_stringbuf()</code>
vfunc[1]:	<code>basic_stringbuf&lt;char,</code>

	<code>char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;::~basic_stringbuf()</code>
vfunc[2]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt; &gt;::imbue(locale const&amp;)</code>
vfunc[3]:	See The Architecture Specific Specification
vfunc[4]:	See The Architecture Specific Specification
vfunc[5]:	<code>basic_stringbuf&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;::seekpos(fpos&lt;__mbstate_t&gt;, _Ios_Openmode)</code>
vfunc[6]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt; &gt;::sync()</code>
vfunc[7]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt; &gt;::showmanyc()</code>
vfunc[8]:	See The Architecture Specific Specification
vfunc[9]:	<code>basic_stringbuf&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;::underflow()</code>
vfunc[10]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt; &gt;::uflow()</code>
vfunc[11]:	<code>basic_stringbuf&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;::pbackfail(int)</code>
vfunc[12]:	See The Architecture Specific Specification
vfunc[13]:	<code>basic_stringbuf&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;::overflow(int)</code>

The Run Time Type Information for the `std::basic_stringbuf<char, std::char_traits<char>, std::allocator<char> >` class is described by [Table 9-176](#)

**Table 9-176 typeinfo for `basic_stringbuf<char, char_traits<char>, allocator<char> >`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>basic_stringbuf&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt;</code>

### 9.1.66.2 Interfaces for Class `basic_stringbuf<char, char_traits<char>, allocator<char> >`

An LSB conforming implementation shall provide the generic methods for Class `std::basic_stringbuf<char, std::char_traits<char>, std::allocator<char> >` speci-

fied in [Table 9-177](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-177 libstdcxx - Class basic\_stringbuf<char, char\_traits<char>, allocator<char> > Function Interfaces**

basic_stringbuf<char, char_traits<char>, allocator<char> >::str() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringbuf<char, char_traits<char>, allocator<char> >::_M_update_egptr()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringbuf<char, char_traits<char>, allocator<char> >::_M_stringbuf_init(_Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringbuf<char, char_traits<char>, allocator<char> >::str(basic_string<char, char_traits<char>, allocator<char> > const&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringbuf<char, char_traits<char>, allocator<char> >::seekpos(fpos<_mbstate_t>, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringbuf<char, char_traits<char>, allocator<char> >::overflow(int) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringbuf<char, char_traits<char>, allocator<char> >::pbackfail(int) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringbuf<char, char_traits<char>, allocator<char> >::showmanyc() (GLIBCXX_3.4.6) <a href="#">[ISOCXX]</a>
basic_stringbuf<char, char_traits<char>, allocator<char> >::underflow() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringbuf<char, char_traits<char>, allocator<char> >::basic_stringbuf(basic_string<char, char_traits<char>, allocator<char> > const&, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringbuf<char, char_traits<char>, allocator<char> >::basic_stringbuf(_Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringbuf<char, char_traits<char>, allocator<char> >::basic_stringbuf(basic_string<char, char_traits<char>, allocator<char> > const&, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringbuf<char, char_traits<char>, allocator<char> >::basic_stringbuf(_Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringbuf<char, char_traits<char>, allocator<char> >::~basic_stringbuf()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringbuf<char, char_traits<char>, allocator<char> >::~basic_stringbuf()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::basic\_stringbuf<char, std::char\_traits<char>, std::allocator<char> > specified in [Table 9-178](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-178 libstdcxx - Class basic\_stringbuf<char, char\_traits<char>, allocator<char> > Data Interfaces**

typeinfo for basic_stringbuf<char, char_traits<char>, allocator<char> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
---

typeinfo name for basic_stringbuf<char, char_traits<char>, allocator<char>>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
---

vtable for basic_stringbuf<char, char_traits<char>, allocator<char>>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
--

## 9.1.67 Class `basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >`

### 9.1.67.1 Class data for `basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >`

The virtual table for the `std::basic_stringbuf<wchar_t, std::char_traits<wchar_t>, std::allocator<wchar_t> >` class is described by [Table 9-179](#)

**Table 9-179 Primary vtable for `basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>basic_stringbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt;</code>
vfunc[0]:	<code>basic_stringbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt;::~basic_stringbuf()</code>
vfunc[1]:	<code>basic_stringbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt;::~basic_stringbuf()</code>
vfunc[2]:	<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::imbue(locale const&amp;)</code>
vfunc[3]:	See The Architecture Specific Specification
vfunc[4]:	See The Architecture Specific Specification
vfunc[5]:	<code>basic_stringbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt;::seekpos(fpos&lt;__mbstate_t&gt;, _Ios_Openmode)</code>
vfunc[6]:	<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::sync()</code>
vfunc[7]:	<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::showmanyc()</code>

vfunc[8]:	See The Architecture Specific Specification
vfunc[9]:	basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::underflow()
vfunc[10]:	basic_streambuf<wchar_t, char_traits<wchar_t>>::uflow()
vfunc[11]:	basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::pbackfail(unsigned int)
vfunc[12]:	See The Architecture Specific Specification
vfunc[13]:	basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::overflow(unsigned int)

The Run Time Type Information for the std::basic\_stringbuf<wchar\_t, std::char\_traits<wchar\_t>, std::allocator<wchar\_t> > class is described by [Table 9-180](#)

**Table 9-180 typeinfo for basic\_stringbuf<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> >**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >

### 9.1.67.2 Interfaces for Class basic\_stringbuf<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> >

An LSB conforming implementation shall provide the generic methods for Class std::basic\_stringbuf<wchar\_t, std::char\_traits<wchar\_t>, std::allocator<wchar\_t> > specified in [Table 9-181](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-181 libstdcxx - Class basic\_stringbuf<wchar\_t, char\_traits<wchar\_t>, allocator<wchar\_t> > Function Interfaces**

basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::str() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::_M_update_egptr()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::_M_stringbuf_init(_Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t> >::str(basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::seekpos(fpos<_mbstate_t>, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::overflow(unsigned int)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::pbackfail(unsigned int)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::showmany(c)(GLIBCXX_3.4.6) <a href="#">[ISOCXX]</a>
basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::underflow()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::basic_stringbuf(basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>> const&, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::basic_stringbuf(_Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::basic_stringbuf(basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t>> const&, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::basic_stringbuf(_Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::~basic_stringbuf()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>::~basic_stringbuf()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class `std::basic_stringbuf<wchar_t, std::char_traits<wchar_t>, std::allocator<wchar_t>>` specified in [Table 9-182](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-182 libstdcxx - Class `basic_stringbuf<wchar_t, char_traits<wchar_t>, allocator<wchar_t>>` Data Interfaces**

typeinfo for <code>basic_stringbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;</code> (GLIBCXX_3.4) <a href="#">[CXABI]</a>
typeinfo name for <code>basic_stringbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;</code> (GLIBCXX_3.4) <a href="#">[CXABI]</a>
vtable for <code>basic_stringbuf&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt;&gt;</code> (GLIBCXX_3.4) <a href="#">[CXABI]</a>

## 9.1.68 Class `basic_iostream<char, char_traits<char>>`

>

### 9.1.68.1 Class data for `basic_iostream<char, char_traits<char>>`

The virtual table for the `std::basic_iostream<char, std::char_traits<char>>` class is described in the relevant architecture specific part of this specification.

The VTT for the `std::basic_iostream<char, std::char_traits<char>>` class is described by [Table 9-183](#)

**Table 9-183 VTT for basic\_iostream<char, char\_traits<char> >**

VTT Name	_ZTTSd
Number of Entries	7

### 9.1.68.2 Interfaces for Class basic\_iostream<char, char\_traits<char> >

An LSB conforming implementation shall provide the generic methods for Class std::basic\_iostream<char, std::char\_traits<char> > specified in [Table 9-184](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-184 libstdcxx - Class basic\_iostream<char, char\_traits<char> > Function Interfaces**

basic_iostream<char, char_traits<char> >::basic_iostream(basic_streambuf<char, char_traits<char> >*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_iostream<char, char_traits<char> >::basic_iostream()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_iostream<char, char_traits<char> >::basic_iostream(basic_streambuf<char, char_traits<char> >*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_iostream<char, char_traits<char> >::basic_iostream()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_iostream<char, char_traits<char> >::~basic_iostream()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_iostream<char, char_traits<char> >::~basic_iostream()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >& operator><(char_traits<char> >)(basic_istream<char, char_traits<char> >&, signed char*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::basic\_iostream<char, std::char\_traits<char> > specified in [Table 9-185](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-185 libstdcxx - Class basic\_iostream<char, char\_traits<char> > Data Interfaces**

typeinfo for basic_iostream<char, char_traits<char> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for basic_iostream<char, char_traits<char> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
VTT for basic_iostream<char, char_traits<char> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for basic_iostream<char, char_traits<char> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.69 Class `basic_iostream<wchar_t, char_traits<wchar_t>>`

### 9.1.69.1 Class data for `basic_iostream<wchar_t, char_traits<wchar_t>>`

The virtual table for the `std::basic_iostream<wchar_t, std::char_traits<wchar_t>>` class is described in the relevant architecture specific part of this specification.

The VTT for the `std::basic_iostream<wchar_t, std::char_traits<wchar_t>>` class is described by [Table 9-186](#)

**Table 9-186 VTT for `basic_iostream<wchar_t, char_traits<wchar_t>>`**

VTT Name	<code>_ZTTSt14basic_iostreamIwSt11char_traitsIwEE</code>
Number of Entries	7

### 9.1.69.2 Interfaces for Class `basic_iostream<wchar_t, char_traits<wchar_t>>`

An LSB conforming implementation shall provide the generic methods for Class `std::basic_iostream<wchar_t, std::char_traits<wchar_t>>` specified in [Table 9-187](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-187 libstdcxx - Class `basic_iostream<wchar_t, char_traits<wchar_t>>` Function Interfaces**

<code>basic_iostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::basic_iostream(basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;*)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_iostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::basic_iostream()</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_iostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::basic_iostream(basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;*)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_iostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::basic_iostream()</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_iostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_iostream()</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_iostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_iostream()</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_iostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_iostream()</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class `std::basic_iostream<wchar_t, std::char_traits<wchar_t>>` specified in [Table 9-188](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-188 libstdc++ - Class `basic_ostream<wchar_t, char_traits<wchar_t>` > Data Interfaces**

typeinfo for <code>basic_ostream&lt;wchar_t, char_traits&lt;wchar_t&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for <code>basic_ostream&lt;wchar_t, char_traits&lt;wchar_t&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
VTT for <code>basic_ostream&lt;wchar_t, char_traits&lt;wchar_t&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for <code>basic_ostream&lt;wchar_t, char_traits&lt;wchar_t&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.70 Class `basic_istream<char, char_traits<char>` >

### 9.1.70.1 Class data for `basic_istream<char, char_traits<char>` >

The virtual table for the `std::basic_istream<char, std::char_traits<char>` class is described in the relevant architecture specific part of this specification.

The VTT for the `std::basic_istream<char, std::char_traits<char>` class is described by [Table 9-189](#)

**Table 9-189 VTT for `basic_istream<char, char_traits<char>` >**

VTT Name	_ZTTSi
Number of Entries	2

### 9.1.70.2 Interfaces for Class `basic_istream<char, char_traits<char>` >

An LSB conforming implementation shall provide the generic methods for Class `std::basic_istream<char, std::char_traits<char>` specified in [Table 9-190](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-190 libstdc++ - Class `basic_istream<char, char_traits<char>` > Function Interfaces**

<code>basic_istream&lt;char, char_traits&lt;char&gt;</code> :: <code>gcount()</code> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_istream&lt;char, char_traits&lt;char&gt;</code> :: <code>sentry::operator bool()</code> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_istream&lt;char, char_traits&lt;char&gt;</code> :: <code>get(basic_streambuf&lt;char, char_traits&lt;char&gt; &amp;)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_istream&lt;char, char_traits&lt;char&gt;</code> :: <code>get(basic_streambuf&lt;char, char_traits&lt;char&gt; &amp;, char)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_istream&lt;char, char_traits&lt;char&gt;</code> :: <code>get(char &amp;)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_istream&lt;char, char_traits&lt;char&gt;</code> :: <code>get()</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_istream&lt;char, char_traits&lt;char&gt;</code> :: <code>peek()</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_istream&lt;char, char_traits&lt;char&gt;</code> :: <code>sync()</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_istream&lt;char, char_traits&lt;char&gt;</code> :: <code>seekg(fpos&lt;__mbstate_t&gt;)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

basic_istream<char, char_traits<char> >::tellg()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >::unget()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >::ignore()(GLIBCXX_3.4.5) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >::sentry::sentry(basic_istream<char, char_traits<char> >&, bool)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >::sentry::sentry(basic_istream<char, char_traits<char> >&, bool)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >::putback(char)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >::basic_istream(basic_streambuf<char, char_traits<char> >*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >::basic_istream()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >::basic_istream(basic_streambuf<char, char_traits<char> >*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >::basic_istream()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >::~basic_istream()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >::~basic_istream()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >::operator>>(basic_istream<char, char_traits<char> >& (*)(basic_istream<char, char_traits<char> >&)) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >::operator>>(ios_base& (*)(ios_base&))(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >::operator>>(basic_ios<char, char_traits<char> >& (*)(basic_ios<char, char_traits<char> >&)) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >::operator>>(basic_streambuf<char, char_traits<char> >*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >::operator>>(void*&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >::operator>>(bool&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >::operator>>(double&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >::operator>>(long double&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >::operator>>(float&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >::operator>>(int&)(GLIBCXX_3.4)

[\[ISOCXX\]](#)

basic\_istream<char, char\_traits<char> >::operator>>(unsigned int&)(GLIBCXX\_3.4) [\[ISOCXX\]](#)

basic\_istream<char, char\_traits<char> >::operator>>(long&)(GLIBCXX\_3.4) [\[ISOCXX\]](#)

basic\_istream<char, char\_traits<char> >::operator>>(unsigned long&)(GLIBCXX\_3.4) [\[ISOCXX\]](#)

basic\_istream<char, char\_traits<char> >::operator>>(short&)(GLIBCXX\_3.4) [\[ISOCXX\]](#)

basic\_istream<char, char\_traits<char> >::operator>>(unsigned short&)(GLIBCXX\_3.4) [\[ISOCXX\]](#)

basic\_istream<char, char\_traits<char> >::operator>>(long long&)(GLIBCXX\_3.4) [\[ISOCXX\]](#)

basic\_istream<char, char\_traits<char> >::operator>>(unsigned long long&)(GLIBCXX\_3.4) [\[ISOCXX\]](#)

basic\_istream<char, char\_traits<char> >& ws<char, char\_traits<char> >(basic\_istream<char, char\_traits<char> >&)(GLIBCXX\_3.4) [\[ISOCXX\]](#)

basic\_istream<char, char\_traits<char> >& getline<char, char\_traits<char> , allocator<char> >(basic\_istream<char, char\_traits<char> >&, basic\_string<char, char\_traits<char> , allocator<char> >&)(GLIBCXX\_3.4) [\[ISOCXX\]](#)

basic\_istream<char, char\_traits<char> >& getline<char, char\_traits<char> , allocator<char> >(basic\_istream<char, char\_traits<char> >&, basic\_string<char, char\_traits<char> , allocator<char> >&, char)(GLIBCXX\_3.4) [\[ISOCXX\]](#)

basic\_istream<char, char\_traits<char> >& operator>><char\_traits<char> >(basic\_istream<char, char\_traits<char> >&, unsigned char\*)(GLIBCXX\_3.4) [\[ISOCXX\]](#)

basic\_istream<char, char\_traits<char> >& operator>><char\_traits<char> >(basic\_istream<char, char\_traits<char> >&, signed char&)(GLIBCXX\_3.4) [\[ISOCXX\]](#)

basic\_istream<char, char\_traits<char> >& operator>><char\_traits<char> >(basic\_istream<char, char\_traits<char> >&, unsigned char&)(GLIBCXX\_3.4) [\[ISOCXX\]](#)

basic\_istream<char, char\_traits<char> >& operator>><char, char\_traits<char> >(basic\_istream<char, char\_traits<char> >&, char\*)(GLIBCXX\_3.4) [\[ISOCXX\]](#)

basic\_istream<char, char\_traits<char> >& operator>><char, char\_traits<char> >(basic\_istream<char, char\_traits<char> >&, char&)(GLIBCXX\_3.4) [\[ISOCXX\]](#)

basic\_istream<char, char\_traits<char> >& operator>><char, char\_traits<char> >(basic\_istream<char, char\_traits<char> >&, \_Setiosflags)(GLIBCXX\_3.4) [\[ISOCXX\]](#)

basic\_istream<char, char\_traits<char> >& operator>><char, char\_traits<char> >(basic\_istream<char, char\_traits<char> >&, \_Setprecision)(GLIBCXX\_3.4) [\[ISOCXX\]](#)

basic\_istream<char, char\_traits<char> >& operator>><char,

char_traits<char> >(basic_istream<char, char_traits<char> >&, _Resetiosflags)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >& operator>><char, char_traits<char> >(basic_istream<char, char_traits<char> >&, _Setw)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >& operator>><char, char_traits<char> >(basic_istream<char, char_traits<char> >&, _Setbase)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >& operator>><char, char_traits<char> >(basic_istream<char, char_traits<char> >&, _Setfill<char>)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >& operator>><char, char_traits<char>, allocator<char> >(basic_istream<char, char_traits<char> >&, basic_string<char, char_traits<char>, allocator<char> >&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >& operator>><double, char, char_traits<char> >(basic_istream<char, char_traits<char> >&, complex<double>&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >& operator>><long double, char, char_traits<char> >(basic_istream<char, char_traits<char> >&, complex<long double>&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<char, char_traits<char> >& operator>><float, char, char_traits<char> >(basic_istream<char, char_traits<char> >&, complex<float>&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::basic\_istream<char, std::char\_traits<char> > specified in [Table 9-191](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-191 libstdc++ - Class basic\_istream<char, char\_traits<char> > Data Interfaces**

typeinfo for basic_istream<char, char_traits<char> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for basic_istream<char, char_traits<char> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
VTT for basic_istream<char, char_traits<char> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for basic_istream<char, char_traits<char> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.71 Class basic\_istream<wchar\_t, char\_traits<wchar\_t> >

### 9.1.71.1 Class data for basic\_istream<wchar\_t, char\_traits<wchar\_t> >

The virtual table for the std::basic\_istream<wchar\_t, std::char\_traits<wchar\_t> > class is described in the relevant architecture specific part of this specification.

The VTT for the std::basic\_istream<wchar\_t, std::char\_traits<wchar\_t> > class is described by [Table 9-192](#)

**Table 9-192 VTT for basic\_istream<wchar\_t, char\_traits<wchar\_t> >**

VTT Name	_ZTTSt13basic_istreamIwSt11char_traitsIwEE
Number of Entries	2

### 9.1.71.2 Interfaces for Class basic\_istream<wchar\_t, char\_traits<wchar\_t> >

An LSB conforming implementation shall provide the generic methods for Class std::basic\_istream<wchar\_t, std::char\_traits<wchar\_t> > specified in [Table 9-193](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-193 libstdcxx - Class basic\_istream<wchar\_t, char\_traits<wchar\_t> > Function Interfaces**

basic_istream<wchar_t, char_traits<wchar_t> >::gcount() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t> >::sentry::operator bool() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t> >::get(basic_streampbuf<wchar_t, char_traits<wchar_t> >&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t> >::get(basic_streampbuf<wchar_t, char_traits<wchar_t> >&, wchar_t) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t> >::get(wchar_t&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t> >::get()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t> >::peek()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t> >::sync()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t> >::seekg(fpos<__mbstate_t>) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t> >::tellg()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t> >::unget()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t> >::ignore()(GLIBCXX_3.4.5) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t> >::sentry::sentry(basic_istream<wchar_t, char_traits<wchar_t> >&, bool) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t> >::sentry::sentry(basic_istream<wchar_t, char_traits<wchar_t> >&, bool) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t> >::putback(wchar_t)

(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t>>::basic_istream(basic_streambuf<wchar_t, char_traits<wchar_t>>*) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t>>::basic_istream(basic_streambuf<wchar_t, char_traits<wchar_t>>*) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t>>::~basic_istream() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t>>::~basic_istream() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t>>::~basic_istream() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t>>::operator>>(basic_istream<wchar_t, char_traits<wchar_t>>& (*)(basic_istream<wchar_t, char_traits<wchar_t>>&))(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t>>::operator>>(ios_base& (*)(ios_base&))(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t>>::operator>>(basic_ios<wchar_t, char_traits<wchar_t>>& (*)(basic_ios<wchar_t, char_traits<wchar_t>>&))(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t>>::operator>>(basic_streambuf<wchar_t, char_traits<wchar_t>>*) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t>>::operator>>(void*&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t>>::operator>>(bool&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t>>::operator>>(double&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t>>::operator>>(long double&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t>>::operator>>(float&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t>>::operator>>(int&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t>>::operator>>(unsigned int&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t>>::operator>>(long&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t>>::operator>>(unsigned long&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t>>::operator>>(short&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t>>::operator>>(unsigned short&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>



<code>_Setfill&lt;wchar_t&gt;)(GLIBCXX_3.4) [ISOcxx]</code>
---

<code>basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;&amp; operator&gt;&gt;&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt;(basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;&amp;, basic_string&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &amp;)(GLIBCXX_3.4) [ISOcxx]</code>
---

An LSB conforming implementation shall provide the generic data interfaces for Class `std::basic_istream<wchar_t, std::char_traits<wchar_t> >` specified in [Table 9-194](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-194 libstdc++ - Class `basic_istream<wchar_t, char_traits<wchar_t> >` Data Interfaces**

<code>typeinfo for basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;(GLIBCXX_3.4) [Cxxabi]</code>
---

<code>typeinfo name for basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;(GLIBCXX_3.4) [Cxxabi]</code>
--

<code>VTT for basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;(GLIBCXX_3.4) [Cxxabi]</code>
--

<code>vtable for basic_istream&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;(GLIBCXX_3.4) [Cxxabi]</code>
---

## 9.1.72 Class `istreambuf_iterator<wchar_t, char_traits<wchar_t> >`

### 9.1.72.1 Interfaces for Class `istreambuf_iterator<wchar_t, char_traits<wchar_t> >`

An LSB conforming implementation shall provide the generic methods for Class `std::istreambuf_iterator<wchar_t, std::char_traits<wchar_t> >` specified in [Table 9-195](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-195 libstdc++ - Class `istreambuf_iterator<wchar_t, char_traits<wchar_t> >` Function Interfaces**

<code>istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::operator++()</code> (GLIBCXX_3.4.5) [ISOcxx]
--

## 9.1.73 Class `istreambuf_iterator<char, char_traits<char> >`

### 9.1.73.1 Interfaces for Class `istreambuf_iterator<char, char_traits<char> >`

An LSB conforming implementation shall provide the generic methods for Class `std::istreambuf_iterator<char, std::char_traits<char> >` specified in [Table 9-196](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-196 libstdc++ - Class istreambuf\_iterator<char, char\_traits<char> > Function Interfaces**

istreambuf_iterator<char, char_traits<char> >::operator++()(GLIBCXX_3.4.5) <a href="#">[ISOcxx]</a>
--

## 9.1.74 Class basic\_ostream<char, char\_traits<char> >

### 9.1.74.1 Class data for basic\_ostream<char, char\_traits<char> >

The virtual table for the std::basic\_ostream<char, std::char\_traits<char> > class is described in the relevant architecture specific part of this specification.

The VTT for the std::basic\_ostream<char, std::char\_traits<char> > class is described by [Table 9-197](#)

**Table 9-197 VTT for basic\_ostream<char, char\_traits<char> >**

VTT Name	ZTTSO
Number of Entries	2

### 9.1.74.2 Interfaces for Class basic\_ostream<char, char\_traits<char> >

An LSB conforming implementation shall provide the generic methods for Class std::basic\_ostream<char, std::char\_traits<char> > specified in [Table 9-198](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-198 libstdc++ - Class basic\_ostream<char, char\_traits<char> > Function Interfaces**

basic_ostream<char, char_traits<char> >::sentry::operator bool() const(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_ostream<char, char_traits<char> >::put(char)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_ostream<char, char_traits<char> >::flush()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_ostream<char, char_traits<char> >::seekp(fpos<__mbstate_t>) (GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_ostream<char, char_traits<char> >::tellp()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_ostream<char, char_traits<char> >::sentry::sentry(basic_ostream<char, char_traits<char> >&)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_ostream<char, char_traits<char> >::sentry::sentry(basic_ostream<char, char_traits<char> >&)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_ostream<char, char_traits<char> >::sentry::~sentry()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_ostream<char, char_traits<char> >::sentry::~sentry()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_ostream<char, char_traits<char> >::basic_ostream(basic_streambuf<char, char_traits<char> >*)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_ostream<char, char_traits<char> >::basic_ostream()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>

basic_ostream<char, char_traits<char>>::basic_ostream(basic_streambuf<char, char_traits<char>>*)(GLIBCXX_3.4) [ISOCXX]
basic_ostream<char, char_traits<char>>::basic_ostream()(GLIBCXX_3.4) [ISOCXX]
basic_ostream<char, char_traits<char>>::~basic_ostream()(GLIBCXX_3.4) [ISOCXX]
basic_ostream<char, char_traits<char>>::~basic_ostream()(GLIBCXX_3.4) [ISOCXX]
basic_ostream<char, char_traits<char>>::~basic_ostream()(GLIBCXX_3.4) [ISOCXX]
basic_ostream<char, char_traits<char>>::operator<<(basic_ostream<char, char_traits<char>>& (*)(basic_ostream<char, char_traits<char>>&)) (GLIBCXX_3.4) [ISOCXX]
basic_ostream<char, char_traits<char>>::operator<<(ios_base& (*)(ios_base&))(GLIBCXX_3.4) [ISOCXX]
basic_ostream<char, char_traits<char>>::operator<<(basic_ios<char, char_traits<char>>& (*)(basic_ios<char, char_traits<char>>&)) (GLIBCXX_3.4) [ISOCXX]
basic_ostream<char, char_traits<char>>::operator<<(void const*)(GLIBCXX_3.4) [ISOCXX]
basic_ostream<char, char_traits<char>>::operator<<(basic_streambuf<char, char_traits<char>>*)(GLIBCXX_3.4) [ISOCXX]
basic_ostream<char, char_traits<char>>::operator<<(bool)(GLIBCXX_3.4) [ISOCXX]
basic_ostream<char, char_traits<char>>::operator<<(double)(GLIBCXX_3.4) [ISOCXX]
basic_ostream<char, char_traits<char>>::operator<<(long double)(GLIBCXX_3.4) [ISOCXX]
basic_ostream<char, char_traits<char>>::operator<<(float)(GLIBCXX_3.4) [ISOCXX]
basic_ostream<char, char_traits<char>>::operator<<(int)(GLIBCXX_3.4) [ISOCXX]
basic_ostream<char, char_traits<char>>::operator<<(unsigned int)(GLIBCXX_3.4) [ISOCXX]
basic_ostream<char, char_traits<char>>::operator<<(long)(GLIBCXX_3.4) [ISOCXX]
basic_ostream<char, char_traits<char>>::operator<<(unsigned long)(GLIBCXX_3.4) [ISOCXX]
basic_ostream<char, char_traits<char>>::operator<<(short)(GLIBCXX_3.4) [ISOCXX]
basic_ostream<char, char_traits<char>>::operator<<(unsigned short)(GLIBCXX_3.4) [ISOCXX]
basic_ostream<char, char_traits<char>>::operator<<(long long)(GLIBCXX_3.4) [ISOCXX]
basic_ostream<char, char_traits<char>>::operator<<(unsigned long long)



char_traits<char> >(basic_ostream<char, char_traits<char> >&, complex<double> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<char, char_traits<char> >& operator<< <long double, char, char_traits<char> >(basic_ostream<char, char_traits<char> >&, complex<long double> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<char, char_traits<char> >& operator<< <float, char, char_traits<char> >(basic_ostream<char, char_traits<char> >&, complex<float> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::basic\_ostream<char, std::char\_traits<char> > specified in [Table 9-199](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-199 libstdcxx - Class basic\_ostream<char, char\_traits<char> > Data Interfaces**

typeinfo for basic_ostream<char, char_traits<char> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for basic_ostream<char, char_traits<char> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
VTT for basic_ostream<char, char_traits<char> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for basic_ostream<char, char_traits<char> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.75 Class basic\_ostream<wchar\_t, char\_traits<wchar\_t> >

### 9.1.75.1 Class data for basic\_ostream<wchar\_t, char\_traits<wchar\_t> >

The virtual table for the std::basic\_ostream<wchar\_t, std::char\_traits<wchar\_t> > class is described in the relevant architecture specific part of this specification.

The VTT for the std::basic\_ostream<wchar\_t, std::char\_traits<wchar\_t> > class is described by [Table 9-200](#)

**Table 9-200 VTT for basic\_ostream<wchar\_t, char\_traits<wchar\_t> >**

VTT Name	_ZTTSt13basic_ostreamIwSt11char_traitsIwEE
Number of Entries	2

### 9.1.75.2 Interfaces for Class basic\_ostream<wchar\_t, char\_traits<wchar\_t> >

An LSB conforming implementation shall provide the generic methods for Class std::basic\_ostream<wchar\_t, std::char\_traits<wchar\_t> > specified in [Table 9-201](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-201 libstdcxx - Class basic\_ostream<wchar\_t, char\_traits<wchar\_t> > Function Interfaces**

basic_ostream<wchar_t, char_traits<wchar_t> >::sentry::operator bool()
--

const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::put(wchar_t) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::flush()(GLIBCXX_3.4) [ISOCXX]
basic_ostream<wchar_t, char_traits<wchar_t>>::seekp(fpos<__mbstate_t>) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::tellp()(GLIBCXX_3.4) [ISOCXX]
basic_ostream<wchar_t, char_traits<wchar_t>>::sentry::sentry(basic_ostream<wchar_t, char_traits<wchar_t>>&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::sentry::sentry(basic_ostream<wchar_t, char_traits<wchar_t>>&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::sentry::~sentry() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::sentry::~sentry() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::basic_ostream(basic_streampbuf<wchar_t, char_traits<wchar_t>>*) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::basic_ostream(basic_streampbuf<wchar_t, char_traits<wchar_t>>*) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::~basic_ostream() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::~basic_ostream() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::~basic_ostream() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::operator<<(basic_ostream<wchar_t, char_traits<wchar_t>>& (*)) (basic_ostream<wchar_t, char_traits<wchar_t>>&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::operator<<(ios_base& (*)) (ios_base&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::operator<<(basic_ios<wchar_t, char_traits<wchar_t>>& (*)) (basic_ios<wchar_t, char_traits<wchar_t>>&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::operator<<(void const*)><> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::operator<<(basic_streampbuf<wchar_t, char_traits<wchar_t>>*) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::operator<<(bool)

(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::operator<<(double) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::operator<<(long double) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::operator<<(float) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::operator<<(int) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::operator<<(unsigned int) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::operator<<(long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::operator<<(unsigned long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::operator<<(short) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::operator<<(unsigned short) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::operator<<(long long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::operator<<(unsigned long long) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>& endl<wchar_t, char_traits<wchar_t>>(basic_ostream<wchar_t, char_traits<wchar_t>>&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>& ends<wchar_t, char_traits<wchar_t>>(basic_ostream<wchar_t, char_traits<wchar_t>>&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>& flush<wchar_t, char_traits<wchar_t>>(basic_ostream<wchar_t, char_traits<wchar_t>>&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>& operator<<<double, wchar_t, char_traits<wchar_t>>(basic_ostream<wchar_t, char_traits<wchar_t>>&, complex<double> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>& operator<<<long double, wchar_t, char_traits<wchar_t>>(basic_ostream<wchar_t, char_traits<wchar_t>>&, complex<long double> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>& operator<<<float, wchar_t, char_traits<wchar_t>>(basic_ostream<wchar_t, char_traits<wchar_t>>&, complex<float> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>& operator<<<wchar_t, char_traits<wchar_t>>(basic_ostream<wchar_t, char_traits<wchar_t>>&, wchar_t const*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

basic_ostream<wchar_t, char_traits<wchar_t>>& operator<< <wchar_t, char_traits<wchar_t>>(basic_ostream<wchar_t, char_traits<wchar_t>>&, char const*)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>& operator<< <wchar_t, char_traits<wchar_t>>(basic_ostream<wchar_t, char_traits<wchar_t>>&, wchar_t)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>& operator<< <wchar_t, char_traits<wchar_t>>(basic_ostream<wchar_t, char_traits<wchar_t>>&, _Setiosflags)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>& operator<< <wchar_t, char_traits<wchar_t>>(basic_ostream<wchar_t, char_traits<wchar_t>>&, _Setprecision)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>& operator<< <wchar_t, char_traits<wchar_t>>(basic_ostream<wchar_t, char_traits<wchar_t>>&, _Resetiosflags)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>& operator<< <wchar_t, char_traits<wchar_t>>(basic_ostream<wchar_t, char_traits<wchar_t>>&, _Resetw)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>& operator<< <wchar_t, char_traits<wchar_t>>(basic_ostream<wchar_t, char_traits<wchar_t>>&, _Setbase)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>& operator<< <wchar_t, char_traits<wchar_t>>(basic_ostream<wchar_t, char_traits<wchar_t>>&, _Setfill<wchar_t>)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>& operator<< <wchar_t, char_traits<wchar_t>>(basic_ostream<wchar_t, char_traits<wchar_t>>&, char)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>& operator<< <wchar_t, char_traits<wchar_t>, allocator<wchar_t>>(basic_ostream<wchar_t, char_traits<wchar_t>>&, basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> > const&)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class `std::basic_ostream<wchar_t, std::char_traits<wchar_t>>` specified in [Table 9-202](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-202 libstdcxx - Class `basic_ostream<wchar_t, char_traits<wchar_t>>` Data Interfaces**

typeinfo for <code>basic_ostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for <code>basic_ostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
VTT for <code>basic_ostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for <code>basic_ostream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.76 Class `basic_fstream<char, char_traits<char>>`

### 9.1.76.1 Class data for `basic_fstream<char, char_traits<char>>`

The virtual table for the `std::basic_fstream<char, std::char_traits<char>>` class is described in the relevant architecture specific part of this specification.

The VTT for the `std::basic_fstream<char, std::char_traits<char>>` class is described by [Table 9-203](#)

**Table 9-203 VTT for `basic_fstream<char, char_traits<char>>`**

VTT Name	<code>_ZTTSt13basic_fstreamIcSt11char_traitsIcEE</code>
Number of Entries	10

### 9.1.76.2 Interfaces for Class `basic_fstream<char, char_traits<char>>`

>

An LSB conforming implementation shall provide the generic methods for Class `std::basic_fstream<char, std::char_traits<char>>` specified in [Table 9-204](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-204 libstdcxx - Class `basic_fstream<char, char_traits<char>>` Function Interfaces**

<code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;::rdbuf() const(GLIBCXX_3.4) [ISOcxx]</code>
<code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;::is_open() const(GLIBCXX_3.4.5) [ISOcxx]</code>
<code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;::open(char const*, _Ios_Openmode) (GLIBCXX_3.4) [ISOcxx]</code>
<code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;::close()(GLIBCXX_3.4) [ISOcxx]</code>
<code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;::is_open()(GLIBCXX_3.4) [ISOcxx]</code>
<code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;::basic_fstream(char const*, _Ios_Openmode)(GLIBCXX_3.4) [ISOcxx]</code>
<code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;::basic_fstream()(GLIBCXX_3.4) [ISOcxx]</code>
<code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;::basic_fstream(char const*, _Ios_Openmode)(GLIBCXX_3.4) [ISOcxx]</code>
<code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;::basic_fstream()(GLIBCXX_3.4) [ISOcxx]</code>
<code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;::~basic_fstream()(GLIBCXX_3.4) [ISOcxx]</code>
<code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;::~basic_fstream()(GLIBCXX_3.4) [ISOcxx]</code>
<code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;::~basic_fstream()(GLIBCXX_3.4) [ISOcxx]</code>

An LSB conforming implementation shall provide the generic data interfaces for Class `std::basic_fstream<char, std::char_traits<char>>` specified in [Table 9-205](#),

with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-205 libstdcxx - Class `basic_fstream<char, char_traits<char>>` Data Interfaces**

typeinfo for <code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for <code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
VTT for <code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for <code>basic_fstream&lt;char, char_traits&lt;char&gt;&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.77 Class `basic_fstream<wchar_t, char_traits<wchar_t>>`

### 9.1.77.1 Class data for `basic_fstream<wchar_t, char_traits<wchar_t>>`

The virtual table for the `std::basic_fstream<wchar_t, std::char_traits<wchar_t>>` class is described in the relevant architecture specific part of this specification.

The VTT for the `std::basic_fstream<wchar_t, std::char_traits<wchar_t>>` class is described by [Table 9-206](#)

**Table 9-206 VTT for `basic_fstream<wchar_t, char_traits<wchar_t>>`**

VTT Name	_ZTTSt13basic_fstreamIwSt11char_traitsIwEE
Number of Entries	10

### 9.1.77.2 Interfaces for Class `basic_fstream<wchar_t, char_traits<wchar_t>>`

An LSB conforming implementation shall provide the generic methods for Class `std::basic_fstream<wchar_t, std::char_traits<wchar_t>>` specified in [Table 9-207](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-207 libstdcxx - Class `basic_fstream<wchar_t, char_traits<wchar_t>>` Function Interfaces**

<code>basic_fstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::rdbuf()</code> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_fstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::is_open()</code> const(GLIBCXX_3.4.5) <a href="#">[ISOCXX]</a>
<code>basic_fstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::open(char const*, _Ios_Openmode)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_fstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::close()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_fstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::is_open()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_fstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::basic_fstream(char const*, _Ios_Openmode)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

basic_fstream<wchar_t, char_traits<wchar_t>>::basic_fstream() (GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_fstream<wchar_t, char_traits<wchar_t>>::basic_fstream(char const*, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_fstream<wchar_t, char_traits<wchar_t>>::basic_fstream() (GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_fstream<wchar_t, char_traits<wchar_t>>::~basic_fstream() (GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_fstream<wchar_t, char_traits<wchar_t>>::~basic_fstream() (GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_fstream<wchar_t, char_traits<wchar_t>>::~basic_fstream() (GLIBCXX_3.4) <a href="#">[ISOcxx]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::basic\_fstream<wchar\_t, std::char\_traits<wchar\_t>> specified in [Table 9-208](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-208 libstdcxx - Class basic\_fstream<wchar\_t, char\_traits<wchar\_t>> Data Interfaces**

typeinfo for basic_fstream<wchar_t, char_traits<wchar_t>>(GLIBCXX_3.4) <a href="#">[Cxxabi]</a>
typeinfo name for basic_fstream<wchar_t, char_traits<wchar_t>>(GLIBCXX_3.4) <a href="#">[Cxxabi]</a>
VTT for basic_fstream<wchar_t, char_traits<wchar_t>>(GLIBCXX_3.4) <a href="#">[Cxxabi]</a>
vtable for basic_fstream<wchar_t, char_traits<wchar_t>>(GLIBCXX_3.4) <a href="#">[Cxxabi]</a>

## 9.1.78 Class basic\_ifstream<char, char\_traits<char>>

>

### 9.1.78.1 Class data for basic\_ifstream<char, char\_traits<char>>

The virtual table for the std::basic\_ifstream<char, std::char\_traits<char>> class is described in the relevant architecture specific part of this specification.

The VTT for the std::basic\_ifstream<char, std::char\_traits<char>> class is described by [Table 9-209](#)

**Table 9-209 VTT for basic\_ifstream<char, char\_traits<char>>**

VTT Name	_ZTTSt14basic_ifstreamIcSt11char_traitsIcEE
Number of Entries	4

## 9.1.78.2 Interfaces for Class basic\_ifstream<char, char\_traits<char>>

>

An LSB conforming implementation shall provide the generic methods for Class std::basic\_ifstream<char, std::char\_traits<char>> specified in [Table 9-210](#), with the full mandatory functionality as described in the referenced underlying spec-

ification.

**Table 9-210 libstdcxx - Class `basic_ifstream<char, char_traits<char>>` Function Interfaces**

basic_ifstream<char, char_traits<char>>::rdbuf() const(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_ifstream<char, char_traits<char>>::is_open() const(GLIBCXX_3.4.5) <a href="#">[ISOcxx]</a>
basic_ifstream<char, char_traits<char>>::open(char const*, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_ifstream<char, char_traits<char>>::close()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_ifstream<char, char_traits<char>>::is_open()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_ifstream<char, char_traits<char>>::basic_ifstream(char const*, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_ifstream<char, char_traits<char>>::basic_ifstream()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_ifstream<char, char_traits<char>>::basic_ifstream(char const*, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_ifstream<char, char_traits<char>>::basic_ifstream()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_ifstream<char, char_traits<char>>::~basic_ifstream()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_ifstream<char, char_traits<char>>::~basic_ifstream()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
basic_ifstream<char, char_traits<char>>::~basic_ifstream()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::basic\_ifstream<char, std::char\_traits<char>> specified in [Table 9-211](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-211 libstdcxx - Class `basic_ifstream<char, char_traits<char>>` Data Interfaces**

typeinfo for basic_ifstream<char, char_traits<char>>(GLIBCXX_3.4) <a href="#">[Cxxabi]</a>
typeinfo name for basic_ifstream<char, char_traits<char>>(GLIBCXX_3.4) <a href="#">[Cxxabi]</a>
VTT for basic_ifstream<char, char_traits<char>>(GLIBCXX_3.4) <a href="#">[Cxxabi]</a>
vtable for basic_ifstream<char, char_traits<char>>(GLIBCXX_3.4) <a href="#">[Cxxabi]</a>

## 9.1.79 Class `basic_ifstream<wchar_t, char_traits<wchar_t>>`

### 9.1.79.1 Class data for `basic_ifstream<wchar_t, char_traits<wchar_t>>`

The virtual table for the std::basic\_ifstream<wchar\_t, std::char\_traits<wchar\_t>>

> class is described in the relevant architecture specific part of this specification.  
 The VTT for the `std::basic_ifstream<wchar_t, std::char_traits<wchar_t>>` class is described by [Table 9-212](#)

**Table 9-212 VTT for basic\_ifstream<wchar\_t, char\_traits<wchar\_t>>**

VTT Name	<code>_ZTTSt14basic_ifstreamIwSt11char_traitsIwEE</code>
Number of Entries	4

### 9.1.79.2 Interfaces for Class basic\_ifstream<wchar\_t, char\_traits<wchar\_t>>

An LSB conforming implementation shall provide the generic methods for Class `std::basic_ifstream<wchar_t, std::char_traits<wchar_t>>` specified in [Table 9-213](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-213 libstdc++ - Class basic\_ifstream<wchar\_t, char\_traits<wchar\_t>> Function Interfaces**

<code>basic_ifstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::rdbuf()</code> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_ifstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::is_open()</code> const(GLIBCXX_3.4.5) <a href="#">[ISOCXX]</a>
<code>basic_ifstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::open(char const*, _Ios_Openmode)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_ifstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::close()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_ifstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::is_open()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_ifstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::basic_ifstream(char const*, _Ios_Openmode)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_ifstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::basic_ifstream()</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_ifstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::basic_ifstream(char const*, _Ios_Openmode)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_ifstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::basic_ifstream()</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_ifstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_ifstream()</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_ifstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_ifstream()</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_ifstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_ifstream()</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class `std::basic_ifstream<wchar_t, std::char_traits<wchar_t>>` specified in [Table 9-214](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-214 libstdcxx - Class basic\_ifstream<wchar\_t, char\_traits<wchar\_t> > Data Interfaces**

typeinfo for basic_ifstream<wchar_t, char_traits<wchar_t> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo for basic_streambuf<wchar_t, char_traits<wchar_t> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for basic_ifstream<wchar_t, char_traits<wchar_t> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for basic_streambuf<wchar_t, char_traits<wchar_t> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
VTT for basic_ifstream<wchar_t, char_traits<wchar_t> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for basic_ifstream<wchar_t, char_traits<wchar_t> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for basic_streambuf<wchar_t, char_traits<wchar_t> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.80 Class basic\_ofstream<char, char\_traits<char> >

>

### 9.1.80.1 Class data for basic\_ofstream<char, char\_traits<char> >

The virtual table for the std::basic\_ofstream<char, std::char\_traits<char> > class is described in the relevant architecture specific part of this specification.

The VTT for the std::basic\_ofstream<char, std::char\_traits<char> > class is described by [Table 9-215](#)

**Table 9-215 VTT for basic\_ofstream<char, char\_traits<char> >**

VTT Name	_ZTTSt14basic_ofstreamIcSt11char_traitsIcEE
Number of Entries	4

### 9.1.80.2 Interfaces for Class basic\_ofstream<char, char\_traits<char> >

An LSB conforming implementation shall provide the generic methods for Class std::basic\_ofstream<char, std::char\_traits<char> > specified in [Table 9-216](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-216 libstdcxx - Class basic\_ofstream<char, char\_traits<char> > Function Interfaces**

basic_ofstream<char, char_traits<char> >::rdbuf() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ofstream<char, char_traits<char> >::is_open() const(GLIBCXX_3.4.5) <a href="#">[ISOCXX]</a>
basic_ofstream<char, char_traits<char> >::open(char const*, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ofstream<char, char_traits<char> >::close()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

basic_ofstream<char, char_traits<char>>::is_open()(GLIBCXX_3.4) [ISOcxx]
basic_ofstream<char, char_traits<char>>::basic_ofstream(char const*, _Ios_Openmode)(GLIBCXX_3.4) [ISOcxx]
basic_ofstream<char, char_traits<char>>::basic_ofstream()(GLIBCXX_3.4) [ISOcxx]
basic_ofstream<char, char_traits<char>>::basic_ofstream(char const*, _Ios_Openmode)(GLIBCXX_3.4) [ISOcxx]
basic_ofstream<char, char_traits<char>>::basic_ofstream()(GLIBCXX_3.4) [ISOcxx]
basic_ofstream<char, char_traits<char>>::~basic_ofstream()(GLIBCXX_3.4) [ISOcxx]
basic_ofstream<char, char_traits<char>>::~basic_ofstream()(GLIBCXX_3.4) [ISOcxx]
basic_ofstream<char, char_traits<char>>::~basic_ofstream()(GLIBCXX_3.4) [ISOcxx]

An LSB conforming implementation shall provide the generic data interfaces for Class std::basic\_ofstream<char, std::char\_traits<char>> specified in [Table 9-217](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-217 libstdcxx - Class basic\_ofstream<char, char\_traits<char>> Data Interfaces**

typeinfo for basic_ofstream<char, char_traits<char>>(GLIBCXX_3.4) [Cxxabi]
typeinfo name for basic_ofstream<char, char_traits<char>>(GLIBCXX_3.4) [Cxxabi]
VTT for basic_ofstream<char, char_traits<char>>(GLIBCXX_3.4) [Cxxabi]
vtable for basic_ofstream<char, char_traits<char>>(GLIBCXX_3.4) [Cxxabi]

## 9.1.81 Class basic\_ofstream<wchar\_t, char\_traits<wchar\_t>>

### 9.1.81.1 Class data for basic\_ofstream<wchar\_t, char\_traits<wchar\_t>>

The virtual table for the std::basic\_ofstream<wchar\_t, std::char\_traits<wchar\_t>> class is described in the relevant architecture specific part of this specification.

The VTT for the std::basic\_ofstream<wchar\_t, std::char\_traits<wchar\_t>> class is described by [Table 9-218](#)

**Table 9-218 VTT for basic\_ofstream<wchar\_t, char\_traits<wchar\_t>>**

VTT Name	_ZTTSt14basic_ofstreamIwSt11char_traitsIwEE
Number of Entries	4

### 9.1.81.2 Interfaces for Class `basic_ofstream<wchar_t, char_traits<wchar_t>>`

An LSB conforming implementation shall provide the generic methods for Class `std::basic_ofstream<wchar_t, std::char_traits<wchar_t>>` specified in [Table 9-219](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-219 libstdc++ - Class `basic_ofstream<wchar_t, char_traits<wchar_t>>` Function Interfaces**

<code>basic_ofstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::rdbuf()</code> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_ofstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::is_open()</code> const(GLIBCXX_3.4.5) <a href="#">[ISOCXX]</a>
<code>basic_ofstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::open(char const*, _Ios_Openmode)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_ofstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::close()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_ofstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::is_open()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_ofstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::basic_ofstream(char const*, _Ios_Openmode)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_ofstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::basic_ofstream()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_ofstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::basic_ofstream(char const*, _Ios_Openmode)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_ofstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::basic_ofstream()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_ofstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_ofstream()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_ofstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_ofstream()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>basic_ofstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_ofstream()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class `std::basic_ofstream<wchar_t, std::char_traits<wchar_t>>` specified in [Table 9-220](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-220 libstdc++ - Class `basic_ofstream<wchar_t, char_traits<wchar_t>>` Data Interfaces**

<code>typeinfo for basic_ofstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>
<code>typeinfo name for basic_ofstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>
<code>VTT for basic_ofstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>
<code>vtable for basic_ofstream&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;(GLIBCXX_3.4)</code>

[CXXABI]

## 9.1.82 Class `basic_streambuf<char, char_traits<char> >`

### 9.1.82.1 Class data for `basic_streambuf<char, char_traits<char> >`

The virtual table for the `std::basic_streambuf<char, std::char_traits<char> >` class is described by [Table 9-221](#)

**Table 9-221 Primary vtable for `basic_streambuf<char, char_traits<char> >`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>basic_streambuf&lt;char, char_traits&lt;char&gt; &gt;</code>
vfunc[0]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt; &gt;::~basic_streambuf()</code>
vfunc[1]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt; &gt;::~basic_streambuf()</code>
vfunc[2]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt; &gt;::imbue(locale const&amp;)</code>
vfunc[3]:	See The Architecture Specific Specification
vfunc[4]:	See The Architecture Specific Specification
vfunc[5]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt; &gt;::seekpos(fpos&lt;__mbstate_t&gt;, _Ios_Openmode)</code>
vfunc[6]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt; &gt;::sync()</code>
vfunc[7]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt; &gt;::showmanyc()</code>
vfunc[8]:	See The Architecture Specific Specification
vfunc[9]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt; &gt;::underflow()</code>
vfunc[10]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt; &gt;::uflow()</code>
vfunc[11]:	<code>basic_streambuf&lt;char, char_traits&lt;char&gt; &gt;::pbackfail(int)</code>
vfunc[12]:	See The Architecture Specific Specification
vfunc[13]:	<code>basic_streambuf&lt;char,</code>

	char_traits<char> >::overflow(int)
--	------------------------------------

The Run Time Type Information for the std::basic\_streambuf<char, std::char\_traits<char> > class is described by [Table 9-222](#)

**Table 9-222 typeinfo for basic\_streambuf<char, char\_traits<char> >**

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for basic_streambuf<char, char_traits<char> >

### 9.1.82.2 Interfaces for Class basic\_streambuf<char, char\_traits<char> >

An LSB conforming implementation shall provide the generic methods for Class std::basic\_streambuf<char, std::char\_traits<char> > specified in [Table 9-223](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-223 libstdc++ - Class basic\_streambuf<char, char\_traits<char> > Function Interfaces**

basic_streambuf<char, char_traits<char> >::gptr() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::pptr() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::eback() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::egptr() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::eptr() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::pbase() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::getloc() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::pubseekpos(fpos<__mbstate_t>, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::setg(char*, char*, char*) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::setp(char*, char*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::sync()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::gbump(int)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::imbue(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::pbump(int)(GLIBCXX_3.4)

<a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::sgetc()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::sputc(char)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::uflow()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::sbumpc()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::snextc()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::pubsync()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::seekpos(fpos<__mbstate_t>, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::sungetc()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::in_avail()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::overflow(int)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::pubimbue(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::pbackfail(int)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::showmanyc()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::sputbackc(char)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::underflow()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::basic_streambuf(basic_streambuf<char, char_traits<char> > const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::basic_streambuf()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::basic_streambuf(basic_streambuf<char, char_traits<char> > const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::basic_streambuf()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::~basic_streambuf()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::~basic_streambuf()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::~basic_streambuf()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<char, char_traits<char> >::operator=(basic_streambuf<char,

<code>char_traits&lt;char&gt; &gt; const&amp;)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
---

An LSB conforming implementation shall provide the generic data interfaces for Class `std::basic_streambuf<char, std::char_traits<char> >` specified in [Table 9-224](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-224 libstdc++ - Class `basic_streambuf<char, char_traits<char> >` Data Interfaces**

typeinfo for <code>basic_streambuf&lt;char, char_traits&lt;char&gt; &gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for <code>basic_streambuf&lt;char, char_traits&lt;char&gt; &gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for <code>basic_streambuf&lt;char, char_traits&lt;char&gt; &gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.83 Class `basic_streambuf<wchar_t, char_traits<wchar_t> >`

### 9.1.83.1 Class data for `basic_streambuf<wchar_t, char_traits<wchar_t> >`

The virtual table for the `std::basic_streambuf<wchar_t, std::char_traits<wchar_t> >` class is described by [Table 9-225](#)

**Table 9-225 Primary vtable for `basic_streambuf<wchar_t, char_traits<wchar_t> >`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;</code>
vfunc[0]:	<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::~basic_streambuf()</code>
vfunc[1]:	<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::~basic_streambuf()</code>
vfunc[2]:	<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::imbue(locale const&amp;)</code>
vfunc[3]:	See The Architecture Specific Specification
vfunc[4]:	See The Architecture Specific Specification
vfunc[5]:	<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;::seekpos(fpos&lt;__mbstate_t&gt;, _Ios_Openmode)</code>

vfunc[6]:	basic_streambuf<wchar_t, char_traits<wchar_t>>::sync()
vfunc[7]:	basic_streambuf<wchar_t, char_traits<wchar_t>>::showmany()
vfunc[8]:	See The Architecture Specific Specification
vfunc[9]:	basic_streambuf<wchar_t, char_traits<wchar_t>>::underflow()
vfunc[10]:	basic_streambuf<wchar_t, char_traits<wchar_t>>::uflow()
vfunc[11]:	basic_streambuf<wchar_t, char_traits<wchar_t>>::pbackfail(unsigned int)
vfunc[12]:	See The Architecture Specific Specification
vfunc[13]:	basic_streambuf<wchar_t, char_traits<wchar_t>>::overflow(unsigned int)

The Run Time Type Information for the `std::basic_streambuf<wchar_t, std::char_traits<wchar_t>>` class is described by [Table 9-226](#)

**Table 9-226 typeinfo for basic\_streambuf<wchar\_t, char\_traits<wchar\_t>>**

Base Vtable	vtable for <code>_cxxabiv1::__class_type_info</code>
Name	typeinfo name for <code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code>

### 9.1.83.2 Interfaces for Class `basic_streambuf<wchar_t, char_traits<wchar_t>>`

An LSB conforming implementation shall provide the generic methods for Class `std::basic_streambuf<wchar_t, std::char_traits<wchar_t>>` specified in [Table 9-227](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-227 libstdc++ - Class `basic_streambuf<wchar_t, char_traits<wchar_t>>` Function Interfaces**

<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::gptr()</code> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::pptr()</code> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::eback()</code> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::egptr()</code> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::eptr()</code>

const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t> >::pbase() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t> >::getloc() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t> >::pubseekpos(fpos<__mbstate_t>, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t> >::setg(wchar_t*, wchar_t*, wchar_t*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t> >::setp(wchar_t*, wchar_t*) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t> >::sync()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t> >::gbump(int) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t> >::imbue(locale const&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t> >::pbump(int) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t> >::sgetc()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t> >::sputc(wchar_t) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t> >::uflow()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t> >::sbumpc()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t> >::snextc()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t> >::pubsync()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t> >::seekpos(fpos<__mbstate_t>, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t> >::sungetc()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t> >::in_avail()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t> >::overflow(unsigned int) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t> >::pubimbue(locale const&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t> >::pbackfail(unsigned int) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t> >::showmanyc() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

basic_streambuf<wchar_t, char_traits<wchar_t>>::sputbackc(wchar_t) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t>>::underflow() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t>> >::basic_streambuf(basic_streambuf<wchar_t, char_traits<wchar_t>> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t>>::basic_streambuf() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t>>::basic_streambuf() >::basic_streambuf(basic_streambuf<wchar_t, char_traits<wchar_t>> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t>>::basic_streambuf() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t>>::~basic_streambuf() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t>>::~basic_streambuf() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t>>::~basic_streambuf() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_streambuf<wchar_t, char_traits<wchar_t>>::operator=(basic_streambuf<wchar_t, char_traits<wchar_t>> const&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 9.1.84 Class basic\_filebuf<char, char\_traits<char> >

### 9.1.84.1 Class data for basic\_filebuf<char, char\_traits<char> >

The virtual table for the std::basic\_filebuf<char, std::char\_traits<char> > class is described by [Table 9-228](#)

**Table 9-228 Primary vtable for basic\_filebuf<char, char\_traits<char> >**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for basic_filebuf<char, char_traits<char> >
vfunc[0]:	basic_filebuf<char, char_traits<char> >::~basic_filebuf()
vfunc[1]:	basic_filebuf<char, char_traits<char> >::~basic_filebuf()
vfunc[2]:	basic_filebuf<char, char_traits<char> >::imbue(locale const&)
vfunc[3]:	See The Architecture Specific Specification
vfunc[4]:	See The Architecture Specific Specification
vfunc[5]:	basic_filebuf<char, char_traits<char> >

	>::seekpos(fpos<__mbstate_t>, _Ios_Openmode)
vfunc[6]:	basic_filebuf<char, char_traits<char>>::sync()
vfunc[7]:	basic_filebuf<char, char_traits<char>>::showmany()
vfunc[8]:	See The Architecture Specific Specification
vfunc[9]:	basic_filebuf<char, char_traits<char>>::underflow()
vfunc[10]:	basic_streambuf<char, char_traits<char>>::uflow()
vfunc[11]:	basic_filebuf<char, char_traits<char>>::pbackfail(int)
vfunc[12]:	See The Architecture Specific Specification
vfunc[13]:	basic_filebuf<char, char_traits<char>>::overflow(int)

The Run Time Type Information for the std::basic\_filebuf<char, std::char\_traits<char> > class is described by [Table 9-229](#)

**Table 9-229 typeinfo for basic\_filebuf<char, char\_traits<char> >**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for basic_filebuf<char, char_traits<char> >

#### 9.1.84.2 Interfaces for Class basic\_filebuf<char, char\_traits<char> >

An LSB conforming implementation shall provide the generic methods for Class std::basic\_filebuf<char, std::char\_traits<char> > specified in [Table 9-230](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-230 libstdc++ - Class basic\_filebuf<char, char\_traits<char> > Function Interfaces**

basic_filebuf<char, char_traits<char>>::is_open() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<char, char_traits<char>>::_M_create_pback()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<char, char_traits<char>>::_M_destroy_pback()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<char, char_traits<char>>::_M_terminate_output() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<char, char_traits<char>>::_M_destroy_internal_buffer() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

basic_filebuf<char, char_traits<char>>::_M_allocate_internal_buffer() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<char, char_traits<char>>::open(char const*, _Ios_Openmode) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<char, char_traits<char>>::sync()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<char, char_traits<char>>::close()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<char, char_traits<char>>::imbue(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<char, char_traits<char>>::seekpos(fpos<__mbstate_t>, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<char, char_traits<char>>::overflow(int)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<char, char_traits<char>>::pbackfail(int)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<char, char_traits<char>>::showmanyc()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<char, char_traits<char>>::underflow()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<char, char_traits<char>>::basic_filebuf()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<char, char_traits<char>>::basic_filebuf()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<char, char_traits<char>>::~basic_filebuf()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<char, char_traits<char>>::~basic_filebuf()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<char, char_traits<char>>::~basic_filebuf()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::basic\_filebuf<char, std::char\_traits<char>> specified in [Table 9-231](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-231 libstdcxx - Class basic\_filebuf<char, char\_traits<char>> Data Interfaces**

typeinfo for basic_filebuf<char, char_traits<char>>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for basic_filebuf<char, char_traits<char>>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for basic_filebuf<char, char_traits<char>>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.85 Class `basic_filebuf<wchar_t, char_traits<wchar_t>>`

### 9.1.85.1 Class data for `basic_filebuf<wchar_t, char_traits<wchar_t>>`

The virtual table for the `std::basic_filebuf<wchar_t, std::char_traits<wchar_t>>` class is described by [Table 9-232](#)

**Table 9-232 Primary vtable for `basic_filebuf<wchar_t, char_traits<wchar_t>>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code>
vfunc[0]:	<code>basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_filebuf()</code>
vfunc[1]:	<code>basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::~basic_filebuf()</code>
vfunc[2]:	<code>basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::imbue(locale const&amp;)</code>
vfunc[3]:	See The Architecture Specific Specification
vfunc[4]:	See The Architecture Specific Specification
vfunc[5]:	<code>basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::seekpos(fpos&lt;__mbstate_t&gt;, _Ios_Openmode)</code>
vfunc[6]:	<code>basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::sync()</code>
vfunc[7]:	<code>basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::showmany()</code>
vfunc[8]:	See The Architecture Specific Specification
vfunc[9]:	<code>basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::underflow()</code>
vfunc[10]:	<code>basic_streambuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::uflow()</code>
vfunc[11]:	<code>basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;::pbackfail(unsigned int)</code>
vfunc[12]:	See The Architecture Specific Specification

vfunc[13]:	basic_filebuf<wchar_t, char_traits<wchar_t> >::overflow(unsigned int)
------------	---

The Run Time Type Information for the std::basic\_filebuf<wchar\_t, std::char\_traits<wchar\_t>> class is described by [Table 9-233](#)

**Table 9-233 typeinfo for basic\_filebuf<wchar\_t, char\_traits<wchar\_t>>**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>basic_filebuf&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code>

### 9.1.85.2 Interfaces for Class basic\_filebuf<wchar\_t, char\_traits<wchar\_t>>

An LSB conforming implementation shall provide the generic methods for Class std::basic\_filebuf<wchar\_t, std::char\_traits<wchar\_t>> specified in [Table 9-234](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-234 libstdc++ - Class basic\_filebuf<wchar\_t, char\_traits<wchar\_t>> Function Interfaces**

basic_filebuf<wchar_t, char_traits<wchar_t>>::is_open() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>	
basic_filebuf<wchar_t, char_traits<wchar_t>>::_M_create_pback() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>	
basic_filebuf<wchar_t, char_traits<wchar_t>>::_M_destroy_pback() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>	
basic_filebuf<wchar_t, char_traits<wchar_t>>::_M_terminate_output() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>	
basic_filebuf<wchar_t, char_traits<wchar_t>>::_M_destroy_internal_buffer() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>	
basic_filebuf<wchar_t, char_traits<wchar_t>>::_M_allocate_internal_buffer() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>	
basic_filebuf<wchar_t, char_traits<wchar_t>>::open(char const*, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>	
basic_filebuf<wchar_t, char_traits<wchar_t>>::sync()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>	
basic_filebuf<wchar_t, char_traits<wchar_t>>::close()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>	
basic_filebuf<wchar_t, char_traits<wchar_t>>::imbue(locale const&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>	
basic_filebuf<wchar_t, char_traits<wchar_t>>::seekpos(fpos<__mbstate_t>, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>	
basic_filebuf<wchar_t, char_traits<wchar_t>>::overflow(unsigned int) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>	
basic_filebuf<wchar_t, char_traits<wchar_t>>::pbackfail(unsigned int)	

(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<wchar_t, char_traits<wchar_t>>::showmany()
(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<wchar_t, char_traits<wchar_t>>::underflow()
(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<wchar_t, char_traits<wchar_t>>::basic_filebuf()
(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<wchar_t, char_traits<wchar_t>>::basic_filebuf()
(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<wchar_t, char_traits<wchar_t>>::~basic_filebuf()
(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<wchar_t, char_traits<wchar_t>>::~basic_filebuf()
(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_filebuf<wchar_t, char_traits<wchar_t>>::~basic_filebuf()
(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t>>::basic_istream()
(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_istream<wchar_t, char_traits<wchar_t>>::basic_istream()
(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::basic_ostream()
(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ostream<wchar_t, char_traits<wchar_t>>::basic_ostream()
(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::basic\_filebuf<wchar\_t, std::char\_traits<wchar\_t>> specified in [Table 9-235](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-235 libstdcxx - Class basic\_filebuf<wchar\_t, char\_traits<wchar\_t>> Data Interfaces**

typeinfo for basic_filebuf<wchar_t, char_traits<wchar_t>>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for basic_filebuf<wchar_t, char_traits<wchar_t>>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for basic_filebuf<wchar_t, char_traits<wchar_t>>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.86 Class ios\_base

### 9.1.86.1 Class data for ios\_base

The virtual table for the std::ios\_base class is described by [Table 9-236](#)

**Table 9-236 Primary vtable for ios\_base**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for ios_base

vfunc[0]:	ios_base::~ios_base()
vfunc[1]:	ios_base::~ios_base()

The Run Time Type Information for the std::ios\_base class is described by [Table 9-237](#)

**Table 9-237 typeinfo for ios\_base**

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for ios_base

### 9.1.86.2 Interfaces for Class ios\_base

An LSB conforming implementation shall provide the generic methods for Class std::ios\_base specified in [Table 9-238](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-238 libstdc++ - Class ios\_base Function Interfaces**

ios_base::_M_grow_words(int, bool)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::sync_with_stdio(bool)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::_M_call_callbacks(ios_base::event)(GLIBCXX_3.4.6) <a href="#">[ISOCXX]</a>
ios_base::register_callback(void (*) (ios_base::event, ios_base&, int), int)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::_M_dispose_callbacks()(GLIBCXX_3.4.6) <a href="#">[ISOCXX]</a>
ios_base::Init::Init()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::Init::Init()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::Init::~Init()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::Init::~Init()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::imbue(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::xalloc()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::_M_init()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::failure::failure(basic_string<char, char_traits<char>, allocator<char> > const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::failure::failure(basic_string<char, char_traits<char>, allocator<char> > const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::failure::~failure()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::failure::~failure()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::failure::~failure()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::ios_base()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::ios_base()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::~ios_base()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::~ios_base()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::~ios_base()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::ios\_base specified in [Table 9-239](#), with the full mandatory functional-

ity as described in the referenced underlying specification.

**Table 9-239 libstdcxx - Class ios\_base Data Interfaces**

ios_base::floatfield(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::scientific(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::adjustfield(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::in(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::app(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::ate(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::beg(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::cur(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::dec(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::end(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::hex(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::oct(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::out(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::left(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::fixed(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::right(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::trunc(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::badbit(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::binary(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::eofbit(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::skipws(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::failbit(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::goodbit(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::showpos(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::unitbuf(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::internal(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::showbase(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::basefield(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::boolalpha(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::showpoint(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ios_base::uppercase(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
typeinfo for ios_base(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for ios_base(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for ios_base(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.87 Class basic\_ios<char, char\_traits<char> >

### 9.1.87.1 Class data for basic\_ios<char, char\_traits<char> >

The virtual table for the std::basic\_ios<char, std::char\_traits<char> > class is de-

scribed by [Table 9-240](#)

**Table 9-240 Primary vtable for basic\_ios<char, char\_traits<char> >**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for basic_ios<char, char_traits<char> >
vfunc[0]:	basic_ios<char, char_traits<char> >::~basic_ios()
vfunc[1]:	basic_ios<char, char_traits<char> >::~basic_ios()

### 9.1.87.2 Interfaces for Class basic\_ios<char, char\_traits<char> >

An LSB conforming implementation shall provide the generic methods for Class std::basic\_ios<char, std::char\_traits<char> > specified in [Table 9-241](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-241 libstdcxx - Class basic\_ios<char, char\_traits<char> > Function Interfaces**

basic_ios<char, char_traits<char> >::exceptions() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<char, char_traits<char> >::bad() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<char, char_traits<char> >::eof() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<char, char_traits<char> >::tie() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<char, char_traits<char> >::fail() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<char, char_traits<char> >::fill() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<char, char_traits<char> >::good() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<char, char_traits<char> >::rdbuf() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<char, char_traits<char> >::widen(char) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<char, char_traits<char> >::narrow(char, char) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<char, char_traits<char> >::rdstate() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<char, char_traits<char> >::operator void*() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<char, char_traits<char> >::operator!() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<char, char_traits<char> >::exceptions(_Ios_Iostate)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<char, char_traits<char> >::_M_setstate(_Ios_Iostate)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<char, char_traits<char> >::tie(basic_ostream<char, char_traits<char> >*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<char, char_traits<char> >::fill(char)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<char, char_traits<char> >::init(basic_streambuf<char,

char_traits<char> >*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<char, char_traits<char> >::clear(_Ios_Iostate)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<char, char_traits<char> >::imbue(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<char, char_traits<char> >::rdbuf(basic_streambuf<char, char_traits<char> >*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<char, char_traits<char> >::copyfmt(basic_ios<char, char_traits<char> > const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<char, char_traits<char> >::setstate(_Ios_Iostate)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<char, char_traits<char> >::basic_ios(basic_streambuf<char, char_traits<char> >*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<char, char_traits<char> >::basic_ios()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<char, char_traits<char> >::basic_ios(basic_streambuf<char, char_traits<char> >*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<char, char_traits<char> >::basic_ios()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<char, char_traits<char> >::~basic_ios()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<char, char_traits<char> >::~basic_ios()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<char, char_traits<char> >::~basic_ios()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::basic\_ios<char, std::char\_traits<char> > specified in [Table 9-242](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-242 libstdc++ - Class basic\_ios<char, char\_traits<char> > Data Interfaces**

typeinfo for basic_ios<char, char_traits<char> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for basic_ios<char, char_traits<char> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for basic_ios<char, char_traits<char> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.88 Class basic\_ios<wchar\_t, char\_traits<wchar\_t> >

### 9.1.88.1 Class data for basic\_ios<wchar\_t, char\_traits<wchar\_t> >

The virtual table for the std::basic\_ios<wchar\_t, std::char\_traits<wchar\_t> > class is described by [Table 9-243](#)

**Table 9-243 Primary vtable for basic\_ios<wchar\_t, char\_traits<wchar\_t> >**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for basic_ios<wchar_t, char_traits<wchar_t> >
vfunc[0]:	basic_ios<wchar_t,

	char_traits<wchar_t> >::~basic_ios()
vfunc[1]:	basic_ios<wchar_t>, char_traits<wchar_t> >::~basic_ios()

The Run Time Type Information for the std::basic\_ios<wchar\_t, std::char\_traits<wchar\_t>> class is described by [Table 9-244](#)

**Table 9-244 typeinfo for basic\_ios<wchar\_t, char\_traits<wchar\_t>>**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info	
Name	typeinfo name for basic_ios<wchar_t, char_traits<wchar_t>>	
flags:	8	
basetype:	typeinfo for ios_base	

### 9.1.88.2 Interfaces for Class basic\_ios<wchar\_t, char\_traits<wchar\_t>>

An LSB conforming implementation shall provide the generic methods for Class std::basic\_ios<wchar\_t, std::char\_traits<wchar\_t>> specified in [Table 9-245](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-245 libstdc++ - Class basic\_ios<wchar\_t, char\_traits<wchar\_t>> Function Interfaces**

basic_ios<wchar_t, char_traits<wchar_t>>::exceptions() const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
basic_ios<wchar_t, char_traits<wchar_t>>::bad() const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
basic_ios<wchar_t, char_traits<wchar_t>>::eof() const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
basic_ios<wchar_t, char_traits<wchar_t>>::tie() const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
basic_ios<wchar_t, char_traits<wchar_t>>::fail() const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
basic_ios<wchar_t, char_traits<wchar_t>>::fill() const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
basic_ios<wchar_t, char_traits<wchar_t>>::good() const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
basic_ios<wchar_t, char_traits<wchar_t>>::rdbuf() const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
basic_ios<wchar_t, char_traits<wchar_t>>::widen(char) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
basic_ios<wchar_t, char_traits<wchar_t>>::narrow(wchar_t, char) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
basic_ios<wchar_t, char_traits<wchar_t>>::rdstate() const(GLIBCXX_3.4)

<a href="#">[ISOCXX]</a>
basic_ios<wchar_t, char_traits<wchar_t>>::operator void*() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<wchar_t, char_traits<wchar_t>>::operator!() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<wchar_t, char_traits<wchar_t>>::exceptions(_Ios_Iostate) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<wchar_t, char_traits<wchar_t>>::_M_setstate(_Ios_Iostate) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<wchar_t, char_traits<wchar_t>>::tie(basic_ostream<wchar_t, char_traits<wchar_t>>*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<wchar_t, char_traits<wchar_t>>::fill(wchar_t)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<wchar_t, char_traits<wchar_t>>::init(basic_streambuf<wchar_t, char_traits<wchar_t>>*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<wchar_t, char_traits<wchar_t>>::clear(_Ios_Iostate) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<wchar_t, char_traits<wchar_t>>::imbue(locale const&) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<wchar_t, char_traits<wchar_t>>::rdbuf(basic_streambuf<wchar_t, char_traits<wchar_t>>*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<wchar_t, char_traits<wchar_t>>::copyfmt(basic_ios<wchar_t, char_traits<wchar_t>> const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<wchar_t, char_traits<wchar_t>>::setstate(_Ios_Iostate) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<wchar_t, char_traits<wchar_t>> >::basic_ios(basic_streambuf<wchar_t, char_traits<wchar_t>>*) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<wchar_t, char_traits<wchar_t>>::basic_ios()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<wchar_t, char_traits<wchar_t>> >::basic_ios(basic_streambuf<wchar_t, char_traits<wchar_t>>*) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<wchar_t, char_traits<wchar_t>>::basic_ios()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<wchar_t, char_traits<wchar_t>>::~basic_ios()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<wchar_t, char_traits<wchar_t>>::~basic_ios()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
basic_ios<wchar_t, char_traits<wchar_t>>::~basic_ios()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::basic\_ios<wchar\_t, std::char\_traits<wchar\_t>> specified in [Table 9-246](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-246 libstdc++ - Class `basic_ios<wchar_t, char_traits<wchar_t>` > Data Interfaces**

typeinfo for <code>basic_ios&lt;wchar_t, char_traits&lt;wchar_t&gt;</code> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for <code>basic_ios&lt;wchar_t, char_traits&lt;wchar_t&gt;</code> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for <code>basic_ios&lt;wchar_t, char_traits&lt;wchar_t&gt;</code> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.89 Class `ios_base::failure`

### 9.1.89.1 Class data for `ios_base::failure`

The virtual table for the `std::ios_base::failure` class is described by [Table 9-247](#)

**Table 9-247 Primary vtable for `ios_base::failure`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>ios_base::failure</code>
vfunc[0]:	<code>ios_base::failure::~failure()</code>
vfunc[1]:	<code>ios_base::failure::~failure()</code>
vfunc[2]:	<code>ios_base::failure::what() const</code>

The Run Time Type Information for the `std::ios_base::failure` class is described by [Table 9-248](#)

**Table 9-248 typeinfo for `ios_base::failure`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>ios_base::failure</code>

### 9.1.89.2 Interfaces for Class `ios_base::failure`

An LSB conforming implementation shall provide the generic methods for Class `std::ios_base::failure` specified in [Table 9-249](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-249 libstdc++ - Class `ios_base::failure` Function Interfaces**

ios_base::failure::what() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
---

An LSB conforming implementation shall provide the generic data interfaces for Class `std::ios_base::failure` specified in [Table 9-250](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-250 libstdc++ - Class `ios_base::failure` Data Interfaces**

typeinfo for <code>ios_base::failure</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for <code>ios_base::failure</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for <code>ios_base::failure</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.90 Class `_timepunct<char>`

### 9.1.90.1 Class data for `_timepunct<char>`

The virtual table for the `std::_timepunct<char>` class is described by [Table 9-251](#)

**Table 9-251 Primary vtable for `_timepunct<char>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>_timepunct&lt;char&gt;</code>
vfunc[0]:	<code>_timepunct&lt;char&gt;::~_timepunct()</code>
vfunc[1]:	<code>_timepunct&lt;char&gt;::~_timepunct()</code>

The Run Time Type Information for the `std::_timepunct<char>` class is described by [Table 9-252](#)

**Table 9-252 typeinfo for `_timepunct<char>`**

Base Vtable	vtable for <code>_cxxabiv1::si_class_type_info</code>
Name	typeinfo name for <code>_timepunct&lt;char&gt;</code>

### 9.1.90.2 Interfaces for Class `_timepunct<char>`

An LSB conforming implementation shall provide the generic methods for Class `std::_timepunct<char>` specified in [Table 9-253](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-253 libstdc++ - Class `_timepunct<char>` Function Interfaces**

<code>_timepunct&lt;char&gt;::_M_am_pm_format(char const*) const(GLIBCXX_3.4)</code> [ISOCXX]
<code>_timepunct&lt;char&gt;::_M_date_formats(char const**) const(GLIBCXX_3.4)</code> [ISOCXX]
<code>_timepunct&lt;char&gt;::_M_time_formats(char const**) const(GLIBCXX_3.4)</code> [ISOCXX]
<code>_timepunct&lt;char&gt;::_M_days_abbreviated(char const**) const(GLIBCXX_3.4)</code> [ISOCXX]
<code>_timepunct&lt;char&gt;::_M_date_time_formats(char const**) const(GLIBCXX_3.4)</code> [ISOCXX]
<code>_timepunct&lt;char&gt;::_M_months_abbreviated(char const**) const(GLIBCXX_3.4)</code> [ISOCXX]
<code>_timepunct&lt;char&gt;::_M_days(char const**) const(GLIBCXX_3.4)</code> [ISOCXX]
<code>_timepunct&lt;char&gt;::_M_am_pm(char const**) const(GLIBCXX_3.4)</code> [ISOCXX]
<code>_timepunct&lt;char&gt;::_M_months(char const**) const(GLIBCXX_3.4)</code> [ISOCXX]
<code>_timepunct&lt;wchar_t&gt;::_M_am_pm_format(wchar_t const*) const(GLIBCXX_3.4)</code> [ISOCXX]

<code>__timepunct&lt;char&gt;::__M_initialize_timepunct(__locale_struct*)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>__timepunct&lt;char&gt;::~__timepunct()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>__timepunct&lt;char&gt;::~__timepunct()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>__timepunct&lt;char&gt;::~__timepunct()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>bool has_facet&lt;__timepunct&lt;char&gt;&gt;(locale const&amp;)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::\_\_timepunct<char> specified in [Table 9-254](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-254 libstdc++ - Class \_\_timepunct<char> Data Interfaces**

guard variable for __timepunct<char>::id(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
<code>__timepunct&lt;char&gt;::id(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
typeinfo for __timepunct<char>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for __timepunct<char>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for __timepunct<char>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.91 Class \_\_timepunct<wchar\_t>

### 9.1.91.1 Class data for \_\_timepunct<wchar\_t>

The virtual table for the std::\_\_timepunct<wchar\_t> class is described by [Table 9-255](#)

**Table 9-255 Primary vtable for \_\_timepunct<wchar\_t>**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for __timepunct<wchar_t>
vfunc[0]:	<code>__timepunct&lt;wchar_t&gt;::~__timepunct()</code>
vfunc[1]:	<code>__timepunct&lt;wchar_t&gt;::~__timepunct()</code>

The Run Time Type Information for the std::\_\_timepunct<wchar\_t> class is described by [Table 9-256](#)

**Table 9-256 typeinfo for \_\_timepunct<wchar\_t>**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for __timepunct<wchar_t>

### 9.1.91.2 Interfaces for Class \_\_timepunct<wchar\_t>

An LSB conforming implementation shall provide the generic methods for Class std::\_\_timepunct<wchar\_t> specified in [Table 9-257](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-257 libstdc++ - Class `_timepunct<wchar_t>` Function Interfaces**

<code>_timepunct&lt;wchar_t&gt;::_M_date_formats(wchar_t const**)</code> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>_timepunct&lt;wchar_t&gt;::_M_time_formats(wchar_t const**)</code> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>_timepunct&lt;wchar_t&gt;::_M_days_abbreviated(wchar_t const**)</code> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>_timepunct&lt;wchar_t&gt;::_M_date_time_formats(wchar_t const**)</code> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>_timepunct&lt;wchar_t&gt;::_M_months_abbreviated(wchar_t const**)</code> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>_timepunct&lt;wchar_t&gt;::_M_days(wchar_t const**)</code> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>_timepunct&lt;wchar_t&gt;::_M_am_pm(wchar_t const**)</code> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>_timepunct&lt;wchar_t&gt;::_M_months(wchar_t const**)</code> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>_timepunct&lt;wchar_t&gt;::_M_initialize_timepunct(_locale_struct*)</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>_timepunct&lt;wchar_t&gt;::~_timepunct()</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>_timepunct&lt;wchar_t&gt;::~_timepunct()</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>_timepunct&lt;wchar_t&gt;::~_timepunct()</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
bool has_facet< <code>_timepunct&lt;wchar_t&gt;</code> >(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::`_timepunct<wchar_t>` specified in [Table 9-258](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-258 libstdc++ - Class `_timepunct<wchar_t>` Data Interfaces**

guard variable for <code>_timepunct&lt;wchar_t&gt;::id</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
<code>_timepunct&lt;wchar_t&gt;::id</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
typeinfo for <code>_timepunct&lt;wchar_t&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for <code>_timepunct&lt;wchar_t&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for <code>_timepunct&lt;wchar_t&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.92 Class `messages_base`

### 9.1.92.1 Class data for `messages_base`

The Run Time Type Information for the std::`messages_base` class is described by [Table 9-259](#)

**Table 9-259 typeinfo for `messages_base`**

Base Vtable	vtable for <code>_cxxabiv1::__class_type_info</code>
Name	typeinfo name for <code>messages_base</code>

### 9.1.92.2 Interfaces for Class `messages_base`

No external methods are defined for libstdcxx - Class `std::messages_base` in this part of the specification. See also the relevant architecture specific part of this specification.

An LSB conforming implementation shall provide the generic data interfaces for Class `std::messages_base` specified in [Table 9-260](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-260 libstdcxx - Class `messages_base` Data Interfaces**

typeinfo for <code>messages_base(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>
typeinfo name for <code>messages_base(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>

## 9.1.93 Class `messages<char>`

### 9.1.93.1 Class data for `messages<char>`

The virtual table for the `std::messages<char>` class is described by [Table 9-261](#)

**Table 9-261 Primary vtable for `messages<char>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>messages&lt;char&gt;</code>
vfunc[0]:	<code>messages&lt;char&gt;::~messages()</code>
vfunc[1]:	<code>messages&lt;char&gt;::~messages()</code>
vfunc[2]:	<code>messages&lt;char&gt;::do_open(basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt; const&amp;, locale const&amp;) const</code>
vfunc[3]:	<code>messages&lt;char&gt;::do_get(int, int, int, basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt; const&amp;) const</code>
vfunc[4]:	<code>messages&lt;char&gt;::do_close(int) const</code>

### 9.1.93.2 Interfaces for Class `messages<char>`

An LSB conforming implementation shall provide the generic methods for Class `std::messages<char>` specified in [Table 9-262](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-262 libstdcxx - Class `messages<char>` Function Interfaces**

<code>messages&lt;char&gt;::_M_convert_to_char(basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt; const&amp;) const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>messages&lt;char&gt;::_M_convert_from_char(char*) const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>messages&lt;char&gt;::get(int, int, int, basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt; const&amp;) const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>messages&lt;char&gt;::open(basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt; const&amp;, locale const&amp;) const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>messages&lt;char&gt;::open(basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt; const&amp;, locale const&amp;) const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

> const&, locale const&, char const*) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages<char>::close(int) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages<char>::do_get(int, int, int, basic_string<char, char_traits<char>, allocator<char> > const&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages<char>::do_open(basic_string<char, char_traits<char>, allocator<char> > const&, locale const&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages<char>::do_close(int) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages<char>::~messages()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages<char>::~messages()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages<char>::~messages()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::messages<char> specified in [Table 9-263](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-263 libstdcxx - Class messages<char> Data Interfaces**

guard variable for messages<char>::id(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
messages<char>::id(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
typeinfo for messages<char>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for messages<char>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for messages<char>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.94 Class messages<wchar\_t>

### 9.1.94.1 Class data for messages<wchar\_t>

The virtual table for the std::messages<wchar\_t> class is described by [Table 9-264](#)

**Table 9-264 Primary vtable for messages<wchar\_t>**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for messages<wchar_t>
vfunc[0]:	messages<wchar_t>::~messages()
vfunc[1]:	messages<wchar_t>::~messages()
vfunc[2]:	messages<wchar_t>::do_open(basic_string<char, char_traits<char>, allocator<char> > const&, locale const&) const
vfunc[3]:	messages<wchar_t>::do_get(int, int, int, basic_string<wchar_t, char_traits<wchar_t>, allocator<wchar_t> > const&) const
vfunc[4]:	messages<wchar_t>::do_close(int) const

### 9.1.94.2 Interfaces for Class `messages<wchar_t>`

An LSB conforming implementation shall provide the generic methods for Class `std::messages<wchar_t>` specified in [Table 9-265](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-265 libstdc++ - Class `messages<wchar_t>` Function Interfaces**

messages<wchar_t>::__M_convert_to_char(basic_string<wchar_t,> char_traits<wchar_t>, allocator<wchar_t> > const&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages<wchar_t>::__M_convert_from_char(char*) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages<wchar_t>::get(int, int, int, basic_string<wchar_t,> char_traits<wchar_t>, allocator<wchar_t> > const&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages<wchar_t>::open(basic_string<char, char_traits<char>,> allocator<char> > const&, locale const&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages<wchar_t>::open(basic_string<char, char_traits<char>,> allocator<char> > const&, locale const&, char const*) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages<wchar_t>::close(int) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages<wchar_t>::do_get(int, int, int, basic_string<wchar_t,> char_traits<wchar_t>, allocator<wchar_t> > const&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages<wchar_t>::do_open(basic_string<char, char_traits<char>,> allocator<char> > const&, locale const&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages<wchar_t>::do_close(int) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages<wchar_t>::~messages() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages<wchar_t>::~messages() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages<wchar_t>::~messages() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class `std::messages<wchar_t>` specified in [Table 9-266](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-266 libstdc++ - Class `messages<wchar_t>` Data Interfaces**

guard variable for messages<wchar_t>::id(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
messages<wchar_t>::id(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
typeinfo for messages<wchar_t> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for messages<wchar_t> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for messages<wchar_t> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>

### 9.1.95 Class `messages_byname<char>`

#### 9.1.95.1 Class data for `messages_byname<char>`

The virtual table for the `std::messages_byname<char>` class is described by [Table 9-267](#)

**Table 9-267 Primary vtable for messages\_byname<char>**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for messages_byname<char>
vfunc[0]:	messages_byname<char>::~messages_byname()
vfunc[1]:	messages_byname<char>::~messages_byname()
vfunc[2]:	messages<char>::do_open(basic_string<char, char_traits<char>, allocator<char> > const&, locale const&) const
vfunc[3]:	messages<char>::do_get(int, int, int, basic_string<char, char_traits<char>, allocator<char> > const&) const
vfunc[4]:	messages<char>::do_close(int) const

The Run Time Type Information for the std::messages\_byname<char> class is described by [Table 9-268](#)

**Table 9-268 typeinfo for messages\_byname<char>**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for messages_byname<char>

### 9.1.95.2 Interfaces for Class messages\_byname<char>

An LSB conforming implementation shall provide the generic methods for Class std::messages\_byname<char> specified in [Table 9-269](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-269 libstdcxx - Class messages\_byname<char> Function Interfaces**

messages_byname<char>::~messages_byname()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages_byname<char>::~messages_byname()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages_byname<char>::~messages_byname()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::messages\_byname<char> specified in [Table 9-270](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-270 libstdcxx - Class messages\_byname<char> Data Interfaces**

typeinfo for messages_byname<char>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for messages_byname<char>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for messages_byname<char>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.96 Class `messages_byname<wchar_t>`

### 9.1.96.1 Class data for `messages_byname<wchar_t>`

The virtual table for the `std::messages_byname<wchar_t>` class is described by [Table 9-271](#)

**Table 9-271 Primary vtable for `messages_byname<wchar_t>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>messages_byname&lt;wchar_t&gt;</code>
vfunc[0]:	<code>messages_byname&lt;wchar_t&gt;::~messages_byname()</code>
vfunc[1]:	<code>messages_byname&lt;wchar_t&gt;::~messages_byname()</code>
vfunc[2]:	<code>messages&lt;wchar_t&gt;::do_open(basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt; const&amp;, locale const&amp;) const</code>
vfunc[3]:	<code>messages&lt;wchar_t&gt;::do_get(int, int, int, basic_string&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt; const&amp;) const</code>
vfunc[4]:	<code>messages&lt;wchar_t&gt;::do_close(int) const</code>

The Run Time Type Information for the `std::messages_byname<wchar_t>` class is described by [Table 9-272](#)

**Table 9-272 typeinfo for `messages_byname<wchar_t>`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>messages_byname&lt;wchar_t&gt;</code>

### 9.1.96.2 Interfaces for Class `messages_byname<wchar_t>`

An LSB conforming implementation shall provide the generic methods for Class `std::messages_byname<wchar_t>` specified in [Table 9-273](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-273 libstdc++ - Class `messages_byname<wchar_t>` Function Interfaces**

<code>messages_byname&lt;wchar_t&gt;::~messages_byname()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>messages_byname&lt;wchar_t&gt;::~messages_byname()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>messages_byname&lt;wchar_t&gt;::~messages_byname()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::messages\_byname<wchar\_t> specified in [Table 9-274](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-274 libstdc++ - Class messages\_byname<wchar\_t> Data Interfaces**

typeinfo for messages_byname<wchar_t>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for messages_byname<wchar_t>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for messages_byname<wchar_t>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.97 Class numpunct<char>

### 9.1.97.1 Class data for numpunct<char>

The virtual table for the std::numpunct<char> class is described by [Table 9-275](#)

**Table 9-275 Primary vtable for numpunct<char>**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for numpunct<char>
vfunc[0]:	numpunct<char>::~numpunct()
vfunc[1]:	numpunct<char>::~numpunct()
vfunc[2]:	numpunct<char>::do_decimal_point() const
vfunc[3]:	numpunct<char>::do_thousands_sep() const
vfunc[4]:	numpunct<char>::do_grouping() const
vfunc[5]:	numpunct<char>::do_truename() const
vfunc[6]:	numpunct<char>::do_falsename() const

The Run Time Type Information for the std::numpunct<char> class is described by [Table 9-276](#)

**Table 9-276 typeinfo for numpunct<char>**

Base Vtable	vtable for <u>_cxxabiv1::__si_class_type_info</u>
Name	typeinfo name for numpunct<char>

### 9.1.97.2 Interfaces for Class numpunct<char>

An LSB conforming implementation shall provide the generic methods for Class std::numpunct<char> specified in [Table 9-277](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-277 libstdc++ - Class numpunct<char> Function Interfaces**

numpunct<char>::do_grouping() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<char>::do_truename() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

numpunct<char>::do_falsename() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<char>::decimal_point() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<char>::thousands_sep() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<char>::do_decimal_point() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<char>::do_thousands_sep() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<char>::grouping() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<char>::truename() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<char>::falsename() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<char>::_M_initialize_numpunct(__locale_struct*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<char>::~numpunct()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<char>::~numpunct()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<char>::~numpunct()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::numpunct<char> specified in [Table 9-278](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-278 libstdc++ - Class numpunct<char> Data Interfaces**

guard variable for numpunct<char>::id(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
numpunct<char>::id(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
typeinfo for numpunct<char>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for numpunct<char>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for numpunct<char>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.98 Class numpunct<wchar\_t>

### 9.1.98.1 Class data for numpunct<wchar\_t>

The virtual table for the std::numpunct<wchar\_t> class is described by [Table 9-279](#)

**Table 9-279 Primary vtable for numpunct<wchar\_t>**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for numpunct<wchar_t>
vfunc[0]:	numpunct<wchar_t>::~numpunct()
vfunc[1]:	numpunct<wchar_t>::~numpunct()
vfunc[2]:	numpunct<wchar_t>::do_decimal_p oint() const
vfunc[3]:	numpunct<wchar_t>::do_thousan ds_sep() const
vfunc[4]:	numpunct<wchar_t>::do_grouping() const
vfunc[5]:	numpunct<wchar_t>::do_truename( ) const

vfunc[6]:	numpunct<wchar_t>::do_falsename() const
-----------	--

The Run Time Type Information for the std::numpunct<wchar\_t> class is described by [Table 9-280](#)

**Table 9-280 typeinfo for numpunct<wchar\_t>**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for numpunct<wchar_t>

### 9.1.98.2 Interfaces for Class numpunct<wchar\_t>

An LSB conforming implementation shall provide the generic methods for Class std::numpunct<wchar\_t> specified in [Table 9-281](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-281 libstdc++ - Class numpunct<wchar\_t> Function Interfaces**

numpunct<wchar_t>::do_grouping() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<wchar_t>::do_truename() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<wchar_t>::do_falsename() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<wchar_t>::decimal_point() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<wchar_t>::thousands_sep() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<wchar_t>::do_decimal_point() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<wchar_t>::do_thousands_sep() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<wchar_t>::grouping() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<wchar_t>::truename() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<wchar_t>::falsename() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<wchar_t>::_M_initialize_numpunct(__locale_struct*) (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<wchar_t>::~numpunct()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<wchar_t>::~numpunct()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<wchar_t>::~numpunct()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::numpunct<wchar\_t> specified in [Table 9-282](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-282 libstdc++ - Class numpunct<wchar\_t> Data Interfaces**

guard variable for numpunct<wchar_t>::id(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
numpunct<wchar_t>::id(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
typeinfo for numpunct<wchar_t>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for numpunct<wchar_t>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for numpunct<wchar_t>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.99 Class `numpunct_byname<char>`

### 9.1.99.1 Class data for `numpunct_byname<char>`

The virtual table for the `std::numpunct_byname<char>` class is described by [Table 9-283](#)

**Table 9-283 Primary vtable for `numpunct_byname<char>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>numpunct_byname&lt;char&gt;</code>
vfunc[0]:	<code>numpunct_byname&lt;char&gt;::~numpunct_byname()</code>
vfunc[1]:	<code>numpunct_byname&lt;char&gt;::~numpunct_byname()</code>
vfunc[2]:	<code>numpunct&lt;char&gt;::do_decimal_point() const</code>
vfunc[3]:	<code>numpunct&lt;char&gt;::do_thousands_sep() const</code>
vfunc[4]:	<code>numpunct&lt;char&gt;::do_grouping() const</code>
vfunc[5]:	<code>numpunct&lt;char&gt;::do_truename() const</code>
vfunc[6]:	<code>numpunct&lt;char&gt;::do_falsename() const</code>

The Run Time Type Information for the `std::numpunct_byname<char>` class is described by [Table 9-284](#)

**Table 9-284 typeinfo for `numpunct_byname<char>`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>numpunct_byname&lt;char&gt;</code>

### 9.1.99.2 Interfaces for Class `numpunct_byname<char>`

An LSB conforming implementation shall provide the generic methods for Class `std::numpunct_byname<char>` specified in [Table 9-285](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-285 libstdc++ - Class `numpunct_byname<char>` Function Interfaces**

<code>numpunct_byname&lt;char&gt;::~numpunct_byname()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>numpunct_byname&lt;char&gt;::~numpunct_byname()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>numpunct_byname&lt;char&gt;::~numpunct_byname()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class `std::numpunct_byname<char>` specified in [Table 9-286](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-286 libstdc++ - Class `numpunct_byname<char>` Data Interfaces**

typeinfo for <code>numpunct_byname&lt;char&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for <code>numpunct_byname&lt;char&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for <code>numpunct_byname&lt;char&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.100 Class `numpunct_byname<wchar_t>`

### 9.1.100.1 Class data for `numpunct_byname<wchar_t>`

The virtual table for the `std::numpunct_byname<wchar_t>` class is described by [Table 9-287](#)

**Table 9-287 Primary vtable for `numpunct_byname<wchar_t>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>numpunct_byname&lt;wchar_t&gt;</code>
vfunc[0]:	<code>numpunct_byname&lt;wchar_t&gt;::~numpunct_byname()</code>
vfunc[1]:	<code>numpunct_byname&lt;wchar_t&gt;::~numpunct_byname()</code>
vfunc[2]:	<code>numpunct&lt;wchar_t&gt;::do_decimal_point()</code> const
vfunc[3]:	<code>numpunct&lt;wchar_t&gt;::do_thousands_sep()</code> const
vfunc[4]:	<code>numpunct&lt;wchar_t&gt;::do_grouping()</code> const
vfunc[5]:	<code>numpunct&lt;wchar_t&gt;::do_truename()</code> const
vfunc[6]:	<code>numpunct&lt;wchar_t&gt;::do_falsename()</code> const

The Run Time Type Information for the `std::numpunct_byname<wchar_t>` class is described by [Table 9-288](#)

**Table 9-288 typeinfo for `numpunct_byname<wchar_t>`**

Base Vtable	vtable for <code>_cxxabiv1::_si_class_type_info</code>
Name	typeinfo name for <code>numpunct_byname&lt;wchar_t&gt;</code>

### 9.1.100.2 Interfaces for Class `numpunct_byname<wchar_t>`

An LSB conforming implementation shall provide the generic methods for Class `std::numpunct_byname<wchar_t>` specified in [Table 9-289](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-289 libstdcxx - Class `numpunct_byname<wchar_t>` Function Interfaces**

<code>numpunct_byname&lt;wchar_t&gt;::~numpunct_byname()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>numpunct_byname&lt;wchar_t&gt;::~numpunct_byname()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>numpunct_byname&lt;wchar_t&gt;::~numpunct_byname()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class `std::numpunct_byname<wchar_t>` specified in [Table 9-290](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-290 libstdcxx - Class `numpunct_byname<wchar_t>` Data Interfaces**

<code>typeinfo</code> for <code>numpunct_byname&lt;wchar_t&gt;(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>
<code>typeinfo name</code> for <code>numpunct_byname&lt;wchar_t&gt;(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>
<code>vtable</code> for <code>numpunct_byname&lt;wchar_t&gt;(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>

## 9.1.101 Class `__codecvt_abstract_base<char, char, __mbstate_t>`

### 9.1.101.1 Interfaces for Class `__codecvt_abstract_base<char, char, __mbstate_t>`

No external methods are defined for libstdcxx - Class `std::__codecvt_abstract_base<char, char, __mbstate_t>` in this part of the specification. See also the relevant architecture specific part of this specification.

## 9.1.102 Class `__codecvt_abstract_base<wchar_t, char, __mbstate_t>`

### 9.1.102.1 Class data for `__codecvt_abstract_base<wchar_t, char, __mbstate_t>`

The virtual table for the `std::__codecvt_abstract_base<wchar_t, char, __mbstate_t>` class is described by [Table 9-291](#)

**Table 9-291 Primary vtable for `__codecvt_abstract_base<wchar_t, char, __mbstate_t>`**

Base Offset	0
Virtual Base Offset	0
RTTI	<code>typeinfo</code> for <code>__codecvt_abstract_base&lt;wchar_t, char, __mbstate_t&gt;</code>
vfunc[0]:	NULL or <code>__codecvt_abstract_base&lt;wchar_t, char, __mbstate_t&gt;::~__codecvt_abstract_b ase()</code>
vfunc[1]:	NULL or

	<code>__codecvt_abstract_base&lt;wchar_t, char, __mbstate_t&gt;::~__codecvt_abstract_b ase()</code>
vfunc[2]:	<code>__cxa_pure_virtual</code>
vfunc[3]:	<code>__cxa_pure_virtual</code>
vfunc[4]:	<code>__cxa_pure_virtual</code>
vfunc[5]:	<code>__cxa_pure_virtual</code>
vfunc[6]:	<code>__cxa_pure_virtual</code>
vfunc[7]:	<code>__cxa_pure_virtual</code>
vfunc[8]:	<code>__cxa_pure_virtual</code>

### 9.1.102.2 Interfaces for Class `__codecvt_abstract_base<wchar_t, char, __mbstate_t>`

No external methods are defined for libstdcxx - Class `std::__codecvt_abstract_base<wchar_t, char, __mbstate_t>` in this part of the specification. See also the relevant architecture specific part of this specification.

An LSB conforming implementation shall provide the generic data interfaces for Class `std::__codecvt_abstract_base<wchar_t, char, __mbstate_t>` specified in [Table 9-292](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-292 libstdcxx - Class `__codecvt_abstract_base<wchar_t, char,  
__mbstate_t>` Data Interfaces**

typeinfo for <code>__codecvt_abstract_base&lt;wchar_t, char, __mbstate_t&gt;(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>
typeinfo name for <code>__codecvt_abstract_base&lt;wchar_t, char, __mbstate_t&gt;(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>
vtable for <code>__codecvt_abstract_base&lt;wchar_t, char, __mbstate_t&gt;(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>

## 9.1.103 Class `codecvt_base`

### 9.1.103.1 Class data for `codecvt_base`

The Run Time Type Information for the `std::codecvt_base` class is described by [Table 9-293](#)

**Table 9-293 typeinfo for `codecvt_base`**

Base Vtable	vtable for <code>__cxxabiv1::__class_type_info</code>
Name	typeinfo name for <code>codecvt_base</code>

### 9.1.103.2 Interfaces for Class `codecvt_base`

No external methods are defined for libstdcxx - Class `std::codecvt_base` in this part of the specification. See also the relevant architecture specific part of this specification.

An LSB conforming implementation shall provide the generic data interfaces for

Class std::codecvt\_base specified in [Table 9-294](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-294 libstdc++ - Class codecvt\_base Data Interfaces**

typeinfo for codecvt_base(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for codecvt_base(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.104 Class codecvt<char, char, \_\_mbstate\_t>

### 9.1.104.1 Class data for codecvt<char, char, \_\_mbstate\_t>

The virtual table for the std::codecvt<char, char, \_\_mbstate\_t> class is described by [Table 9-295](#)

**Table 9-295 Primary vtable for codecvt<char, char, \_\_mbstate\_t>**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for codecvt<char, char, __mbstate_t>
vfunc[0]:	codecvt<char, char, __mbstate_t>::~codecvt()
vfunc[1]:	codecvt<char, char, __mbstate_t>::~codecvt()
vfunc[2]:	codecvt<char, char, __mbstate_t>::do_out(__mbstate_t&, char const*, char const*, char const*&, char*, char*, char*&) const
vfunc[3]:	codecvt<char, char, __mbstate_t>::do_unshift(__mbstate_t&, char*, char*, char*&) const
vfunc[4]:	codecvt<char, char, __mbstate_t>::do_in(__mbstate_t&, char const*, char const*, char const*&, char*, char*, char*&) const
vfunc[5]:	codecvt<char, char, __mbstate_t>::do_encoding() const
vfunc[6]:	codecvt<char, char, __mbstate_t>::do_always_noconv() const
vfunc[7]:	See The Architecture Specific Specification
vfunc[8]:	codecvt<char, char, __mbstate_t>::do_max_length() const

The Run Time Type Information for the std::codecvt<char, char, \_\_mbstate\_t> class is described by [Table 9-296](#)

**Table 9-296 typeinfo for codecvt<char, char, \_\_mbstate\_t>**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for codecvt<char, char, __mbstate_t>

### 9.1.104.2 Class data for \_\_codecvt\_abstract\_base<char, char, \_\_mbstate\_t>

The virtual table for the std::\_\_codecvt\_abstract\_base<char, char, \_\_mbstate\_t> class is described by [Table 9-297](#)

**Table 9-297 Primary vtable for \_\_codecvt\_abstract\_base<char, char, \_\_mbstate\_t>**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for __codecvt_abstract_base<char, char, __mbstate_t>
vfunc[0]:	NULL or __codecvt_abstract_base<char, char, __mbstate_t>::~__codecvt_abstract_base()
vfunc[1]:	NULL or __codecvt_abstract_base<char, char, __mbstate_t>::~__codecvt_abstract_base()
vfunc[2]:	<u>__cxa_pure_virtual</u>
vfunc[3]:	<u>__cxa_pure_virtual</u>
vfunc[4]:	<u>__cxa_pure_virtual</u>
vfunc[5]:	<u>__cxa_pure_virtual</u>
vfunc[6]:	<u>__cxa_pure_virtual</u>
vfunc[7]:	<u>__cxa_pure_virtual</u>
vfunc[8]:	<u>__cxa_pure_virtual</u>

### 9.1.104.3 Interfaces for Class codecvt<char, char, \_\_mbstate\_t>

An LSB conforming implementation shall provide the generic methods for Class std::codecvt<char, char, \_\_mbstate\_t> specified in [Table 9-298](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-298 libstdcxx - Class codecvt<char, char, \_\_mbstate\_t> Function Interfaces**

codecvt<char, char, __mbstate_t>::do_unshift(__mbstate_t&, char*, char*, char*&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
codecvt<char, char, __mbstate_t>::do_encoding() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
codecvt<char, char, __mbstate_t>::do_max_length() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

codecvt<char, char, __mbstate_t>::do_always_noconv() const(GLIBCXX_3.4) [ISOcxx]
codecvt<char, char, __mbstate_t>::do_in(__mbstate_t&, char const*, char const*, char const*&, char*, char*, char*&) const(GLIBCXX_3.4) [ISOcxx]
codecvt<char, char, __mbstate_t>::do_out(__mbstate_t&, char const*, char const*, char const*&, char*, char*, char*&) const(GLIBCXX_3.4) [ISOcxx]
codecvt<char, char, __mbstate_t>::~codecvt()(GLIBCXX_3.4) [ISOcxx]
codecvt<char, char, __mbstate_t>::~codecvt()(GLIBCXX_3.4) [ISOcxx]
codecvt<char, char, __mbstate_t>::~codecvt()(GLIBCXX_3.4) [ISOcxx]

An LSB conforming implementation shall provide the generic data interfaces for Class std::codecvt<char, char, \_\_mbstate\_t> specified in [Table 9-299](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-299 libstdc++ - Class codecvt<char, char, \_\_mbstate\_t> Data Interfaces**

codecvt<char, char, __mbstate_t>::id(GLIBCXX_3.4) [ISOcxx]
typeinfo for __codecvt_abstract_base<char, char, __mbstate_t>(GLIBCXX_3.4) [Cxxabi]
typeinfo for codecvt<char, char, __mbstate_t>(GLIBCXX_3.4) [Cxxabi]
typeinfo name for __codecvt_abstract_base<char, char, __mbstate_t>(GLIBCXX_3.4) [Cxxabi]
typeinfo name for codecvt<char, char, __mbstate_t>(GLIBCXX_3.4) [Cxxabi]
vtable for __codecvt_abstract_base<char, char, __mbstate_t>(GLIBCXX_3.4) [Cxxabi]
vtable for codecvt<char, char, __mbstate_t>(GLIBCXX_3.4) [Cxxabi]

## 9.1.105 Class codecvt<wchar\_t, char, \_\_mbstate\_t>

### 9.1.105.1 Class data for codecvt<wchar\_t, char, \_\_mbstate\_t>

The virtual table for the std::codecvt<wchar\_t, char, \_\_mbstate\_t> class is described by [Table 9-300](#)

**Table 9-300 Primary vtable for codecvt<wchar\_t, char, \_\_mbstate\_t>**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for codecvt<wchar_t, char, __mbstate_t>
vfunc[0]:	codecvt<wchar_t, char, __mbstate_t>::~codecvt()
vfunc[1]:	codecvt<wchar_t, char, __mbstate_t>::~codecvt()
vfunc[2]:	codecvt<wchar_t, char, __mbstate_t>::do_out(__mbstate_t&, wchar_t const*, wchar_t const*, wchar_t const*&, char*, char*, char*)

	char*&) const
vfunc[3]:	codecvt<wchar_t, char, __mbstate_t>::do_unshift(__mbstate_t&, char*, char*, char*&) const
vfunc[4]:	codecvt<wchar_t, char, __mbstate_t>::do_in(__mbstate_t&, char const*, char const*, char const*&, wchar_t*, wchar_t*, wchar_t*&) const
vfunc[5]:	codecvt<wchar_t, char, __mbstate_t>::do_encoding() const
vfunc[6]:	codecvt<wchar_t, char, __mbstate_t>::do_always_noconv() const
vfunc[7]:	See The Architecture Specific Specification
vfunc[8]:	codecvt<wchar_t, char, __mbstate_t>::do_max_length() const

The Run Time Type Information for the std::codecvt<wchar\_t, char, \_\_mbstate\_t> class is described by [Table 9-301](#)

**Table 9-301 typeinfo for codecvt<wchar\_t, char, \_\_mbstate\_t>**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for codecvt<wchar_t, char, __mbstate_t>

### 9.1.105.2 Interfaces for Class codecvt<wchar\_t, char, \_\_mbstate\_t>

An LSB conforming implementation shall provide the generic methods for Class std::codecvt<wchar\_t, char, \_\_mbstate\_t> specified in [Table 9-302](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-302 libstdc++ - Class codecvt<wchar\_t, char, \_\_mbstate\_t> Function Interfaces**

codecvt<wchar_t, char, __mbstate_t>::do_unshift(__mbstate_t&, char*, char*, char*&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
codecvt<wchar_t, char, __mbstate_t>::do_encoding() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
codecvt<wchar_t, char, __mbstate_t>::do_max_length() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
codecvt<wchar_t, char, __mbstate_t>::do_always_noconv() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
codecvt<wchar_t, char, __mbstate_t>::do_in(__mbstate_t&, char const*, char const*, char const*&, wchar_t*, wchar_t*, wchar_t*&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
codecvt<wchar_t, char, __mbstate_t>::do_out(__mbstate_t&, wchar_t const*,

wchar_t const*, wchar_t const*&, char*, char*, char*&) const(GLIBCXX_3.4) [ISOCXX]
codecvt<wchar_t, char, __mbstate_t>::~codecvt()(GLIBCXX_3.4) [ISOCXX]
codecvt<wchar_t, char, __mbstate_t>::~codecvt()(GLIBCXX_3.4) [ISOCXX]
codecvt<wchar_t, char, __mbstate_t>::~codecvt()(GLIBCXX_3.4) [ISOCXX]

An LSB conforming implementation shall provide the generic data interfaces for Class std::codecvt<wchar\_t, char, \_\_mbstate\_t> specified in [Table 9-303](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-303 libstdcxx - Class codecvt<wchar\_t, char, \_\_mbstate\_t> Data Interfaces**

codecvt<wchar_t, char, __mbstate_t>::id(GLIBCXX_3.4) [ISOCXX]
typeinfo for codecvt<wchar_t, char, __mbstate_t>(GLIBCXX_3.4) [CXXABI]
typeinfo name for codecvt<wchar_t, char, __mbstate_t>(GLIBCXX_3.4) [CXXABI]
vtable for codecvt<wchar_t, char, __mbstate_t>(GLIBCXX_3.4) [CXXABI]

## 9.1.106 Class `codecvt_byname<char, char, __mbstate_t>`

### 9.1.106.1 Class data for `codecvt_byname<char, char, __mbstate_t>`

The virtual table for the std::codecvt\_byname<char, char, \_\_mbstate\_t> class is described by [Table 9-304](#)

**Table 9-304 Primary vtable for `codecvt_byname<char, char, __mbstate_t>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>codecvt_byname&lt;char, char, __mbstate_t&gt;</code>
vfunc[0]:	<code>codecvt_byname&lt;char, char, __mbstate_t&gt;::~codecvt_byname()</code>
vfunc[1]:	<code>codecvt_byname&lt;char, char, __mbstate_t&gt;::~codecvt_byname()</code>
vfunc[2]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::do_out(__mbstate_t&amp;, char const*, char const*, char const*&amp;, char*, char*, char*&amp;) const</code>
vfunc[3]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::do_unshift(__mbstate_t&amp;, char*, char*, char*&amp;) const</code>
vfunc[4]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::do_in(__mbstate_t&amp;, char const*, char const*, char const*&amp;, char*, char*, char*&amp;) const</code>
vfunc[5]:	<code>codecvt&lt;char, char,</code>

	<code>__mbstate_t&gt;::do_encoding() const</code>
vfunc[6]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::do_always_noconv() const</code>
vfunc[7]:	See The Architecture Specific Specification
vfunc[8]:	<code>codecvt&lt;char, char, __mbstate_t&gt;::do_max_length() const</code>

The Run Time Type Information for the `std::codecvt_byname<char, char, __mbstate_t>` class is described by [Table 9-305](#)

**Table 9-305 typeinfo for `codecvt_byname<char, char, __mbstate_t>`**

Base Vtable	vtable for <code>_cxxabiv1::_si_class_type_info</code>
Name	typeinfo name for <code>codecvt_byname&lt;char, char, __mbstate_t&gt;</code>

### 9.1.106.2 Interfaces for Class `codecvt_byname<char, char, __mbstate_t>`

An LSB conforming implementation shall provide the generic methods for Class `std::codecvt_byname<char, char, __mbstate_t>` specified in [Table 9-306](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-306 libstdc++ - Class `codecvt_byname<char, char, __mbstate_t>` Function Interfaces**

<code>codecvt_byname&lt;char, char, __mbstate_t&gt;::~codecvt_byname()</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>codecvt_byname&lt;char, char, __mbstate_t&gt;::~codecvt_byname()</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>codecvt_byname&lt;char, char, __mbstate_t&gt;::~codecvt_byname()</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class `std::codecvt_byname<char, char, __mbstate_t>` specified in [Table 9-307](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-307 libstdc++ - Class `codecvt_byname<char, char, __mbstate_t>` Data Interfaces**

typeinfo for <code>codecvt_byname&lt;char, char, __mbstate_t&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for <code>codecvt_byname&lt;char, char, __mbstate_t&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for <code>codecvt_byname&lt;char, char, __mbstate_t&gt;</code> (GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.107 Class `codecvt_byname<wchar_t, char, __mbstate_t>`

### 9.1.107.1 Class data for `codecvt_byname<wchar_t, char, __mbstate_t>`

The virtual table for the `std::codecvt_byname<wchar_t, char, __mbstate_t>` class is described by [Table 9-308](#)

**Table 9-308 Primary vtable for `codecvt_byname<wchar_t, char, __mbstate_t>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>codecvt_byname&lt;wchar_t, char, __mbstate_t&gt;</code>
vfunc[0]:	<code>codecvt_byname&lt;wchar_t, char, __mbstate_t&gt;::~codecvt_byname()</code>
vfunc[1]:	<code>codecvt_byname&lt;wchar_t, char, __mbstate_t&gt;::~codecvt_byname()</code>
vfunc[2]:	<code>codecvt&lt;wchar_t, char, __mbstate_t&gt;::do_out(__mbstate_t&amp;, wchar_t const*, wchar_t const*, wchar_t const*&amp;, char*, char*, char*&amp;) const</code>
vfunc[3]:	<code>codecvt&lt;wchar_t, char, __mbstate_t&gt;::do_unshift(__mbstate_t&amp;, char*, char*, char*&amp;) const</code>
vfunc[4]:	<code>codecvt&lt;wchar_t, char, __mbstate_t&gt;::do_in(__mbstate_t&amp;, char const*, char const*, char const*&amp;, wchar_t*, wchar_t*, wchar_t*&amp;) const</code>
vfunc[5]:	<code>codecvt&lt;wchar_t, char, __mbstate_t&gt;::do_encoding() const</code>
vfunc[6]:	<code>codecvt&lt;wchar_t, char, __mbstate_t&gt;::do_always_noconv() const</code>
vfunc[7]:	See The Architecture Specific Specification
vfunc[8]:	<code>codecvt&lt;wchar_t, char, __mbstate_t&gt;::do_max_length() const</code>

The Run Time Type Information for the `std::codecvt_byname<wchar_t, char, __mbstate_t>` class is described by [Table 9-309](#)

**Table 9-309 typeinfo for `codecvt_byname<wchar_t, char, __mbstate_t>`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
-------------	--

Name	typeinfo name for codecvt_byname<wchar_t, char, __mbstate_t>
------	--

### 9.1.107.2 Class data for collate\_byname<wchar\_t>

The virtual table for the std::collate\_byname<wchar\_t> class is described by [Table 9-310](#)

**Table 9-310 Primary vtable for collate\_byname<wchar\_t>**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for collate_byname<wchar_t>
vfunc[0]:	collate_byname<wchar_t>::~collate_byname()
vfunc[1]:	collate_byname<wchar_t>::~collate_byname()
vfunc[2]:	collate<wchar_t>::do_compare(wchar_t const*, wchar_t const*, wchar_t const*, wchar_t const*) const
vfunc[3]:	collate<wchar_t>::do_transform(wchar_t const*, wchar_t const*) const
vfunc[4]:	collate<wchar_t>::do_hash(wchar_t const*, wchar_t const*) const

The Run Time Type Information for the std::collate\_byname<wchar\_t> class is described by [Table 9-311](#)

**Table 9-311 typeinfo for collate\_byname<wchar\_t>**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for collate_byname<wchar_t>

### 9.1.107.3 Interfaces for Class codecvt\_byname<wchar\_t, char, \_\_mbstate\_t>

An LSB conforming implementation shall provide the generic methods for Class std::codecvt\_byname<wchar\_t, char, \_\_mbstate\_t> specified in [Table 9-312](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-312 libstdc++ - Class codecvt\_byname<wchar\_t, char, \_\_mbstate\_t> Function Interfaces**

codecvt_byname<wchar_t, char, __mbstate_t>::~codecvt_byname() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
codecvt_byname<wchar_t, char, __mbstate_t>::~codecvt_byname() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
codecvt_byname<wchar_t, char, __mbstate_t>::~codecvt_byname()

(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
collate_byname<wchar_t>::~collate_byname()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
collate_byname<wchar_t>::~collate_byname()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
collate_byname<wchar_t>::~collate_byname()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::codecvt\_byname<wchar\_t, char, \_\_mbstate\_t> specified in [Table 9-313](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-313 libstdcxx - Class codecvt\_byname<wchar\_t, char, \_\_mbstate\_t> Data Interfaces**

typeinfo for codecvt_byname<wchar_t, char, __mbstate_t>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo for collate_byname<wchar_t>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for codecvt_byname<wchar_t, char, __mbstate_t>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for collate_byname<wchar_t>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for codecvt_byname<wchar_t, char, __mbstate_t>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for collate_byname<wchar_t>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.108 Class collate<char>

### 9.1.108.1 Class data for collate<char>

The virtual table for the std::collate<char> class is described by [Table 9-314](#)

**Table 9-314 Primary vtable for collate<char>**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for collate<char>
vfunc[0]:	collate<char>::~collate()
vfunc[1]:	collate<char>::~collate()
vfunc[2]:	collate<char>::do_compare(char const*, char const*, char const*, char const*) const
vfunc[3]:	collate<char>::do_transform(char const*, char const*) const
vfunc[4]:	collate<char>::do_hash(char const*, char const*) const

The Run Time Type Information for the std::collate<char> class is described by [Table 9-315](#)

**Table 9-315 typeinfo for collate<char>**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
-------------	--

Name	typeinfo name for collate<char>
------	---------------------------------

### 9.1.108.2 Interfaces for Class `collate<char>`

An LSB conforming implementation shall provide the generic methods for Class `std::collate<char>` specified in [Table 9-316](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-316 libstdcxx - Class `collate<char>` Function Interfaces**

<code>collate&lt;char&gt;::_M_compare(char const*, char const*) const(GLIBCXX_3.4) [ISOCXX]</code>
<code>collate&lt;char&gt;::do_compare(char const*, char const*, char const*, char const*) const(GLIBCXX_3.4) [ISOCXX]</code>
<code>collate&lt;char&gt;::do_transform(char const*, char const*) const(GLIBCXX_3.4) [ISOCXX]</code>
<code>collate&lt;char&gt;::hash(char const*, char const*) const(GLIBCXX_3.4) [ISOCXX]</code>
<code>collate&lt;char&gt;::compare(char const*, char const*, char const*, char const*) const(GLIBCXX_3.4) [ISOCXX]</code>
<code>collate&lt;char&gt;::do_hash(char const*, char const*) const(GLIBCXX_3.4) [ISOCXX]</code>
<code>collate&lt;char&gt;::transform(char const*, char const*) const(GLIBCXX_3.4) [ISOCXX]</code>
<code>collate&lt;char&gt;::~collate()(GLIBCXX_3.4) [ISOCXX]</code>
<code>collate&lt;char&gt;::~collate()(GLIBCXX_3.4) [ISOCXX]</code>
<code>collate&lt;char&gt;::~collate()(GLIBCXX_3.4) [ISOCXX]</code>

An LSB conforming implementation shall provide the generic data interfaces for Class `std::collate<char>` specified in [Table 9-317](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-317 libstdcxx - Class `collate<char>` Data Interfaces**

<code>guard variable for collate&lt;char&gt;::id(GLIBCXX_3.4) [CXXABI]</code>
<code>collate&lt;char&gt;::id(GLIBCXX_3.4) [ISOCXX]</code>
<code>typeinfo for collate&lt;char&gt;(GLIBCXX_3.4) [CXXABI]</code>
<code>typeinfo name for collate&lt;char&gt;(GLIBCXX_3.4) [CXXABI]</code>
<code>vtable for collate&lt;char&gt;(GLIBCXX_3.4) [CXXABI]</code>

### 9.1.109 Class `collate<wchar_t>`

#### 9.1.109.1 Class data for `collate<wchar_t>`

The virtual table for the `std::collate<wchar_t>` class is described by [Table 9-318](#)

**Table 9-318 Primary vtable for `collate<wchar_t>`**

Base Offset	0
Virtual Base Offset	0
RTTI	<code>typeinfo for collate&lt;wchar_t&gt;</code>
vfunc[0]:	<code>collate&lt;wchar_t&gt;::~collate()</code>

vfunc[1]:	collate<wchar_t>::~collate()
vfunc[2]:	collate<wchar_t>::do_compare(wchar_t const*, wchar_t const*, wchar_t const*, wchar_t const*) const
vfunc[3]:	collate<wchar_t>::do_transform(wchar_t const*, wchar_t const*) const
vfunc[4]:	collate<wchar_t>::do_hash(wchar_t const*, wchar_t const*) const

The Run Time Type Information for the std::collate<wchar\_t> class is described by [Table 9-319](#)

**Table 9-319 typeinfo for collate<wchar\_t>**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for collate<wchar_t>

### 9.1.109.2 Interfaces for Class collate<wchar\_t>

An LSB conforming implementation shall provide the generic methods for Class std::collate<wchar\_t> specified in [Table 9-320](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-320 libstdcxx - Class collate<wchar\_t> Function Interfaces**

collate<wchar_t>::_M_compare(wchar_t const*, wchar_t const*) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
collate<wchar_t>::do_compare(wchar_t const*, wchar_t const*, wchar_t const*, wchar_t const*) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
collate<wchar_t>::do_transform(wchar_t const*, wchar_t const*) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
collate<wchar_t>::hash(wchar_t const*, wchar_t const*) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
collate<wchar_t>::compare(wchar_t const*, wchar_t const*, wchar_t const*, wchar_t const*) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
collate<wchar_t>::do_hash(wchar_t const*, wchar_t const*) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
collate<wchar_t>::transform(wchar_t const*, wchar_t const*) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
collate<wchar_t>::~collate()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
collate<wchar_t>::~collate()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
collate<wchar_t>::~collate()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::collate<wchar\_t> specified in [Table 9-321](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-321 libstdcxx - Class collate<wchar\_t> Data Interfaces**

guard variable for collate<wchar_t>::id(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
collate<wchar_t>::id(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

typeinfo for collate<wchar_t>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for collate<wchar_t>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for collate<wchar_t>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.110 Class `collate_byname<char>`

### 9.1.110.1 Class data for `collate_byname<char>`

The virtual table for the `std::collate_byname<char>` class is described by [Table 9-322](#)

**Table 9-322 Primary vtable for `collate_byname<char>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>collate_byname&lt;char&gt;</code>
vfunc[0]:	<code>collate_byname&lt;char&gt;::~collate_byname()</code>
vfunc[1]:	<code>collate_byname&lt;char&gt;::~collate_byname()</code>
vfunc[2]:	<code>collate&lt;char&gt;::do_compare(char const*, char const*, char const*, char const*) const</code>
vfunc[3]:	<code>collate&lt;char&gt;::do_transform(char const*, char const*) const</code>
vfunc[4]:	<code>collate&lt;char&gt;::do_hash(char const*, char const*) const</code>

The Run Time Type Information for the `std::collate_byname<char>` class is described by [Table 9-323](#)

**Table 9-323 typeinfo for `collate_byname<char>`**

Base Vtable	vtable for <code>_cxxabiv1::_si_class_type_info</code>
Name	typeinfo name for <code>collate_byname&lt;char&gt;</code>

### 9.1.110.2 Interfaces for Class `collate_byname<char>`

An LSB conforming implementation shall provide the generic methods for Class `std::collate_byname<char>` specified in [Table 9-324](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-324 libstdc++ - Class `collate_byname<char>` Function Interfaces**

<code>collate_byname&lt;char&gt;::~collate_byname()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>collate_byname&lt;char&gt;::~collate_byname()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>collate_byname&lt;char&gt;::~collate_byname()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class `std::collate_byname<char>` specified in [Table 9-325](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-325 libstdc++ - Class collate\_byname<char> Data Interfaces**

typeinfo for collate_byname<char>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for collate_byname<char>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for collate_byname<char>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.111 Class collate\_byname<wchar\_t>

### 9.1.111.1 Interfaces for Class collate\_byname<wchar\_t>

No external methods are defined for libstdc++ - Class std::collate\_byname<wchar\_t> in this part of the specification. See also the relevant architecture specific part of this specification.

## 9.1.112 Class time\_base

### 9.1.112.1 Class data for time\_base

The Run Time Type Information for the std::time\_base class is described by [Table 9-326](#)

**Table 9-326 typeinfo for time\_base**

Base Vtable	vtable for <u>_cxxabiv1::__class_type_info</u>
Name	typeinfo name for time_base

### 9.1.112.2 Interfaces for Class time\_base

No external methods are defined for libstdc++ - Class std::time\_base in this part of the specification. See also the relevant architecture specific part of this specification.

An LSB conforming implementation shall provide the generic data interfaces for Class std::time\_base specified in [Table 9-327](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-327 libstdc++ - Class time\_base Data Interfaces**

typeinfo for time_base(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for time_base(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.113 Class time\_get\_byname<char, istreambuf\_iterator<char, char\_traits<char>>>

### 9.1.113.1 Class data for time\_get\_byname<char, istreambuf\_iterator<char, char\_traits<char>>>

The virtual table for the std::time\_get\_byname<char, std::istreambuf\_iterator<char, std::char\_traits<char>>> class is described by [Table 9-328](#)

**Table 9-328 Primary vtable for time\_get\_byname<char, istreambuf\_iterator<char, char\_traits<char>>>**

Base Offset	0
-------------	---

Virtual Base Offset	0
RTTI	typeinfo for time_get_byname<char, istreambuf_iterator<char, char_traits<char> >>
vfunc[0]:	time_get_byname<char, istreambuf_iterator<char, char_traits<char> >>::time_get_byname()
vfunc[1]:	time_get_byname<char, istreambuf_iterator<char, char_traits<char> >>::time_get_byname()
vfunc[2]:	time_get<char, istreambuf_iterator<char, char_traits<char> >>::do_date_order() const
vfunc[3]:	time_get<char, istreambuf_iterator<char, char_traits<char> >>::do_get_time(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, tm*) const
vfunc[4]:	time_get<char, istreambuf_iterator<char, char_traits<char> >>::do_get_date(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, tm*) const
vfunc[5]:	time_get<char, istreambuf_iterator<char, char_traits<char> >>::do_get_weekday(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, tm*) const
vfunc[6]:	time_get<char, istreambuf_iterator<char, char_traits<char> >>::do_get_monthname(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, tm*) const
vfunc[7]:	time_get<char, istreambuf_iterator<char,

	char_traits<char> > >::do_get_year(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, tm*) const
--	--

The Run Time Type Information for the `std::time_get_byname<char, std::istreambuf_iterator<char, std::char_traits<char> >>` class is described by [Table 9-329](#)

**Table 9-329 typeinfo for time\_get\_byname<char, istreambuf\_iterator<char, char\_traits<char> >>**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>time_get_byname&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;&gt;</code>

### 9.1.113.2 Interfaces for Class `time_get_byname<char, istreambuf_iterator<char, char_traits<char> >>`

An LSB conforming implementation shall provide the generic methods for Class `std::time_get_byname<char, std::istreambuf_iterator<char, std::char_traits<char> >>` specified in [Table 9-330](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-330 libstdcxx - Class `time_get_byname<char, istreambuf_iterator<char, char_traits<char> >>` Function Interfaces**

<code>time_get_byname&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;&gt;::time_get_byname()(GLIBCXX_3.4)</code> <a href="#">[ISO CXX]</a>
<code>time_get_byname&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;&gt;::~time_get_byname()(GLIBCXX_3.4)</code> <a href="#">[ISO CXX]</a>
<code>time_get_byname&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;&gt;::~time_get_byname()(GLIBCXX_3.4)</code> <a href="#">[ISO CXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class `std::time_get_byname<char, std::istreambuf_iterator<char, std::char_traits<char> >>` specified in [Table 9-331](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-331 libstdcxx - Class `time_get_byname<char, istreambuf_iterator<char, char_traits<char> >>` Data Interfaces**

<code>typeinfo for time_get_byname&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;&gt;(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>
<code>typeinfo name for time_get_byname&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;&gt;(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>
<code>vtable for time_get_byname&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;&gt;(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>

**9.1.114 Class `time_get_byname<wchar_t,  
istreambuf_iterator<wchar_t, char_traits<wchar_t> >`**  
**>**

**9.1.114.1 Class data for `time_get_byname<wchar_t,  
istreambuf_iterator<wchar_t, char_traits<wchar_t> >>`**

The virtual table for the `std::time_get_byname<wchar_t, std::istreambuf_iterator<wchar_t, std::char_traits<wchar_t> >>` class is described by [Table 9-332](#)

**Table 9-332 Primary vtable for `time_get_byname<wchar_t,  
istreambuf_iterator<wchar_t, char_traits<wchar_t> >>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>time_get_byname&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;&gt;</code>
vfunc[0]:	<code>time_get_byname&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;::~time_get_byname()</code>
vfunc[1]:	<code>time_get_byname&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;::~time_get_byname()</code>
vfunc[2]:	<code>time_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;::do_date_order() const</code>
vfunc[3]:	<code>time_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;::do_get_time(istreambuf_iterator&lt; wchar_t, char_traits&lt;wchar_t&gt; &gt;, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, _Ios_Iostate&amp;, tm*) const</code>
vfunc[4]:	<code>time_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;::do_get_date(istreambuf_iterator&lt; wchar_t, char_traits&lt;wchar_t&gt; &gt;, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, _Ios_Iostate&amp;, tm*) const</code>
vfunc[5]:	<code>time_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;</code>

	>::do_get_weekday(istreambuf_iterator<wchar_t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, _Ios_Iostate&, tm*) const
vfunc[6]:	time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>> >::do_get_mmonthname(istreambuf_iterator<wchar_t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, _Ios_Iostate&, tm*) const
vfunc[7]:	time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>> >::do_get_year(istreambuf_iterator<wchar_t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, _Ios_Iostate&, tm*) const

The Run Time Type Information for the `std::time_get_byname<wchar_t, std::istreambuf_iterator<wchar_t, std::char_traits<wchar_t>>>` class is described by [Table 9-333](#)

**Table 9-333 typeinfo for `time_get_byname<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>`**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>time_get_byname&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;</code>

#### **9.1.114.2 Interfaces for Class `time_get_byname<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>`**

An LSB conforming implementation shall provide the generic methods for Class `std::time_get_byname<wchar_t, std::istreambuf_iterator<wchar_t, std::char_traits<wchar_t>>>` specified in [Table 9-334](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-334 libstdcxx - Class `time_get_byname<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>` Function Interfaces**

<code>time_get_byname&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;::~time_get_byname()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>time_get_byname&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;::~time_get_byname()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>time_get_byname&lt;wchar_t, istreambuf_iterator&lt;wchar_t,</code>

char_traits<wchar_t> > >::~time_get_byname()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
--

An LSB conforming implementation shall provide the generic data interfaces for Class std::time\_get\_byname<wchar\_t, std::istreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t> > > specified in [Table 9-335](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-335 libstdc++ - Class time\_get\_byname<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t> > > Data Interfaces**

typeinfo for time_get_byname<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for time_get_byname<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for time_get_byname<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.115 Class time\_put\_byname<char, ostreambuf\_iterator<char, char\_traits<char> > >

### 9.1.115.1 Class data for time\_put\_byname<char, ostreambuf\_iterator<char, char\_traits<char> > >

The virtual table for the std::time\_put\_byname<char, std::ostreambuf\_iterator<char, std::char\_traits<char> > > class is described by [Table 9-336](#)

**Table 9-336 Primary vtable for time\_put\_byname<char, ostreambuf\_iterator<char, char\_traits<char> > >**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for time_put_byname<char, ostreambuf_iterator<char, char_traits<char> > >
vfunc[0]:	time_put_byname<char, ostreambuf_iterator<char, char_traits<char> > >::~time_put_byname()
vfunc[1]:	time_put_byname<char, ostreambuf_iterator<char, char_traits<char> > >::~time_put_byname()
vfunc[2]:	time_put<char, ostreambuf_iterator<char, char_traits<char> > >::do_put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, tm const*, char, char) const

The Run Time Type Information for the std::time\_put\_byname<char, std::ostreambuf\_iterator<char, std::char\_traits<char> > > class is described by [Table 9-](#)

337**Table 9-337 typeinfo for time\_put\_byname<char, ostreambuf\_iterator<char, char\_traits<char> > >**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for time_put_byname<char, ostreambuf_iterator<char, char_traits<char> > >

**9.1.115.2 Interfaces for Class time\_put\_byname<char, ostreambuf\_iterator<char, char\_traits<char> > >**

An LSB conforming implementation shall provide the generic methods for Class std::time\_put\_byname<char, std::ostreambuf\_iterator<char, std::char\_traits<char> > > specified in [Table 9-338](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-338 libstdcxx - Class time\_put\_byname<char, ostreambuf\_iterator<char, char\_traits<char> > > Function Interfaces**

time_put_byname<char, ostreambuf_iterator<char, char_traits<char> > >::~time_put_byname()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
time_put_byname<char, ostreambuf_iterator<char, char_traits<char> > >::~time_put_byname()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
time_put_byname<char, ostreambuf_iterator<char, char_traits<char> > >::~time_put_byname()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::time\_put\_byname<char, std::ostreambuf\_iterator<char, std::char\_traits<char> > > specified in [Table 9-339](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-339 libstdcxx - Class time\_put\_byname<char, ostreambuf\_iterator<char, char\_traits<char> > > Data Interfaces**

typeinfo for time_put_byname<char, ostreambuf_iterator<char, char_traits<char> > >(GLIBCXX_3.4) <a href="#">[Cxxabi]</a>
typeinfo name for time_put_byname<char, ostreambuf_iterator<char, char_traits<char> > >(GLIBCXX_3.4) <a href="#">[Cxxabi]</a>
vtable for time_put_byname<char, ostreambuf_iterator<char, char_traits<char> > >(GLIBCXX_3.4) <a href="#">[Cxxabi]</a>

**9.1.116 Class time\_put\_byname<wchar\_t, ostreambuf\_iterator<wchar\_t, char\_traits<wchar\_t> > >****9.1.116.1 Class data for time\_put\_byname<wchar\_t, ostreambuf\_iterator<wchar\_t, char\_traits<wchar\_t> > >**

The virtual table for the std::time\_put\_byname<wchar\_t, std::ostreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t> > > class is described by [Table 9-340](#)

**Table 9-340 Primary vtable for time\_put\_byname<wchar\_t, ostreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>>**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for time_put_byname<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>
vfunc[0]:	time_put_byname<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>> >::~time_put_byname()
vfunc[1]:	time_put_byname<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>> >::~time_put_byname()
vfunc[2]:	time_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>> >::do_put(ostreambuf_iterator<wcha r_t, char_traits<wchar_t> >, ios_base&, wchar_t, tm const*, char, char) const

The Run Time Type Information for the std::time\_put\_byname<wchar\_t, std::ostreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t>>> class is described by [Table 9-341](#)

**Table 9-341 typeinfo for time\_put\_byname<wchar\_t, ostreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>>**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for time_put_byname<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>

### 9.1.116.2 Interfaces for Class time\_put\_byname<wchar\_t, ostreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>>

An LSB conforming implementation shall provide the generic methods for Class std::time\_put\_byname<wchar\_t, std::ostreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t>>> specified in [Table 9-342](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-342 libstdc++ - Class time\_put\_byname<wchar\_t, ostreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>> Function Interfaces**

time_put_byname<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>::~time_put_byname()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
time_put_byname<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>::~time_put_byname()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

time_put_byname<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>::~time_put_byname()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
---

An LSB conforming implementation shall provide the generic data interfaces for Class std::time\_put\_byname<wchar\_t, std::ostreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t>>> specified in [Table 9-343](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-343 libstdcxx - Class time\_put\_byname<wchar\_t, ostreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>> Data Interfaces**

typeinfo for time_put_byname<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for time_put_byname<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for time_put_byname<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.117 Class time\_get<char, istreambuf\_iterator<char, char\_traits<char>>>

### 9.1.117.1 Class data for time\_get<char, istreambuf\_iterator<char, char\_traits<char>>>

The virtual table for the std::time\_get<char, std::istreambuf\_iterator<char, std::char\_traits<char>>> class is described by [Table 9-344](#)

**Table 9-344 Primary vtable for time\_get<char, istreambuf\_iterator<char, char\_traits<char>>>**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for time_get<char, istreambuf_iterator<char, char_traits<char>>>
vfunc[0]:	time_get<char, istreambuf_iterator<char, char_traits<char>>>::~time_get()
vfunc[1]:	time_get<char, istreambuf_iterator<char, char_traits<char>>>::~time_get()
vfunc[2]:	time_get<char, istreambuf_iterator<char, char_traits<char>>>::do_date_order() const
vfunc[3]:	time_get<char, istreambuf_iterator<char, char_traits<char>>>::do_get_time(istreambuf_iterator<char, char_traits<char>>, istreambuf_iterator<char, char_traits<char>>, ios_base&,

	<code>_Ios_Iostate&amp;, tm*) const</code>
vfunc[4]:	<code>time_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; &gt;::do_get_date(istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, ios_base&amp;, _Ios_Iostate&amp;, tm*) const</code>
vfunc[5]:	<code>time_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; &gt;::do_get_weekday(istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, ios_base&amp;, _Ios_Iostate&amp;, tm*) const</code>
vfunc[6]:	<code>time_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; &gt;::do_get_monthname(istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, ios_base&amp;, _Ios_Iostate&amp;, tm*) const</code>
vfunc[7]:	<code>time_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; &gt;::do_get_year(istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, ios_base&amp;, _Ios_Iostate&amp;, tm*) const</code>

### 9.1.117.2 Interfaces for Class `time_get<char, istreambuf_iterator<char, char_traits<char>>`

An LSB conforming implementation shall provide the generic methods for Class `std::time_get<char, std::istreambuf_iterator<char, std::char_traits<char>>>` specified in [Table 9-345](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-345 libstdcxx - Class `time_get<char, istreambuf_iterator<char, char_traits<char>>` Function Interfaces**

<code>time_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;::date_order() const(GLIBCXX_3.4) [ISO CXX]</code>
<code>time_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt; &gt;::do_get_date(istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, ios_base&amp;, _Ios_Iostate&amp;, tm*) const(GLIBCXX_3.4) [ISO CXX]</code>
<code>time_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;</code>

>::do_get_time(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, tm*) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
time_get<char, istreambuf_iterator<char, char_traits<char> > >::do_get_year(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, tm*) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
time_get<char, istreambuf_iterator<char, char_traits<char> > >::get_weekday(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, tm*) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
time_get<char, istreambuf_iterator<char, char_traits<char> > >::do_date_order() const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
time_get<char, istreambuf_iterator<char, char_traits<char> > >::get_monthname(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, tm*) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
time_get<char, istreambuf_iterator<char, char_traits<char> > >::do_get_weekday(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, tm*) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
time_get<char, istreambuf_iterator<char, char_traits<char> > >::do_get_monthname(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, tm*) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
time_get<char, istreambuf_iterator<char, char_traits<char> > >::_M_extract_via_format(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, tm*, char const*) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
time_get<char, istreambuf_iterator<char, char_traits<char> > >::get_date(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, tm*) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
time_get<char, istreambuf_iterator<char, char_traits<char> > >::get_time(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, tm*) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
time_get<char, istreambuf_iterator<char, char_traits<char> > >::get_year(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, tm*) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
time_get<char, istreambuf_iterator<char, char_traits<char> > >::~time_get() (GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
time_get<char, istreambuf_iterator<char, char_traits<char> > >::~time_get() (GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
time_get<char, istreambuf_iterator<char, char_traits<char> > >::~time_get() (GLIBCXX_3.4) <a href="#">[ISO CXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for

Class `std::time_get<char, std::istreambuf_iterator<char, std::char_traits<char> >` specified in [Table 9-346](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-346 libstdcxx - Class `time_get<char, istreambuf_iterator<char, char_traits<char> >` Data Interfaces**

guard variable for <code>time_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;</code> ::id(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
<code>time_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;</code> ::id(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
typeinfo for <code>time_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;</code> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for <code>time_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;</code> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for <code>time_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;</code> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.118 Class `time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> >`

>

### 9.1.118.1 Class data for `time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> >`

The virtual table for the `std::time_get<wchar_t, std::istreambuf_iterator<wchar_t, std::char_traits<wchar_t> >` class is described by [Table 9-347](#)

**Table 9-347 Primary vtable for `time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> >`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>time_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;</code>
vfunc[0]:	<code>time_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;</code> ::~ <code>time_get()</code>
vfunc[1]:	<code>time_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;</code> ::~ <code>time_get()</code>
vfunc[2]:	<code>time_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;</code> :: <code>do_date_order()</code> const
vfunc[3]:	<code>time_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t,</code>

	<code>char_traits&lt;wchar_t&gt; &gt; &gt;::do_get_time(istreambuf_iterator&lt; wchar_t, char_traits&lt;wchar_t&gt; &gt;, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, _Ios_Iostate&amp;, tm*) const</code>
vfunc[4]:	<code>time_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;::do_get_date(istreambuf_iterator&lt; wchar_t, char_traits&lt;wchar_t&gt; &gt;, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, _Ios_Iostate&amp;, tm*) const</code>
vfunc[5]:	<code>time_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;::do_get_weekday(istreambuf_iterator&lt; wchar_t, char_traits&lt;wchar_t&gt; &gt;, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, _Ios_Iostate&amp;, tm*) const</code>
vfunc[6]:	<code>time_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;::do_get_monthname(istreambuf_iterator&lt; wchar_t, char_traits&lt;wchar_t&gt; &gt;, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, _Ios_Iostate&amp;, tm*) const</code>
vfunc[7]:	<code>time_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;::do_get_year(istreambuf_iterator&lt; wchar_t, char_traits&lt;wchar_t&gt; &gt;, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, _Ios_Iostate&amp;, tm*) const</code>

### 9.1.118.2 Interfaces for Class `time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> >>`

An LSB conforming implementation shall provide the generic methods for Class `std::time_get<wchar_t, std::istreambuf_iterator<wchar_t, std::char_traits<wchar_t> >>` specified in [Table 9-348](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-348 libstdc++ - Class time\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>> Function Interfaces**

time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>> >::date_order() const(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>> >::do_get_date(istreambuf_iterator<wchar_t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, _Ios_Iostate&, tm*) const(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>> >::do_get_time(istreambuf_iterator<wchar_t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, _Ios_Iostate&, tm*) const(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>> >::do_get_year(istreambuf_iterator<wchar_t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, _Ios_Iostate&, tm*) const(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>> >::get_weekday(istreambuf_iterator<wchar_t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, _Ios_Iostate&, tm*) const(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>> >::do_date_order() const(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>> >::get_monthname(istreambuf_iterator<wchar_t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, _Ios_Iostate&, tm*) const(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>> >::do_get_monthname(istreambuf_iterator<wchar_t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, _Ios_Iostate&, tm*) const(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>> >::_M_extract_via_format(istreambuf_iterator<wchar_t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, _Ios_Iostate&, tm*, wchar_t const*) const(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>> >::get_date(istreambuf_iterator<wchar_t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, _Ios_Iostate&, tm*) const(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>> >::get_time(istreambuf_iterator<wchar_t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, _Ios_Iostate&, tm*) const(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>> >::get_year(istreambuf_iterator<wchar_t, char_traits<wchar_t>>,

istreambuf_iterator<wchar_t, char_traits<wchar_t> >, ios_base&, _Ios_Iostate&, tm*) const(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >::~time_get()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >::~time_get()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >::~time_get()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::time\_get<wchar\_t, std::istreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t> > > specified in [Table 9-349](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-349 libstdcxx - Class time\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t> > > Data Interfaces**

guard variable for time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >::id(GLIBCXX_3.4) <a href="#">[Cxxabi]</a>
time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >::id(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
typeinfo for time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >::(GLIBCXX_3.4) <a href="#">[Cxxabi]</a>
typeinfo name for time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >::(GLIBCXX_3.4) <a href="#">[Cxxabi]</a>
vtable for time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >::(GLIBCXX_3.4) <a href="#">[Cxxabi]</a>

## 9.1.119 Class time\_put<char, ostreambuf\_iterator<char, char\_traits<char> > >

### 9.1.119.1 Class data for time\_put<char, ostreambuf\_iterator<char, char\_traits<char> > >

The virtual table for the std::time\_put<char, std::ostreambuf\_iterator<char, std::char\_traits<char> > > class is described by [Table 9-350](#)

**Table 9-350 Primary vtable for time\_put<char, ostreambuf\_iterator<char, char\_traits<char> > >**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for time_put<char, ostreambuf_iterator<char, char_traits<char> > >
vfunc[0]:	time_put<char, ostreambuf_iterator<char, char_traits<char> > >::~time_put()
vfunc[1]:	time_put<char, ostreambuf_iterator<char, char_traits<char> > >::~time_put()

vfunc[2]:	time_put<char, ostreambuf_iterator<char, char_traits<char> > >::do_put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, tm const*, char, char) const
-----------	--

The Run Time Type Information for the std::time\_put<char, std::ostreambuf\_iterator<char, std::char\_traits<char> >> class is described by [Table 9-351](#)

**Table 9-351 typeinfo for time\_put<char, ostreambuf\_iterator<char, char\_traits<char> >>**

Base Vtable	vtable for __cxxabiv1::__si_class_t ype_info	
Name	typeinfo name for time_put<char, ostreambuf_iterator<ch ar, char_traits<char> > >	
flags:	8	
basetype:	typeinfo for locale::facet	2
basetype:	typeinfo for time_base	2

### **9.1.119.2 Interfaces for Class time\_put<char, ostreambuf\_iterator<char, char\_traits<char> >>**

An LSB conforming implementation shall provide the generic methods for Class std::time\_put<char, std::ostreambuf\_iterator<char, std::char\_traits<char> >> specified in [Table 9-352](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-352 libstdc++ - Class time\_put<char, ostreambuf\_iterator<char, char\_traits<char> >> Function Interfaces**

time_put<char, ostreambuf_iterator<char, char_traits<char> > >::put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, tm const*, char const*, char const*) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>	
time_put<char, ostreambuf_iterator<char, char_traits<char> > >::put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, tm const*, char, char) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>	
time_put<char, ostreambuf_iterator<char, char_traits<char> > >::do_put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, tm const*, char, char) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>	
time_put<char, ostreambuf_iterator<char, char_traits<char> >>::~time_put() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>	
time_put<char, ostreambuf_iterator<char, char_traits<char> >>::~time_put() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>	
time_put<char, ostreambuf_iterator<char, char_traits<char> >>::~time_put() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>	

An LSB conforming implementation shall provide the generic data interfaces for Class `std::time_put<char, std::ostreambuf_iterator<char, std::char_traits<char>>` specified in [Table 9-353](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-353 libstdc++ - Class `time_put<char, ostreambuf_iterator<char, char_traits<char>>` Data Interfaces**

guard variable for <code>time_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;</code> ::id(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
<code>time_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;</code> ::id(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>typeinfo</code> for <code>time_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;</code> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
<code>typeinfo</code> name for <code>time_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;</code> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for <code>time_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;</code> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

### **9.1.120 Class `time_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>`**

&gt;

#### **9.1.120.1 Class data for `time_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>`**

The virtual table for the `std::time_put<wchar_t, std::ostreambuf_iterator<wchar_t, std::char_traits<wchar_t>>` class is described by [Table 9-354](#)

**Table 9-354 Primary vtable for `time_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>`**

Base Offset	0
Virtual Base Offset	0
RTTI	<code>typeinfo</code> for <code>time_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code>
vfunc[0]:	<code>time_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code> ::~ <code>time_put()</code>
vfunc[1]:	<code>time_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code> ::~ <code>time_put()</code>
vfunc[2]:	<code>time_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code> :: <code>do_put(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;,</code>

	ios_base&, wchar_t, tm const*, char, char) const
--	--

The Run Time Type Information for the `std::time_put<wchar_t, std::ostreambuf_iterator<wchar_t, std::char_traits<wchar_t>>>` class is described by [Table 9-355](#)

**Table 9-355 typeinfo for time\_put<wchar\_t, ostreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>>**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info	
Name	typeinfo name for time_put<wchar_t, ostreambuf_iterator<w char_t, char_traits<wchar_t> >	
flags:	8	
basetype:	typeinfo for locale::facet	2
basetype:	typeinfo for time_base	2

### 9.1.120.2 Interfaces for Class `time_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>`

An LSB conforming implementation shall provide the generic methods for Class `std::time_put<wchar_t, std::ostreambuf_iterator<wchar_t, std::char_traits<wchar_t>>>` specified in [Table 9-356](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-356 libstdc++ - Class `time_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>` Function Interfaces**

time_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>::put(ostreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, wchar_t, tm const*, wchar_t const*, wchar_t const*) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
time_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>::put(ostreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, wchar_t, tm const*, char, char) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
time_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>::do_put(ostreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, wchar_t, tm const*, char, char) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
time_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>::~time_put()(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
time_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>::~time_put()(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
time_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>::~time_put()(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class `std::time_put<wchar_t, std::ostreambuf_iterator<wchar_t, std::char_traits<wchar_t>>>` specified in [Table 9-357](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-357 libstdc++ - Class `time_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>` Data Interfaces**

guard variable for <code>time_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;::id(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>
<code>time_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;::id(GLIBCXX_3.4)</code> <a href="#">[ISOcxx]</a>
typeinfo for <code>time_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>
typeinfo name for <code>time_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>
vtable for <code>time_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;&gt;(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>

## 9.1.121 Class `moneypunct<char, false>`

### 9.1.121.1 Class data for `moneypunct<char, false>`

The virtual table for the `std::moneypunct<char, false>` class is described by [Table 9-358](#)

**Table 9-358 Primary vtable for `moneypunct<char, false>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>moneypunct&lt;char, false&gt;</code>
vfunc[0]:	<code>moneypunct&lt;char, false&gt;::~moneypunct()</code>
vfunc[1]:	<code>moneypunct&lt;char, false&gt;::~moneypunct()</code>
vfunc[2]:	<code>moneypunct&lt;char, false&gt;::do_decimal_point() const</code>
vfunc[3]:	<code>moneypunct&lt;char, false&gt;::do_thousands_sep() const</code>
vfunc[4]:	<code>moneypunct&lt;char, false&gt;::do_grouping() const</code>
vfunc[5]:	<code>moneypunct&lt;char, false&gt;::do_curr_symbol() const</code>
vfunc[6]:	<code>moneypunct&lt;char, false&gt;::do_positive_sign() const</code>
vfunc[7]:	<code>moneypunct&lt;char, false&gt;::do_negative_sign() const</code>
vfunc[8]:	<code>moneypunct&lt;char, false&gt;::do_frac_digits() const</code>

vfunc[9]:	moneypunct<char, false>::do_pos_format() const
vfunc[10]:	moneypunct<char, false>::do_neg_format() const

### 9.1.121.2 Interfaces for Class moneypunct<char, false>

An LSB conforming implementation shall provide the generic methods for Class std::moneypunct<char, false> specified in [Table 9-359](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-359 libstdc++ - Class moneypunct<char, false> Function Interfaces**

moneypunct<char, false>::neg_format() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, false>::pos_format() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, false>::curr_symbol() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, false>::do_grouping() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, false>::frac_digits() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, false>::decimal_point() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, false>::do_neg_format() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, false>::do_pos_format() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, false>::negative_sign() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, false>::positive_sign() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, false>::thousands_sep() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, false>::do_curr_symbol() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, false>::do_frac_digits() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, false>::do_decimal_point() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, false>::do_negative_sign() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, false>::do_positive_sign() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, false>::do_thousands_sep() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, false>::grouping() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, false>::_M_initialize_moneypunct(__locale_struct*, char const*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, false>::~moneypunct()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, false>::~moneypunct()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, false>::~moneypunct()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::moneypunct<char, false> specified in [Table 9-360](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-360 libstdc++ - Class moneypunct<char, false> Data Interfaces**

guard variable for moneypunct<char, false>::id(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
moneypunct<char, false>::id(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

<code>moneypunct&lt;char, false&gt;::intl(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>typeinfo for moneypunct&lt;char, false&gt;(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>
<code>typeinfo name for moneypunct&lt;char, false&gt;(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>
<code>vtable for moneypunct&lt;char, false&gt;(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>

## 9.1.122 Class `moneypunct<char, true>`

### 9.1.122.1 Class data for `moneypunct<char, true>`

The virtual table for the `std::moneypunct<char, true>` class is described by [Table 9-361](#)

**Table 9-361 Primary vtable for `moneypunct<char, true>`**

Base Offset	0
Virtual Base Offset	0
RTTI	<code>typeinfo for moneypunct&lt;char, true&gt;</code>
<code>vfunc[0]:</code>	<code>moneypunct&lt;char, true&gt;::~moneypunct()</code>
<code>vfunc[1]:</code>	<code>moneypunct&lt;char, true&gt;::~moneypunct()</code>
<code>vfunc[2]:</code>	<code>moneypunct&lt;char, true&gt;::do_decimal_point() const</code>
<code>vfunc[3]:</code>	<code>moneypunct&lt;char, true&gt;::do_thousands_sep() const</code>
<code>vfunc[4]:</code>	<code>moneypunct&lt;char, true&gt;::do_grouping() const</code>
<code>vfunc[5]:</code>	<code>moneypunct&lt;char, true&gt;::do_curr_symbol() const</code>
<code>vfunc[6]:</code>	<code>moneypunct&lt;char, true&gt;::do_positive_sign() const</code>
<code>vfunc[7]:</code>	<code>moneypunct&lt;char, true&gt;::do_negative_sign() const</code>
<code>vfunc[8]:</code>	<code>moneypunct&lt;char, true&gt;::do_frac_digits() const</code>
<code>vfunc[9]:</code>	<code>moneypunct&lt;char, true&gt;::do_pos_format() const</code>
<code>vfunc[10]:</code>	<code>moneypunct&lt;char, true&gt;::do_neg_format() const</code>

### 9.1.122.2 Interfaces for Class `moneypunct<char, true>`

An LSB conforming implementation shall provide the generic methods for Class `std::moneypunct<char, true>` specified in [Table 9-362](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-362 libstdc++ - Class `moneypunct<char, true>` Function Interfaces**

<code>moneypunct&lt;char, true&gt;::neg_format() const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
---

moneypunct<char, true>::pos_format() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, true>::curr_symbol() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, true>::do_grouping() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, true>::frac_digits() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, true>::decimal_point() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, true>::do_neg_format() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, true>::do_pos_format() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, true>::negative_sign() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, true>::positive_sign() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, true>::thousands_sep() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, true>::do_curr_symbol() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, true>::do_frac_digits() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, true>::do_decimal_point() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, true>::do_negative_sign() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, true>::do_positive_sign() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, true>::do_thousands_sep() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, true>::grouping() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, true>::_M_initialize_moneypunct(__locale_struct*, char const*)(GLIBCXX_3.4) <a href="#">[ISOCXXI]</a>
moneypunct<char, true>::~moneypunct()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, true>::~moneypunct()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, true>::~moneypunct()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::moneypunct<char, true> specified in [Table 9-363](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-363 libstdc++ - Class moneypunct<char, true> Data Interfaces**

guard variable for moneypunct<char, true>::id(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
moneypunct<char, true>::id(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<char, true>::intl(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
typeinfo for moneypunct<char, true>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for moneypunct<char, true>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for moneypunct<char, true>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.123 Class moneypunct<wchar\_t, false>

### 9.1.123.1 Class data for moneypunct<wchar\_t, false>

The virtual table for the std::moneypunct<wchar\_t, false> class is described by [Table 9-364](#)

**Table 9-364 Primary vtable for moneypunct<wchar\_t, false>**

Base Offset	0
-------------	---

Virtual Base Offset	0
RTTI	typeinfo for moneypunct<wchar_t, false>
vfunc[0]:	moneypunct<wchar_t, false>::~moneypunct()
vfunc[1]:	moneypunct<wchar_t, false>::~moneypunct()
vfunc[2]:	moneypunct<wchar_t, false>::do_decimal_point() const
vfunc[3]:	moneypunct<wchar_t, false>::do_thousands_sep() const
vfunc[4]:	moneypunct<wchar_t, false>::do_grouping() const
vfunc[5]:	moneypunct<wchar_t, false>::do_curr_symbol() const
vfunc[6]:	moneypunct<wchar_t, false>::do_positive_sign() const
vfunc[7]:	moneypunct<wchar_t, false>::do_negative_sign() const
vfunc[8]:	moneypunct<wchar_t, false>::do_frac_digits() const
vfunc[9]:	moneypunct<wchar_t, false>::do_pos_format() const
vfunc[10]:	moneypunct<wchar_t, false>::do_neg_format() const

### 9.1.123.2 Interfaces for Class `moneypunct<wchar_t, false>`

An LSB conforming implementation shall provide the generic methods for Class `std::moneypunct<wchar_t, false>` specified in [Table 9-365](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-365 libstdcxx - Class `moneypunct<wchar_t, false>` Function Interfaces**

<code>moneypunct&lt;wchar_t, false&gt;::neg_format() const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>moneypunct&lt;wchar_t, false&gt;::pos_format() const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>moneypunct&lt;wchar_t, false&gt;::curr_symbol() const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>moneypunct&lt;wchar_t, false&gt;::do_grouping() const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>moneypunct&lt;wchar_t, false&gt;::frac_digits() const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>moneypunct&lt;wchar_t, false&gt;::decimal_point() const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>moneypunct&lt;wchar_t, false&gt;::do_neg_format() const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>moneypunct&lt;wchar_t, false&gt;::do_pos_format() const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>moneypunct&lt;wchar_t, false&gt;::negative_sign() const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>moneypunct&lt;wchar_t, false&gt;::positive_sign() const(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

moneypunct<wchar_t, false>::thousands_sep() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, false>::do_curr_symbol() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, false>::do_frac_digits() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, false>::do_decimal_point() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, false>::do_negative_sign() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, false>::do_positive_sign() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, false>::do_thousands_sep() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, false>::grouping() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, false>::_M_initialize_moneypunct(__locale_struct*, char const*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, false>::~moneypunct()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, false>::~moneypunct()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, false>::~moneypunct()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::moneypunct<wchar\_t, false> specified in [Table 9-366](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-366 libstdc++ - Class moneypunct<wchar\_t, false> Data Interfaces**

guard variable for moneypunct<wchar_t, false>::id(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
moneypunct<wchar_t, false>::id(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, false>::intl(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
typeinfo for moneypunct<wchar_t, false>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for moneypunct<wchar_t, false>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for moneypunct<wchar_t, false>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.124 Class moneypunct<wchar\_t, true>

### 9.1.124.1 Class data for moneypunct<wchar\_t, true>

The virtual table for the std::moneypunct<wchar\_t, true> class is described by [Table 9-367](#)

**Table 9-367 Primary vtable for moneypunct<wchar\_t, true>**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for moneypunct<wchar_t, true>
vfunc[0]:	moneypunct<wchar_t, true>::~moneypunct()

vfunc[1]:	moneypunct<wchar_t, true>::~moneypunct()
vfunc[2]:	moneypunct<wchar_t, true>::do_decimal_point() const
vfunc[3]:	moneypunct<wchar_t, true>::do_thousands_sep() const
vfunc[4]:	moneypunct<wchar_t, true>::do_grouping() const
vfunc[5]:	moneypunct<wchar_t, true>::do_curr_symbol() const
vfunc[6]:	moneypunct<wchar_t, true>::do_positive_sign() const
vfunc[7]:	moneypunct<wchar_t, true>::do_negative_sign() const
vfunc[8]:	moneypunct<wchar_t, true>::do_frac_digits() const
vfunc[9]:	moneypunct<wchar_t, true>::do_pos_format() const
vfunc[10]:	moneypunct<wchar_t, true>::do_neg_format() const

### 9.1.124.2 Interfaces for Class moneypunct<wchar\_t, true>

An LSB conforming implementation shall provide the generic methods for Class std::moneypunct<wchar\_t, true> specified in [Table 9-368](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-368 libstdc++ - Class moneypunct<wchar\_t, true> Function Interfaces**

moneypunct<wchar_t, true>::neg_format() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, true>::pos_format() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, true>::curr_symbol() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, true>::do_grouping() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, true>::frac_digits() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, true>::decimal_point() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, true>::do_neg_format() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, true>::do_pos_format() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, true>::negative_sign() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, true>::positive_sign() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, true>::thousands_sep() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, true>::do_curr_symbol() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, true>::do_frac_digits() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, true>::do_decimal_point() const(GLIBCXX_3.4)

<a href="#">[ISOCXX]</a>
moneypunct<wchar_t, true>::do_negative_sign() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, true>::do_positive_sign() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, true>::do_thousands_sep() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, true>::grouping() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, true>::_M_initialize_moneypunct(__locale_struct*, char const*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, true>::~moneypunct()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, true>::~moneypunct()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, true>::~moneypunct()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::moneypunct<wchar\_t, true> specified in [Table 9-369](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-369 libstdc++ - Class moneypunct<wchar\_t, true> Data Interfaces**

guard variable for moneypunct<wchar_t, true>::id(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
moneypunct<wchar_t, true>::id(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, true>::intl(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
typeinfo for moneypunct<wchar_t, true>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for moneypunct<wchar_t, true>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for moneypunct<wchar_t, true>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.125 Class moneypunct\_byname<char, false>

### 9.1.125.1 Class data for moneypunct\_byname<char, false>

The virtual table for the std::moneypunct\_byname<char, false> class is described by [Table 9-370](#)

**Table 9-370 Primary vtable for moneypunct\_byname<char, false>**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for moneypunct_byname<char, false>
vfunc[0]:	moneypunct_byname<char, false>::~moneypunct_byname()
vfunc[1]:	moneypunct_byname<char, false>::~moneypunct_byname()
vfunc[2]:	moneypunct<char, false>::do_decimal_point() const
vfunc[3]:	moneypunct<char, false>::do_thousands_sep() const

vfunc[4]:	moneypunct<char, false>::do_grouping() const
vfunc[5]:	moneypunct<char, false>::do_curr_symbol() const
vfunc[6]:	moneypunct<char, false>::do_positive_sign() const
vfunc[7]:	moneypunct<char, false>::do_negative_sign() const
vfunc[8]:	moneypunct<char, false>::do_frac_digits() const
vfunc[9]:	moneypunct<char, false>::do_pos_format() const
vfunc[10]:	moneypunct<char, false>::do_neg_format() const

The Run Time Type Information for the std::moneypunct\_byname<char, false> class is described by [Table 9-371](#)

**Table 9-371 typeinfo for moneypunct\_byname<char, false>**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for moneypunct_byname<char, false>

### 9.1.125.2 Interfaces for Class moneypunct\_byname<char, false>

An LSB conforming implementation shall provide the generic methods for Class std::moneypunct\_byname<char, false> specified in [Table 9-372](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-372 libstdc++ - Class moneypunct\_byname<char, false> Function Interfaces**

moneypunct_byname<char, false>::~moneypunct_byname()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct_byname<char, false>::~moneypunct_byname()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct_byname<char, false>::~moneypunct_byname()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::moneypunct\_byname<char, false> specified in [Table 9-373](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-373 libstdc++ - Class moneypunct\_byname<char, false> Data Interfaces**

moneypunct_byname<char, false>::intl(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
typeinfo for moneypunct_byname<char, false>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for moneypunct_byname<char, false>(GLIBCXX_3.4)

**[CXXABI]**vtable for moneypunct\_byname<char, false>(GLIBCXX\_3.4) **[CXXABI]****9.1.126 Class moneypunct\_byname<char, true>****9.1.126.1 Class data for moneypunct\_byname<char, true>**

The virtual table for the std::moneypunct\_byname<char, true> class is described by [Table 9-374](#)

**Table 9-374 Primary vtable for moneypunct\_byname<char, true>**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for moneypunct_byname<char, true>
vfunc[0]:	moneypunct_byname<char, true>::~moneypunct_byname()
vfunc[1]:	moneypunct_byname<char, true>::~moneypunct_byname()
vfunc[2]:	moneypunct<char, true>::do_decimal_point() const
vfunc[3]:	moneypunct<char, true>::do_thousands_sep() const
vfunc[4]:	moneypunct<char, true>::do_grouping() const
vfunc[5]:	moneypunct<char, true>::do_curr_symbol() const
vfunc[6]:	moneypunct<char, true>::do_positive_sign() const
vfunc[7]:	moneypunct<char, true>::do_negative_sign() const
vfunc[8]:	moneypunct<char, true>::do_frac_digits() const
vfunc[9]:	moneypunct<char, true>::do_pos_format() const
vfunc[10]:	moneypunct<char, true>::do_neg_format() const

The Run Time Type Information for the std::moneypunct\_byname<char, true> class is described by [Table 9-375](#)

**Table 9-375 typeinfo for moneypunct\_byname<char, true>**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for moneypunct_byname<char, true>

### 9.1.126.2 Interfaces for Class `moneypunct_byname<char, true>`

An LSB conforming implementation shall provide the generic methods for Class `std::moneypunct_byname<char, true>` specified in [Table 9-376](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-376 libstdc++ - Class `moneypunct_byname<char, true>` Function Interfaces**

<code>moneypunct_byname&lt;char, true&gt;::~moneypunct_byname()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>moneypunct_byname&lt;char, true&gt;::~moneypunct_byname()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>moneypunct_byname&lt;char, true&gt;::~moneypunct_byname()(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class `std::moneypunct_byname<char, true>` specified in [Table 9-377](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-377 libstdc++ - Class `moneypunct_byname<char, true>` Data Interfaces**

<code>moneypunct_byname&lt;char, true&gt;::intl(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>typeinfo for moneypunct_byname&lt;char, true&gt;(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>
<code>typeinfo name for moneypunct_byname&lt;char, true&gt;(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>
<code>vtable for moneypunct_byname&lt;char, true&gt;(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>

### 9.1.127 Class `moneypunct_byname<wchar_t, false>`

#### 9.1.127.1 Class data for `moneypunct_byname<wchar_t, false>`

The virtual table for the `std::moneypunct_byname<wchar_t, false>` class is described by [Table 9-378](#)

**Table 9-378 Primary vtable for `moneypunct_byname<wchar_t, false>`**

Base Offset	0
Virtual Base Offset	0
RTTI	<code>typeinfo for moneypunct_byname&lt;wchar_t, false&gt;</code>
<code>vfunc[0]:</code>	<code>moneypunct_byname&lt;wchar_t, false&gt;::~moneypunct_byname()</code>
<code>vfunc[1]:</code>	<code>moneypunct_byname&lt;wchar_t, false&gt;::~moneypunct_byname()</code>
<code>vfunc[2]:</code>	<code>moneypunct&lt;wchar_t, false&gt;::do_decimal_point() const</code>
<code>vfunc[3]:</code>	<code>moneypunct&lt;wchar_t, false&gt;::do_thousands_sep() const</code>
<code>vfunc[4]:</code>	<code>moneypunct&lt;wchar_t,</code>

	false>::do_grouping() const
vfunc[5]:	moneypunct<wchar_t, false>::do_curr_symbol() const
vfunc[6]:	moneypunct<wchar_t, false>::do_positive_sign() const
vfunc[7]:	moneypunct<wchar_t, false>::do_negative_sign() const
vfunc[8]:	moneypunct<wchar_t, false>::do_frac_digits() const
vfunc[9]:	moneypunct<wchar_t, false>::do_pos_format() const
vfunc[10]:	moneypunct<wchar_t, false>::do_neg_format() const

The Run Time Type Information for the std::moneypunct\_byname<wchar\_t, false> class is described by [Table 9-379](#)

**Table 9-379 typeinfo for moneypunct\_byname<wchar\_t, false>**

Base Vtable	vtable for _cxxabiv1::_si_class_type_info
Name	typeinfo name for moneypunct_byname<wchar_t, false>

### 9.1.127.2 Interfaces for Class moneypunct\_byname<wchar\_t, false>

An LSB conforming implementation shall provide the generic methods for Class std::moneypunct\_byname<wchar\_t, false> specified in [Table 9-380](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-380 libstdcxx - Class moneypunct\_byname<wchar\_t, false> Function Interfaces**

moneypunct_byname<wchar_t, false>::~moneypunct_byname() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct_byname<wchar_t, false>::~moneypunct_byname() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct_byname<wchar_t, false>::~moneypunct_byname() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::moneypunct\_byname<wchar\_t, false> specified in [Table 9-381](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-381 libstdcxx - Class moneypunct\_byname<wchar\_t, false> Data Interfaces**

moneypunct_byname<wchar_t, false>::intl(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
typeinfo for moneypunct_byname<wchar_t, false>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for moneypunct_byname<wchar_t, false>(GLIBCXX_3.4)

[\[CXXABI\]](#)vtable for moneypunct\_byname<wchar\_t, false>(GLIBCXX\_3.4) [\[CXXABI\]](#)**9.1.128 Class moneypunct\_byname<wchar\_t, true>****9.1.128.1 Class data for moneypunct\_byname<wchar\_t, true>**

The virtual table for the std::moneypunct\_byname<wchar\_t, true> class is described by [Table 9-382](#)

**Table 9-382 Primary vtable for moneypunct\_byname<wchar\_t, true>**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for moneypunct_byname<wchar_t, true>
vfunc[0]:	moneypunct_byname<wchar_t, true>::~moneypunct_byname()
vfunc[1]:	moneypunct_byname<wchar_t, true>::~moneypunct_byname()
vfunc[2]:	moneypunct<wchar_t, true>::do_decimal_point() const
vfunc[3]:	moneypunct<wchar_t, true>::do_thousands_sep() const
vfunc[4]:	moneypunct<wchar_t, true>::do_grouping() const
vfunc[5]:	moneypunct<wchar_t, true>::do_curr_symbol() const
vfunc[6]:	moneypunct<wchar_t, true>::do_positive_sign() const
vfunc[7]:	moneypunct<wchar_t, true>::do_negative_sign() const
vfunc[8]:	moneypunct<wchar_t, true>::do_frac_digits() const
vfunc[9]:	moneypunct<wchar_t, true>::do_pos_format() const
vfunc[10]:	moneypunct<wchar_t, true>::do_neg_format() const

The Run Time Type Information for the std::moneypunct\_byname<wchar\_t, true> class is described by [Table 9-383](#)

**Table 9-383 typeinfo for moneypunct\_byname<wchar\_t, true>**

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for moneypunct_byname<wchar_t, true>

### **9.1.128.2 Interfaces for Class `moneypunct_byname<wchar_t, true>`**

An LSB conforming implementation shall provide the generic methods for Class `std::moneypunct_byname<wchar_t, true>` specified in [Table 9-384](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-384 libstdcxx - Class `moneypunct_byname<wchar_t, true>` Function Interfaces**

<code>moneypunct_byname&lt;wchar_t, true&gt;::~moneypunct_byname()</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>moneypunct_byname&lt;wchar_t, true&gt;::~moneypunct_byname()</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
<code>moneypunct_byname&lt;wchar_t, true&gt;::~moneypunct_byname()</code> (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class `std::moneypunct_byname<wchar_t, true>` specified in [Table 9-385](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-385 libstdcxx - Class `moneypunct_byname<wchar_t, true>` Data Interfaces**

<code>moneypunct_byname&lt;wchar_t, true&gt;::intl(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>typeinfo</code> for <code>moneypunct_byname&lt;wchar_t, true&gt;(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>
<code>typeinfo</code> name for <code>moneypunct_byname&lt;wchar_t, true&gt;(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>
<code>vtable</code> for <code>moneypunct_byname&lt;wchar_t, true&gt;(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>

### **9.1.129 Class `money_base`**

#### **9.1.129.1 Class data for `money_base`**

The Run Time Type Information for the `std::money_base` class is described by [Table 9-386](#)

**Table 9-386 typeinfo for `money_base`**

Base Vtable	<code>vtable for __cxxabiv1::__class_type_info</code>
Name	<code>typeinfo</code> name for <code>money_base</code>

#### **9.1.129.2 Interfaces for Class `money_base`**

An LSB conforming implementation shall provide the generic methods for Class `std::money_base` specified in [Table 9-387](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-387 libstdcxx - Class `money_base` Function Interfaces**

<code>money_base::__S_construct_pattern(char, char, char)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
--

An LSB conforming implementation shall provide the generic data interfaces for Class `std::money_base` specified in [Table 9-388](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-388 libstdc++ - Class money\_base Data Interfaces**

money_base:: S_default_pattern(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
money_base:: S_atoms(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
typeinfo for money_base(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for money_base(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

### 9.1.130 Class `money_get<char, istreambuf_iterator<char, char_traits<char>>>`

#### 9.1.130.1 Class data for `money_get<char, istreambuf_iterator<char, char_traits<char>>>`

The virtual table for the `std::money_get<char, std::istreambuf_iterator<char, std::char_traits<char>>>` class is described by [Table 9-389](#)

**Table 9-389 Primary vtable for `money_get<char, istreambuf_iterator<char, char_traits<char>>>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>money_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;</code>
vfunc[0]:	<code>money_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;::~money_get()</code>
vfunc[1]:	<code>money_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;::~money_get()</code>
vfunc[2]:	<code>money_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;::do_get(istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, bool, ios_base&amp;, _Ios_Iostate&amp;, long double&amp;) const</code>
vfunc[3]:	<code>money_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;&gt;::do_get(istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt;&gt;&amp;) const</code>

The Run Time Type Information for the `std::money_get<char, std::istreambuf_iterator<char, std::char_traits<char>>>` class is described by [Table 9-390](#)

**Table 9-390 typeinfo for money\_get<char, istreambuf\_iterator<char, char\_traits<char> >>**

Base Vtable	vtable for _cxxabiv1::__si_class_type_info
Name	typeinfo name for money_get<char, istreambuf_iterator<char, char_traits<char> >>

### 9.1.130.2 Interfaces for Class money\_get<char, istreambuf\_iterator<char, char\_traits<char> >>

An LSB conforming implementation shall provide the generic methods for Class std::money\_get<char, std::istreambuf\_iterator<char, std::char\_traits<char> >> specified in [Table 9-391](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-391 libstdcxx - Class money\_get<char, istreambuf\_iterator<char, char\_traits<char> >> Function Interfaces**

istreambuf_iterator<char, char_traits<char> > money_get<char, istreambuf_iterator<char, char_traits<char> >>::_M_extract<false>(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, basic_string<char, char_traits<char>, allocator<char> >&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
istreambuf_iterator<char, char_traits<char> > money_get<char, istreambuf_iterator<char, char_traits<char> >>::_M_extract<true>(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, basic_string<char, char_traits<char>, allocator<char> >&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
money_get<char, istreambuf_iterator<char, char_traits<char> >>::get(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, bool, ios_base&, _Ios_Iostate&, basic_string<char, char_traits<char>, allocator<char> >&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
money_get<char, istreambuf_iterator<char, char_traits<char> >>::get(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, bool, ios_base&, _Ios_Iostate&, long double&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
money_get<char, istreambuf_iterator<char, char_traits<char> >>::do_get(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, bool, ios_base&, _Ios_Iostate&, basic_string<char, char_traits<char>, allocator<char> >&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
money_get<char, istreambuf_iterator<char, char_traits<char> >>::do_get(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, bool, ios_base&, _Ios_Iostate&, long double&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
money_get<char, istreambuf_iterator<char, char_traits<char> >>::~money_get()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

money_get<char, istreambuf_iterator<char, char_traits<char> > >::~money_get()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
money_get<char, istreambuf_iterator<char, char_traits<char> > >::~money_get()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::money\_get<char, std::istreambuf\_iterator<char, std::char\_traits<char> >> specified in [Table 9-392](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-392 libstdc++ - Class money\_get<char, istreambuf\_iterator<char, char\_traits<char> >> Data Interfaces**

guard variable for money_get<char, istreambuf_iterator<char, char_traits<char> >>::id(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
money_get<char, istreambuf_iterator<char, char_traits<char> >>::id(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
typeinfo for money_get<char, istreambuf_iterator<char, char_traits<char> >>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for money_get<char, istreambuf_iterator<char, char_traits<char> >>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for money_get<char, istreambuf_iterator<char, char_traits<char> >>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

### 9.1.131 Class money\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t> >>

#### 9.1.131.1 Class data for money\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t> >>

The virtual table for the std::money\_get<wchar\_t, std::istreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t> >> class is described by [Table 9-393](#)

**Table 9-393 Primary vtable for money\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t> >>**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> >>
vfunc[0]:	money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> >>::~money_get()
vfunc[1]:	money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> >>::money_get()

vfunc[2]:	money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>> >::do_get(istreambuf_iterator<wchar _t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, bool, ios_base&, _Ios_Iostate&, long double&) const
vfunc[3]:	money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>> >::do_get(istreambuf_iterator<wchar _t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, bool, ios_base&, _Ios_Iostate&, basic_string<wchar_t, char_traits<wchar_t>,  allocator<wchar_t>>&) const

The Run Time Type Information for the std::money\_get<wchar\_t, std::istreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t>>> class is described by [Table 9-394](#)

**Table 9-394 typeinfo for money\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>>**

Base Vtable	vtable for <code>_cxxabiv1::_si_class_type_info</code>
Name	typeinfo name for money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>

### 9.1.131.2 Interfaces for Class money\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>>

An LSB conforming implementation shall provide the generic methods for Class std::money\_get<wchar\_t, std::istreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t>>> specified in [Table 9-395](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-395 libstdcxx - Class money\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>> Function Interfaces**

istreambuf_iterator<wchar_t, char_traits<wchar_t>> money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>> >::_M_extract<false>(istreambuf_iterator<wchar_t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, _Ios_Iostate&, basic_string<char, char_traits<char>, allocator<char>>&) const(GLIBCXX_3.4) [ <a href="#">ISO CXX</a> ]
istreambuf_iterator<wchar_t, char_traits<wchar_t>> money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>

>:_M_extract<true>(istreambuf_iterator<wchar_t, char_traits<wchar_t> >, istreambuf_iterator<wchar_t, char_traits<wchar_t> >, ios_base&, _Ios_Iostate&, basic_string<char, char_traits<char>, allocator<char> >&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >::get(istreambuf_iterator<wchar_t, char_traits<wchar_t> >, istreambuf_iterator<wchar_t, char_traits<wchar_t> >, bool, ios_base&, _Ios_Iostate&, basic_string<wchar_t, char_traits<wchar_t> >, allocator<wchar_t> >&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >::get(istreambuf_iterator<wchar_t, char_traits<wchar_t> >, istreambuf_iterator<wchar_t, char_traits<wchar_t> >, bool, ios_base&, _Ios_Iostate&, long double&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >::do_get(istreambuf_iterator<wchar_t, char_traits<wchar_t> >, istreambuf_iterator<wchar_t, char_traits<wchar_t> >, bool, ios_base&, _Ios_Iostate&, basic_string<wchar_t, char_traits<wchar_t> >, allocator<wchar_t> >&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >::do_get(istreambuf_iterator<wchar_t, char_traits<wchar_t> >, istreambuf_iterator<wchar_t, char_traits<wchar_t> >, bool, ios_base&, _Ios_Iostate&, long double&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >::~money_get()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >::~money_get()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >::~money_get()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::money\_get<wchar\_t, std::istreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t> > > specified in [Table 9-396](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-396 libstdcxx - Class money\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t> > > Data Interfaces**

guard variable for money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >::id(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >::id(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
typeinfo for money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >::(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >::(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for money_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t> > >::(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## **9.1.132 Class `money_put<char, ostreambuf_iterator<char, char_traits<char> >>`**

### **9.1.132.1 Class data for `money_put<char, ostreambuf_iterator<char, char_traits<char> >>`**

The virtual table for the `std::money_put<char, std::ostreambuf_iterator<char, std::char_traits<char> >>` class is described by [Table 9-397](#)

**Table 9-397 Primary vtable for `money_put<char, ostreambuf_iterator<char, char_traits<char> >>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;&gt;</code>
vfunc[0]:	<code>money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;&gt;::~money_put()</code>
vfunc[1]:	<code>money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;&gt;::~money_put()</code>
vfunc[2]:	<code>money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;&gt;::do_put(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, bool, ios_base&amp;, char, long double) const</code>
vfunc[3]:	<code>money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;&gt;::do_put(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, bool, ios_base&amp;, char, basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt; const&amp;) const</code>

The Run Time Type Information for the `std::money_put<char, std::ostreambuf_iterator<char, std::char_traits<char> >>` class is described by [Table 9-398](#)

**Table 9-398 typeinfo for `money_put<char, ostreambuf_iterator<char, char_traits<char> >>`**

Base Vtable	vtable for <code>__cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;&gt;</code>

### 9.1.132.2 Interfaces for Class `money_put<char, ostreambuf_iterator<char, char_traits<char> >`

An LSB conforming implementation shall provide the generic methods for Class `std::money_put<char, std::ostreambuf_iterator<char, std::char_traits<char> >` specified in [Table 9-399](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-399 libstdc++ - Class `money_put<char, ostreambuf_iterator<char, char_traits<char> >` Function Interfaces**

<code>money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;</code> <code>&gt;::put(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, bool, ios_base&amp;, char,</code> <code>basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt; const&amp;)</code> <code>const(GLIBCXX_3.4) [ISOcxx]</code>
<code>money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;</code> <code>&gt;::put(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, bool, ios_base&amp;, char,</code> <code>long double) const(GLIBCXX_3.4) [ISOcxx]</code>
<code>money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;</code> <code>&gt;::do_put(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, bool, ios_base&amp;,</code> <code>char, basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt; const&amp;)</code> <code>const(GLIBCXX_3.4) [ISOcxx]</code>
<code>money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;</code> <code>&gt;::do_put(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, bool, ios_base&amp;,</code> <code>char, long double) const(GLIBCXX_3.4) [ISOcxx]</code>
<code>ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; money_put&lt;char,</code> <code>ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;</code> <code>&gt;::_M_insert&lt;false&gt;(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;,</code> <code>ios_base&amp;, char, basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt;</code> <code>const&amp;) const(GLIBCXX_3.4) [ISOcxx]</code>
<code>ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; money_put&lt;char,</code> <code>ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;</code> <code>&gt;::_M_insert&lt;true&gt;(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;,</code> <code>ios_base&amp;, char, basic_string&lt;char, char_traits&lt;char&gt;, allocator&lt;char&gt; &gt;</code> <code>const&amp;) const(GLIBCXX_3.4) [ISOcxx]</code>
<code>money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;</code> <code>&gt;::~money_put()(GLIBCXX_3.4) [ISOcxx]</code>
<code>money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;</code> <code>&gt;::~money_put()(GLIBCXX_3.4) [ISOcxx]</code>
<code>money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;</code> <code>&gt;::~money_put()(GLIBCXX_3.4) [ISOcxx]</code>

An LSB conforming implementation shall provide the generic data interfaces for Class `std::money_put<char, std::ostreambuf_iterator<char, std::char_traits<char> > >` specified in [Table 9-400](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-400 libstdc++ - Class `money_put<char, ostreambuf_iterator<char, char_traits<char> >` Data Interfaces**

guard variable for <code>money_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; ::id(GLIBCXX_3.4) [CXXABI]</code>
---

money_put<char, ostreambuf_iterator<char, char_traits<char> > >::id(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
typeinfo for money_put<char, ostreambuf_iterator<char, char_traits<char> > >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for money_put<char, ostreambuf_iterator<char, char_traits<char> > >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for money_put<char, ostreambuf_iterator<char, char_traits<char> > >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

### 9.1.133 Class `money_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> >`

>

#### 9.1.133.1 Class data for `money_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> > >`

The virtual table for the `std::money_put<wchar_t, std::ostreambuf_iterator<wchar_t, std::char_traits<wchar_t> > >` class is described by [Table 9-401](#)

**Table 9-401 Primary vtable for `money_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> > >`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for money_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> > >
vfunc[0]:	<code>money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;::~money_put()</code>
vfunc[1]:	<code>money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;::~money_put()</code>
vfunc[2]:	<code>money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;::do_put(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, bool, ios_base&amp;, wchar_t, long double)</code> const
vfunc[3]:	<code>money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;::do_put(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, bool, ios_base&amp;, wchar_t, basic_string&lt;wchar_t,</code>

	char_traits<wchar_t>, allocator<wchar_t> > const&) const
--	---

The Run Time Type Information for the `std::money_put<wchar_t, std::ostreambuf_iterator<wchar_t, std::char_traits<wchar_t> > >` class is described by [Table 9-402](#)

**Table 9-402 typeinfo for `money_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> > >`**

Base Vtable	vtable for <code>_cxxabiv1::_si_class_type_info</code>
Name	typeinfo name for <code>money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;</code>

### 9.1.133.2 Interfaces for Class `money_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> > >`

An LSB conforming implementation shall provide the generic methods for Class `std::money_put<wchar_t, std::ostreambuf_iterator<wchar_t, std::char_traits<wchar_t> > >` specified in [Table 9-403](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-403 libstdcxx - Class `money_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> > >` Function Interfaces**

<code>money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;::put(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, bool, ios_base&amp;, wchar_t, basic_string&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt; const&amp;) const(GLIBCXX_3.4) [ISOCXX]</code>
<code>money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;::put(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, bool, ios_base&amp;, wchar_t, long double) const(GLIBCXX_3.4) [ISOCXX]</code>
<code>money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;::do_put(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, bool, ios_base&amp;, wchar_t, basic_string&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt; const&amp;) const(GLIBCXX_3.4) [ISOCXX]</code>
<code>money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;::do_put(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, bool, ios_base&amp;, wchar_t, long double) const(GLIBCXX_3.4) [ISOCXX]</code>
<code>ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;::_M_insert&lt;false&gt;(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, wchar_t, basic_string&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt; const&amp;) const(GLIBCXX_3.4) [ISOCXX]</code>
<code>ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;::_M_insert&lt;true&gt;(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, wchar_t, basic_string&lt;wchar_t, char_traits&lt;wchar_t&gt;, allocator&lt;wchar_t&gt; &gt; const&amp;) const(GLIBCXX_3.4) [ISOCXX]</code>
<code>money_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;</code>

>::~money_put()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
money_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>> >::~money_put()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
money_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>> >::~money_put()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::money\_put<wchar\_t, std::ostreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t>>> specified in [Table 9-404](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-404 libstdcxx - Class money\_put<wchar\_t, ostreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>> Data Interfaces**

guard variable for money_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>::id(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
money_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>> >::id(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
typeinfo for money_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for money_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for money_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.134 Class locale

### 9.1.134.1 Interfaces for Class locale

An LSB conforming implementation shall provide the generic methods for Class std::locale specified in [Table 9-405](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-405 libstdcxx - Class locale Function Interfaces**

locale::id::_M_id() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
locale::name() const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
locale::operator==(locale const&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
locale::_M_coalesce(locale const&, locale const&, int)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
locale::_S_normalize_category(int)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
locale::_Impl::_M_install_facet(locale::id const*, locale::facet const*) (GLIBCXX_3.4) <a href="#">[LSB]</a>
locale::_Impl::_M_replace_facet(locale::_Impl const*, locale::id const*) (GLIBCXX_3.4) <a href="#">[LSB]</a>
locale::_Impl::~_Impl()(GLIBCXX_3.4) <a href="#">[LSB]</a>
locale::_Impl::~_Impl()(GLIBCXX_3.4) <a href="#">[LSB]</a>
locale::global(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
locale::classic()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

locale::locale(char const*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
locale::locale(locale::_Impl*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
locale::locale(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
locale::locale(locale const&, locale const&, int)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
locale::locale()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
locale::locale(char const*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
locale::locale(locale::_Impl*)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
locale::locale(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
locale::locale(locale const&, char const*, int)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
locale::locale(locale const&, locale const&, int)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
locale::locale()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
locale::~locale()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
locale::~locale()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
locale::operator=(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::locale specified in [Table 9-406](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-406 libstdcxx - Class locale Data Interfaces**

locale::all(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
locale::none(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
locale::time(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
locale::ctype(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
locale::collate(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
locale::numeric(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
locale::messages(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
locale::monetary(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

## 9.1.135 Class locale::facet

### 9.1.135.1 Class data for locale::facet

The virtual table for the std::locale::facet class is described by [Table 9-407](#)

**Table 9-407 Primary vtable for locale::facet**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for locale::facet
vfunc[0]:	locale::facet::~facet()
vfunc[1]:	locale::facet::~facet()

The Run Time Type Information for the std::locale::facet class is described by [Table 9-408](#)

**Table 9-408 typeinfo for locale::facet**

Base Vtable	vtable for <code>_cxxabiv1::__class_type_info</code>
Name	typeinfo name for locale::facet

### 9.1.135.2 Interfaces for Class locale::facet

An LSB conforming implementation shall provide the generic methods for Class std::locale::facet specified in [Table 9-409](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-409 libstdc++ - Class locale::facet Function Interfaces**

<code>locale::facet::_S_get_c_name(GLIBCXX_3.4.6)</code> <a href="#">[ISOCXX]</a>
<code>locale::facet::_S_get_c_locale(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>locale::facet::_S_clone_c_locale(__locale_struct*&amp;)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>locale::facet::_S_create_c_locale(__locale_struct*&amp;, char const*, __locale_struct*)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>locale::facet::_S_destroy_c_locale(__locale_struct*&amp;)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>locale::facet::~facet(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>locale::facet::~facet(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>locale::facet::~facet(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>locale::locale(locale const&amp;, char const*, int)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::locale::facet specified in [Table 9-410](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-410 libstdc++ - Class locale::facet Data Interfaces**

<code>__timepunct_cache&lt;char&gt;::_S_timezones(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>__timepunct_cache&lt;wchar_t&gt;::_S_timezones(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>typeinfo for locale::facet(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>
<code>typeinfo name for locale::facet(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>
<code>vtable for locale::facet(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>

### 9.1.136 facet functions

#### 9.1.136.1 Interfaces for facet functions

An LSB conforming implementation shall provide the generic methods for facet functions specified in [Table 9-411](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-411 libstdc++ - facet functions Function Interfaces**

<code>void __convert_to_v&lt;double&gt;(char const*, double&amp;, _Ios_Iostate&amp;, __locale_struct* const&amp;)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
<code>void __convert_to_v&lt;long double&gt;(char const*, long double&amp;, _Ios_Iostate&amp;, __locale_struct* const&amp;)(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>

```

void __convert_to_v<float>(char const*, float&, _Ios_Iostate&,
__locale_struct* const&)(GLIBCXX_3.4) [ISOCXX]

bool has_facet<moneypunct<char, false>>(locale const&)(GLIBCXX_3.4)
[ISOCXX]

bool has_facet<moneypunct<wchar_t, false>>(locale const&)(GLIBCXX_3.4)
[ISOCXX]

bool has_facet<ctype<wchar_t>>(locale const&)(GLIBCXX_3.4) [ISOCXX]

bool has_facet<codecvt<char, char, __mbstate_t>>(locale const&)
(GLIBCXX_3.4) [ISOCXX]

bool has_facet<codecvt<wchar_t, char, __mbstate_t>>(locale const&)
(GLIBCXX_3.4) [ISOCXX]

bool has_facet<collate<char>>(locale const&)(GLIBCXX_3.4) [ISOCXX]

bool has_facet<collate<wchar_t>>(locale const&)(GLIBCXX_3.4) [ISOCXX]

bool has_facet<num_get<char, istreambuf_iterator<char, char_traits<char>>
>>(locale const&)(GLIBCXX_3.4) [ISOCXX]

bool has_facet<num_get<wchar_t, istreambuf_iterator<wchar_t,
char_traits<wchar_t>>>>(locale const&)(GLIBCXX_3.4) [ISOCXX]

bool has_facet<num_put<char, ostreambuf_iterator<char, char_traits<char>>
>>>(locale const&)(GLIBCXX_3.4) [ISOCXX]

bool has_facet<num_put<wchar_t, ostreambuf_iterator<wchar_t,
char_traits<wchar_t>>>>(locale const&)(GLIBCXX_3.4) [ISOCXX]

bool has_facet<messages<char>>(locale const&)(GLIBCXX_3.4) [ISOCXX]

bool has_facet<messages<wchar_t>>(locale const&)(GLIBCXX_3.4)
[ISOCXX]

bool has_facet<numpunct<char>>(locale const&)(GLIBCXX_3.4) [ISOCXX]

bool has_facet<numpunct<wchar_t>>(locale const&)(GLIBCXX_3.4)
[ISOCXX]

bool has_facet<time_get<char, istreambuf_iterator<char, char_traits<char>>
>>(locale const&)(GLIBCXX_3.4) [ISOCXX]

bool has_facet<time_get<wchar_t, istreambuf_iterator<wchar_t,
char_traits<wchar_t>>>>(locale const&)(GLIBCXX_3.4) [ISOCXX]

bool has_facet<time_put<char, ostreambuf_iterator<char, char_traits<char>>
>>>(locale const&)(GLIBCXX_3.4) [ISOCXX]

bool has_facet<time_put<wchar_t, ostreambuf_iterator<wchar_t,
char_traits<wchar_t>>>>(locale const&)(GLIBCXX_3.4) [ISOCXX]

bool has_facet<money_get<char, istreambuf_iterator<char, char_traits<char>>
>>>(locale const&)(GLIBCXX_3.4) [ISOCXX]

bool has_facet<money_get<wchar_t, istreambuf_iterator<wchar_t,
char_traits<wchar_t>>>>(locale const&)(GLIBCXX_3.4) [ISOCXX]

bool has_facet<money_put<char, ostreambuf_iterator<char,
char_traits<char>>>>(locale const&)(GLIBCXX_3.4) [ISOCXX]

bool has_facet<money_put<wchar_t, ostreambuf_iterator<wchar_t,
char_traits<wchar_t>>>>>(locale const&)(GLIBCXX_3.4) [ISOCXX]

moneypunct<char, false> const& use_facet<moneypunct<char, false>
>(locale const&)(GLIBCXX_3.4) [ISOCXX]

```

moneypunct<char, true> const& use_facet<moneypunct<char, true>>(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, false> const& use_facet<moneypunct<wchar_t, false>>(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
moneypunct<wchar_t, true> const& use_facet<moneypunct<wchar_t, true>>(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
__timepunct<char> const& use_facet<__timepunct<char>>(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
__timepunct<wchar_t> const& use_facet<__timepunct<wchar_t>>(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype<char> const& use_facet<ctype<char>>(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
ctype<wchar_t> const& use_facet<ctype<wchar_t>>(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
codecvt<char, char, __mbstate_t> const& use_facet<codecvt<char, char, __mbstate_t>>(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
codecvt<wchar_t, char, __mbstate_t> const& use_facet<codecvt<wchar_t, char, __mbstate_t>>(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
collate<char> const& use_facet<collate<char>>(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
collate<wchar_t> const& use_facet<collate<wchar_t>>(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
num_get<char, istreambuf_iterator<char, char_traits<char>>> const& use_facet<num_get<char, istreambuf_iterator<char, char_traits<char>>>(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
num_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>> const& use_facet<num_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
num_put<char, ostreambuf_iterator<char, char_traits<char>>> const& use_facet<num_put<char, ostreambuf_iterator<char, char_traits<char>>>(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>> const& use_facet<num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages<char> const& use_facet<messages<char>>(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
messages<wchar_t> const& use_facet<messages<wchar_t>>(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<char> const& use_facet<numpunct<char>>(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
numpunct<wchar_t> const& use_facet<numpunct<wchar_t>>(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
time_get<char, istreambuf_iterator<char, char_traits<char>>> const& use_facet<time_get<char, istreambuf_iterator<char, char_traits<char>>>(locale const&)(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>

const& use_facet<time_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>(locale const&)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
time_put<char, ostreambuf_iterator<char, char_traits<char>>> const& use_facet<time_put<char, ostreambuf_iterator<char, char_traits<char>>>(locale const&)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
time_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>> const& use_facet<time_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>(locale const&)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
money_get<char, istreambuf_iterator<char, char_traits<char>>> const& use_facet<money_get<char, istreambuf_iterator<char, char_traits<char>>>(locale const&)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
money_get<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>> const& use_facet<money_get<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>(locale const&)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
money_put<char, ostreambuf_iterator<char, char_traits<char>>> const& use_facet<money_put<char, ostreambuf_iterator<char, char_traits<char>>>(locale const&)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
money_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>> const& use_facet<money_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>(locale const&)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>

## 9.1.137 Class `__num_base`

### 9.1.137.1 Class data for `__num_base`

### 9.1.137.2 Interfaces for Class `__num_base`

An LSB conforming implementation shall provide the generic methods for Class `std::__num_base` specified in [Table 9-412](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-412 libstdc++ - Class `__num_base` Function Interfaces**

<code>__num_base::S_format_float(ios_base const&amp;, char*, char)(GLIBCXX_3.4)</code> <a href="#">[ISOcxx]</a>
---

An LSB conforming implementation shall provide the generic data interfaces for Class `std::__num_base` specified in [Table 9-413](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-413 libstdc++ - Class `__num_base` Data Interfaces**

<code>__num_base::S_atoms_in(GLIBCXX_3.4)</code> <a href="#">[ISOcxx]</a>
<code>__num_base::S_atoms_out(GLIBCXX_3.4)</code> <a href="#">[ISOcxx]</a>

## 9.1.138 Class `num_get<char, istreambuf_iterator<char, char_traits<char>>>`

### 9.1.138.1 Class data for `num_get<char, istreambuf_iterator<char, char_traits<char>>>`

The virtual table for the `std::num_get<char, std::istreambuf_iterator<char, std::char_traits<char>>>` class is described by [Table 9-414](#)

**Table 9-414 Primary vtable for num\_get<char, istreambuf\_iterator<char, char\_traits<char> >>**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for num_get<char, istreambuf_iterator<char, char_traits<char> >>
vfunc[0]:	num_get<char, istreambuf_iterator<char, char_traits<char> >>::~num_get()
vfunc[1]:	num_get<char, istreambuf_iterator<char, char_traits<char> >>::~num_get()
vfunc[2]:	num_get<char, istreambuf_iterator<char, char_traits<char> >>::do_get(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, bool&) const
vfunc[3]:	num_get<char, istreambuf_iterator<char, char_traits<char> >>::do_get(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, long&) const
vfunc[4]:	num_get<char, istreambuf_iterator<char, char_traits<char> >>::do_get(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, unsigned short&) const
vfunc[5]:	num_get<char, istreambuf_iterator<char, char_traits<char> >>::do_get(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, unsigned int&) const
vfunc[6]:	num_get<char, istreambuf_iterator<char, char_traits<char> >>::do_get(istreambuf_iterator<char,

	<code>char_traits&lt;char&gt; &gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, _Ios_Iostate&amp;, unsigned long&amp;) const</code>
vfunc[7]:	<code>num_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::do_get(istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, _Ios_Iostate&amp;, long long&amp;) const</code>
vfunc[8]:	<code>num_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::do_get(istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, _Ios_Iostate&amp;, unsigned long long&amp;) const</code>
vfunc[9]:	<code>num_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::do_get(istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, _Ios_Iostate&amp;, float&amp;) const</code>
vfunc[10]:	<code>num_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::do_get(istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, _Ios_Iostate&amp;, double&amp;) const</code>
vfunc[11]:	<code>num_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::do_get(istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, _Ios_Iostate&amp;, long double&amp;) const</code>
vfunc[12]:	<code>num_get&lt;char, istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::do_get(istreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;,</code>

	istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, void*&) const
--	--

The Run Time Type Information for the std::num\_get<char, std::istreambuf\_iterator<char, std::char\_traits<char> >> class is described by [Table 9-415](#)

**Table 9-415 typeinfo for num\_get<char, istreambuf\_iterator<char, char\_traits<char> >>**

Base Vtable	vtable for <code>_cxxabiv1::_si_class_type_info</code>
Name	typeinfo name for num_get<char, istreambuf_iterator<char, char_traits<char> >>
basetype:	typeinfo for locale::facet

### **9.1.138.2 Interfaces for Class num\_get<char, istreambuf\_iterator<char, char\_traits<char> >>**

An LSB conforming implementation shall provide the generic methods for Class std::num\_get<char, std::istreambuf\_iterator<char, std::char\_traits<char> >> specified in [Table 9-416](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-416 libstdcxx - Class num\_get<char, istreambuf\_iterator<char, char\_traits<char> >> Function Interfaces**

istreambuf_iterator<char, char_traits<char> > num_get<char, istreambuf_iterator<char, char_traits<char> >>::_M_extract_int<unsigned int>(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, unsigned int&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
istreambuf_iterator<char, char_traits<char> > num_get<char, istreambuf_iterator<char, char_traits<char> >>::_M_extract_int<long>(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, long&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
istreambuf_iterator<char, char_traits<char> > num_get<char, istreambuf_iterator<char, char_traits<char> >>::_M_extract_int<unsigned long>(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, unsigned long&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
istreambuf_iterator<char, char_traits<char> > num_get<char, istreambuf_iterator<char, char_traits<char> >>::_M_extract_int<unsigned short>(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, unsigned short&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
istreambuf_iterator<char, char_traits<char> > num_get<char, istreambuf_iterator<char, char_traits<char> >>::_M_extract_int<long long>(istreambuf_iterator<char, char_traits<char> >, istreambuf_iterator<char, char_traits<char> >, ios_base&, _Ios_Iostate&, long long&) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>





num_get<char, istreambuf_iterator<char, char_traits<char>> >::~num_get() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
num_get<char, istreambuf_iterator<char, char_traits<char>> >::~num_get() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
num_get<char, istreambuf_iterator<char, char_traits<char>> >::~num_get() (GLIBCXX_3.4) <a href="#">[ISOCXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::num\_get<char, std::istreambuf\_iterator<char, std::char\_traits<char>>> specified in [Table 9-417](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-417 libstdcxx - Class num\_get<char, istreambuf\_iterator<char, char\_traits<char>>> Data Interfaces**

guard variable for num_get<char, istreambuf_iterator<char, char_traits<char>> >::id(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
num_get<char, istreambuf_iterator<char, char_traits<char>>>::id(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
typeinfo for num_get<char, istreambuf_iterator<char, char_traits<char>>>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for num_get<char, istreambuf_iterator<char, char_traits<char>>>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

### 9.1.139 Class num\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>>

#### 9.1.139.1 Class data for num\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>>

The virtual table for the std::num\_get<wchar\_t, std::istreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t>>> class is described by [Table 9-418](#)

**Table 9-418 Primary vtable for num\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>>**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for num_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>
vfunc[0]:	num_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>::~num_get()
vfunc[1]:	num_get<wchar_t, istreambuf_iterator<wchar_t,

	<code>char_traits&lt;wchar_t&gt; &gt; &gt;::~num_get()</code>
vfunc[2]:	<code>num_get&lt;wchar_t,&amp;br/&gt;istreambuf_iterator&lt;wchar_t,&amp;br/&gt;char_traits&lt;wchar_t&gt; &gt; &gt;::do_get(istreambuf_iterator&lt;wchar _t, char_traits&lt;wchar_t&gt; &gt;, istreambuf_iterator&lt;wchar_t,&amp;br/&gt;char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, _Ios_Iostate&amp;, bool&amp;) const</code>
vfunc[3]:	<code>num_get&lt;wchar_t,&amp;br/&gt;istreambuf_iterator&lt;wchar_t,&amp;br/&gt;char_traits&lt;wchar_t&gt; &gt; &gt;::do_get(istreambuf_iterator&lt;wchar _t, char_traits&lt;wchar_t&gt; &gt;, istreambuf_iterator&lt;wchar_t,&amp;br/&gt;char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, _Ios_Iostate&amp;, long&amp;) const</code>
vfunc[4]:	<code>num_get&lt;wchar_t,&amp;br/&gt;istreambuf_iterator&lt;wchar_t,&amp;br/&gt;char_traits&lt;wchar_t&gt; &gt; &gt;::do_get(istreambuf_iterator&lt;wchar _t, char_traits&lt;wchar_t&gt; &gt;, istreambuf_iterator&lt;wchar_t,&amp;br/&gt;char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, _Ios_Iostate&amp;, unsigned short&amp;) const</code>
vfunc[5]:	<code>num_get&lt;wchar_t,&amp;br/&gt;istreambuf_iterator&lt;wchar_t,&amp;br/&gt;char_traits&lt;wchar_t&gt; &gt; &gt;::do_get(istreambuf_iterator&lt;wchar _t, char_traits&lt;wchar_t&gt; &gt;, istreambuf_iterator&lt;wchar_t,&amp;br/&gt;char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, _Ios_Iostate&amp;, unsigned int&amp;) const</code>
vfunc[6]:	<code>num_get&lt;wchar_t,&amp;br/&gt;istreambuf_iterator&lt;wchar_t,&amp;br/&gt;char_traits&lt;wchar_t&gt; &gt; &gt;::do_get(istreambuf_iterator&lt;wchar _t, char_traits&lt;wchar_t&gt; &gt;, istreambuf_iterator&lt;wchar_t,&amp;br/&gt;char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, _Ios_Iostate&amp;, unsigned long&amp;) const</code>
vfunc[7]:	<code>num_get&lt;wchar_t,&amp;br/&gt;istreambuf_iterator&lt;wchar_t,&amp;br/&gt;char_traits&lt;wchar_t&gt; &gt; &gt;::do_get(istreambuf_iterator&lt;wchar _t, char_traits&lt;wchar_t&gt; &gt;, istreambuf_iterator&lt;wchar_t,&amp;br/&gt;char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;,</code>

	_Ios_Iostate&, long long&) const
vfunc[8]:	num_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>> >::do_get(istreambuf_iterator<wchar _t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, _Ios_Iostate&, unsigned long long&) const
vfunc[9]:	num_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>> >::do_get(istreambuf_iterator<wchar _t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, _Ios_Iostate&, float&) const
vfunc[10]:	num_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>> >::do_get(istreambuf_iterator<wchar _t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, _Ios_Iostate&, double&) const
vfunc[11]:	num_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>> >::do_get(istreambuf_iterator<wchar _t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, _Ios_Iostate&, long double&) const
vfunc[12]:	num_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>> >::do_get(istreambuf_iterator<wchar _t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, _Ios_Iostate&, void*&) const

The Run Time Type Information for the `std::num_get<wchar_t, std::istreambuf_iterator<wchar_t, std::char_traits<wchar_t>>>` class is described by [Table 9-419](#)

**Table 9-419 typeinfo for num\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>>**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
-------------	--

Name	typeinfo name for num_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>
basetype:	typeinfo for locale::facet

### 9.1.139.2 Interfaces for Class num\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>>

An LSB conforming implementation shall provide the generic methods for Class std::num\_get<wchar\_t, std::istreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t>>> specified in [Table 9-420](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-420 libstdc++ - Class num\_get<wchar\_t, istreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>> Function Interfaces**

istreambuf_iterator<wchar_t, char_traits<wchar_t>> num_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>> >::_M_extract_int<unsigned int>(istreambuf_iterator<wchar_t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, _Ios_Iostate&, unsigned int&) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
istreambuf_iterator<wchar_t, char_traits<wchar_t>> num_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>> >::_M_extract_int<long>(istreambuf_iterator<wchar_t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, _Ios_Iostate&, long&) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
istreambuf_iterator<wchar_t, char_traits<wchar_t>> num_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>> >::_M_extract_int<unsigned long>(istreambuf_iterator<wchar_t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, _Ios_Iostate&, unsigned long&) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
istreambuf_iterator<wchar_t, char_traits<wchar_t>> num_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>> >::_M_extract_int<unsigned short>(istreambuf_iterator<wchar_t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, _Ios_Iostate&, unsigned short&) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
istreambuf_iterator<wchar_t, char_traits<wchar_t>> num_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>>::_M_extract_int<long long>(istreambuf_iterator<wchar_t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, _Ios_Iostate&, long long&) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
istreambuf_iterator<wchar_t, char_traits<wchar_t>> num_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>> >::_M_extract_int<unsigned long long>(istreambuf_iterator<wchar_t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, _Ios_Iostate&, unsigned long long&) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
num_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>> >::_M_extract_float(istreambuf_iterator<wchar_t, char_traits<wchar_t>>, istreambuf_iterator<wchar_t, char_traits<wchar_t>>, ios_base&, _Ios_Iostate&, float&) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>



<code>_Ios_Iostate&amp;, void*&amp;) const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::do_get(istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, ios_base&amp;, <u>_Ios_Iostate&amp;, bool&amp;)</u> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::do_get(istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, ios_base&amp;, <u>_Ios_Iostate&amp;, double&amp;)</u> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::do_get(istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, ios_base&amp;, <u>_Ios_Iostate&amp;, long double&amp;)</u> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::do_get(istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, ios_base&amp;, <u>_Ios_Iostate&amp;, float&amp;)</u> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::do_get(istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, ios_base&amp;, <u>_Ios_Iostate&amp;, unsigned int&amp;)</u> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::do_get(istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, ios_base&amp;, <u>_Ios_Iostate&amp;, long&amp;)</u> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::do_get(istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, ios_base&amp;, <u>_Ios_Iostate&amp;, unsigned long&amp;)</u> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::do_get(istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, ios_base&amp;, <u>_Ios_Iostate&amp;, unsigned short&amp;)</u> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::do_get(istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, ios_base&amp;, <u>_Ios_Iostate&amp;, long long&amp;)</u> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::do_get(istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;, ios_base&amp;, <u>_Ios_Iostate&amp;, unsigned long long&amp;)</u> const(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::~num_get()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::~num_get()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>
<code>num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt; &gt;::~num_get()(GLIBCXX_3.4) <a href="#">[ISOCXX]</a></code>

An LSB conforming implementation shall provide the generic data interfaces for

Class `std::num_get<wchar_t, std::istreambuf_iterator<wchar_t, std::char_traits<wchar_t>>` specified in [Table 9-421](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-421 libstdc++ - Class `num_get<wchar_t, istreambuf_iterator<wchar_t, char_traits<wchar_t>>` Data Interfaces**

guard variable for <code>num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code> : <code>::id(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>
<code>num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code> : <code>::id(GLIBCXX_3.4)</code> <a href="#">[ISOCXX]</a>
typeinfo for <code>num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code> : <code>(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>
typeinfo name for <code>num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code> : <code>(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>
vtable for <code>num_get&lt;wchar_t, istreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt;&gt;</code> : <code>(GLIBCXX_3.4)</code> <a href="#">[CXXABI]</a>

### 9.1.140 Class `num_put<char, ostreambuf_iterator<char, char_traits<char>>`

#### 9.1.140.1 Class data for `num_put<char, ostreambuf_iterator<char, char_traits<char>>`

The virtual table for the `std::num_put<char, std::ostreambuf_iterator<char, std::char_traits<char>>` class is described by [Table 9-422](#)

**Table 9-422 Primary vtable for `num_put<char, ostreambuf_iterator<char, char_traits<char>>`**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;</code>
vfunc[0]:	<code>num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;</code> : <code>::~num_put()</code>
vfunc[1]:	<code>num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;</code> : <code>::~num_put()</code>
vfunc[2]:	<code>num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;</code> : <code>::do_put(ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;, ios_base&amp;, char, bool) const</code>
vfunc[3]:	<code>num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt;&gt;</code> : <code>::do_put(ostreambuf_iterator&lt;char,</code>

	<code>char_traits&lt;char&gt; &gt;, ios_base&amp;, char, long) const</code>
vfunc[4]:	<code>num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;&gt;::do_put(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, char, unsigned long) const</code>
vfunc[5]:	<code>num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;&gt;::do_put(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, char, long long) const</code>
vfunc[6]:	<code>num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;&gt;::do_put(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, char, unsigned long long) const</code>
vfunc[7]:	<code>num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;&gt;::do_put(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, char, double) const</code>
vfunc[8]:	<code>num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;&gt;::do_put(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, char, long double) const</code>
vfunc[9]:	<code>num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;&gt;::do_put(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, char, void const*) const</code>

The Run Time Type Information for the `std::num_put<char, std::ostreambuf_iterator<char, std::char_traits<char> >>` class is described by [Table 9-423](#)

**Table 9-423 typeinfo for num\_put<char, ostreambuf\_iterator<char, char\_traits<char> >>**

Base Vtable	vtable for <code>_cxxabiv1::_si_class_type_info</code>
Name	typeinfo name for <code>num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;&gt;</code>
basetype:	typeinfo for <code>locale::facet</code>

### 9.1.140.2 Interfaces for Class `num_put<char, ostreambuf_iterator<char, char_traits<char> >`

An LSB conforming implementation shall provide the generic methods for Class `std::num_put<char, std::ostreambuf_iterator<char, std::char_traits<char> >` specified in [Table 9-424](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-424 libstdc++ - Class `num_put<char, ostreambuf_iterator<char, char_traits<char> >` Function Interfaces**

<code>ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::_M_insert_int&lt;long&gt;(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, char, long) const(GLIBCXX_3.4) [ISOcxx]</code>
<code>ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::_M_insert_int&lt;unsigned long&gt;(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, char, unsigned long) const(GLIBCXX_3.4) [ISOcxx]</code>
<code>ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::_M_insert_int&lt;long long&gt;(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, char, long long) const(GLIBCXX_3.4) [ISOcxx]</code>
<code>ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::_M_insert_int&lt;unsigned long long&gt;(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, char, unsigned long long) const(GLIBCXX_3.4) [ISOcxx]</code>
<code>ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::_M_insert_float&lt;double&gt;(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, char, double) const(GLIBCXX_3.4) [ISOcxx]</code>
<code>ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::_M_insert_float&lt;long double&gt;(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, char, long double) const(GLIBCXX_3.4) [ISOcxx]</code>
<code>num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::put(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, char, void const*) const(GLIBCXX_3.4) [ISOcxx]</code>
<code>num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::put(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, char, bool) const(GLIBCXX_3.4) [ISOcxx]</code>
<code>num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::put(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, char, double) const(GLIBCXX_3.4) [ISOcxx]</code>
<code>num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::put(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, char, long double) const(GLIBCXX_3.4) [ISOcxx]</code>
<code>num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt; &gt;::put(ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;, ios_base&amp;, char, long) const(GLIBCXX_3.4) [ISOcxx]</code>
<code>num_put&lt;char, ostreambuf_iterator&lt;char, char_traits&lt;char&gt; &gt;</code>

>::put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
num_put<char, ostreambuf_iterator<char, char_traits<char> > >::put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, long long) const(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
num_put<char, ostreambuf_iterator<char, char_traits<char> > >::put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, unsigned long long) const(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
num_put<char, ostreambuf_iterator<char, char_traits<char> > >::do_put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, void const*) const(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
num_put<char, ostreambuf_iterator<char, char_traits<char> > >::do_put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, bool) const(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
num_put<char, ostreambuf_iterator<char, char_traits<char> > >::do_put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, double) const(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
num_put<char, ostreambuf_iterator<char, char_traits<char> > >::do_put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, long double) const(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
num_put<char, ostreambuf_iterator<char, char_traits<char> > >::do_put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, long) const(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
num_put<char, ostreambuf_iterator<char, char_traits<char> > >::do_put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
num_put<char, ostreambuf_iterator<char, char_traits<char> > >::do_put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, long long) const(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
num_put<char, ostreambuf_iterator<char, char_traits<char> > >::do_put(ostreambuf_iterator<char, char_traits<char> >, ios_base&, char, unsigned long long) const(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
num_put<char, ostreambuf_iterator<char, char_traits<char> > >::~num_put()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
num_put<char, ostreambuf_iterator<char, char_traits<char> > >::~num_put()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
num_put<char, ostreambuf_iterator<char, char_traits<char> > >::~num_put()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class std::num\_put<char, std::ostreambuf\_iterator<char, std::char\_traits<char> > > specified in [Table 9-425](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-425 libstdcxx - Class num\_put<char, ostreambuf\_iterator<char, char\_traits<char> > > Data Interfaces**

guard variable for num_put<char, ostreambuf_iterator<char, char_traits<char> > >::id(GLIBCXX_3.4) <a href="#">[Cxxabi]</a>
--

num_put<char, ostreambuf_iterator<char, char_traits<char>> >::id(GLIBCXX_3.4) <a href="#">[ISOCXX]</a>
typeinfo for num_put<char, ostreambuf_iterator<char, char_traits<char>> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for num_put<char, ostreambuf_iterator<char, char_traits<char>>>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for num_put<char, ostreambuf_iterator<char, char_traits<char>> >(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

### 9.1.141 Class num\_put<wchar\_t, ostreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>> >

#### 9.1.141.1 Class data for num\_put<wchar\_t, ostreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>>

The virtual table for the std::num\_put<wchar\_t, std::ostreambuf\_iterator<wchar\_t, std::char\_traits<wchar\_t>>> class is described by [Table 9-426](#)

**Table 9-426 Primary vtable for num\_put<wchar\_t,  
ostreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>>>**

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>>>
vfunc[0]:	num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>> >::~num_put()
vfunc[1]:	num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>> >::~num_put()
vfunc[2]:	num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>> >::do_put(ostreambuf_iterator<wcha r_t, char_traits<wchar_t> >, ios_base&, wchar_t, bool) const
vfunc[3]:	num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>> >::do_put(ostreambuf_iterator<wcha r_t, char_traits<wchar_t> >, ios_base&, wchar_t, long) const
vfunc[4]:	num_put<wchar_t, ostreambuf_iterator<wchar_t,

	<code>char_traits&lt;wchar_t&gt; &gt; &gt;::do_put(ostreambuf_iterator&lt;wchar_t&gt;, ios_base&amp;, wchar_t, unsigned long) const</code>
vfunc[5]:	<code>num_put&lt;wchar_t,&lt;br/&gt;ostreambuf_iterator&lt;wchar_t&gt;,&lt;br/&gt;char_traits&lt;wchar_t&gt;&gt;&lt;br/&gt;&gt;::do_put(ostreambuf_iterator&lt;wchar_t&gt;,&lt;br/&gt;char_traits&lt;wchar_t&gt;&gt;,&lt;br/&gt;ios_base&amp;, wchar_t, long long) const</code>
vfunc[6]:	<code>num_put&lt;wchar_t,&lt;br/&gt;ostreambuf_iterator&lt;wchar_t&gt;,&lt;br/&gt;char_traits&lt;wchar_t&gt;&gt;&lt;br/&gt;&gt;::do_put(ostreambuf_iterator&lt;wchar_t&gt;,&lt;br/&gt;char_traits&lt;wchar_t&gt;&gt;,&lt;br/&gt;ios_base&amp;, wchar_t, unsigned long long) const</code>
vfunc[7]:	<code>num_put&lt;wchar_t,&lt;br/&gt;ostreambuf_iterator&lt;wchar_t&gt;,&lt;br/&gt;char_traits&lt;wchar_t&gt;&gt;&lt;br/&gt;&gt;::do_put(ostreambuf_iterator&lt;wchar_t&gt;,&lt;br/&gt;char_traits&lt;wchar_t&gt;&gt;,&lt;br/&gt;ios_base&amp;, wchar_t, double) const</code>
vfunc[8]:	<code>num_put&lt;wchar_t,&lt;br/&gt;ostreambuf_iterator&lt;wchar_t&gt;,&lt;br/&gt;char_traits&lt;wchar_t&gt;&gt;&lt;br/&gt;&gt;::do_put(ostreambuf_iterator&lt;wchar_t&gt;,&lt;br/&gt;char_traits&lt;wchar_t&gt;&gt;,&lt;br/&gt;ios_base&amp;, wchar_t, long double) const</code>
vfunc[9]:	<code>num_put&lt;wchar_t,&lt;br/&gt;ostreambuf_iterator&lt;wchar_t&gt;,&lt;br/&gt;char_traits&lt;wchar_t&gt;&gt;&lt;br/&gt;&gt;::do_put(ostreambuf_iterator&lt;wchar_t&gt;,&lt;br/&gt;char_traits&lt;wchar_t&gt;&gt;,&lt;br/&gt;ios_base&amp;, wchar_t, void const*) const</code>

The Run Time Type Information for the `std::num_put<wchar_t, std::ostreambuf_iterator<wchar_t, std::char_traits<wchar_t> >>` class is described by [Table 9-427](#)

**Table 9-427 typeinfo for num\_put<wchar\_t, ostreambuf\_iterator<wchar\_t, char\_traits<wchar\_t> >>**

Base Vtable	vtable for <code>_cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>num_put&lt;wchar_t,&lt;br/&gt;ostreambuf_iterator&lt;wchar_t,&lt;br/&gt;char_traits&lt;wchar_t&gt; &gt;&gt;</code>

basetype:	typeinfo for locale::facet
<b>9.1.141.2 Interfaces for Class num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;</b>	
An LSB conforming implementation shall provide the generic methods for Class std::num_put<wchar_t, std::ostreambuf_iterator<wchar_t, std::char_traits<wchar_t> > > specified in <a href="#">Table 9-428</a> , with the full mandatory functionality as described in the referenced underlying specification.	
<b>Table 9-428 libstdcxx - Class num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt; Function Interfaces</b>	
<pre>ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;::_M_insert_int&lt;long&gt;(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, wchar_t, long) const(GLIBCXX_3.4) [ISOCXX]</pre>	
<pre>ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;::_M_insert_int&lt;unsigned long&gt;(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, wchar_t, unsigned long) const(GLIBCXX_3.4) [ISOCXX]</pre>	
<pre>ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;::_M_insert_int&lt;long long&gt;(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, wchar_t, long long) const(GLIBCXX_3.4) [ISOCXX]</pre>	
<pre>ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;::_M_insert_int&lt;unsigned long long&gt;(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, wchar_t, unsigned long long) const(GLIBCXX_3.4) [ISOCXX]</pre>	
<pre>ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;::_M_insert_float&lt;double&gt;(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, wchar_t, char, double) const(GLIBCXX_3.4) [ISOCXX]</pre>	
<pre>ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;::_M_insert_float&lt;long double&gt;(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, wchar_t, char, long double) const(GLIBCXX_3.4) [ISOCXX]</pre>	
<pre>num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;::put(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, wchar_t, void const*) const(GLIBCXX_3.4) [ISOCXX]</pre>	
<pre>num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;::put(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, wchar_t, bool) const(GLIBCXX_3.4) [ISOCXX]</pre>	
<pre>num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt; &gt;::put(ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;, ios_base&amp;, wchar_t, double) const(GLIBCXX_3.4) [ISOCXX]</pre>	
<pre>num_put&lt;wchar_t, ostreambuf_iterator&lt;wchar_t, char_traits&lt;wchar_t&gt; &gt;</pre>	

>::put(ostreambuf_iterator<wchar_t, char_traits<wchar_t> >, ios_base&, wchar_t, long double) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> >>::put(ostreambuf_iterator<wchar_t, char_traits<wchar_t> >, ios_base&, wchar_t, long) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> >>::put(ostreambuf_iterator<wchar_t, char_traits<wchar_t> >, ios_base&, wchar_t, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> >>::put(ostreambuf_iterator<wchar_t, char_traits<wchar_t> >, ios_base&, wchar_t, long long) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> >>::put(ostreambuf_iterator<wchar_t, char_traits<wchar_t> >, ios_base&, wchar_t, unsigned long long) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> >>::do_put(ostreambuf_iterator<wchar_t, char_traits<wchar_t> >, ios_base&, wchar_t, void const*) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> >>::do_put(ostreambuf_iterator<wchar_t, char_traits<wchar_t> >, ios_base&, wchar_t, bool) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> >>::do_put(ostreambuf_iterator<wchar_t, char_traits<wchar_t> >, ios_base&, wchar_t, double) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> >>::do_put(ostreambuf_iterator<wchar_t, char_traits<wchar_t> >, ios_base&, wchar_t, long double) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> >>::do_put(ostreambuf_iterator<wchar_t, char_traits<wchar_t> >, ios_base&, wchar_t, long) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> >>::do_put(ostreambuf_iterator<wchar_t, char_traits<wchar_t> >, ios_base&, wchar_t, unsigned long) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> >>::do_put(ostreambuf_iterator<wchar_t, char_traits<wchar_t> >, ios_base&, wchar_t, long long) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> >>::do_put(ostreambuf_iterator<wchar_t, char_traits<wchar_t> >, ios_base&, wchar_t, unsigned long long) const(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> >>::~num_put()(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> >>::~num_put()(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t> >>::~num_put()(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>

An LSB conforming implementation shall provide the generic data interfaces for Class `std::num_put<wchar_t, std::ostreambuf_iterator<wchar_t, std::char_traits<wchar_t> > >` specified in [Table 9-429](#), with the full mandatory

functionality as described in the referenced underlying specification.

**Table 9-429 libstdc++ - Class num\_put<wchar\_t, ostreambuf\_iterator<wchar\_t, char\_traits<wchar\_t>> >> Data Interfaces**

guard variable for num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>> >>::id(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>> >>::id(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
typeinfo for num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>> >>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
typeinfo name for num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>> >>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>
vtable for num_put<wchar_t, ostreambuf_iterator<wchar_t, char_traits<wchar_t>> >>(GLIBCXX_3.4) <a href="#">[CXXABI]</a>

## 9.1.142 Class gslice

### 9.1.142.1 Class data for gslice

### 9.1.142.2 Interfaces for Class gslice

No external methods are defined for libstdc++ - Class std::gslice in this part of the specification. See also the relevant architecture specific part of this specification.

## 9.1.143 Class \_\_basic\_file<char>

### 9.1.143.1 Class data for \_\_basic\_file<char>

### 9.1.143.2 Interfaces for Class \_\_basic\_file<char>

An LSB conforming implementation shall provide the generic methods for Class std::\_\_basic\_file<char> specified in [Table 9-430](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-430 libstdc++ - Class \_\_basic\_file<char> Function Interfaces**

__basic_file<char>::is_open() const(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
__basic_file<char>::fd()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
__basic_file<char>::file()(GLIBCXX_3.4.1) <a href="#">[ISOcxx]</a>
__basic_file<char>::open(char const*, _Ios_Openmode, int)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
__basic_file<char>::sync()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
__basic_file<char>::close()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
__basic_file<char>::sys_open(_IO_FILE*, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
__basic_file<char>::sys_open(int, _Ios_Openmode)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
__basic_file<char>::showmany_c()(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
__basic_file<char>::__basic_file(pthread_mutex_t*)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>
__basic_file<char>::__basic_file(pthread_mutex_t*)(GLIBCXX_3.4) <a href="#">[ISOcxx]</a>

<code>_basic_file&lt;char&gt;::~_basic_file()(GLIBCXX_3.4) [ISOCXX]</code>
<code>_basic_file&lt;char&gt;::~_basic_file()(GLIBCXX_3.4) [ISOCXX]</code>

## 9.1.144 Class `_List_node_base`

### 9.1.144.1 Interfaces for Class `_List_node_base`

An LSB conforming implementation shall provide the generic methods for Class `std::_List_node_base` specified in [Table 9-431](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-431 libstdcxx - Class `_List_node_base` Function Interfaces**

<code>_List_node_base::hook(_List_node_base*)(GLIBCXX_3.4) [LSB]</code>
<code>_List_node_base::swap(_List_node_base&amp;, _List_node_base&amp;)(GLIBCXX_3.4) [LSB]</code>
<code>_List_node_base::unhook()(GLIBCXX_3.4) [LSB]</code>
<code>_List_node_base::reverse()(GLIBCXX_3.4) [LSB]</code>
<code>_List_node_base::transfer(_List_node_base*, _List_node_base*)(GLIBCXX_3.4) [LSB]</code>

## 9.1.145 Class `valarray<unsigned int>`

### 9.1.145.1 Class data for `valarray<unsigned int>`

### 9.1.145.2 Interfaces for Class `valarray<unsigned int>`

No external methods are defined for libstdcxx - Class `std::valarray<unsigned int>` in this part of the specification. See also the relevant architecture specific part of this specification.

## 9.1.146 Class `allocator<char>`

### 9.1.146.1 Class data for `allocator<char>`

### 9.1.146.2 Interfaces for Class `allocator<char>`

An LSB conforming implementation shall provide the generic methods for Class `std::allocator<char>` specified in [Table 9-432](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-432 libstdcxx - Class `allocator<char>` Function Interfaces**

<code>allocator&lt;char&gt;::allocator(allocator&lt;char&gt; const&amp;)(GLIBCXX_3.4) [ISOCXX]</code>
<code>allocator&lt;char&gt;::allocator()(GLIBCXX_3.4) [ISOCXX]</code>
<code>allocator&lt;char&gt;::allocator(allocator&lt;char&gt; const&amp;)(GLIBCXX_3.4) [ISOCXX]</code>
<code>allocator&lt;char&gt;::allocator()(GLIBCXX_3.4) [ISOCXX]</code>
<code>allocator&lt;char&gt;::~allocator()(GLIBCXX_3.4) [ISOCXX]</code>
<code>allocator&lt;char&gt;::~allocator()(GLIBCXX_3.4) [ISOCXX]</code>

## 9.1.147 Class allocator<wchar\_t>

### 9.1.147.1 Class data for allocator<wchar\_t>

### 9.1.147.2 Interfaces for Class allocator<wchar\_t>

An LSB conforming implementation shall provide the generic methods for Class std::allocator<wchar\_t> specified in [Table 9-433](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-433 libstdc++ - Class allocator<wchar\_t> Function Interfaces**

allocator<wchar_t>::allocator(allocator<wchar_t> const&)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
allocator<wchar_t>::allocator()(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
allocator<wchar_t>::allocator(allocator<wchar_t> const&)(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
allocator<wchar_t>::allocator()(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
allocator<wchar_t>::~allocator()(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>
allocator<wchar_t>::~allocator()(GLIBCXX_3.4) <a href="#">[ISO CXX]</a>

## 9.1.148 Class \_\_gnu\_cxx::\_\_pool<true>

### 9.1.148.1 Interfaces for Class \_\_gnu\_cxx::\_\_pool<true>

An LSB conforming implementation shall provide the generic methods for Class \_\_gnu\_cxx::\_\_pool<true> specified in [Table 9-434](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-434 libstdc++ - Class \_\_gnu\_cxx::\_\_pool<true> Function Interfaces**

__gnu_cxx::__pool<true>::__M_destroy()(GLIBCXX_3.4.4) <a href="#">[LSB]</a>
__gnu_cxx::__pool<true>::__M_initialize(void (*) (void*))(GLIBCXX_3.4.4) <a href="#">[LSB]</a>
__gnu_cxx::__pool<true>::__M_initialize()(GLIBCXX_3.4.6) <a href="#">[LSB]</a>
__gnu_cxx::__pool<true>::__M_get_thread_id()(GLIBCXX_3.4.4) <a href="#">[LSB]</a>
__gnu_cxx::__pool<true>::__M_destroy_thread_key(void*)(GLIBCXX_3.4.4) <a href="#">[LSB]</a>

## 9.1.149 Class \_\_gnu\_cxx::\_\_pool<false>

### 9.1.149.1 Interfaces for Class \_\_gnu\_cxx::\_\_pool<false>

An LSB conforming implementation shall provide the generic methods for Class \_\_gnu\_cxx::\_\_pool<false> specified in [Table 9-435](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-435 libstdc++ - Class \_\_gnu\_cxx::\_\_pool<false> Function Interfaces**

__gnu_cxx::__pool<false>::__M_destroy()(GLIBCXX_3.4.4) <a href="#">[LSB]</a>
__gnu_cxx::__pool<false>::__M_initialize()(GLIBCXX_3.4.4) <a href="#">[LSB]</a>

## **9.1.150 Class `_gnu_cxx::free_list`**

### **9.1.150.1 Interfaces for Class `_gnu_cxx::free_list`**

An LSB conforming implementation shall provide the generic methods for Class `_gnu_cxx::free_list` specified in [Table 9-436](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-436 libstdcxx - Class `_gnu_cxx::free_list` Function Interfaces**

<code>_gnu_cxx::free_list::M_clear()(GLIBCXX_3.4.4)</code> <a href="#">[LSB]</a>
--

## **9.1.151 Class `locale::Impl`**

### **9.1.151.1 Interfaces for Class `locale::Impl`**

No external methods are defined for libstdcxx - Class `std::locale::Impl` in this part of the specification. See also the relevant architecture specific part of this specification.

## **9.1.152 Namespace std Functions**

### **9.1.152.1 Interfaces for Namespace std Functions**

No external methods are defined for libstdcxx - Namespace `std` Functions in this part of the specification. See also the relevant architecture specific part of this specification.

## **9.1.153 Class `char_traits<char>`**

### **9.1.153.1 Interfaces for Class `char_traits<char>`**

An LSB conforming implementation shall provide the generic methods for Class `std::char_traits<char>` specified in [Table 9-437](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-437 libstdcxx - Class `char_traits<char>` Function Interfaces**

<code>char_traits&lt;char&gt;::eq(char const&amp;, char const&amp;)(GLIBCXX_3.4.5)</code> <a href="#">[ISOCXX]</a>
--

## **9.1.154 Class `char_traits<wchar_t>`**

### **9.1.154.1 Interfaces for Class `char_traits<wchar_t>`**

An LSB conforming implementation shall provide the generic methods for Class `std::char_traits<wchar_t>` specified in [Table 9-438](#), with the full mandatory functionality as described in the referenced underlying specification.

**Table 9-438 libstdcxx - Class `char_traits<wchar_t>` Function Interfaces**

<code>char_traits&lt;wchar_t&gt;::eq(wchar_t const&amp;, wchar_t const&amp;)(GLIBCXX_3.4.5)</code> <a href="#">[ISOCXX]</a>
---

## **9.2 Interface Definitions for libstdcxx**

The interfaces defined on the following pages are included in libstdcxx and are defined by this specification. Unless otherwise noted, these interfaces shall be included in the source standard.

Other interfaces listed in [Section 9.1](#) shall behave as described in the referenced base document.

## **Annex A GNU Free Documentation License (Informative)**

This specification is published under the terms of the GNU Free Documentation License, Version 1.1, March 2000

Copyright (C) 2000 Free Software Foundation, Inc. 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

### **A.1 PREAMBLE**

The purpose of this License is to make a manual, textbook, or other written document "free" in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondarily, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of "copyleft", which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

### **A.2 APPLICABILITY AND DEFINITIONS**

This License applies to any manual or other work that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. The "Document", below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as "you".

A "Modified Version" of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A "Secondary Section" is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (For example, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The "Invariant Sections" are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License.

The "Cover Texts" are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License.

A "Transparent" copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, whose contents can be viewed and edited directly and straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup has been designed to thwart or discourage subsequent modification by readers is not Transparent. A copy that is not "Transparent" is called "Opaque".

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML designed for human modification. Opaque formats include PostScript, PDF, proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML produced by some word processors for output purposes only.

The "Title Page" means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, "Title Page" means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

### **A.3 VERBATIM COPYING**

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

### **A.4 COPYING IN QUANTITY**

If you publish printed copies of the Document numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a publicly-accessible computer-network location containing a complete Transparent copy of the Document, free of added material, which the general network-using public has access to download anonymously at no charge using public-standard network protocols. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

## A.5 MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

- A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.
- B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has less than five).
- C. State on the Title page the name of the publisher of the Modified Version, as the publisher.
- D. Preserve all the copyright notices of the Document.
- E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.
- F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.
- G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.
- H. Include an unaltered copy of this License.
  - I. Preserve the section entitled "History", and its title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.

- J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.
- K. In any section entitled "Acknowledgements" or "Dedications", preserve the section's title, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.
- L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.
- M. Delete any section entitled "Endorsements". Such a section may not be included in the Modified Version.
- N. Do not retitle any existing section as "Endorsements" or to conflict in title with any Invariant Section.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version's license notice. These titles must be distinct from any other section titles.

You may add a section entitled "Endorsements", provided it contains nothing but endorsements of your Modified Version by various parties--for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

## A.6 COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the ti-

tle of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections entitled "History" in the various original documents, forming one section entitled "History"; likewise combine any sections entitled "Acknowledgements", and any sections entitled "Dedications". You must delete all sections entitled "Endorsements."

## A.7 COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

## A.8 AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, does not as a whole count as a Modified Version of the Document, provided no compilation copyright is claimed for the compilation. Such a compilation is called an "aggregate", and this License does not apply to the other self-contained works thus compiled with the Document, on account of their being thus compiled, if they are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one quarter of the entire aggregate, the Document's Cover Texts may be placed on covers that surround only the Document within the aggregate. Otherwise they must appear on covers around the whole aggregate.

## A.9 TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License provided that you also include the original English version of this License. In case of a disagreement between the translation and the original English version of this License, the original English version will prevail.

## A.10 TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided for under this License. Any other attempt to copy, modify, sublicense or distribute the Document is void, and will automatically terminate your rights under this License. However, parties who have received copies, or

rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

## **A.11 FUTURE REVISIONS OF THIS LICENSE**

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See <http://www.gnu.org/copyleft/>.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License "or any later version" applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation.

## **A.12 How to use this License for your documents**

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

Copyright (c) YEAR YOUR NAME. Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.1 or any later version published by the Free Software Foundation; with the Invariant Sections being LIST THEIR TITLES, with the Front-Cover Texts being LIST, and with the Back-Cover Texts being LIST. A copy of the license is included in the section entitled "GNU Free Documentation License".

If you have no Invariant Sections, write "with no Invariant Sections" instead of saying which ones are invariant. If you have no Front-Cover Texts, write "no Front-Cover Texts" instead of "Front-Cover Texts being LIST"; likewise for Back-Cover Texts.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.